

**PERFORATORS**  
**KS-13882 L1, L2, AND L3**  
**PIECE-PART DATA AND REPLACEMENT PROCEDURES**

**1. GENERAL**

**1.001** This addendum supplements Section 034-306-801, Issue 5.

**1.002** This addendum is issued to change the specified oil and lubricant, to change the pliers specified in the List of Tools and Materials, and to add a piece-part number for the relay mounting assembly cover.

**2. CHANGES TO SECTION**

**ISSUE 1 CHANGES**

**2.001** On Page 1, change the heading of 1.06 as follows: *One dip of ~~KS-7470 L1 oil or KS-19589 L2~~ lubricant*

**2.002** On Page 1, revise the heading of 1.07 as follows: *Preparation of ~~KS-19589 L2~~ Lubricant:*

**2.003** On Page 5, Fig. 5, add note as follows:

*Note:* ~~The~~ The part number for the relay mounting assembly cover is P-462807 (not shown).

**2.004** On Page 9 in the List of Tools, change P-Long-Nose Pliers to B-Long-Nose Pliers.

**2.005** On Page 9 in the List of Materials, change KS-19326 L1 Oil to KS-7470 L1 Oil and change KS-16832 L2 Lubricant to KS-19589 L2 Lubricant.

**2.006** On Page 14 in 3.17, change P-long-nose pliers to B-long-nose pliers and change KS-19326 L1 oil to KS-7470 L1 oil.

**2.007** On Page 14 in 3.19(3), change KS-16832 L2 lubricant to KS-19589 L2 lubricant.

**2.008** On Page 16 in two places in 3.26, change the KS-16832 L2 lubricant to KS-19589 L2 lubricant.

**2.009** On Page 17 in 3.33, change KS-16326 L1 oil to KS-7470 L1 oil and, in two places, change KS-16832 L2 lubricant to KS-19589 L2 lubricant.

**2.010** On Page 18 in two places in 3.36(2), change KS-16326 L1 oil to KS-7470 L1 oil.

**2.011** On Page 18 in 3.37(2), change the KS-16832 L2 lubricant to KS-19589 L1 lubricant.