

3-PORT CONFERENCE CIRCUIT (SD-2H137)

TESTS

NO. 2 AND NO. 2B ELECTRONIC SWITCHING SYSTEMS

1. GENERAL

1.001 This addendum supplements Section 232-158-501, Issue 2. Place this pink sheet ahead of Page 1 of the section.

1.002 This addendum is reissued to change transmission loss requirements. This addendum does not affect the Equipment Test List.

1.003 Issue 1 of this addendum was issued to include changes due to EF-2 and 2B-EF-2 generic programs.

2. CHANGES TO SECTION

ISSUE 1 CHANGES

2.001 On Page 1, add the following paragraph:

1.02.1 New (conventional) service order codes were adopted for use with the EF-2 and 2B-EF-2 generic programs. However, the translations can be configured with the old (No. 2 ESS unique) service order codes as an option. The old codes are common to all previous No. 2 and No. 2B ESS generic programs. The EF-2 and EF-2 generic programs can be arranged to recognize either option. In this section the term "conventional (new)" or "No. 2 ESS unique (old)" is used to identify the service order code for the keywords in each TTY input message given.

2.002 On Page 2, paragraph 3.02, change the system response to read as follows:

The system response for offices using No. 2 ESS unique (old) code is as follows:

AR VY SVC 012 bbb
TEN nn gcsl

.
.
.
SPN ss rrb
TRK 064 bbb

The system response for offices using conventional (new) code is as follows:

AR VY SVC 012 bbb
OE nn gcsl

.
.
.
SP ss rrb
TRK 064 bbb

2.003 On Page 5, Step 10, for No. 2B ESS offices, change ss = Number of trunk scanner in decimal (0-11) from Step 9 to ss = Number of trunk scanner in decimal (00-11 for offices using 2B-EF-1 generic program) or (00-30) for offices using 2B-EF-2 generic program) from Step 9.

ISSUE 2 CHANGES

2.004 On Page 13, Step 20 in VERIFICATION column change -2.7 dB to -3.7 dB and in Step 24 in VERIFICATION column change -2.2 dB to -3.2 dB.

2.005 On Page 14, Step 33 in VERIFICATION column change -2.2 dB to -3.2 dB and in Step 38 in VERIFICATION column change -2.7 dB to -3.7 dB.

2.006 On Page 15, Step 51 in VERIFICATION column change -3.2 dB to -4.2 dB.

2.007 On Page 16, Step 53 in VERIFICATION column change -2.7 dB to -3.7 dB.

NOTICE

Not for use or disclosure outside the
Bell System except under written agreement