



Alcatel-Lucent

IP MULTIMEDIA SUBSYSTEM RELEASE 08.03.01

SOLUTION EXTERNAL RELEASE NOTES

275-100-
004R08.03.01
JANUARY 2010
ISSUE 1

Legal Notice

Alcatel, Lucent, Alcatel-Lucent and the Alcatel-Lucent logo are trademarks of Alcatel-Lucent. All other trademarks are the property of their respective owners.

The information presented is subject to change without notice. Alcatel-Lucent assumes no responsibility for inaccuracies contained herein.

Copyright © 2010 Alcatel-Lucent. All Rights Reserved.

Contents



About this document	v
Purpose.....	v
Reason for revision	v
Intended audience.....	v
Supported systems.....	v
Conventions used	v
Technical support.....	v
How to order	vi
How to comment.....	vi
1 Release components	1-1
Overview.....	1-1
Purpose.....	1-1
Software deliverables.....	1-2
How to obtain software	1-4
Document deliverables.....	1-4
To obtain documentation.....	1-5
2 New features	2-1
Overview.....	2-1
Purpose.....	2-1
New features.....	2-1
Functionality	2-2
Enhancements	2-2
3 Test results	3-1
Overview.....	3-1
Purpose.....	3-1
Test results/exit criteria.....	3-1
4 Changes to fault management, ports, protocols, and parameters	4-1
Overview.....	4-1
Purpose.....	4-1
Interface changes.....	4-1

	Changes to Northbound Interfaces.....	4-1
	Changes to Southbound Interfaces.....	4-2
	Alarm changes	4-2
	Message changes.....	4-2
	Port changes.....	4-2
	Protocol changes.....	4-3
	System parameter changes.....	4-4
5	Resolved issues	5-1
	Overview.....	5-1
	Purpose.....	5-1
	Resolved issues.....	5-2
6	Known issues	6-1
	Overview.....	6-1
	Purpose.....	6-1
	Known issues and workarounds.....	6-2
7	System requirements	7-1
	Overview.....	7-1
	Purpose.....	7-1
	Software requirements	7-1
	IMS GUIs JAVA Dependency.....	7-1
	SUN Operating System Patch Level for Non-Integrated Components.....	7-2
	Software licensing keys	7-2
	Hardware requirements.....	7-2
	Compatibility restrictions.....	7-3
8	Installation and upgrade notes	8-1
	Overview.....	8-1
	Purpose.....	8-1
	Performing first-time installation.....	8-1
	Performing upgrades.....	8-1
	Upgrade paths	8-1
	Security hardening	8-2
	Feature activation.....	8-2
	Obtaining and installing third-party software	8-2
	Acronym List	1

About this document



Purpose

The purpose of this document is to provide a general overview of the IP Multimedia Subsystem (IMS) Release 08.03.01, including a list of the network element load versions, IMS network level test results, and known issues to assist service providers with field deployments of IMS Release 08.03.01.

Reason for revision

This is the first issue of the IMS Release 08.03.01 Release Notes document.

Intended audience

The intended audience for this document includes all personnel who need information about the IMS 08.03.01 release, its functions, and network elements.

This document can be used by the following audiences:

- Planning and design personnel
- Maintenance personnel
- Management personnel
- System installation and integration personnel

Supported systems

See Chapter 7, System Requirements, for information on systems supported in Release 08.03.01.

Conventions used

There are no special typographical conventions used in this document.

Technical support

For technical support, contact your local Alcatel-Lucent customer support team. See the Alcatel-Lucent Support web site (<http://alcatel-lucent.com/support/>) for contact information.

How to order

This document is available on the Online Customer Support Site (OLCS). To order this document and other Alcatel-Lucent documents, contact your local sales representative or use the OLCS web site (<https://support.alcatel-lucent.com>).

How to comment

To comment on this document, go to the Online Comment Form (<http://infodoc.alcatel-lucent.com/comments>) or e-mail your comments to the Comments Hotline (comments@alcatel-lucent.com).



1 Release components

Overview

Purpose

This chapter describes the software loads that comprise Release 08.03.01 and the documentation deliverables included in this release.

Software deliverables

Table 1-1 lists the loads that comprise Release 08.03.01. New or changed load names are shown in bold-face type.

Table 1-1 Software release identification

Network Element/Application	Load Name in IMS 08.03.00	Load Name in IMS 08.03.01	Load Changed Since IMS 08.03.00?
1300 Cross Management Center (XMC)	R7.0.0.3 + IAP01 (also required OS upgrade 4.3 to 5.3) Due to OS change, instead of upgrade a fresh installation with backup/restore procedures has been done.	R7.0.0.4 + IAP04	Yes
1310 Operations and Maintenance Console – Provisioning (OMC-P)	OMC-P R14.00.00.01	OMC-P14_01_02_00	Yes
1357 Unified Lawful Intercept Suite (ULIS) Lawful Interception Gateway (LIG)	R12.3.6	R12.4.2	Yes
1440 Unified Subscriber Data Server (USDS) (Includes MAS/AHE)	R7.3 SPA: h1r7.3.n04.upd72.01 MAS: ltm27-p0207 Then upgrade to: 1440 USDS R7.3 P01 MAS R27 SU2 Patch (ltmasr27-p0214)	R7.3 SPA: h1r7.3.n04.upd72.01 MAS: ltm27-p0207 Then upgrade to: 1440 USDS R7.3 P01 MAS R27 SU2 Patch (ltmasr27-p0214)	No
5020 Media Gateway Controller – 8 (MGC-8)	LGP-7.0.0.1	LGP7-0-0-3 SP6	Yes
5100 Converged Messaging System (CMS)	CMS-10SU4 (must be a minimum of build 1000.40.037)	CMS-10SU4 (must be a minimum of build 1000.40.038)	Yes
5420 Converged Telephony Server (CTS)	R18.22.00.00 Plus Patch: R18.22.00.05	R18.28.01.00 Plus Patch: R18.28.01.02	Yes
5440 IMS-PC Client	5440_PCC_r4.0 (non-PCM) Load 4.0.0.2315	5440_PCC_r4.1.0_2364_n onpcm	Yes
5450 Access Gateway Control Function (AGCF)	AGCF-5-1-1 R1S3 Then patch to AGCF511R1S3P1	AGCF5_1_2R1S2 + AGCF5_1_2R1S2P1	Yes

Network Element/Application	Load Name in IMS 08.03.00	Load Name in IMS 08.03.01	Load Changed Since IMS 08.03.00?
5450 IP Session Control (ISC)/ IP Resource Controller (IRC) (includes iAGCF)	R18.22.00.00 Plus Patch: R18.22.00.05	R18.28.01.00 Plus Patch: R18.28.01.02	Yes
5750 Subscriber Services Controller (SSC)	SSC 3.1R5 and SAC/CLF 3.1R5	SSC 3.1R5 and SAC/CLF 3.1R5	No
5900 Media Resource Function (MRF)	MRF7.0.2	MRF7.0.2	No
7302 Intelligent Services Access Manager (ISAM) -V	ISAM-V-R40 R 40.126 Plus R 4.0.0.a (load 40.129)	ISAM-V-R40 R 40.129 Plus R 4.0.0.a (load 40.132)	Yes
7510 Media Gateway (MGW)	7510 R3.1SP2 (R31N_07_05_2009_B06)	7510 R32_10_23_2009_B01 (for IPv6) A7510_R31N_10_09_20 09_B08 (for IPv4)	Yes
7515 Media Gateway (MGW)	7515m2.4B0120	7515m2.4B0120	No
7515 SIP-MGW	7515R3.1S B0105 ¹	7515R31S B0110	New
7520 Media Gateway (MGW)	LGP-7.0.0.1	LGP7-0-0-3 SP6	Yes
7750 Service Router	7750_R6.0_R9	7750_R6.0_R9	No
8610 Instant Convergent Charging (ICC)	ICC462-MD02-DR4	ICCR462MD02	No
8615 Instant enhanced Charging Collection Function (leCCF)	leCCF 27.5 hotslide00101 MAS -> ltmshr27-p0219 N440 Hardware & T2000 Hardware	leCCF 276 Mapdata script leCCF 27.6 hotslide0101	Yes
8650 Subscriber Data Manager (SDM) (HSS on ATCA)	SDM2.1SU1	8650 SDM R2.1 SU1 IAP001	Yes
8920 Service Quality Manager (SQM)	Not Applicable	R3.7.6	New
8950 Services Activation Manager (SAM) (Sun/Linux Platform)	Not Applicable	R16.0.3.B9	New
Acme Packet Session Director (4250)	C6.10M2	C6.10M2	No
enhanced Service Manager (eSM)	eSM R26 SU9	eSM R26 SU9	No
Fortinet Fortigate Firewall	v3.0.MR5.8108	v3.0.MR5.8108	No

¹ 7515 SIP-MGW cannot be combined with a 7515 MGW on the same equipment.

Network Element/Application	Load Name in IMS 08.03.00	Load Name in IMS 08.03.01	Load Changed Since IMS 08.03.00?
Gateway Platform Includes: - 5020 MGC - 5025 Voice Signaling Gateway - 7520 MGW	LGP-7.0.0.1	LGP7-0-0-3 SP6	Yes
Lucent Communication Manager (LCM)	Not Applicable	R6.3.6 (bld.201)	New
OXE OmniPCX Enterprise	R9.0-h1.301-28-b-us-c80s1	R9.0-h1.301-28-b-us-c80s1	No
Billing and Traffic System (BTS)	BTS_7.0.0.0.14	BTS_7.0.0.0.14	No
VitalQIP	VitalQIP R7.2 DNS R4.1 Build 11 ENUM R1.3	VitalQIP R7.2 DNS R4.1 Build 11 ENUM R1.3	No

How to obtain software

Please contact your Alcatel-Lucent representative to obtain software.

Document deliverables

Table 1-2 shows the solution documentation available for IMS Release 08.03.01.

Table 1-2 IMS 08.03.01 solution documentation

Title	Ordering number
<i>IMS Release 08.03.00 Solution Technical Description</i>	275-100-000R08.03.00
<i>IMS Release 08.03.00 Solution Operations, Administration, Maintenance, & Provisioning</i>	275-100-001R08.03.00
<i>IMS Release 08.03.01 Solution Release Notes</i>	275-100-004R08.03.01
<i>IMS Release 08.03.00 Software Upgrade</i>	275-100-035R08.03.00

Title	Ordering number
<i>IMS Release 08.03.00 Interface Changes Specifications</i>	275-100-050R08.03.00
<i>IMS Release 08.03.00 Solution System Parameters</i>	275-100-057R08.03.00
<i>IMS Release 08.03.00 Solution Ports and Protocols</i>	275-100-058R08.03.00
<i>IMS Release 08.03.00 Solution Growth</i>	275-100-059R08.03.00
<i>IMS Release 08.03.00 Solution Provisioning</i>	275-100-060R08.03.00

See the next section, “To obtain documentation”, for detailed information on how to obtain IMS Solution documentation.

To obtain documentation

IMS Solution and product documentation is available to IMS Solution customers through OnLine Customer Support (OLCS).

To obtain IMS Solution documentation, do the following:

1. Go to (<https://services.support.alcatel-lucent.com/services/ims/>).
2. After a successful login, select **Solution level Manuals and Guides** (for manuals and guides) or **Solution level Release Information** (for release notes and software upgrade documents) under IMS Solution Level Documentation.

To obtain product documentation, do the following:

1. Go to (<https://services.support.alcatel-lucent.com/services/ims/>).
2. After a successful login, select a network element from the **Links to network elements in the IMS Solution** section or use the pull-down in the upper-right corner and select Documentation to get to the Product Index.

2 New features



Overview

Purpose

This chapter lists the features included in Release 08.03.01.

New features

The following features are included in this release:

Table 2-1 Features released in 08.03.01

Feature Number	Feature Title
33333.25	ALU IMS business trunking solution for ISDN-PBX using wildcard PUID
33333.28	IMS Solution: Subscription Locator Function (SLF)
33333.74	Cluster Testing for bVoIP VDNA
33333.79	E2E Testing of Centralized Subscriber Data Base
33333.87	IMS 8.x Interoperability Testing with IMS 7.x Components for CVoIP
33333.125	CVoIP Solution End-to-End Subscriber Provisioning Validation for 1 st Generation Workflows
33333.173	Alcatel-Lucent Border Solution Testing – IMS 8.3
33333.180	IP Peering Border Solution Testing
33333.183	CVoIP Solution E2E Subscriber Provisioning Validation for 2 nd Generation Workflows (with CSDB - Regression)
33333.185	Capacity testing for IMS 8.3
33333.187	E2E Performance, Reliability, Stability testing for IMS 8.3
33333.189	IMS Solution IPv6 Support Phase 1
33333.191	IMS Solution Level Testing of Geographic Redundancy

Feature Number	Feature Title
33333.195	IMS Solution: E2E Testing of 5420 CTS Service Enhancements
33333.201	IMS 8.3 Codenomicon & DOS NLT Testing
33333.244	E2E Solution Testing of LCM Upsynch to OMC-P Using Bulk Synch
33333.266	CVoIP Solution End-to-End Subscriber Provisioning Validation for 2 nd Generation Workflows
33333.268	CVoIP Solution End-to-End Subscriber Provisioning Performance for 2 nd Generation Workflows (without CSDB - Regression)

Table 2-2 Features released in 08.03.00

Feature Number	Feature Title
33333.25	ALU IMS business trunking solution for ISDN-PBX using wildcard PUID
33333.185	Capacity testing for IMS 8.3
33333.187	E2E Performance, Reliability, Stability testing for IMS 8.3
33333.195	IMS Solution: E2E Testing of 5420 CTS Service Enhancements
33333.213	IMS Solution: Class 5 PSTN Emulation Subsystem Services
33333.218	IMS Solution Level Software Upgrade Development & Test for IMS 8.1 to IMS 8.3 Software Upgrade Path
33333.232	Solution: Distributed IMS Consumer VoIP (CVoIP)
33333.234	IMS Solution: PBX Support Enhancements

Functionality

See the specific NE documentation for configuration information.

Enhancements

There are no non-feature enhancements in this release.

3 Test results



Overview

Purpose

This chapter provides information on test execution and pass rates.

Test results/exit criteria

The following table shows the results of the IMS 08.03.01 test program. See Table 6-1 for exceptions.

Table 3-1 NLT test results

Solution	Progress Rate	Quality (Pass Rate)	Exit Criteria Status (Reached/Not Reached)
<i>Border Solution</i>	100%	99%	Reached
<i>beVoIP Solution</i>	100%	98%	Reached
<i>CVoIP Solution</i>	100%	97%	Reached



4 Changes to fault management, ports, protocols, and parameters

Overview

Purpose

This chapter describes fault management changes (interfaces, alarms, and messages), port and protocol, and system parameter changes in this release.

Interface changes

Changes to Northbound Interfaces

The following document describes the Northbound interface changes for the 1300 XMC:

- *Alcatel-Lucent 1300 XMC SNMP Alarm Forwarding, 3BL59971GCCAPCZAA* (See Appendix A)

The following document describes the Northbound interface changes for the 5100 CMS:

- *5100 CMS (Converged Messaging System) Release 10.4 Documentation, 270-715-123R10.4* (See Chapter 3)

The following document describes the Northbound interface changes for the 5420 CTS:

- *Alcatel-Lucent Control Platform 1800/1000/5400 Release 18.0 Charging Interface Specification, 275-900-393R18.0* (See Chapter 5)

The following documents describe the Northbound interface changes for the 5900 MRF:

- *MRF Statistics Dictionary*, 3AT34450AAAPDTZZA
- *MRF Alarms Dictionary – User Guide*, 3AT34450AAAGDTZZA

The following document describes the Northbound interface changes for the 8615 IeCCF:

- *8615 Instant Enhanced Charging Collection Function (IeCCF) R27.6 IMS Offline Charging Interface specification*, 270-725-059R27.6

The following document describes the Northbound interface changes for the BTS:

- *Alcatel-Lucent Gateway Platform Release 7.0.0.0.14 Billing and Traffic System (BTS) Release Notes*, 255-400-404R7.0.0.0.14 (See Appendix A)

You can also refer to the following solution-level document additional information about interface changes for IMS 08.03.00 Network Elements:

- *IP Multimedia Subsystem Release 08.03.00 Solution Interface Changes Specifications*, 275-100-050R08.03.00

Changes to Southbound Interfaces

Please consult the NE-specific documentation for southbound interface changes in this release.

Alarm changes

Please consult the NE-specific documentation for alarm changes in this release.

Message changes

Please consult the NE-specific documentation for new messages or changes to messages in this release.

Port changes

The following document describes the port changes for the 1310 OMC-P:

- *Alcatel-Lucent 1310 OMC-P Server Management & System Administration Guide, 255-400-423R14.0* (See Chapter 6)

The following document describes the port changes for the 5100 CMS:

- *5100 CMS (Converged Messaging System) Release 10.4 Documentation, 270-715-123R10.4* (See Chapter 3)

The following document describes the port changes for the 5420 CTS:

- *1310 OMC-P for Alcatel-Lucent Control Platform User Guide for Managing the 5420 CTS & 5450 IP Session Control Function, 25-400-420R14.1* (See Chapter 4)

The following document describes the port changes for the 5900 MRF:

- *IP Multimedia Subsystem (IMS) Release 08.03.00 Solution Ports and Protocols, 275-100-058R08.03.00*

The following document describes the port changes for the 8615 IeCCF:

- *8615 Instant Enhanced Charging Collection Function (IeCCF) R27.6 IMS Offline Charging Interface specification, 270-725-059R27.6*

Protocol changes

The following document describes the protocol changes for the 5100 CMS:

- *5100 CMS (Converged Messaging System) Release 10.4 Documentation, 270-715-123R10.4* (See Chapter 3)

The following document describes the protocol changes for the 5420 CTS:

- *1310 OMC-P for Alcatel-Lucent Control Platform User Guide for Managing the 5420 CTS & 5450 IP Session Control Function, 255-400-420R14.1* (See Chapter 4)

The following document describes the protocol changes for the 5900 MRF:

- *IP Multimedia Subsystem (IMS) Release 08.03.00 Solution Ports and Protocols, 275-100-058R08.03.00*

The following document describes the protocol changes for the 8615 IeCCF:

- *8615 Instant Enhanced Charging Collection Function (IeCCF) R27.6 IMS Offline Charging Interface specification, 270-725-059R27.6*

System parameter changes

The following document describes the system parameter changes for the 1310 OMC-P:

- *Alcatel-Lucent 1310 OMC-P for Alcatel-Lucent Gateway Platform Management User Guide, 255-400-400R14.0* (See the section Reason for Revision)

The following document describes the system parameter changes for the 5100 CMS:

- *5100 CMS (Converged Messaging System) Release 10.4 Documentation, 270-715-123R10.4* (See Chapter 3)

The following document describes the system parameter changes for the 5420 CTS:

- *Alcatel-Lucent 5420 Converged Telephony System (CTS) Release 6.2 Application User Guide, 275-900-366R6.2* (See Chapter 5)

The following document describes the system parameter changes for the 5900 MRF:

- *IP Multimedia Subsystem (IMS) Release 08.03.00 Solution System Parameters, 275-100-057R08.03.00*

The following document describes the system parameter changes for the 7302 ISAM-V:

- *CLI Command Guide, 3HH-04416-DAAA-TCZZA* (See Chart 37)

The following document describes the system parameter changes for the 8615 IeCCF:

- *8615 Instant Enhanced Charging Collection Function (IeCCF) R27.6 IMS Offline Charging Interface specification, 270-725-059R27.6*



5 Resolved issues

Overview

Purpose

This chapter describes customer-reported ARs and NLT-reported problems resolved in this release.

Resolved issues

This section lists resolved issues that were previously reported as *Known Issues* in Chapter 6.

Table 5-1 lists the severity 1 and 2 issues that were resolved in the loads that are part of this release.

Table 5-1 NLT-Reported severity 1 and 2 open issues - resolved

NE to Lead	Resolve RIs	Fixed in Load	Current Status	Solution(s)	Exception Description
8650 SDM	IMS08.03.01	SDM R2.1 SU1 IAP001	Resolved	sub_provision, install/upgrade	SDM: R2.1SU1 table GlobalFC error in provisioning.
5900 MRF, CTS	Not Applicable	Not Applicable	Resolved no change, lab issue	cvoip_xdsl, pstn	Music On Hold and some announcements sometimes not heard; MRF responds 491 to INFO.
ISC	IMS08.03.01	18.28.01.01	Resolved in ISC r18.28.01.01	pstn	AGW registrations with high background call load. M-PPR download stops at random.
MGC-8	IMS08.03.01	LGP 7.0.0.3	Resolved in LGP 7.0.0.3	ip_xform	INVITE From header should not have user=phone for non digit. PSTN (MGC-8) –to- ISDN Failed (Presentation Restricted/Unavailable).

6 Known issues



Overview

Purpose

This chapter describes NLT-reported issues that remain open in Release 08.03.01.

Known issues and workarounds

As of January 2010, no customer-reported ARs have been opened against this release.

Table 6-1 lists the severity 2 issues that were not resolved in the network element loads that are part of this release. Table 6-2 lists the severity 2 issues from IMS 08.03.00 that were not resolved in the network element loads that are part of this release.

Table 6-1 NLT-reported severity 2 open issues from IMS 08.03.01

NE to Lead	Resolve RIs	Fixed in Load	Current Status	Solution(s)	Exception Description	Impact Statement / Workaround
7510 MGW	IMS8.3 maintenance	A7510_R31 N_11_27_20 09_B09	Fix is available to be tested for IMS8.3 Maintenance	core	7510MGW does not have enough RTP resource after second SCM takeover.	If a second SCM board failover occurs too soon before the synch of information after the first SCM board failover, there will not be enough RTP resources to continue call processing.
7515 MGW	Under Investigation	Under Investigation	Under Investigation	core	On XMC, 7515MGW PM data error occurred & 7515 MGW alarm also can't be displayed.	XMC cannot monitor the 7515 successfully in IMS 8.3. Interface mismatch between 7515 and XMC, limited PM and FM available.
MGC-8	Under Investigation	Under Investigation	Under Investigation	cvoip_xdsl	MGC8/BTS not recording calling/called party in CDRS for non-e164 sip uri.	Billing records are not available for a non-E164 SIP URI in a Peering scenario with an MGC-8 IBCF (incoming call to IMS from the Peer and an outgoing call from IMS to the Peer with a non-E164 SIP URI).

Table 6-2 NLT-reported severity 2 open issues from IMS 08.03.00

NE to Lead	Resolve RIs	Fixed in Load	Current Status	Solution(s)	Exception Description	Impact Statement / Workaround
5900 MRF	IMS9.0	MRF 7.0.4	Under Investigation	cvoip_xdsl	MRF - G726-32 codec MRF should offer payload type = 2 to Invite W/O SDP.	MRF supports G.726-32 codec with dynamic payload. MGWs, such as the 7520, which require a payload of "2" will cause certain scenarios, such as conference call to fail.
ISAM-V	IMS9.0	r4003	Targeted for January 2010	pstn	ISAM-V VGW does not support TCP and does not send the required message indicating that to the core, therefore, calls will fail when packet size is larger than 1300bytes.	TCP/UDP switching has to be disabled in the ISC to fully support ISAM-V in the network. Once a packet reaches 1300 bytes, P-CSCF will switch to TCP transmission. ISAM-V only supports UDP so calls fail. The particular situation where this was discovered was interworking with MRF and such services that cause large messages such as 3-way calling. WORKAROUND: Disable TCP/UDP switching or limit the number of codecs installed on the MRF.



7 System requirements

Overview

Purpose

This chapter describes IMS GUI Java dependencies and compatibility restrictions.

Software requirements

IMS GUIs JAVA Dependency

Table 7-1 shows IMS GUIs with Java installation dependencies (listed in order of installation sequence).

Table 7-1 IMS GUIs with Java installation dependencies

LCP MI GUI	Java installed per link provided during initial start of MI GUI (Java 1.5.0_06)
XMC GUI	Java installed per link provided during initial start of MI GUI (Java 1.5.0_15)

The following NE GUIs do not have Java dependencies: 5420 CTS, 5450 ISC, 1310 OMC-P, 5900 MRF.

SUN Operating System Patch Level for Non-Integrated Components

Table 7-2 shows the SUN OS patch level for non-integrated components.

Table 7-2 SUN OS system patch level for non-integrated components

Network Element	OS Level
VitalQIP Enterprise	Solaris 10 Generic_127111-09
VitalQIP DNS	Solaris 10 Generic_127111-09
1310 OMC-P	Solaris 10 Generic_127111-09
BTS	Solaris 10 Generic_127111-09

Software licensing keys

This section does not apply to this release. See the specific NE documentation for more information.

Hardware requirements

Specific hardware requirements are addressed by the network element level release notes and documentation.

Compatibility restrictions

Backward compatibility is supported for the IMS solution software upgrade sequence from IMS 08.03.00 to IMS 08.03.01. See the *Alcatel-Lucent Internet Protocol Multimedia Subsystem (IMS) Solution 08.03.00 Software Upgrade* document, 275-100-035R08.03.00, and specific NE documentation for more information. The specific upgrade path must be provided by each NE.



8 Installation and upgrade notes

Overview

Purpose

This chapter provides information on installation, upgrade procedures and security hardening.

Performing first-time installation

Contact your Alcatel-Lucent representative for first-time installation assistance.

Performing upgrades

The following solution-level document describes the recommended installation and upgrade sequence for the IMS network elements:

- *Alcatel-Lucent Internet Protocol Multimedia Subsystem (IMS) Solution 08.03.00 Software Upgrade 275-100-035R08.03.00*

Refer to the NE documentation for specific software upgrade information.

Upgrade paths

Upgrade to IMS 08.03.01 is supported from IMS 08.03.00. Network Elements may require multiple transitions to go from IMS 08.03.00 to IMS 08.03.01; refer to the specific NE documentation for further details.

Security hardening

Security hardening procedures and information for IMS Release 08.03 NEs are on OLCS. Go to: <https://services.support.lucent.com/services/>, click on IMS Solutions, then click on Security Hardening IMS Release 07.06.00/08.03.00. From this page, you can click on each NE for security hardening details.

Feature activation

Feature activation is done at the NE-level. Please consult with your Alcatel-Lucent customer support team for more information.

Obtaining and installing third-party software

Contact your Alcatel-Lucent customer support team for more information.

Acronym List



A

AGCF
Access Gateway Control Function

ATCA
Advanced Telecommunications Computing Architecture

AR
Action Register

B

BTS
Billing and Traffic System

C

CMS
Change Management System

CTS
Converged Telephony Server

CVoIP
Consumer Voice over IP

D

DNS
Domain Name System

E

eSM
enhanced Service Manager

F

FS
Feature Server

G

GUI
Graphical User Interface

H

HSS
Home Subscriber Server

I

ICC
Instant Convergent Charging

IeCCF
Instant enhanced Charging Collection Function

IMS
IP Multimedia System

IRC
IP Resource Control

ISAM
Intelligent Services Access Manager

ISC

L

LCM
Lucent Communication Manager

M

MGC
Media Gateway Controller

MGW
Media Gateway

MRF
Media Resource Function

N

NE
Network Element

NLT
Network Level Test

O

OAM
Operations, Administration, Maintenance

OLCS
OnLine Customer Support

OMC-P
Operations and Maintenance Console – Provisioning

P

PES
PSTN Emulation Solution

PCM
Personal Communication Manager

PSTN
Public Switched Telephony Network

S

SAM
Services Activation Manager

SDM
Subscriber Data Manager

SQM
Service Quality Manager

SSC
Subscriber Services Controller

U

ULIS
Unified Lawful Intercept Suite

USDS
Unified Subscriber Data Server

V

VoIP

Voice over Internet Protocol

VSG

Voice Signaling Gateway

X

XMC

Cross-domain Management Center
