

DIMENSION<sup>®</sup> PBX  
FEATURE TEST  
OUTWARD RESTRICTION

CONTENTS

1. GENERAL INFORMATION
  2. RECORDS AND REQUIREMENTS
  3. TEST EQUIPMENT
  4. PROCEDURE
- 

1. GENERAL INFORMATION

1.1 Description

1.11 This section describes the tests to be performed whenever the Outward Restriction feature is utilized.

1.12 This feature restricts a station from accessing outgoing trunks and when attempted the station receives intercept tone.

2. RECORDS AND REQUIREMENTS

2.1 Records

2.11 Form SD-97-1313 is required for recording the results of this test.

3. TEST EQUIPMENT

3.1 Handsets

<u>AMT</u>	<u>ITE</u>	<u>DESCRIPTION</u>
1	4208A	Telephone Handset

3.2 Cords

<u>AMT</u>	<u>ITE</u>	<u>DESCRIPTION</u>
1	9153L	Cord Assembly

PRIVATE

THE INFORMATION CONTAINED HEREIN SHOULD NOT BE DISCLOSED TO UNAUTHORIZED PERSONS. IT IS MEANT SOLELY FOR USE BY AUTHORIZED BELL SYSTEM EMPLOYEES.

Printed in U.S.A.

4. PROCEDURE

4.1 Test Procedure

- 4.11 From the Class-of-Service and Station Line Assignments sections of the Customer Order Document choose a station that has outward restriction.
- 4.12 Utilizing the 249A Adapter connect the handset to the test line, at the circuit pack, associated with the station chosen in Step 4.11.
- 4.13 Go off-hook with the handset, verify dial tone, and then dial a CO trunk access code. Verify:
  - a) That the handset receives intercept tone.
- 4.14 Go on-hook with the handset and remove the handset and 249A Adapter from the circuit pack test line.
- 4.15 This completes the testing of the Outward Restriction feature.