

DIMENSION® PBX  
TRAFFIC MEASUREMENT CONNECTION  
(724A PANEL)

CONTENTS

1. GENERAL
2. MOUNTING
3. CABLING

---

1. GENERAL

- 1.1 A 724A panel may be provided for traffic set connection at the cross connect field.

2. MOUNTING

- 2.1 Mount 724A panel at cross connect field per Telephone Company information. This panel must be mounted within 100 feet of the CSS 201 system.

3. CABLING

- 3.1 Using gummed label provided designate and label C2A cable connector CX04. Tag raw end of cable 00CX04.
- 3.2 Connect cable at Control Carrier connector CX04 and route to 724A panel located on the cross connect field.
- 3.3 Connect cable at 724A panel as follows:

<u>724A PANEL TERMINAL BLOCK</u>	<u>COLOR</u>
XA	RED
XB	BLACK
GRD	GRD
RA	WHITE
RB	GREEN
GRD	GRD

Manager, Denver PBX PECC

PRIVATE

THE INFORMATION CONTAINED HEREIN SHOULD NOT BE DISCLOSED  
TO UNAUTHORIZED PERSONS. IT IS MEANT SOLELY FOR USE BY  
AUTHORIZED BELL SYSTEM EMPLOYEES.

Printed in U.S.A.