

STRUCTURAL RETURN LOSS ADJUSTMENTS  
FOR SHORT LENGTHS OF LOADED FACILITY

NOTE

<u>Facility Loss</u>	<u>Correction to be Added to Structural Return Loss</u>
0.5 db	6.8 db
0.6 db	6.2 db
0.7 db	5.6 db
0.8 db	5.1 db
0.9 db	4.7 db
1.0 db	4.3 db
1.1-1.2 db	3.7 db
1.3-1.4 db	3.2 db
1.5-1.6 db	2.8 db
1.7-1.8 db	2.5 db
1.9-2.0 db	2.2 db
2.1-2.2 db	1.9 db
2.3-2.4 db	1.7 db
2.5-2.7 db	1.5 db
2.8-3.0 db	1.3 db
3.0-3.3 db	1.1 db
3.4-3.5 db	1.0 db
3.6-3.7 db	0.9 db
3.8-3.9 db	0.8 db
4.0-4.1 db	0.7 db
4.2-4.4 db	0.6 db
4.5-4.8 db	0.5 db
4.9-5.3 db	0.4 db
5.4-5.9 db	0.3 db
6.0-6.8 db	0.2 db
6.9-8.1 db	0.1 db
8.2 or more	0.0 db

Note: This table is based on information given in Section 352-153-100.