

## VOICE BANDWIDTH PRIVATE LINE DATA CIRCUITS DESCRIPTION

### 1. GENERAL

**1.001** This addendum supplements Section 314-410-100, Issue 3. Place this pink sheet ahead of Page 1 of this section.

**1.002** This addendum adds information concerning type D5 high performance data conditioning (HPDC) circuits.

### 2. CHANGES TO SECTION

**2.001** On Page 9, add subparagraph (d) to paragraph 5.04 as follows:

(d) Type D5 HPDC is designed for multipoint voice-grade 3002-type analog data channels within the contiguous 48 states. Multipoint voice-grade HPDC-type D5 can be provided only on those circuits operating in a polling environment. The HPDC-type D5 conditioning will be provided between the master station and each remote station. The number of simultaneously active channels/remotes is limited to two.

**2.002** On Page 9, at the end of paragraph 5.05, add the following:

Alternate voice-data arrangements are not available on type D5 HPDC circuits.

**2.003** On Page 10, add paragraph 5.15 as follows:

**5.15** The HPDC-type D5 conditioned circuits require two additional facility and equipment considerations.

(a) When N type carrier is used only N4 is acceptable

(b) Energy gated amplifiers (EGA) (Section 880-420-102) may be required to meet the signal-to-noise parameter.

**2.004** On Page 14, add the following publication and section:

AT&T PUB 62103 High Performance  
Data Conditioning, Type D5 For  
Multipoint Private Line Data  
Channels, September, 1982

010-522-100 Network Technical  
Support (NTS) Plan.

**2.005** On Page 15, add the following section:

880-420-102 Private Data Circuits  
Standard Design of 2-Point and  
Multipoint Circuits Data  
Communications Engineering.

### NOTICE

Not for use or disclosure outside the  
Bell System except under written agreement