

NTN469GF

323-1059-090

Nortel Networks

OPTera Metro 3500 Multiservice Platform

About the OPTera Metro 3500 NTP Library

Standard Release 12.0 Issue 1 November 2003

What's inside...

[Documentation overview](#)

[Release history](#)

[List of terms](#)

[Master index](#)

Copyright © 2000–2003 Nortel Networks, All Rights Reserved

The information contained herein is the property of Nortel Networks and is strictly confidential. Except as expressly authorized in writing by Nortel Networks, the holder shall keep all information contained herein confidential, shall disclose the information only to its employees with a need to know, and shall protect the information, in whole or in part, from disclosure and dissemination to third parties with the same degree of care it uses to protect its own confidential information, but with no less than reasonable care. Except as expressly authorized in writing by Nortel Networks, the holder is granted no rights to use the information contained herein.

Nortel Networks, the Nortel Networks logo, the Globemark, OPTera, and Preside are trademarks of Nortel Networks.

Hewlett-Packard, HP, and HP-UX are trademarks of Hewlett-Packard Company.

Microsoft, Windows, and Windows NT are trademarks of Microsoft Corporation.

Solaris, Sun, Sun Blade, Sun Microsystems, and Ultra are trademarks of Sun Microsystems, Inc.

SPARC is a trademark of SPARC International, Inc.

Telcordia is a trademark of Telcordia Technologies, Inc.

Printed in Canada

Contents

| | |
|-------------------------------------|------------|
| About this document | v |
| Documentation overview | 1-1 |
| Release information | 1-1 |
| Documents in this library | 1-2 |
| Document identification numbers | 1-2 |
| Associated documents | 1-3 |
| NTP product engineering codes | 1-3 |
| Ordering NTPs | 1-4 |
| Document content description | 1-4 |
| Site Manager and user documentation | 1-7 |
| Release history | 2-1 |
| List of terms | 3-1 |
| Master index | 4-1 |

About this document

This document provides an overview of the Nortel Networks technical publications (NTPs) and describes the content of each document. Also included in this document is a list of terms and acronyms, and master index to guide the user of the documentation on where to find information on a particular topic.

Standards

The Telecommunications Industry Association (TIA) and the Electronics Industries Alliance (EIA) accepted RS-232 as a standard in 1997 and renumbered this standard as TIA/EIA-232. In this document, RS-232 is used to reflect current labels on the hardware and in the software for the OPTera Metro 3500 Multiservice Platform.

Supported software

This document supports the software release for Nortel Networks OPTera Metro 3500 Multiservice Platform Release 12.0.

Supported hardware

This document supports the OPTera Metro 3500 shelf and Universal OPTera Metro 3500 shelf.

Audience

The following members of your company are the intended audience of this Nortel Networks technical publication (NTP):

- planners
- provisioners
- network administrators
- transmission standards engineers


Hardware naming conventions

The following naming conventions are used throughout this document to identify the OPTera Metro 3500 hardware:

- The extended shelf processor (SPx) is referred to as the shelf processor.
- The extended network processor (NPx) is referred to as the network processor.

OPTera Metro 3500 NTP library

EX1478p



Technical support and information

For technical support and information from Nortel Networks, refer to the following table.


| Technical Assistance Service | |
|--|--|
| <p>For service-affecting problems: For 24-hour emergency recovery or software upgrade support, that is, for:</p> <ul style="list-style-type: none"> • restoration of service for equipment that has been carrying traffic and is out of service • issues that prevent traffic protection switching • issues that prevent completion of software upgrades | <p>North America: 1-800-4NORTEL (1-800-466-7835)</p> <p>International: 001-919-992-8300</p> |
| <p>For non-service-affecting problems: For 24-hour support on issues requiring immediate support or for 14-hour support (8 a.m. to 10 p.m. EST) on non-urgent issues.</p> | <p>North America: 1-800-4NORTEL (1-800-466-7835)</p> <p>Note: You require an express routing code (ERC). To determine the ERC, see our corporate Web site at www.nortelnetworks.com. Click on the Express Routing Codes link.</p> <p>International: Varies according to country. For a list of telephone numbers, see our corporate Web site at www.nortelnetworks.com. Click on the Contact Us link.</p> |
| <p>Global software upgrade support: For non-service affecting software upgrade issues</p> | <p>North America: 1-800-4NORTEL (1-800-466-7835)</p> <p>International: Varies according to country. For a list of telephone numbers, see our corporate Web site at www.nortelnetworks.com. Click on the Contact Us link.</p> |

Documentation overview

This *Technical Reference Library* is an integral part of the OPTera Metro 3500 Multiservice Platform network elements and is considered part of the equipment.

Release information

The current release of the *Technical Reference Library* is Release 12.0 Standard and is defined as follows:



Release information is found on the cover page and at the bottom of every page of a document.

Documents in this library

The *Technical Reference Library* consists of three volumes of information and a *Guides and Shelf Setup* module. See [Document content description on page 1-4](#) for a description of each document.

Guides and Shelf Setup

| | |
|--------------|---|
| 323-1059-090 | About the OPTera Metro 3500 NTP Library |
| NTRN10AM | Planning and Ordering Guide |
| NTRN15AA | Interworking Application Guide |
| NTRN16AA | Network Interoperability Guide |
| 323-1059-201 | Installation |
| 323-1059-210 | Commissioning |
| 323-1059-222 | System Testing |
| 323-1059-180 | DWDM Application Overview |

Note: NTP 323-1059-180 (DWDM Application Overview), has changed to *DWDM Application Guide*, NTRN12AA. This guide is now listed as an associated document to the Technical Reference Library.

Volume 1 TL1 Reference

| | |
|--------------|---|
| 323-1059-090 | About the OPTera Metro 3500 NTP Library |
| 323-1059-190 | TL1 Reference |

Volume 2 Operations, Administration and Provisioning

| | |
|--------------|---------------------------------------|
| 323-1059-224 | System Reconfiguration |
| 323-1059-302 | Security and Administration |
| 323-1059-310 | Provisioning Synchronization |
| 323-1059-311 | Protection Switching |
| 323-1059-320 | Bandwidth Management |
| 323-1059-350 | Provisioning Equipment and Facilities |

Volume 3 Maintenance

| | |
|--------------|----------------------------|
| 323-1059-510 | Performance Monitoring |
| 323-1059-520 | Network Surveillance |
| 323-1059-543 | Alarm and Trouble Clearing |

Document identification numbers

User documents for the OPTera Metro 3500 shelf are referred to as Nortel Networks technical publications (NTP). Each NTP has a unique ten-digit identification number called an NTP number. This number is used to identify each document, and assist in cross-referencing from one NTP to another. In some instances, an alphanumeric product engineering code (PEC) is assigned to NTPs that are separately orderable.

The NTP number is found on the cover page and at the bottom of every page in a document.

Associated documents

The following are supporting documents to the *Technical Reference Library*:

- Change Application Procedures (CAPs)
- *DWDM Application Guide*, NTRN12AA
- *Data Communications Network Planning Guide*, NTR710AM
- *Site Manager Planning and Installation Guide*, NTN35FA
- *OPTera Packet Edge System Planning Guide*, NTRN10YK
- *OPTera Packet Edge System Network Applications and Management*, NTRN11YK
- *OPTera Packet Edge System User Guide*, NTN465YG

Note: For more information on Site Manager, user documentation and the *Site Manager Planning and Installation Guide*, see [Site Manager and user documentation on page 1-7](#).

NTP product engineering codes

A product engineering code (PEC) is assigned to each unique Nortel Networks product, including NTPs. The PEC is used to identify the product when ordering from Nortel Networks. The PEC is found on the cover page of each document. [Table 1-1](#) shows the PECs for OPTera Metro 3500 Multiservice Platform NTPs.

Table 1-1
Release 12.0 PECs for OPTera Metro 3500 NTPs

| Document Name | PEC code |
|--|----------|
| Guides and Shelf Setup module Note: The Guides and Shelf Setup module (NTN469GF) is automatically included when you order the Technical Reference Library (NTN465GF) | NTN469GF |
| Technical Reference Library (Volumes 1, 2 and 3) including the Shelf Setup and Planning Guide Note: The Guides and Shelf Setup module (NTN469GF) is automatically included when you order the Technical Reference Library (NTN465GF) | NTN465GF |
| Planning and Ordering Guide | NTRN10AM |
| Interactive CD-ROM Technical Reference Library | NTN464GF |
| Helmsman CD-ROM Technical Reference Library | NTN464ZG |

Ordering NTPs

NTPs can be ordered from Nortel Networks. To order NTPs, use the PEC corresponding to the document when placing your order. For complete ordering information, see the *OPTera Metro 3500 Multiservice Platform Planning and Ordering Guide*. To obtain a copy of the planning and ordering guide, call 1-800-4NORTEL.

Document content description

The following describes the content of each OPTera Metro 3500 Multiservice Platform NTP or guide that is part of the *Guides and Shelf Setup* module (NTN469GF) and the *Technical Reference Library* (NTN465GF).

About the OPTera Metro 3500 NTP Library, 323-1059-090

About the OPTera Metro 3500 NTP Library provides an overview of the NTP suite, a consolidated list of terms and abbreviations, and a master index to use in searching for information in the *Technical Reference Library*.

Planning and Ordering Guide, NTRN10AM

The *Planning and Ordering Guide* for the OPTera Metro 3500 Multiservice platform provides descriptive information essential for planning a network and the means for ordering equipment, documentation, and support services.

The *Planning and Ordering Guide* is for network planners, system administrators, provisioners, transmission standards engineers, and maintenance personnel.

Interworking Application Guide, NTRN15AA

The *Interworking Application Guide* describes interworking configurations between the following Nortel Networks products:

- the OPTera Connect DX optical switch and the OPTera Metro 3300/OPTera Metro 3400/OPTera Metro 3500 Multiservice Platforms
- the OPTera Connect HDX optical switch and the OPTera Metro 3300/OPTera Metro 3400/OPTera Metro 3500 Multiservice Platforms
- the OPTera Connect DX/OPTera Connect HDX optical switch and the S/DMS TransportNode OC-48/TN-16X
- the S/DMS TransportNode OC-48 and the OPTera Metro 3300/OPTera Metro 3400/OPTera Metro 3500 Multiservice Platforms

This document is intended to help network planners design networks that contain these products. This document is also intended to help network operators configure and operate interconnections between these products.

Network Interoperability Guide, NTRN16AA

The *Network Interoperability Guide* describes the steps that you must take when you connect non-Nortel Networks equipment with Nortel Networks equipment. The Interoperability Guide covers both SONET and SDH protocols and includes information on interoperability principles, provisioning and troubleshooting.

The *Network Interoperability Guide* is for network planners, provisioners, transmission and standards engineers, network administrators, and system lineup and testing (SLAT) personnel.

Installation, 323-1059-201

Installation enables installation personnel to install the OPTera Metro 3500 Multiservice Platform network element.

Installation is for installation personnel.

Commissioning, 323-1059-210

Commissioning provides the procedures for commissioning the OPTera Metro 3500 network processor and shelf processor. Tasks included are changing the password, adding user accounts, and setting time and date.

Commissioning is for local craft personnel, and system administrators.

System Testing, 323-1059-222

System Testing describes the system and site testing procedures for the OPTera Metro 3500 Multiservice Platform network element. *System Testing* consists of verifying optical path continuity and system level switching.

System Testing is for local craft personnel, installation personnel and system administrators.

TL1 Reference, 323-1059-190

TL1 Reference provides details of the Transaction Language 1 (TL1) user interface implementation on the network element.

Topics covered in *TL1 Reference* include TL1 message common structure, syntax, and description of each TL1 message parameter.

TL1 Reference is for network planners, system administrators, provisioners, transmission standards engineers, and maintenance personnel.

System Reconfiguration, 323-1059-224

System Reconfiguration provides nodal reconfigurations, network reconfigurations, and reconfigurations for DWDM systems.

System Reconfiguration is for local craft personnel and system administrators.

Security and Administration, 323-1059-302

Security and Administration provides procedures for the administrative tasks on a network element, including user account administration, network element name, and time and date settings. *Security and Administration* also provides the procedures for saving and restoring provisioning data, and upgrading the network processor.

Security and Administration is for network planners and system administrators.

Provisioning Synchronization, 323-1059-310

Provisioning Synchronization provides procedures to synchronize each network element in a network and provision timing from a building-integrated timing supply (BITS).

Provisioning Synchronization is for network planners, system administrators, provisioners, transmission standards engineers, and maintenance personnel.

Protection Switching, 323-1059-311

Protection Switching provides procedures for protection switching in 1+1 linear, UPSR and BLSR configurations. Included in *Protection Switching* are the procedures for operating and releasing protection switches on tributary and optical circuit packs.

Protection Switching is for local craft personnel and system administrators.

Bandwidth Management, 323-1059-320

Bandwidth Management provides the procedures for configuring networks, provisioning cross-connects, and performing in-service traffic rollovers.

Bandwidth Management is for network planners, system administrators, provisioners, transmission standards engineers, and maintenance personnel.

Provisioning Equipment and Facilities, 323-1059-350

Provisioning Equipment and Facilities explains how to add and change equipment, facilities, services and SDCC for optical interface circuit packs on the network element.

Provisioning Equipment and Facilities is for network planners, system administrators, provisioners, transmission standards engineers, and maintenance personnel.

Performance Monitoring, 323-1059-510

Performance Monitoring includes procedures for performance monitoring parameter definition and monitoring.

Performance Monitoring is for network planners and surveillance personnel.

Network Surveillance, 323-1059-520

Network Surveillance provides the procedures for provisioning telemetry byte-oriented serial (TBOS). It provides path and section trace procedures as well as network processor and TARP provisioning.

Network Surveillance is for network planners and surveillance personnel.

Alarm and Trouble Clearing, 323-1059-543

Alarm and Trouble Clearing provides procedures for network alarm monitoring and management, trouble clearing, and circuit pack replacement.

Alarm and Trouble Clearing provides the procedures used to identify, isolate and resolve local and remote operational difficulties with the network element.

Alarm and Trouble Clearing is for network surveillance and maintenance personnel.

Site Manager and user documentation

The Site Manager graphical user interface (GUI) is available for the OPTera Metro 3500 Multiservice Platform network element. Site Manager provides a simple-to-use point-and-click user interface that enables you to perform operation, administration, and maintenance of the OPTera Metro 3500 Multiservice Platform network element.

User documentation for Site Manager is provided on-line and on paper. The installation and setup instructions are available in the *Site Manager Planning and Installation Guide*. The *Site Manager Planning and Installation Guide* explains the minimum hardware platform requirements for operation of Site Manager, and how to install the software.

Release history

The following information describes the feature content and NTP restructuring of this release and previous standard releases.

OPTera Metro 3500 Release 12.0

November 2003 OPTera Metro 3500 Multiservice Platform Release 12.0 introduces

- BLSR Line Protection Oscillation Control
- Intrusion Detection enhancements
- Generic Framing Procedure (GFP) and Virtual Concatenation (VCAT) support for Gigabit Ethernet and Fibre Channel (FC-100 and FICON)
- General Broadcast tool
- Modifiable Login Banner
- OPTera Packet Edge (OPE) enhancements
- Optical Loopback enhancements
- Performance monitoring threshold crossing alerts (TCA)
- STS Managed DSM
- Support for 12 DSM
- Test Access enhancements
- Third Level 5 User Support / Increased SOC visibility to 16 network elements per Level 5 user
- 1 new OC-192 IR circuit pack
- 1 new OC-192 LR G.709 FEC circuit pack
- 9 new OC-192 DWDM G.709 FEC circuit packs (Band 1, Channel 1 through to Band 2, Channel 4 and 1535.04 nm)
- 3 new OC-48 STS (single slot) circuit packs (SR, IR-2 and LR)
- 1 new OC-12x4 STS (single slot) circuit pack (IR)
- 1 new 2xGigE/FC-P2P (point-to-point) circuit pack supporting GFP and VCAT
- Small form-factor pluggables (SFP) for new 2xGigE/FC-P2P circuit pack
- 1 new STX-192 circuit pack

Documentation Changes

The NTP Library has expanded from two volumes to three volumes:

- Volume 1: TL1 Reference
- Volume 2: Operations, Administration and Provisioning
- Volume 3: Maintenance

NTP 323-1059-090 (About the OPTera Metro 3500 NTP Library) is now included in the Guides and Shelf Setup module.

The Planning and Ordering Guide (NTRN10AM) has expanded into two parts.

NTP 323-1059-180 (DWDM Application Overview) has been removed from the NTP Library. DWDM application information is now located in the DWDM Application Guide (NTRN12AA).

NTP 323-1059-190 (TL1 Reference) has expanded from three parts to four parts.

Alarm clearing procedures for alarms A through K (inclusive) have been moved from part 2 to part 1 of NTP 323-1059-543 (Alarm and Trouble Clearing).

OPTera Metro 3500 Release 11.0

- April 2003 OPTera Metro 3500 Multiservice Platform Release 11.0 introduces
- Resilient Packet Rings (RPR) support up to 16 nodes
 - BLSR wait-to-restore period supports the 'infinite' parameter
 - Optical Ethernet - Private Line (10/100 Ethernet point-to-point) service
 - Optical Ethernet - Private Line (Gigabit Ethernet point-to-point) service
 - Alarm flow control
 - Channelized DS3 service (DS3VTx12 circuit pack)
 - Common Language Location Identifier (CLLI)
 - OPE Distributed multilink trunking
 - Full VT Access on BLSR pass-through nodes
 - OC-48 physical PMs
 - Optical loopbacks
 - OPE: RPR bandwidth reservation
 - Protection performance monitoring parameters for optical facilities
 - 'Save and Restore' enhancements
 - Centralized Security Administration (CSA)
 - OPE: increased number of TDIs on a mapped UNI
 - Test access
 - Time of day synchronization
 - TL1 event / log feature
 - Topology enhancements
 - 9 new OC-48 ER DWDM circuit packs
 - 16 new OC-48 LR DWDM circuit packs (L-Band).
 - L-Band coverage by 4 new OMX + Fiber Manager 4CH

OPTera Metro 3500 Release 10.1

- June 2002 OPTera Metro 3500 Multiservice Platform Release 10.1 introduces support for the rear-facing I/O modules, DS3x12e, and EC-1x12 circuit packs. Supported configurations include both UPSR and linear point to point as well as BLSR at the OC-48 line rate. Security enhancements and connection ID features have also been introduced.

Documentation Changes

The Quick Configuration Guide, TL1 Quick Reference Booklet and Network Element description have been removed from the NTP suite. The circuit pack, technical specifications and feature descriptions previously given in the Network Element description, have been moved to the Planning and Ordering Guide (NTRN10AK).

OPTera Metro 3500 Release 9.0

July 2001 OPTera Metro 3500 Multiservice Platform Release 9.0 introduces support for the 2xGigE and 4x100FX OPTera Packet Edge System circuit packs on the OPTera Metro 3500 shelf. Also introduced in Release 9.0 is the DS1 service module, which provides up to 84 DS1 connections. Release 9.0 supports both UPSR and linear point to point network configurations at the OC-12 and OC-48 line rates.

Documentation changes

The Quick Configuration Guide (NTN468GC) has been added to the NTP suite, and can be ordered separately. The Ordering Guide and Planning Guides have been merged in to one document (NTRN10AJ). This document forms part of the NTP suite, and can be ordered separately.

The Installation NTP was restructured to segregate Commissioning tasks from installation activities. The Commissioning tasks are now covered in a separate NTP.

OPTera Metro 3500 Release 8.1

November 2000 OPTera Metro 3500 Multiservice Platform Release 8.1 introduces support for the DS3x12 and OPE circuit packs on the OPTera Metro 3500 shelf. Release 8.1 also supports the linear point to point network configuration at the OC-48 line rate.

Documentation changes

The System Reconfiguration NTP (323-1059-224) has been added to the NTP suite.

OPTera Metro 3500 Release 8.0

September 2000 OPTera Metro 3500 Multiservice Platform Release 8.0 introduces the OPTera Metro 3500 product to the OPTera Metro 3000 Multiservice Platform series (formerly Express). OPTera Metro 3500 provides the functionality and features of the OPTera Metro 3300 and 3400 Multiservice Platforms (formerly Express MX and HX), but includes an increase in line rate and switching to OC-48 bandwidth. The OPTera Metro 3500 provides full OC-48 connectivity to the customer premises.

Release 8.0 offers dense wavelength division multiplexing (DWDM) with time-division multiplexing (DS1, DS3, OC-3, OC-12, and OC-48) services. Release 8.0 introduces the OPTera Metro 3500 shelf, the DS3x3 mapper, and the OC-3x4 circuit pack.

Release 8.0 also introduces the Site Manager graphical user interface to the OPTera Metro 3000 Multiservice Platform series.

List of terms

1+1 protection

A protection switching scheme in which two equivalent channels carry the same traffic, but one is protection and one is working. The 1+1 protection switching scheme is nonrevertive.

1:N protection

A protection switching scheme in which one standby protection channel protects failures on any of the N working channels (revertive switching).

1:1 protection

A protection switching scheme in which one standby protection channel protects failures on one working channel.

1WAYPR

unidirectional path ring

2WAYBR

bidirectional bridged ring

4x100BT

4x100BT OPTera Packet Edge circuit pack (formerly called iPT100)

4x100FX

4x100FX OPTera Packet Edge circuit pack

2xGigE

2xGigE OPTera Packet Edge circuit pack

2xGigE/FC-P2P

2xGigE Fibre Channel point-to-point circuit pack

ACO

alarm cut-off

A push-button switch located on the OPTera Metro 3500 left interface (LIF) that disables an audible alarm.

ADM

add/drop multiplexer

A network element in which some facilities are added or dropped and some are passed directly through for transmission to other network elements.

AID

access identifier

An access identifier (AID) appears in most command argument strings. The AID identifies the equipment or facilities accessed by the command.

AINS

auto-in-service

AINS-DEA

auto-in-service-deactivated

AIS

alarm indication signal

A code sent to downstream sites to indicate an upstream failure (used to prevent unnecessary downstream alarms).

alarm cut-off

See [ACO](#) on page 3-2.

AMI

alternate mark inversion (line code, bipolar)

A digital line encoding technique for which a zero is transmitted by no pulse, while a one is transmitted by a pulse opposite in polarity to the previous pulse.

ANSI

American National Standards Institute

An organization supported by U.S. industry to coordinate, develop, and publish standards.

APDFET

avalanche photo diode field-effect transistor

A transistor that uses an avalanche photo diode to convert photons to electrons.

This transistor exhibits very high gain and is used in more sensitive optical receivers.

APS bytes

Automatic Protection Switching bytes

The K1 and K2 bytes of the SONET transport overhead of a line carrying protection channels.

ARP

address resolution protocol

A transmission control protocol/internet (TCP/IP) that dynamically binds a network-layer IP address to a data-link-layer hardware address; for example, an Ethernet address.

ATAG

automatic tag

A unique numeric string generated by the system.

ATM

asynchronous transfer mode

A high-speed connection-oriented multiplexing technology that uses 53-byte cells to transmit data.

B3ZS

bipolar three zero substitution

B8ZS

bipolar eight zero substitution

bandwidth

The difference, in hertz (Hz), between the lowest and highest frequencies of a transmission channel. The range of signal frequencies transmitted by a communications channel with defined maximum loss or distortion. Bandwidth indicates the information carrying capacity of a channel.

BCC

Bay command console

BCVL

line bipolar code violation

For more information, see [323-1059-510, Montype parameter definitions on page 1-51](#).

BER

bit error ratio

A measure of transmission accuracy expressed as a ratio of bit errors received to bits sent.

BESL

line bipolar errored second

For more information, see [323-1059-510, Montype parameter definitions on page 1-51](#).

bidirectional ring

A ring in which all nodes send and receive duplex traffic by traversing the same set of nodes for both directions of transmission under normal circumstances.

bidirectional switching

A bridge to protection channel and a selection from a protection channel of both directions of duplex traffic.

BIP

bit-interleaved parity

bit

binary digit

The smallest unit of information in a binary system represented as a 0 (zero) or as a 1 (one).

bit/s

bits per second

The unit used to express transmission rate.

BITS

building-integrated timing supply

All digital equipment in a structure receives timing from the same master clock, which must be the most accurate and stable clock in the structure. The BITS is driven by a stratum 3 or better reference signal and sends a DS1 signal to all equipment in the same location.

BLSR

bidirectional line-switched ring

A method of SONET transport over a ring configuration for which half of the available channels are working and half are considered protection channels. The traffic is bidirectional. Half of the traffic is sent counter-clockwise over another fiber according to the path provisioned. The ring uses the line level status and performance parameters to initiate Automatic Protection Switching (APS). APS in BLSR is aligned such that working channels 1 through 24 are protected by channels 25 through 48 respectively.

BPV

bipolar violation

An error in the transmission of bipolar signals when two successive marks have the same polarity.

BR

bridged ring

A bidirectional connection at a matched-node network element. A path is selected based on a signal being dropped from the endpoint specified as the FromAID and its default or specified switch mate, to the endpoint specified as the ToAID. Traffic is also passed through from the FromAID to the Switch Mate, to continue around the ring and exit at the other matched node. Traffic is added to the ring in the reverse direction, from the endpoint specified as the ToAID to the endpoint specified as the FromAID.

bridge

The action of transmitting identical traffic on both the working and protection channels.

bridge request

A message sent from the tail-end node to the head-end node requesting the head-end perform a bridge of the working channels onto the protection channels.

bridge request status

A message sent from the tail-end node to all other nodes within the protection system (on the path not carrying the protection channels to be used) indicating the tail end has requested a bridge.

bridging to protection

The action of transmitting identical traffic on both the working and the protection channels.

BSESL

bipolar severely errored seconds count - line

The count of 1-second intervals that contain 51 or more bipolar code violations or a loss-of-signal event.

For more information, see [323-1059-510, Montype parameter definitions on page 1-51](#).

byte

A group of eight binary digits or eight signal elements representing binary digits operated upon as an entity.

CAP

change application procedure

Nortel Networks document used to perform an in-service upgrade or reconfiguration with no effect on traffic.

CBR

constant bit rate

An ATM service category which supports a constant or guaranteed rate to transport services which require rigorous timing control and performance parameters.

CCITT

Consultative Committee on International Telephone and Telegraph

This committee is now replaced by the International Telecommunications Union—Telecommunications (ITU-T). The CCITT prepared a series of recommendations for telecommunications protocol.

See also [ITU-T on page 3-16](#).

CD-ROM

compact disk read-only memory

A read/write digital optical storage device of high capacity.

CI

command interpreter

A support operating system component that functions as the main interface between machine and user.

CLE

customer located equipment

Equipment located on customer premises that provides access to the operating company network.

CLEI

common language equipment identifier

A trademark of Bell Communications Research. It is a standard identification method for telephony equipment.

CLI

command line interface

The TL1 command line interface in the TL1 Command Builder.

CLNP

connection less network protocol

COLAN

central office local area network

A facility on the network processor that allows Preside to communicate with the OPTera Metro 3000 network using TCP/IP and Ethernet protocols.

Comm Log

A dialog box accessible from the File menu in Site Manager. The dialog box contains messages sent between Site Manager and the network elements Site Manager is connected to.

correlation tag

The sequential command identifier with every command input for the TL1 interface. The identifier is called a correlation tag (CTAG).

The format of the CTAG can be used to reflect its purpose, for example, JOB28, and TAG33.

CPE

customer premises equipment

Equipment located on the customer premises that is connected to the telephone line.

CPU

central processing unit

A functional unit that interprets and executes program instructions. The CPU transmits and receives data from the memories and peripheral units of the computer.

craft personnel

maintenance personnel

Employees assigned the routine recurring work required to keep a facility, such as a fiber optic transmission system, plant, building, structure, ground facility, or utility system, in such condition that it may be continuously used (a) at its original or designed capacity and efficiency and (b) for its intended purpose.

cross-connect

Connections between terminal blocks on the two sides of a distribution frame, or between terminals on a terminal block.

CTAG

See [correlation tag on page 3-8](#).

CVL

line code violation

The count of the bipolar code violations on the DS3 line.

CVP

path code violation

The count of parity errors on the DS3 path.

CVS

section code violation

The count of bit-interleaved parity errors at the section layer.

dB

decibel

dBm

Decibels above one milliwatt.

dc

direct current

DCE

data communication equipment

The devices and connections of a communications network that connect the communication circuit between the data source and destination.

DCP

drop and continue on protection

A scheme used for matched-node configurations.

DCW

drop and continue on working

A scheme used for matched-node configurations.

demarcation point

Point of connection between one end of a data transmission circuit and the terminal facilities.

Note: This term does not mean the boundary for installation and maintenance.

DISCD

disconnected - not carrying traffic

DMS

digital multiplex system

A central office switching system in which all external signals are converted to digital data and stored in assigned time slots. Switching is performed by reassigning the original time slots.

DS1

digital signal, level 1 (1.544 Mbit/s)

The 8-bit, 24-channel, 1.544 Mbit/s digital signalling format. DS1 is the North-American standard for digital links and the standard for signals used to interconnect Nortel Networks digital systems.

DS1 service module (DSM)

The DS1 service module is an extension unit of the OPTera Metro 3500 shelf that can multiplex up to 84 DS1 signals, into and from the OPTera Metro 3500 shelf, through an OC-3 SONET interface. The OC-3 line is linked to an OC-3 tributary known as the Host Link on the OPTera Metro 3500 shelf. A single OPTera Metro 3500 shelf can be connected to eight protected DS1 service modules, or eight unprotected DS1 service modules, or a combination of both. The DS1 service module may be connected to an OPTera Metro 3500 shelf using an OC-3 or OC-3x4 circuit pack.

DS1TM

DSM DS1x84 termination module

DS1TM is the term used in Site Manager to identify the DSM DS1x84 termination module.

DS3

digital signal, level 3 (44.7 Mbit/s)

A serial data stream carrying 28 DS1 signals plus overhead bits.

DSM DS1x84 TM

DSM DS1x84 termination module

The DSM DS1x84 termination module is developed for use in the DS1 service module. The DSM DS1x84 termination module supports 84 DS1 facilities.

DTE

data terminal equipment

Equipment which serves as a data transmitter, data receiver, or both. DTE controls information transfer according to a data link protocol, and reconverts the received data signals into user information.

DWDM

dense wavelength division multiplexing

DWDM is a transmission technique of multiplexing on the optical layer. In OPTera Metro 3500, DWDM allows up to 34 optical wavelengths to be transmitted over a single fiber.

EBER

excessive bit error rate

See also [BER](#) on page 3-4.

EC-1

electrical carrier level 1 (51.84 Mbit/s).

EOL

end of life

Stage at which either the hardware or the software has reached the end of its useful function or no longer meets business requirements.

ESD

electrostatic discharge

Sparks generated by static electricity that can damage integrated circuits.

ESL

line errored second

The count of 1-second intervals at the line layer that contain one or more line code violations, alarm indication signals, or loss-of-signal events.

ESP

path errored second

The count of 1-second intervals on the DS3 path that contain one or more path code violations, out-of-frame events, or alarm indication signals.

ESS

section errored second

The count of 1-second intervals at the section layer that contain one or more section code violations, out-of-frame events, or loss-of-signal events.

ESWD

electronic software delivery

exerciser

See [high-speed exerciser on page 3-14](#).

external timing

A synchronization scheme in which timing for a network element is provided by an external source such as BITS.

fault indicator

A device that presents a visual display or audible alarm when a failure or marginal condition exists.

FC

ferrule connector

A mechanical fixture, generally a rigid tube, used to confine the stripped end of a fiber bundle or a fiber.

FC

fibre channel

The Fibre Channel Standard defines a high-speed data transfer interface that can be used to connect together workstations, mainframes, supercomputers, storage devices and displays. This standard addresses the need for very fast transfers of large volumes of information and provides one standard for networking, storage and data transfer.

FCL

line failure count

The count of failure events at the line layer.

FCP

path failure count

The count of failure events on the DS3 path.

FCS

frame check size

Size of the frame used to transmit packets.

FFP

facility fault protection group

Used for 1+1 line switching.

FGRP

facility group

FLT

fault

The secondary state indicating that a fault has been detected in equipment.

freerun timing

A timing scheme in which a free-running clock in the transport interface circuit pack provides timing for a network element.

fromAID

from access identifier

The facility at one end of a cross-connect.

FTAM

file transfer, access, and management

FTP

file transfer protocol

The file-sharing protocol operating at layers 5 through 7 of the open systems interconnection (OSI) model that governs file-sharing and file-transfer capabilities.

full-duplex mode

In full-duplex mode, LAN traffic is transmitted and received simultaneously.

Gbits

gigabits per second

GCF

gateway control function

GCF indicates the session you are in is hosted by a network processor.

GFP

generic framing protocol

Protocol used to encapsulate Ethernet frames or to carry Fibre Channel (FC) traffic.

GigE

Gigabit Ethernet

GUI

graphical user interface

A display format that allows the user to choose commands, start programs, and see lists of files.

half-duplex mode

The mode where LAN traffic is transmitted or received alternately.

HBA

host bus adapter

high-speed exerciser

The high-speed exerciser tests the integrity of the protection switching bytes (K-bytes) communication between a SONET optical interface pair configured in a linear 1+1 or BLSR protected system.

hub

A network element that accepts several inputs originating from different areas.

A point on a network where a group of circuits are connected and provide centralized management capabilities. Hubs are useful for their ability to isolate nodes from disruptions.

ICMP

internet control message protocol

ICMP group

internet control message protocol group

IF group

interface group

The interface group provides configuration information, such as the interface type and speed, the status of the interface, incoming and outgoing traffic statistics, and counts of interface packet errors.

I/O modules

The modules that provide input and output of electrical signals for the traffic in OPTera Metro 3500.

The I/O modules, both front and rear facing, are removable and replaceable. The OPTera Metro 3500 I/O modules include the DS1 1-28 I/O module, DS1 29-56 I/O module, DS1 29-84 I/O module, 8xRJ45 module, and 12 Port I/O module.

ILAN

intershef local area network

A facility that allows the network processor to communicate with the co-located shelf processor using SONET-defined OSI protocols.

ILAN circuit pack

The ILAN circuit pack provides Ethernet hubbing functionality required to interconnect OPTera Metro 3000 shelves.

The ILAN circuit pack provides a low cost solution to Ethernet connectivity between OPTera Metro 3000 multiservice platform series, as well as the capability to daisy-chain up to 16 OPTera Metro 3000 shelves.

IP

Internet protocol

A direct outward dialing (DOD) standard protocol designed for use in interconnected systems of packet-switching computer communication networks.

IS

in-service

An indication that some element of the network is carrying traffic or is ready to carry traffic. Standby units that are IS are prepared to carry traffic.

See also [OOS on page 3-23](#).

IS-ANR

in-service - abnormal, or partial failure detected

ISCR

in-service channel rollover

ISO

International Organization for Standardization

The ISO technical committee was created to provide standards on the area of quality management and quality assurance in a common language for a global audience.

ISRR

in-service route rollover

ISTR

in-service traffic rollover

The ability to switch active traffic from one cross-connect endpoint to another within the transport network. In BLSR, there is route and channel rollover.

ITU-T

International Telecommunications Union—Telecommunications

An international organization with headquarters in Geneva, Switzerland that makes recommendations for standardization of telecommunications and functions through international committees of telephone administrations and private operating agencies. The ITU-T makes recommendations applying to the industry, administrations and agencies. This replaces the former committee known as CCITT.

kbit

kilobit

For processor storage, real and virtual storage, and channel volume, 1024 bits.

See also [bit](#) on page 3-4.

kbit/s

kilobits per second

The number of binary digits transmitted over a communications channel in one second. Standard measure of data rate and transmission capacity; 1024 bits per second.

See also [bit on page 3-4](#).

kbyte

kilobyte

See also [byte on page 3-6](#).

kHz

kilohertz

A measurement of frequency. One thousand cycles per second.

LAN

local area network

A data communications system that lies within a limited geographic area, has a specific user group, has a specific topology, and is not a public switched telecommunications network, but may be connected to one. A LAN has a moderate to high data transmission rate, and supports shared media. Examples of LAN technologies are Ethernet, token ring, and fiber-distributed data interface (FDDI).

LAPB

link access procedure balanced

The link layer for the X.25 protocol. LAPB provides two-way simultaneous communication between the data terminal equipment (DTE) and the data communication equipment (DCE) at the network gateway.

LAPD

link access procedure D-channel

LAPD is a protocol that operates at the data link layer (layer 2) of the OSI architecture.

laser

light amplification by stimulated emission of radiation

Amplification of light by a device that produces an intense, coherent, directional beam of optical radiation by stimulating electronic, ionic, or molecular transitions to higher energy levels, so that when the electrons, ions, or molecules return to lower energy levels, they emit energy.

leased circuit service office

Offices engaged in the business of leased circuit services.

LED

light-emitting diode

A semiconductor diode that emits light when a current is passed through it.

LI

line interface

Refers to the connection requirements at one end of the transmission system for subscriber lines. It is the terminal on the LT (line termination) side of the NT (network termination).

LIF

left interface

One of the core circuit packs of OPTera Metro 3500 network element. The LIF provides connections to the Left OAM (LOAM) and inventory interconnect for power interfaces.

line (SONET)

The segment of a fiber transmission system between network elements where traffic originates and terminates.

line timing

A synchronization scheme in which timing for a network element is derived from the primary or secondary receive line.

LOAM

left OAM

An extender attached onto the left interface (LIF) of OPTera Metro 3500 network element. The LOAM contains connections for the RS-232 terminal, telemetry byte-oriented serial protocol (TBOS), environmental alarms, shelf alarms, X.25 terminal, intershelf LAN, and central-office local-area network (COLAN).

LOF

loss of frame

An alarm where the system is unable to detect a framing indication on the optics signal. The framing indication is a specific pattern of bits that varies depending on traffic. This alarm condition corresponds to an information loss greater than 2 seconds. *See also* [OOF on page 3-23](#).

LOP

loss of pointer

A fault, for example, a circuitry failure, as the misplacement of the address of a memory location. An alarm that occurs when a path endpoint detects a corrupt pointer for 2.5 seconds. The pointer is a mechanism used by the logical path to indicate where data starts in the payload of a frame.

LOS

loss of signal

A fault, for example, a circuitry failure, as the misplacement of telecommunications information. LOS can be caused by an optical signal failure.

LT

line termination

Terminal equipment installed within a leased circuit service office.

MAC

medium access control

A protocol governing access from a station to a network.

Magic number

The magic number is used during PPP negotiation only. When enabled, the magic number field is four octets and helps in detecting looped back links. A random string is sent across the link and if the same value is returned, then the circuit pack determines that the link is looped back and the negotiation fails. If this occurs, a "Link Down" alarm is raised against the WAN port. When disabled, the magic number is always transmitted as zero and is always ignored on reception.

Mbit/s

megabits per second

One megabit per second is equivalent to 1 048 576 bits per second.

MEA

mismatched equipment attributes

MHz

megahertz

One million cycles per second. A unit of frequency denoting one million Hz.

MIB

management information base

All data accessible by the end user is stored in the MIB. The MIB is a tree structure where each leaf of the tree represents a field in the MIB. Internal nodes in the tree depict group information. The MIB defines the field name, type of the field (such as string, unsigned integer, and counters), access type and position in the tree.

MLM

multi longitudinal mode laser, or multi mode laser

An injection laser diode which has a number of longitudinal modes.

MOA

Multiservice Managed Object Agent

See [Multiservice MOA on page 3-21](#).

modem

modulator demodulator

A device that modulates and demodulates signals for transmission and reception, respectively, over communication facilities. Modems convert digital signals into quasi-analog signals for transmission and reconvert the quasi-analog signals into digital signals. Other functions may be added to modems to provide for customer service and control features.

Multiservice MOA

Multiservice Managed Object Agent

UNIX software that allows Preside (network management software) to communicate with the OPTera Metro 3000 Multiservice Platforms.

navigation area

The left side of the Site Manager (see [Preside Site Manager on page 3-27](#)) main window. When you connect to a network processor (NP), the navigation area displays the NP and displays the network elements (NEs) in the NP span of control as items branching from the NP. Use the navigation area to select an NP or an NE to view or edit details.

navigation tree

The network elements within a network processor span of control as represented in the navigation area (see [navigation area on page 3-21](#)) as items branching from the network processor.

NE

See [network element on page 3-21](#).

network element

A collection of equipment that performs some operation in routing or transporting a telecommunications signal.

network processor

A circuit pack on OPTera Metro 3000 shelves that sets up connections for the network to communicate with external equipment such as Preside, Multiservice MOA, other OSSs, or a PC.

non-revertive switch

When the condition that caused a switch to protection is corrected, the traffic remains on the protection channels until another bridge request. Traffic does not automatically revert to its working channel.

NP

See [network processor on page 3-21](#).

NPx

network processor extended. See [network processor on page 3-21](#).

The network processor used on OPTera Metro 3500 shelves running Release 9.0 software or later version.

NSA

non-service-affecting

NSAP

network service access point

A number used internally in a SONET communications network to address a network element. The NSAP is a number up to forty hexadecimal digits.

NT

network termination

Equipment which converts data signals from the terminal equipment (TE) into suitable transmission mode, then sends such converted signals to the circuits. The NT also restores converted signals which have already been transmitted through the circuits back to the original data signals, then sends the restored signals to the TE.

NTP

Nortel Networks technical publication

A technical document that is intended to assist operating company personnel with the operations, administration, maintenance and provisioning of Nortel Networks products, including both hardware and software.

NVS

nonvolatile storage

Storage in which the contents are not permanently lost when power is removed, but become available again when power is restored.

OAM

operations, administration, and maintenance

All the tasks necessary for providing, maintaining, or modifying the services provided by a switching system.

OAM&P

operations, administration, maintenance, and provisioning

OC-1

An STS-1 signal translated into an optical signal.

OC-n

An optical carrier signal in the SONET optical format which is n times (where n is an integer) the OC-1 rate. For example, OC-1, OC-3, OC-12, OC-48, OC-192.

OMX

optical multiplexer

Equipment that uses a passive optical coupler to combine various wavelengths over a single fiber-optical cable.

OOF

out of frame

An event or an alarm where the system is unable to detect a framing indication on the optics signal. The framing indication is a specific pattern of bits that varies depending on the traffic. This alarm condition corresponds to an information loss of less than 2 seconds.

See also [LOF on page 3-19](#).

OOS

out-of-service

An equipment state in which equipment is removed from service either automatically (by the system) or manually (by personnel).

See also [IS on page 3-15](#).

OOS-AU

In-service; failure detected.

OOS-AUMA

Out-of-service autonomous management - the entity is not able to perform its provisioned functions and is intentionally removed from service.

OOS-MA

Out-of service maintenance for provisioning memory administration

OOS-MA-ANR

Out-of-service - maintenance - abnormal or partial failure detected

OPC

operations controller

OPM

optical power meter

Test equipment designed to measure power and attenuation within optical fiber cable.

OPTera Metro 3000

Nortel Networks OPTera Metro 3000 multiservice platform series

The OPTera Metro 3000 includes the series of OPTera Metro products 3100, 3300, 3400, and 3500.

The OPTera Metro 3000 network element provides transport for traffic in a SONET environment. A typical application for the network element is a small business park, where the network element can provide up to 2016 phone lines for voice and data communications. The simplicity and cost effectiveness of the OPTera Metro 3000 make it a logical choice for this small scale environment.

OPTera Metro 3100

Formerly Express CX.

See [OPTera Metro 3000](#) on page 3-24.

OPTera Metro 3300

Formerly Express MX.

See [OPTera Metro 3000](#) on page 3-24.

OPTera Metro 3400

Formerly Express HX.

See [OPTera Metro 3000](#) on page 3-24.

OPTera Metro 3500

Formerly Express GX.

See [OPTera Metro 3000](#) on page 3-24.

optical interface circuit pack

Any supported circuit pack that has an optical interface (OC-3, OC-12, OC-48) installed in shelf slots eleven and twelve.

OS

operations system

Software that controls the management and execution of programs.

OSI

open systems interconnection

A seven-layer reference model that defines a structured protocol suite for data communication. A suite of communication protocols, network architectures, and network management standards produced by the International Organization for Standardization (ISO).

OS-NE

operations system - network element interface.

OSS

operations support system

A network management application providing record keeping tasks such as work orders, invoicing, and trouble reports.

Packet Edge circuit pack

The Packet Edge circuit pack works as a distributed switch and IEEE 802.1D bridge to connect Ethernet LANs on a high-speed SONET network. OPTera Metro 3500 network elements support the following Packet Edge circuit packs: 4x100BT, 4x100FX, and 2xGigE.

pass-through network element

An add/drop multiplexer that does not terminate a connection.

See also [network element on page 3-21](#).

path

Path layer of SONET overhead is a logical connection between a point where an STS or VT is multiplexed to the point where it is demultiplexed.

path AIS

AIS inserted into the SONET path layers (STS path or VT path) to allow suppression of downstream alarms in the event of traffic-affecting failure detected at, or upstream of, the insertion point.

PEC

product engineering code

PDU

protocol data unit

performance monitoring

Statistics which convey information about performance on a given facility.

PID

password identifier

A confidential code used with several security and administration commands, to qualify the authorized system user to access the account specified by a user identifier (UID).

PINFET

positive-intrinsic-negative field-effect transistor

A transistor with a positive-intrinsic-negative (P intrinsic N) diode which converts photons to electrons. This transistor exhibits low gain and is used in less sensitive optical receivers.

PM

See [performance monitoring on page 3-26](#).

POS

PPP over SONET

The use of PPP with SONET, which is a point-to-point circuit.

power module

The module in slots 1b or 1c of an OPTera Metro 3500 shelf. The module provides the required -48 V dc interface to power the shelf.

power module

The module in slots 1b or 1c of an OPTera Metro 3500 shelf. The module provides the required -48 V dc interface to power the shelf.

PPP

point-to-point protocol

PPP is a standard method of communicating over point-to-point links. PPP has three main components:

- A method for encapsulating multi-protocol datagrams.
- A Link Control Protocol (LCP) for establishing, configuring, and testing the data-link connection.
- A family of Network Control Protocols (NCPs) for establishing and configuring different network-layer protocols.

Preside

A suite of service management applications designed to deliver multi-vendor support and end-to-end connection management in real-time.

Preside Site Manager

See [Site Manager on page 3-32](#).

protection channels

The redundant bandwidth allocated to transport the working traffic subsequent to a bridge affecting the working channels.

protection switching (1+1)

A protection switching scheme in which two equivalent channels carry the same traffic, but one is protection and one is working. The 1+1 protection switching scheme is non-revertive.

protection switching (1:N)

A protection switching scheme in which one standby protection channel protects failures on any of the N working channels (revertive switching).

protection switching (1:1)

A protection switching scheme in which one standby protection channel protects failures on one working channel.

provisioning

The assignment of a specific set of parameters to a network element.

Provisioning involves adding, deleting, or changing components and setting the values of their attributes.

PSC

protection switch controller

The PSC circuit pack controls DS1 equipment protection switching for all 84 DS1 ports and monitors DS1 status, including alarm conditions, and performance monitoring thresholds. The PSC houses all the relays that provide protection switching for DS1 ports 1 through 28. The PSC is also responsible for the provisioning of all DS1 mappers.

PSC-W

protection switch count, working line

For a working line, PSC-W is the number of times that service switched from the working line to the protection line, plus the number of times that service switched back to the working line.

PSC-P

protection switch count, protection line

For a protection line, PSC-P is the number of times that service switched from the working line to the protection line, plus the number of times service switched back to the working line.

PSD

protection switch duration

For a working line, PSD is the number of seconds that service was carried on the protection line. For a protection line, PSD is the number of seconds that the line was used to carry service. The PSD parameter is applicable only if the protection scheme is revertive.

PSX

protection switch extender

The PSX circuit pack houses all of the relays that perform DS1 equipment protection switching for DS1 ports 29 through 84.

PUPS

point-of-use power supply

The PUPS converts the -48 V dc central office power supply to the specific, regulated, direct current (dc) voltage levels required for the circuitry on a circuit pack.

PVC

permanent virtual circuit

A continuously available virtual path between remote applications and digital multiplex system (DMS) applications. The PVC eliminates the need to establish a circuit on a per call basis.

See also [VC on page 3-38](#).

RAM

random access memory

Memory into which data can be written and from which data can be read. A solid state memory device used for transient memory stores. Information can be entered and retrieved from any storage position.

reach

The maximum distance a signal is carried.

revertive switch

A 1:N protection scheme where, after a wait-to-restore (WTR) period, the working channels that have requested protection switch back to the working channel provided that the working channel is fully functional.

RFI

remote fault indicator

A message sent out to the upstream network element reporting a fault on the downstream network.

ring

A configuration used for survivability in which the protection channel and working channel are routed in opposite directions in a closed-loop system. This configuration provides immunity to fiber cuts.

ring interworking

A network topology wherein two rings are connected at two points, and operate such that a failure at either of these two points will not cause loss of any traffic, except possibly the traffic dropped or inserted at the point of failure.

ring switching

Protection mechanism that applies to BLSR two-fiber rings. In a ring, when a tail-end NE detects a failure or receives a request to switch working channels, it switches all the working channels that are normally received from the direction of the failure to the protection channels away from the failure, and bridges the outgoing channels in the failure-affected direction to the protection channels away from the failure. Hence, a ring switch is a switch where the nodes adjacent to the failure move the traffic normally sent on the working channels, to the protection channels away from the failure. All nodes on the ring share the protection channels for ring switching.

ROM

read only memory

A solid state memory device that has information permanently written into the memory during manufacture.

route diversity

A configuration used for survivability in which the protection channel fibers and working channel fibers are routed through different paths in order to protect the traffic against cable cuts and equipment failures.

Rx

receive

The incoming direction of signal transmission; signals are carried to a network element from customer equipment.

SA

service-affecting

SASP

path severely errored frame/alarm indication signal second

A 1-second interval at the DS3 section layer that contains one or more out-of-frame events or alarm indication signals.

SDCC

SONET data communications channel

SONET defines two data communications channel: a section data communications channel and a line data communications channel. This term is sometimes referred to as a section data communications channel.

SEFSS

section severely errored frame second

A 1-second interval at the section layer that contains at least one out-of-frame event.

For more information, see [323-1059-510, Montype parameter definitions on page 1-51](#).

SESL

line severely errored second

For more information, see [323-1059-510, Montype parameter definitions on page 1-51](#).

SESP

path severely errored second

For more information, see [323-1059-510, Montype parameter definitions on page 1-51](#).

SESS

section severely errored second

For more information, see [323-1059-510, Montype parameter definitions on page 1-51](#).

SFP

small form-factor pluggable

Module that must be physically attached to the ports of a 2xGigE/FC-P2P circuit pack.

shelf processor

The shelf processor is the circuit pack that houses the CPU, which is the intelligence center of the OPTera Metro 3000 shelves.

The shelf processor provides shelf level control, handles all shelf communications, and runs the system software. System software resides in the shelf processor or network nonvolatile memory.

SID

source identifier

The name assigned to a network element. Each network element must have a SID for the user to direct commands to the network element.

Site Manager

A standalone, nodal management graphical user interface (GUI) that is installed on a PC, and is used to operate, administer, maintain, and provision optical networks.

SLM

single longitudinal mode laser, or single mode laser

An injection laser diode which has a single longitudinal mode.

SNMP

Simple Network Management Protocol

A transmission protocol defined for TCP/IP-based network management. SNMP is used to monitor IP gateways and their networks. It consists of three parts: structure of management information (SMI), Management Information Base (MIB), and the protocol itself. The SMI and MIB define and store the set of managed entities. SNMP conveys information to and from these entities.

SOC

span of control

The total network resources over which a particular network operator has control.

SOL

start of life

Initial period of the lifetime of a product.

SONET

synchronous optical network

A standard for optical transport formulated by the Exchange Carriers Standards Association (ECSA) for the American National Standards Institute (ANSI). The standard defines optical carrier (OC) levels and their electrically equivalent synchronous transport signals (STS).

A fiber optic communication network that: a) consists of fiber optic data links and nodes; b) makes use of synchronous transmission; c) operates with internal synchronism; and d) may operate in synchronism with other networks.

Span

The set of SONET lines between two adjacent nodes on a ring

squelching traffic

In a BLSR configuration, squelching is the act of replacing traffic by the appropriate path AIS to prevent misconnections. STS level squelching occurs only into and out of the protection channels.

SSM

synchronization-status message

SSM indicates the quality of the timing signals currently available to a network element. The timing sources that can be provisioned in a network element include external timing from a BITS, timing derived from SONET interfaces, and the internal clock of the network element.

A network element can select the better of the two timing signals provided by the primary and secondary timing sources provisioned by the user. The selection is based on the quality values carried in the SSM.

STBYH

hot standby

STP

spanning tree protocol

The protocol that MAC bridges use in exchanging information across local area networks, in order to compute the active topology of a bridged local area network in accordance with the spanning tree algorithm.

Stratum n clock

Timing sources for networks are often described in terms of stratum levels. The different stratum clock sources define different levels of accuracy.

STS-1

synchronous transport signal level 1

The basic signaling rate for a synchronous optical network transmission medium (SONET, 51.84 Mbit/s).

STS-nc

synchronous transport signal level <n> concatenated (where <n> is 3, 12, 24 or 48)

A SONET standard for transmission over OC-3, OC-12, OC-48 or OC-192 optical fiber.

An STS-nc signal consists of <n> number of concatenated STS-1 signals. An OPTera Metro 3000 network can be dedicated to the transport of STS-nc signals or can be used to transport both STS-nc and STS-1 signals.

STS-n

synchronous transport signal level n (where n is an integer from 1 through 192)

The signal obtained by multiplexing integer multiples (n) of STS-1 signals (base rate of 51.84 Mbit/s). The rate of the STS-n is n times 51.84 Mbit/s.

| | |
|---------|----------------|
| STS-1 | 51.84 Mbit/s |
| STS-3 | 155.52 Mbit/s |
| STS-12 | 622.08 Mbit/s |
| STS-48 | 2488.32 Mbit/s |
| STS-96 | 4976.64 Mbit/s |
| STS-192 | 9953.28 Mbit/s |

subscriber section

Section from the switchover terminal board on the user premise side of the transmission equipment installed in a leased circuit service office to the demarcation point within the user premise.

STX-192 circuit pack

The STX-192 circuit pack is a fully non-blocking STS switch matrix and clocking module. The STX-192 has switching capability for 40 Gbit/s, supporting 10 Gbit/s links to the line slots 11 and 12 and up to 2.5 Gbit/s links to slots 3 through 10.

The OPTera Metro 3500 network element must be equipped with STX-192 circuit packs to support the following circuit packs:

- OC-12x4 STS interfaces
- OC-48 STS interfaces
- OC-192 interfaces

SVC

switched virtual circuit

A virtual connection that is established for the duration of a transmission. Special signalling packets that have unique bit streams but usually contain no data, are used to set up the connection.

See also [VC on page 3-38](#).

switch completion time

The interval from the decision to switch to the completion of the bridge and switch operation at a switching node initiating the request.

switch mate

The mate path of the FromAID for protected connections.

The FromAID and the SWMATE make up the two paths for path selection. If you do not specify a SWMATE for a protected connection, the default is the optical interface circuit pack in the adjacent odd or even slot of the odd/even pair of slots.

switching node

A node that either sources a bridge request or receives a bridge request. A node that is in any of the pass-through states cannot be a switching node. A switching node also performs any necessary squelching to prevent misconnecting of traffic for STS-1 or higher rate paths.

switching to protection

The action of selecting traffic (at the tail-end) from the protection channels instead of the working channels.

tail-end

The tail-end is the optics unit or the NE where the line overhead is terminated. When a failure occurs on a line, the tail-end NE detects the failure and requests the bridge. For bidirectional switching, a node functions as the head-end for the outgoing line and as the tail-end for the incoming line on the failed span.

TARP

target identifier (TID) address resolution protocol

TBOS

telemetry byte-oriented serial

A function that provides a simple and reliable means of transmitting alarm surveillance and control data between monitoring and monitored equipment.

A standard protocol for communication of alarm information from network elements to an OSS.

TCP/IP

transmission control protocol/Internet protocol

Transmission control protocol/internet protocol (TCP/IP) is a networking protocol that provides communication across interconnected networks, between computers with diverse hardware architectures and various operating systems.

TE

terminal equipment

Equipment connected to the NT (network termination) which transmits and receives data.

terminal facilities

Telecommunications facilities (equipment, lines, and other electrical facilities) which are connected to one end of a leased circuit (wiring board or protector closest to the service provider line facilities). The place of installation is within the same premise (including corresponding facilities) or within the same building.

TID

target identifier

The TID is a non-confidential code to identify the network element being addressed.

TL1

Transaction Language 1

User interface for OPTera Metro 3000 network element used to operate, administer, maintain, and provision the network.

TOD

time of day

The time of day feature maintains synchronized real-time between OPTera Metro 3000 network elements. Network time can be provisioned such that it automatically adjusts for time zone offsets and daylight savings periods from the reference time.

transport

The action of conveying signals from one point to one or more other points in the network.

TransportNode

A group of synchronous optical network (SONET)-based network elements for long-haul, interoffice, and local applications.

tributary

The link between a network element and the customer. The lower rate signal input to a multiplexer for combination (multiplexing) with other low rate signals to form an aggregate higher rate signal.

tributary circuit pack

Any supported circuit pack that is installed in the shelf slots 3 through 10.

TSTF

test failed

Tx

transmit

The outgoing direction of signal transmission; signals are carried from a network element to customer premises equipment.

UASL

line unavailable second

The count of 1-second intervals at the line layer with 10 consecutive severely errored seconds.

UASP

path unavailable second

The count of 1-second intervals at the path layer with 10 consecutive severely errored seconds.

UEQ

unequipped

UID

user identifier

The user identifier (UID) is used with several security and administration commands. It is essential to have a UID in order to activate a user login session.

unidirectional switching

A switching scheme in which only the failed direction of traffic switches to protection.

UPC

user privilege code

The network element supports five user security levels called user privilege codes (UPC). The lowest security of the UPC is 1 and the highest is 5. The five UPC security levels provide varying level of access for task execution.

UPSR

unidirectional path-switched ring

In the UPSR, the ring consists of two fibers on each span, transmitting traffic in opposite directions, between adjacent nodes. Traffic entering the ring at any node is transmitted in both directions around the ring until it reaches its exit point. Each node on the ring is line terminating, such that the connection across the ring is a path layer connection. At the exit point, the path layer integrity information is examined for each of the two signals to select the best quality signal. All of the selectors default to a particular direction, such that under normal conditions, all traffic is routed around the ring in the same direction.

VC

virtual circuit

A facility provided by the network for transferring data between a logical channel from the calling DTE and a logical channel to the called DTE, and which emulates facilities provided by a physical connection. It is established only for the duration of the call, and it may share a physical circuit with other virtual circuits.

See also [PVC on page 3-29](#), and [SVC on page 3-34](#).

virtual concatenation

Allows a number of STS-1 or STS-3c payloads to be cross-connected to the GE/FC WAN port of a 2xGigE/FC-P2P circuit pack. When a WAN port is provisioned in virtual concatenation mode, then one cross connection is needed for every increment of STS1 or STS3c bandwidth.

virtual tributary

A signal designed for transporting and switching of sub-STs-1 payloads. For example, OPTera Metro 3000 network elements use VT1.5 (1.728 Mbit/s).

VOA

variable optical attenuator

A device that prevents overloading the optical receiver.

VT

See [virtual concatenation on page 3-38](#).

VTX-48

VTX-48 circuit packs are equipped in slots 13 and 14 of the OPTera Metro 3500 shelf.

VTX-48 circuit packs provide monitoring and control for provisioning, cross-connect management, shelf timing generation, and synchronization messaging. The circuit packs manage synchronization and shelf bandwidth as separate entities.

VTX-48 equipment operates in 1+1 redundant mode to provide cross-connect and clock distribution functions for OPTera Metro 3500. It is always auto-provisioned and cannot be deleted. Only one of the two VTX-48 circuit packs can be taken out of service at a time.

VTX-48e

VTX-48 enhanced

VTX-48e circuit packs are equipped in slots 13 and 14 of the OPTera Metro 3500 shelf. The VTX-48e circuit pack supports the OC-12 line rate in slots 11 and 12.

VTX-48e circuit packs provide monitoring and control for provisioning, cross-connect management, shelf timing generation, and synchronization messaging. The circuit packs manage synchronization and shelf bandwidth as separate entities.

VTX-48e equipment operates in 1+1 redundant mode to provide cross-connect and clock distribution functions for OPTera Metro 3500. It is always auto-provisioned and cannot be deleted. Only one of the two VTX-48e circuit packs can be taken out of service at a time.

WAN

wide area network

working channels

The channels over which working traffic is transported when there are no switch events. An APS system performs restoration for the working channels only.

working traffic

Traffic traversing a ring normally carried in the working channels, except in the event of a ring or span protection switch, in which case it is restored on the protection channels.

WRKG

working

WRKRX

working in the receive direction

WRKTX

working in the transmit directions

Master index

1WAY cross-connects, adding
 linear networks 320 6-9
 UPSR networks 320 6-9
 1WAYPR cross-connects, adding 320 6-17
 2WAY cross-connects, adding
 BLSR networks 320 6-13
 linear networks 320 6-9
 UPSR networks 320 6-9
 2WAYBR cross-connects, adding 320 6-17
 2WAYPR cross-connects, adding 320 6-17
 2x100BT-P2P circuit pack
 Ethernet facility
 signal attributes 350 2-34
 facility (Ethernet or WAN)
 editing signal attributes 350 2-28
 secondary states 350 2-6
 installing 201 3-141
 replacing 543 3-17
 upgrading FPGA load 302 6-64
 WAN facility
 signal attributes 350 2-35
 2xGigE circuit pack
 installing 201 3-149
 replacing 543 3-15
 2xGigE/FC-P2P circuit pack
 alarm hierarchy
 egress WAN port 543 5-291
 ingress LAN port 543 5-291
 installing 201 3-141
 replacing 543 3-18
 upgrading FPGA load 302 6-64
 4x100BT circuit pack
 installing 201 3-141
 replacing 543 3-15

4x100FX circuit pack
 installing 201 3-141
 replacing 543 3-15

A

access identifier (AID) 190 1-6
 active alarms
 details
 printing 543 2-9
 retrieving 543 2-8
 saving 543 2-10
 filtering for a network element 543 2-5
 identifying the source 543 2-52
 retrieving
 against disabled alarm points 543 2-27
 by network element 543 2-3
 details 543 2-8
 from Shelf Level View 543 2-50
 sorting by network element 543 2-4
 updating
 automatically 543 2-6
 manually 543 2-7
 adding
 ADM network element to a linear
 network 224 2-2
 background image to a map 520 5-27
 connection ID 320 6-32
 cross-connects
 1WAY (BLSR networks) 320 6-13
 1WAY (linear or UPSR networks) 320
 6-9
 1WAYPR 320 6-17
 2WAY (BLSR networks) 320 6-13

- adding (continued)
 - cross-connects (continued)
 - 2WAY (linear or UPSR networks) 320 6-9
 - 2WAYBR 320 6-17
 - 2WAYPR 320 6-17
 - RPR 320 6-21
 - end-to-end connections
 - 1+1 linear network 320 1-7
 - BLSR network 320 1-15
 - UPSR network 320 1-11
 - entry in TARP tables 520 6-4
 - facility 350 2-20
 - invalid password 302 3-21
 - label on a map 520 5-16
 - login profile
 - for a direct cable connection 302 2-25
 - for a modem connection 302 2-22
 - for a network connection 302 2-19
 - for a terminal session using direct cable 302 2-27
 - for a terminal session using modem 302 2-24
 - for a terminal session using the network 302 2-21
 - manual area address 520 3-17
 - network element to a BLSR 224 2-84
 - network element to a BLSR over DWDM 224 3-61
 - network element to a UPSR 224 2-74
 - network element to a UPSR over DWDM 224 3-19
 - network processor facility 520 3-2
 - network processor span of control 520 4-3
 - OMX shelf to an in-service DWDM network 224 3-2
 - software load from
 - OPC or network processor over direct cable 302 6-70
 - OPC or network processor over the network 302 6-68
 - PC over Ethernet 302 6-66
- adding (continued)
 - TBOS mapping assignment 520 1-2
 - terminal network element to a linear network 224 2-53
 - user account 302 3-4
- ADM (add/drop multiplexer), adding to a linear network 224 2-2
- AINS (auto-in-service)
 - default period, changing 350 1-3
 - provisioning for DS1 and DS3 facilities 350 2-27
- air deflector, installing and removing 201 3-183
- air filter, replacing 543 3-85
- AIS/LOP seconds (ALS), definition 510 1-58
- Alarm and Event Throttling Active alarm 543 4-12
- alarm hierarchy 543 5-286
 - 2xGigE/FC-P2P circuit pack egress WAN port 543 5-291
 - ingress LAN port 543 5-291
 - DS1 service module (DSM) 543 5-290
 - EC-1 543 5-289
 - equipment 543 5-288
 - OC-n facility 543 5-287
 - shelf equipment 543 5-292
- alarm points
 - disabling 543 2-28
 - enabling 543 2-29
 - retrieving
 - by alarm class 543 2-25
 - by equipment type 543 2-26
- alarm profiles
 - adding 543 2-33
 - deleting 543 2-37
 - disabling alarms on equipment or facilities 543 2-43
 - editing 543 2-35
 - retrieving
 - by alarm class 543 2-30
 - by equipment 543 2-31
 - by facility type 543 2-31
 - details 543 2-32

-
- alarm profiles (continued)
 - setting
 - as active by alarm class for a particular equipment or facility 543 2-42
 - as active for a specific unit of equipment or facility 543 2-39
 - as active for the common or facility alarm class 543 2-40
 - default profile 543 2-38
 - alarms
 - alarm balloons, clearing on a map 520 5-22, 520 5-23
 - fault clearing priority 543 1-2
 - fault clearing strategy 543 1-1
 - alarms observed table
 - adding a network element to a BLSR reconfiguration 224 2-269
 - adding a network element to a UPSR reconfiguration 224 2-267
 - Full VT to VT assigned BLSR reconfiguration 224 2-275
 - linear point-to-point to UPSR reconfiguration 224 2-274
 - OC-12 to OC-48 line rate upgrade reconfiguration 224 2-273
 - OC-3 to OC-12 line rate upgrade reconfiguration 224 2-271
 - removing a network element from a BLSR 224 2-269
 - removing a network element from a UPSR 224 2-267
 - VT assigned to Full VT BLSR reconfiguration 224 2-275
 - All Provisioned VTs Rx AIS alarm 543 4-13
 - All Provisioned VTs Rx Excessive BIP Error Rate alarm 543 4-16
 - All Provisioned VTs Rx Loss of Pointer alarm 543 4-20
 - All Provisioned VTs Rx RFI alarm 543 4-23
 - All Provisioned VTs Rx Signal Degrade alarm 543 4-25
 - All Provisioned VTs Rx Signal Label Mismatch alarm 543 4-29
 - All Provisioned VTs Rx Unequipped alarm 543 4-31
 - APS Channel Match Fail alarm 543 4-34
 - attaching OPE circuit packs to an existing resilient packet ring 320 5-22
 - audible alarms, clearing 543 2-53
 - Auto Switch Complete alarm 543 4-40
 - auto-in-service (AINS)
 - default period, changing 350 1-3
 - provisioning for DS1 and DS3 facilities 350 2-27
 - Automatic Protection Switch Byte Fail alarm 543 4-36
 - automatic report
 - REPT^ALM^COM 190 24-4
 - REPT^ALM^EC1 190 24-7
 - REPT^ALM^ENV 190 24-9
 - REPT^ALM^EQPT 190 24-12
 - REPT^ALM^FAC 190 24-15
 - REPT^ALM^OC12 190 24-19
 - REPT^ALM^OC192 190 24-23
 - REPT^ALM^OC3 190 24-17
 - REPT^ALM^OC48 190 24-21
 - REPT^ALM^SECU 190 24-25
 - REPT^ALM^STS1 190 24-27
 - REPT^ALM^STS12C 190 24-32
 - REPT^ALM^STS24C 190 24-34
 - REPT^ALM^STS3C 190 24-30
 - REPT^ALM^STS48C 190 24-36
 - REPT^ALM^T1 190 24-38
 - REPT^ALM^T3 190 24-40
 - REPT^ALM^VT1 190 24-42
 - REPT^CONFIG^CHG 190 24-45
 - REPT^DBCHG 190 24-46
 - REPT^EVT^COM 190 24-49
 - REPT^EVT^EC1 190 24-52
 - REPT^EVT^EQPT 190 24-54
 - REPT^EVT^INVENTORY 190 24-57
 - REPT^EVT^LOG 190 24-60
 - REPT^EVT^OC12 190 24-65
 - REPT^EVT^OC192 190 24-70
 - REPT^EVT^OC3 190 24-62
 - REPT^EVT^OC48 190 24-68
 - REPT^EVT^STS1 190 24-72
 - REPT^EVT^STS12C 190 24-78
 - REPT^EVT^STS24C 190 24-81
 - REPT^EVT^STS3C 190 24-75
 - REPT^EVT^STS48C 190 24-84
 - REPT^EVT^T1 190 24-87
 - REPT^EVT^T3 190 24-90
-

automatic report (continued)
 REPT^EVT^VT1 190 24-92
 REPT^EX^LINK 190 24-95
 REPT^SOC 190 24-98
Autoprovisioning Mismatch alarm 543 4-37

B

backups, setting up backup NPx for
 BLSR 320 6-47
Bandwidth Incompatible alarm 543 4-42
batch file
 building 302 7-6
 editing 302 7-11
 loading 302 7-10
 running 302 7-14
bay installation
 connecting bay frame ground to office
 ground 201 3-39
 performing preliminary tasks 201 3-29
 preparing floor 201 3-32
 securing bay frame 201 3-34
BCC CLI
 logging in 302 2-37
 logging out 302 2-39
BIP (NTFW56BA) installation
 inspecting the BIP shipping container 201
 3-52
 installing the BIP 201 3-53
BIP (NTN458RA) installation
 inspecting the BIP shipping container 201
 3-43
 installing the BIP 201 3-45
BITS (building-integrated timing supply)
 BITS in
 parameter 310 1-12
 provisioning 310 1-10
 BITS out
 parameter 310 1-15
 provisioning 310 1-13
 switch, operating 310 1-16
 connecting cable 201 3-101
BITSin-A Rx AIS alarm 543 4-44
BITSin-A Rx BPV exceeds 10E-3 alarm 543
 4-46
BITSin-A Rx Loss of Frame alarm 543 4-48
BITSin-A Rx Loss of Signal alarm 543 4-50

BITSin-B Rx AIS alarm 543 4-44
BITSin-B Rx BPV exceeds 10E-3 alarm 543
 4-46
BITSin-B Rx Loss of Frame alarm 543 4-48
BITSin-B Rx Loss of Signal alarm 543 4-50
BLSR
 setting up backup NPx 320 6-47
BLSR audit
 forcing 320 6-45
 performing 320 6-45
 scheduling 320 6-45
BLSR configuration
 adding a node 224 2-84
 adding a node over DWDM 224 3-61
 deleting from NPx and all SPx 320 6-38
 deleting from NPx only 320 6-38
 deleting from SPx (when absent on
 NPx) 320 6-40
 deleting node from 320 6-43
 editing name 320 6-37
 moving from NPx to NPx 320 6-49
 provisioning 320 6-34
 retrieving 320 6-33
 table 224 2-202
BLSR Configuration Audit Fail alarm 543
 4-52
BLSR Configuration in Progress alarm 543
 4-54
BLSR Connection Audit Fail alarm 543 4-55
breaker interface panel, d.c. power
 connection 201 3-53
Bridge port not in forwarding state alarm 543
 4-56
building a script 302 7-6

C

cable
 BITS 201 3-101
 COLAN 201 3-101
 connecting power to shelf 201 3-95
 defining settings 302 2-15
 DS1 201 3-101
 DS3 201 3-101
 EC-1 201 3-101
 environmental I/O 201 3-101, 201 3-234
 fan alarm 543 3-64

-
- cable (continued)
 - fan power 543 3-64
 - LAN 201 3-101
 - power cable 201 3-95
 - routing
 - T1, T3, and Cat 5 UTP cabling to rear-facing I/O modules 201 3-158
 - T1, T3, and Cat 5 UTP to front-facing I/O modules 201 3-156
 - TBOS 201 3-101
 - testing power level 201 3-95
 - X.25 201 3-101
 - cable pinout
 - DS1 cable 201 5-2
 - DS3 cable 201 5-7
 - EC-1, cable 201 5-7
 - environmental alarm cable 201 5-31
 - NP Ethernet LAN RJ-45 cable 201 5-34
 - office alarm cable 201 5-31
 - power cable 201 5-13
 - RS-232 DCE DB25 cable 201 5-28
 - RS-232 null modem cable 201 5-11
 - TBOS, cable 201 5-10
 - channel identifiers, unlocking 302 3-26
 - circuit pack 201 1-2
 - deleting 350 2-17
 - details, displaying 350 2-2
 - disengaging 543 3-94
 - editing facility state to
 - in-service 350 2-26
 - out-of-service 350 2-25
 - engaging 543 3-94
 - handling 201 1-4, 210 1-3, 222 1-3
 - identifying the source of an alarm 543 2-52
 - information 302 5-3
 - inserting 201 3-192
 - installing 201 1-4, 210 1-3, 222 1-3
 - 2x100BT-P2P circuit pack 201 3-141
 - 2xGigE circuit pack 201 3-149
 - 2xGigE/FC-P2P circuit pack 201 3-141
 - 4x100BT circuit pack 201 3-141
 - 4x100FX circuit pack 201 3-141
 - DS1 201 3-129
 - DS3VTx12 mapper 201 3-134
 - DS3x12 mapper 201 3-134
 - DS3x12e mapper 201 3-134
 - DS3x3 mapper 201 3-134
 - circuit pack (continued)
 - installing (continued)
 - EC-1x12 circuit pack 201 3-134
 - EC-1x3 circuit pack 201 3-134
 - ILAN circuit pack 201 3-125
 - network processor 201 3-125
 - optical interface circuit pack 201 3-119
 - Packet Edge circuit pack 201 3-141, 201 3-149
 - PSC 201 3-129
 - PSX 201 3-129
 - optical, testing functionality and protection 222 2-5
 - provisioning
 - automatically 350 2-7
 - DS1 service module (DSM) DS1x84 termination module (TM)
 - manually 350 2-13
 - manually 350 2-9
 - removing 201 3-192
 - replacing 201 1-4, 210 1-3, 222 1-3
 - 2x100BT-P2P circuit pack 543 3-17
 - 2xGigE circuit pack 543 3-15
 - 2xGigE/FC-P2P circuit pack 543 3-18
 - 4x100BT circuit pack 543 3-15
 - 4x100FX circuit pack 543 3-15, 543 3-16
 - DS1 mapper 543 3-24
 - DS3VTx12 mapper 543 3-30
 - DS3x12 mapper 543 3-30
 - DS3x12e mapper 543 3-30
 - DS3x3 mapper 543 3-30
 - DS3x3 mapper with DS3x12 mapper 224 1-8, 224 1-14
 - DSM DS1x84 TM mapper 543 3-26
 - EC-1x12 circuit pack 543 3-32
 - EC-1x3 circuit pack 543 3-32
 - EC-1x3 circuit pack with EC-1x12 circuit pack 224 1-11
 - ILAN circuit pack 543 3-13
 - ILAN with network processor 224 1-6
 - network processor 543 3-10
 - network processor with ILAN circuit pack 224 1-3
 - OC-3 with OC-3x4 circuit pack 224 1-14
-

- circuit pack (continued)
 - replacing (continued)
 - optical interface circuit pack (BLSR) 543 3-41
 - optical interface circuit pack (linear system) 543 3-34
 - optical interface circuit pack (UPSR) 543 3-38
 - Packet Edge circuit pack 543 3-15
 - PSC circuit pack 543 3-45
 - PSX circuit pack 543 3-47
 - safety requirements 543 3-3, 543 4-11, 543 5-11
 - shelf processor 543 3-7
 - STX-192 circuit pack 543 3-51
 - VTX module 543 3-48
 - reseating 543 3-4
 - restarting 543 2-45
 - seating verification 201 3-180
 - static electricity 201 1-2, 210 1-2, 222 1-2
 - transporting 201 1-5, 210 1-3, 222 1-3
- Circuit Pack Failed - BWM alarm 543 4-63
- Circuit Pack Failed - Pluggable alarm 543 4-65
- Circuit Pack Failed - Sync alarm 543 4-63
- Circuit Pack Failed (network processor) alarm 543 4-61
- Circuit Pack Failed alarm 543 4-57
- Circuit Pack Incompatible alarm 543 4-66
- Circuit Pack Mismatch - Pluggable alarm 543 4-73
- Circuit Pack Mismatch alarm 543 4-70
- Circuit Pack Missing - Pluggable alarm 543 4-80
- Circuit Pack Missing alarm 543 4-74
- Circuit Pack Unknown - Pluggable alarm 543 4-83
- Circuit Pack Unknown alarm 543 4-81
- Circuit Pack Upgrade Failed alarm 543 4-84
- cleaning
 - fiber 201 4-2
 - optical connectors 201 4-9
- clearing
 - audible alarms 543 2-53
 - intrusion alarms 302 3-27
 - PM counts
 - facility 510 1-25
 - untimed 510 1-26
 - security alarms 302 3-27
 - security alarms for customer managed network 302 3-35
- Client Service Mismatch alarm 543 4-87
- closing
 - Comm Log terminal session 302 4-11
 - manual connection terminal session 302 4-10
 - Site Manager 302 2-42
 - telnet terminal session 302 4-9
 - TL1 Command Builder 302 7-3
- coding violations (CV), definition 510 1-56
- COLAN
 - connecting cable 201 3-101
 - facility, editing 520 3-3
- Comm Log
 - closing 302 4-11
 - printing 302 4-8
 - starting 302 4-6
- commissioning
 - network element 210 2-2
 - shelf processor 210 2-2
- Concatenated Path Monitoring Unsupported alarm 543 4-89
- Configuration Mismatch alarm 543 4-90
- connecting
 - BITS cable 201 3-101
 - COLAN cable 201 3-101
 - d.c. power 201 3-53
 - DS1 cable 201 3-101
 - DS1 service module to the OPTera Metro 3500 201 3-246
 - DS3 cable 201 3-101
 - EC-1 cable 201 3-101
 - environmental I/O cable 201 3-101, 201 3-234
 - fiber-optic cable to the optical interface 201 3-175
 - modem 201 3-189

-
- connecting (continued)
 - OMX+Fiber Manager 4CH
(NT0H32AE-HE, NT0H32AF-HF) to
OPTera Metro 3500 201 3-211
 - power cable 201 3-95
 - power cabling to DSM shelf (DSM OAM
HW Rel 5 or earlier) 201 3-226
 - power cabling to DSM shelf (DSM OAM
HW Rel 6 or later) 201 3-231
 - shelf alarm cable 201 3-101, 201 3-234
 - TBOS cable 201 3-101, 201 3-234
 - terminal 201 3-189
 - connection
 - end-to-end
 - adding for 1+1 linear network 320 1-7
 - adding for BLSR 320 1-15
 - adding for UPSR 320 1-11
 - deleting 320 1-23
 - displaying 320 1-2
 - editing 320 1-20
 - filtering 320 1-6
 - saving data to file 320 1-24
 - connection ID
 - adding 320 6-32
 - editing 320 6-32
 - controlled slip seconds (CSS), definition 510
1-57
 - converting
 - OC-48 BLSR to OC-48 BLSR over
DWDM 224 3-51
 - OC-48 linear span to OC-48 linear span over
DWDM 224 3-42
 - OC-48 UPSR to OC-48 UPSR over
DWDM 224 3-9
 - cooling fan, replacing on the DS1 service
module 543 3-54
 - cooling unit assembly 543 3-61
 - replacing 543 3-57
 - cooling unit assembly, universal 543 3-72
 - replacing 543 3-69
 - cooling unit fan module 543 3-60
 - replacing 543 3-67
 - cooling unit fan module, universal 543 3-73
 - replacing 543 3-75
 - cooling unit plenum 543 3-62
 - cooling unit plenum, universal 543 3-74
 - cooling unit upgrade kit, installing 543 3-55
 - copying
 - inventory information 302 5-10
 - Corrupt Network Backup alarm 543 4-92
 - CP Loss of Host Timing Ref. alarm 543 4-93
 - creating a temporary account 302 3-7
 - cross-connects
 - adding
 - 1WAY (BLSR networks) 320 6-13
 - 1WAY (linear or UPSR networks) 320
6-9
 - 1WAYPR 320 6-17
 - 2WAY (BLSR networks) 320 6-13
 - 2WAY (linear or UPSR networks) 320
6-9
 - 2WAYBR 320 6-17
 - 2WAYPR 320 6-17
 - RPR 320 6-21
 - deleting 320 6-4
 - editing
 - 1WAY (BLSR networks) 320 6-29
 - 1WAY (linear or UPSR networks) 320
6-27
 - 1WAYPR 320 6-30
 - 2WAY (BLSR networks) 320 6-29
 - 2WAY (linear or UPSR networks) 320
6-27
 - 2WAYBR 320 6-30
 - 2WAYPR 320 6-30
 - retrieving 320 6-3
 - CTAG, definition 190 1-6
 - customer managed network
 - details
 - changing 302 3-33
 - displaying 302 3-30
 - disabling 302 3-32
 - enabling 302 3-31
- D**
- daisy-chaining
 - ILANs 201 3-187
 - network processors 201 3-187
 - DataBase Corruption Detected alarm 543
4-94
 - Database Not Ready alarm 543 4-98
 - Database Restore in Progress alarm 543 4-99
-

- Database Save and Restore Failed alarm 543 4-100
- daylight savings offset 302 8-8
- default directory for saving map 520 5-7
- Default K-bytes alarm 543 4-101
- defaults
 - intrusion attempt handling, editing 302 3-28
 - security parameters, editing 302 3-14
- defining
 - direct cable settings 302 2-15
 - modem settings 302 2-14
 - site address for a DS1 service module (DSM) 350 2-11
- Degraded Performance alarm 543 4-103
- deleting
 - alarm profiles 543 2-37
 - BLSR configuration
 - from NPx and all SPx 320 6-38
 - from NPx only 320 6-38
 - from SPx (when absent on NPx) 320 6-40
 - circuit pack 350 2-17
 - cross-connects 320 6-4
 - end-to-end connections 320 1-23
 - entry in TARP table 520 6-7
 - environmental alarm attributes 543 2-58
 - facility 350 2-22
 - on working DS1 service module (DSM) DS1x84 termination module (TM) 350 2-24
 - invalid password 302 3-23
 - label on a map 520 5-18
 - login profile 302 2-29
 - manual area address 520 3-20
 - network element from BLSR configuration 320 6-43
 - network processor facility 520 3-21
 - RPR cross-connect 320 6-6
 - shelf processor backups from network processor 302 6-46, 302 6-47
 - software load from network processor 302 6-73
 - TBOS mapping assignment 520 1-4
 - user account 302 3-16
- deprovisioning
 - resilient packet ring 320 5-26
- detaching OPE circuit packs
 - from an existing resilient packet ring 320 5-24
- direct cable
 - defining settings 302 2-15
- disabling
 - alarm points 543 2-28
 - customer managed network 302 3-32
- disconnecting
 - from a network element 302 2-41
 - from a network processor 302 2-41
 - SC, FC, ST, LC or MT-RJ connector 201 3-249
- disengaging a circuit pack 543 3-94
- Disk Full alarm 543 4-105
- displaying
 - active alarms 543 2-8
 - circuit pack details 302 5-3
 - customer managed network details 302 3-30
 - DS1 service module (DSM) inventory 302 5-9
 - DS1 service module (DSM) shelf graphics 302 5-4
 - DSM DS1x84 termination module (TM) details 302 5-5
 - end-to-end connections 320 1-2
 - equipment and facilities information with shelf graphics 302 5-7
 - equipment and facility details 350 2-2
 - event list 543 2-11
 - intrusion attempts handling details 302 3-24
 - invalid password 302 3-19
 - network element information on a map 520 5-33
 - node information 350 1-2
 - shelf graphics 302 5-2
 - shelf inventory information 302 5-8
 - synchronization data 310 1-2
 - time of day servers 302 8-7
 - user account details 302 3-3
- DS1
 - cable
 - assembly 201 5-2
 - connecting 201 3-101
 - pinout 201 5-2

-
- DS1 (continued)
- facility
 - editing signal attributes 350 2-28
 - provisioning AINS 350 2-27
 - secondary states 350 2-4
 - signal attributes 350 2-30
 - provisioning software terminal
 - loopback 222 2-56
 - testing signal continuity 222 2-18
 - DS1 Loopback Active alarm 543 4-106
 - DS1 mapper
 - installing 201 3-129
 - replacing 543 3-24
 - DS1 Rx AIS alarm 543 4-107
 - DS1 Rx Bipolar Violations alarm 543 4-109
 - DS1 Rx Frequency Out of Range alarm 543 4-111
 - DS1 Rx Loss of Frame alarm 543 4-112
 - DS1 Rx Loss of Signal alarm 543 4-114
 - DS1 Rx Yellow alarm 543 4-116
 - DS1 service module (DSM) 190 23-1
 - alarm hierarchy 543 5-290
 - defining site address 350 2-11
 - deleting facility 350 2-24
 - displaying inventory information 302 5-9
 - displaying shelf graphics 302 5-4
 - editing site address 350 2-11
 - performing a lamp test 302 5-6
 - provisioning manually 350 2-13
 - using to log in to a network element 302 2-34
 - DS1 Test Signal Active alarm 543 4-118
 - DS1 Tx AIS alarm 543 4-119
 - DS1 Tx Frequency Out of Range alarm 543 4-121
 - DS1 Tx Loss of Frame alarm 543 4-122
 - DS1-I/O module, replacing on DSM 543 3-84
 - DS3
 - cable
 - assembly 201 5-7
 - pinout 201 5-7
 - connecting cable to shelf 201 3-101
- DS3 (continued)
- facility
 - editing signal attributes 350 2-28
 - provisioning AINS 350 2-27
 - secondary states 350 2-5
 - signal attributes 350 2-33
 - provisioning software terminal
 - loopback 222 2-56
 - testing signal continuity 222 2-18
 - DS3 Loopback Active alarm 543 4-106
 - DS3 Rx AIS alarm 543 4-125
 - DS3 Rx Bipolar Violations alarm 543 4-127
 - DS3 Rx Frequency Out of Range alarm 543 4-130
 - DS3 Rx Loss of Frame alarm 543 4-132
 - DS3 Rx Loss of Signal alarm 543 4-134
 - DS3 Rx Parity Er Rate Exceeds 10E-6 alarm 543 4-136
 - DS3 Rx yellow alarm 543 4-137
 - DS3 test signal active alarm 543 4-139
 - DS3 Tx AIS alarm 543 4-140
 - DS3 Tx Frequency Out of Range alarm 543 4-142
 - DS3 Tx Loss of Frame alarm 543 4-143
 - DS3VTx12 mapper
 - installing 201 3-134
 - replacing 543 3-30
 - DS3x12 mapper
 - installing 201 3-134
 - replacing 543 3-30
 - DS3x12e mapper
 - installing 201 3-134
 - replacing 543 3-30
 - DS3x3 mapper
 - installing 201 3-134
 - replacing 543 3-30
 - replacing with DS3x12 mapper 224 1-8, 224 1-14
 - DSM
 - installation
 - connecting power cabling to DSM shelf (DSM OAM HW Rel 5 or earlier) 201 3-226
 - connecting power cabling to DSM shelf (DSM OAM HW Rel 6 or later) 201 3-231
-

DSM (continued)
 inspecting DSM shipping container
 contents 201 3-216
 installing and removing DSM front
 cover 201 3-225
 installing the DSM shelf 201 3-218
DSM DS1x84 termination module (TM)
 displaying details 302 5-5
 inserting 201 3-243
 removing 201 3-243
 replacing 543 3-26
DSM Fan Failure alarm 543 4-147
DSM Fan Missing alarm 543 4-148
DSM Low Voltage alarm 543 4-151
DSM Power Failure - A alarm 543 4-152
DSM Power Failure - B alarm 543 4-152
DSM SITE Provisioning Required alarm 543
 4-153
DSM-HOST Misconnection alarm 543 4-149
DSM-OAM module, replacing 543 3-82
Duplicate SID Detected alarm 543 4-154
DWDM
 adding a network element to an OC-48
 UPSR over DWDM 224 3-19
 adding a network element to OC-48 BLSR
 over DWDM 224 3-61
 adding an OMX to an in-service
 network 224 3-2
 converting a network element to OC-48
 BLSR over DWDM 224 3-61
 converting an OC-48 UPSR to an OC-48
 UPSR over DWDM 224 3-9
 converting OC-48 BLSR 224 3-51
 converting OC-48 linear point-to-point
 network 224 3-42
 removing a network element from a BLSR
 over DWDM 224 3-72
 removing a network element from a UPSR
 over DWDM 224 3-32

E

EC-1
 cable
 assembly 201 5-7
 connecting 201 3-101
 pinout 201 5-7
 facility
 alarm hierarchy 543 5-289
 editing signal attributes 350 2-28
 secondary states 350 2-5
 signal attributes 350 2-33
EC1 Loopback Active alarm 543 4-157
EC1 Rx AIS alarm 543 4-158
EC1 Rx Loss of Frame alarm 543 4-160
EC1 Rx Loss of Signal alarm 543 4-161
EC1 Rx RFI alarm 543 4-163
EC1 Rx Signal Degrade alarm 543 4-165
EC-1x12 circuit pack
 installing 201 3-134
 replacing 543 3-32
EC-1x3 circuit pack
 installing 201 3-134
 replacing 543 3-32
 replacing with EC-1x12 circuit pack 224
 1-11
editing
 alarm profiles 543 2-35
 an entry in TARP tables 520 6-6
 BLSR configuration name 320 6-37
 COLAN facility 520 3-3
 connection ID 320 6-32
 cross-connects
 1WAY (BLSR networks) 320 6-29
 1WAY (linear or UPSR networks) 320
 6-27
 1WAYPR 320 6-30
 2WAY (BLSR networks) 320 6-29
 2WAY (linear or UPSR networks) 320
 6-27
 2WAYBR 320 6-30
 2WAYPR 320 6-30
 customer managed network details 302
 3-33
 date and time 302 3-40
 environmental alarm attributes 543 2-57

-
- editing (continued)
 - equipment state to
 - in-service 350 2-16
 - out-of-service 350 2-15
 - external control attributes 543 2-59
 - facility PM thresholds
 - default values 510 1-42
 - monitoring status 510 1-43
 - values 510 1-40
 - facility signal attributes 350 2-28
 - facility state to
 - in-service 350 2-26
 - out-of-service 350 2-25
 - intrusion attempt handling defaults 302 3-28
 - label on a map 520 5-17
 - line SDTH 311 1-37
 - login profile 302 2-28
 - lower layer SDCC 350 2-40
 - manual area address 520 3-17
 - network element
 - name 302 3-37
 - type 302 3-42
 - network processor
 - name 302 3-37
 - NSAP 520 6-10
 - password 302 3-17
 - path SDTH 311 1-39
 - path trace messages 520 2-8
 - PM threshold crossing report type 510 1-44
 - protection scheme
 - from 1+1 linear to UPSR 311 1-6
 - from BLSR to UPSR 311 1-12
 - from UPSR to 1+1 linear 311 1-8
 - from UPSR to BLSR 311 1-10
 - protection switch mode (1+1 linear) 311 1-4
 - script 302 7-11
 - SDTH of an optical interface 350 2-38
 - section trace messages 520 2-4
 - security parameter defaults 302 3-14
 - site address for a DS1 service module (DSM) 350 2-11
 - SS bits mode 350 2-19
 - TARP configuration parameters 520 6-2
 - TBOS mapping assignment 520 1-3
 - editing (continued)
 - time zone 302 3-40
 - TL1 commands 302 7-4
 - upper layer SDCC 350 2-42
 - user account 302 3-10
 - user privilege level 302 3-10
 - wait-to-restore period 311 1-14
 - X.25 parameters 520 3-6
 - enabling
 - alarm points 543 2-29
 - customer managed network 302 3-31
 - intrusion attempts handling 302 3-25
 - end-to-end connections
 - adding
 - 1+1 linear network 320 1-7
 - BLSR 320 1-15
 - UPSR 320 1-11
 - deleting 320 1-23
 - displaying 320 1-2
 - editing 320 1-20
 - filtering 320 1-6
 - saving data to file 320 1-24
 - engaging or disengaging a circuit pack 543 3-94
 - environmental alarm cable
 - assembly 201 5-31
 - pinout 201 5-31
 - environmental alarms
 - deleting attributes 543 2-58
 - editing attributes 543 2-57
 - retrieving attributes 543 2-56
 - environmental I/O
 - connecting cables 201 3-101, 201 3-234
 - input interface characteristics 201 3-101, 201 3-234
 - output interface characteristics 201 3-101, 201 3-234
 - equipment
 - alarm hierarchy 543 5-288
 - details, displaying 350 2-2
 - displaying with shelf graphics 302 5-7
 - editing state to
 - in-service 350 2-16
 - out-of-service 350 2-15
 - primary states 350 2-3
 - secondary states 350 2-3
 - Equipment below baseline 543 4-166
-

Equipment upgrade failed alarm 543 4-167
Equipment upgrade in progress alarm 543
4-168
Equipment upgrade required alarm 543
4-169
error codes and messages (TL1),
definition 190 26-1
errored seconds (ES), definition 510 1-56
Ethernet
facility
2x100BT-P2P signal attributes 350 2-34
editing 350 2-28
GE/FC SFP signal attributes 350 2-36
Ethernet loopback active alarm 543 4-170
Ethernet operational measurements
parameter definitions 510 1-63
events
autonomous messages 543 2-19
filtering 543 2-13
logging 543 2-18
printing details 543 2-16
retrieving details 543 2-15
retrieving list 543 2-11
saving details 543 2-17
sorting 543 2-12
updating events window 543 2-14
exerciser
allowing to run as scheduled 311 1-46
inhibiting to run as scheduled 311 1-48
retrieving schedule 311 1-43
running manually 311 1-44
schedule parameters 311 1-42
scheduling 311 1-40
external controls
editing attributes 543 2-59
operating 543 2-62
releasing 543 2-63
retrieving status 543 2-61
external timing source, synchronizing a
network element to 310 1-3

F

facility
adding 350 2-20
deleting 350 2-22
on working DS1 service module (DSM)
DS1x84 termination module
(TM) 350 2-24
details, displaying 350 2-2
displaying with shelf level graphics 302
5-7
editing 350 2-28
identifying the source of an alarm 543 2-52
provisioning AINS for DS1 and DS3 350
2-27
Facility Failure alarm 543 4-171
Facility PM counts table 510 1-45
Facility PM thresholds table 510 1-45
Facility Provisioned Mismatch alarm 543
4-172
facility state
editing
to in-service 350 2-26
to out-of-service 350 2-25
primary states 350 2-3
secondary states
2x100BT-P2P circuit pack 350 2-6
DS1 350 2-4
DS3 350 2-5
EC-1 350 2-5
GE/FC SFP 350 2-6
OC-n 350 2-4
failure count (FC), definition 510 1-57
fan
alarm cable 543 3-64
power cable 543 3-64
replacing on the DS1 service module 543
3-54
replacing the cooling unit fan module 543
3-67
Fan Failure alarm 543 4-174
Fan Missing alarm 543 4-176
Far End Client Rx Signal Failure alarm 543
4-177
fault clearing strategy 543 1-1

-
- fiber
 - cleaning 201 4-2
 - connecting 201 4-2
 - handling 210 1-5, 222 1-5
 - inspecting 201 4-2
 - replacing 210 1-5, 222 1-5
 - routing 201 3-166
 - Fiber cross-connect alarm 543 4-179
 - Fibre Channel (FC)
 - facility
 - editing 350 2-28
 - GE/FC SFP signal attributes 350 2-37
 - Fibre Channel Loopback Active alarm 543 4-178
 - File System Corruption Suspected alarm 543 4-180
 - filtering
 - active alarms 543 2-5
 - events 543 2-13
 - final BLSR configuration data table 224 2-249
 - final section trace parameters (DWDM)
 - table 224 3-84
 - final section trace parameters table 224 2-249
 - FLASH Bank Mismatch alarm 543 4-181
 - Force STS1 Path Switch Complete alarm 543 4-183
 - Force STS12C Path Switch Complete alarm 543 4-183
 - Force STS24C Path Switch Complete alarm 543 4-183
 - Force STS3C Path Switch Complete alarm 543 4-183
 - Force STS48C Path Switch Complete alarm 543 4-183
 - Force Switch Complete alarm 543 4-184
 - Force Switch Complete-Remote alarm 543 4-185
 - Force VT1.5 Path Switch Complete alarm 543 4-186
 - forced line switch
 - operating in BLSR 311 1-32
 - forced path switch
 - operating 311 1-23
 - releasing 311 1-25
 - forced switch
 - operating
 - optical line 311 1-27
 - tributary circuit pack 311 1-18
 - releasing
 - optical interface circuit pack 311 1-30
 - tributary circuit pack 311 1-21
 - FPGA Load Mismatch alarm 543 4-187
 - FPGA load, upgrading 302 6-64
 - FPGA Upgrade Failed alarm 543 4-189
 - FPGA Upgrade in Progress alarm 543 4-188
 - FPGA Upgrade Not Committed alarm 543 4-190
- G**
- GE/FC SFP
 - Ethernet facility
 - signal attributes 350 2-36
 - facility
 - secondary states 350 2-6
 - facility (Ethernet, FC or WAN)
 - editing signal attributes 350 2-28
 - FC facility
 - signal attributes 350 2-37
 - WAN facility
 - signal attributes 350 2-37
 - general broadcast tool
 - sending and receiving messages 302 9-6
 - general requirements for reconfiguration
 - procedures 224 2-253
 - grill/air deflector
 - installing 543 3-65
 - removing 543 3-65
 - grounding
 - installing 201 2-6
 - shelf 543 3-63
- H**
- help for TL1, description 190 1-11
 - hierarchy, alarm 543 5-286
- I**
- I/O module, replacing 543 3-88, 543 3-91
 - identifying faults 543 2-51
 - IEEE routing ID 190 3-7
-

- ILAN circuit pack
 - daisy-chaining 201 3-187
 - replacing 543 3-13
 - replacing with network processor 224 1-6
- ILAN1 Port Failure alarm 543 4-191
- ILAN2 Port Failure alarm 543 4-191
- ILANSP Port Failure alarm 543 4-192
- Incoming Network Access Violation alarm 543 4-193
- Incomplete Load Lineup alarm 543 4-194
- initial BLSR configuration data table 224 2-249
- initial section trace parameters (DWDM) table 224 3-84
- initial section trace parameters table 224 2-249
- in-service
 - editing equipment state to 350 2-16
 - editing facility state to 350 2-26
- inservice traffic rolover
 - backing out 320 6-54
 - bidirectional BLSR channel rolover 320 4-17
 - bidirectional BLSR route rolover 320 4-19
 - bidirectional channel rolover in a BLSR 320 4-24
 - bidirectional matched-node UPSRs 320 3-60
 - bidirectional route rolover in a BLSR 320 4-26
 - bidirectional subtending dual-homed UPSRs 320 3-54
 - bidirectional subtending single-homed UPSRs 320 3-50
 - bidirectional UPSR 320 3-47
 - bidirectional UPSR with linear spur 320 3-48
 - bidirectional VT1.5 rolover within an STS of a BLSR 320 4-21
 - linear drop-and-continue 320 2-10
 - linear network 320 2-8
 - retrieving rolover status 320 6-55
 - rolling
 - between tributary circuit packs 320 6-56
 - endpoints in a network 320 6-52
 - on hairpin cross-connects 320 6-59
 - inservice traffic rolover (continued)
 - unidirectional matched-node UPSRs 320 3-62
 - unidirectional subtending dual-homed UPSRs 320 3-58
 - unidirectional subtending single-homed UPSRs 320 3-52
 - unidirectional UPSR 320 3-46
 - unidirectional UPSR with linear spur 320 3-48
 - inspecting
 - OPTera Metro 3500 shelf container contents 201 3-60
 - installing
 - 2x100BT-P2P circuit pack 201 3-141
 - 2xGigE circuit pack 201 3-149
 - 2xGigE/FC-P2P circuit pack 201 3-141
 - 4x100BT circuit pack 201 3-141
 - 4x100FX circuit pack 201 3-141
 - cable brackets on DS1 I/O module 201 3-92
 - connecting power cable 201 3-95
 - cooling unit upgrade kit 543 3-55
 - drip tray 201 3-41
 - DS1 mapper 201 3-129
 - DS3VTx12 mapper 201 3-134
 - DS3x12 mapper 201 3-134
 - DS3x12e mapper 201 3-134
 - DS3x3 mapper 201 3-134
 - DSM front cover 201 3-225
 - DSM shelf 201 3-218
 - EC-1x12 circuit pack 201 3-134
 - EC-1x3 circuit pack 201 3-134
 - environmental requirements 201 2-1
 - equipment frame requirements 201 2-1
 - Fiber Manager equipment drawer (NT0H57BB) 201 3-202
 - grill/air deflector 201 3-183, 543 3-65
 - grounding and isolation 201 2-6
 - hardware 201 3-2
 - I/O modules on NTN476AH shelf 201 3-80
 - I/O modules on NTN476DA shelf 201 3-71
 - ILAN circuit pack 201 3-125
 - materials required 201 2-5
 - network processor circuit pack 201 3-125

-
- installing (continued)
 - NTFW56BA BIP (European deployment only) 201 3-53
 - NTN458RA BIP 201 3-45
 - OMX shelf 201 3-197
 - OMX+Fiber Manager 4CH equipment drawer (NT0H32AE-HE, NT0H32AF-HF) 201 3-204
 - OPTera Metro 3500 shelf 201 3-63
 - optical interface circuit pack 201 3-119
 - Packet Edge circuit pack 201 3-141, 201 3-149
 - power module kit 543 3-55
 - PSC circuit pack 201 3-129
 - PSX circuit pack 201 3-129
 - rear cable retainer 201 3-93
 - SFP modules 201 3-152
 - shelf air filter 543 3-87
 - shelf front cover 201 3-181, 543 3-66
 - shelf power requirements 201 2-3
 - software on shelf processor
 - from local PC 302 6-49
 - over Ethernet 302 6-52
 - STX-192 circuit pack 201 3-110
 - tools required 201 2-4
 - VTX-48 circuit pack 201 3-110
 - VTX-48e circuit pack 201 3-110
 - installing SPx circuit pack 201 3-110
 - Insufficient Link Capacity alarm 543 4-195
 - Intercard Failed alarm 543 4-196
 - Intercard Serial Link Failed alarm 543 4-199
 - Intercard Suspected - Pluggable alarm 543 4-202
 - Intercard Suspected alarm 543 4-200
 - internal timing source, synchronizing network element 310 1-4
 - intrusion alarms, clearing 302 3-27
 - Intrusion Attempt alarm 543 4-203
 - intrusion attempts handling
 - defaults parameters, editing 302 3-28
 - details, displaying 302 3-24
 - enabling 302 3-25
 - Invalid K-bytes alarm 543 4-204
 - invalid password
 - adding 302 3-21
 - deleting 302 3-23
 - displaying 302 3-19
 - inventory
 - copying information 302 5-10
 - displaying 302 5-8
 - displaying for DS1 service module (DSM) 302 5-9
- L**
- lamp test 543 2-53
 - DS1 service module (DSM) 543 2-53, 302 5-6
 - LAN, connecting cable 201 3-101
 - laser radiation, safety precautions 210 1-4, 222 1-4
 - Latch Open alarm 543 5-12
 - LIF, replacing 543 3-79
 - Line PM Threshold Exceeded alarm 543 5-13
 - line rate upgrade
 - OC-12 to OC-48 224 2-176
 - OC-3 to OC-12 224 2-169
 - linear inservice traffic rollover 320 2-8
 - drop-and-continue 320 2-10
 - linear network, configuration table 224 2-47, 224 2-73, 224 2-140, 224 2-149
 - line-timing source
 - parameter 310 1-6
 - synchronizing network element to 310 1-5
 - Link Degrd and Virtual Ckt Fail alarm 543 5-19
 - Link Down (network processor) alarm 543 5-26
 - Link Down 1/1 alarm 543 5-27
 - Link Down 1/2 alarm 543 5-27
 - Link Down 1/3 alarm 543 5-27
 - Link Down 1/4 alarm 543 5-27
 - Link Down 2/1 alarm 543 5-27
 - Link Down 2/2 alarm 543 5-27
 - Link Down alarm (2x100BT-P2P) 543 5-20
 - Link Down alarm (2XGigE/FC-P2P) 543 5-22
 - Link Performance Degraded alarm 543 5-28
 - Link Pulse Missing alarm 543 5-29
 - Load Installation Failed alarm 543 5-30
 - Load Installation in Progress alarm 543 5-32
 - Loads Mismatch alarm 543 5-33
-

LOAM

- connectors 543 3-81
- replacing 543 3-79
- lockout
 - operating
 - DS1 mapper 311 1-20
 - optical interface circuit pack 311 1-28
 - releasing
 - optical interface circuit pack 311 1-30
 - tributary circuit pack 311 1-21
- lockout of protection
 - operating 311 1-35
 - releasing 311 1-30
- Lockout of Protection Complete alarm 543 5-35
- Lockout of Protection Complete-Remote alarm 543 5-36
- lockout of working
 - operating 311 1-33
 - releasing 311 1-30
- Lockout of Working Complete alarm 543 5-37
- logging events 543 2-18
- logging in
 - BCC CLI 302 2-37
 - network element
 - automatically 302 2-30
 - manually 302 2-31
 - through DS1 service module (DSM) 302 2-34
 - using direct cable 302 2-32
 - network processor
 - and configuring an X25 connection 302 2-10
 - using a modem 302 2-7
 - using direct cable 302 2-11
 - using the network 302 2-4
 - setting preferences 302 2-36
 - using a login profile 302 2-16
- logging out
 - BCC CLI 302 2-39
 - network element 302 2-40
 - network processor 302 2-40

- login banner
 - editing manually 302 9-2
 - refreshing 302 9-5
 - replacing with backup login banner 302 9-2
 - replacing with default login banner 302 9-2
 - saving to a file 302 9-4
- login profile
 - adding
 - for a direct cable connection 302 2-25
 - for a modem connection 302 2-22
 - for a network connection 302 2-19
 - for a terminal session using direct cable 302 2-27
 - for a terminal session using modem 302 2-24
 - for a terminal session using the network 302 2-21
 - deleting 302 2-29
 - editing 302 2-28
 - using to log in 302 2-16
- Loss of BITSout-A Pri. Timing Ref. alarm 543 5-38
- Loss of BITSout-A Sec. Timing Ref. alarm 543 5-38
- Loss of BITSout-B Pri. Timing Ref. alarm 543 5-38
- Loss of BITSout-B Sec. Timing Ref. alarm 543 5-38
- Loss of Shelf Pri. Timing Ref. alarm 543 5-39
- Loss of Shelf Sec. Timing Ref. alarm 543 5-39
- Loss of Traffic alarm 543 5-41
- Low Voltage alarm 543 5-43
- lower layer SDCC attributes 350 2-41

M

- manual area address
 - adding 520 3-17
 - attributes 350 2-44
 - deleting 520 3-20
 - editing 520 3-17
 - retrieving (of the network processor) 520 3-16

-
- manual connection terminal session
 - closing 302 4-10
 - starting 302 4-5
 - manual line switch
 - operating in 1+1 linear 311 1-26
 - operating in BLSR 311 1-31
 - manual path switch
 - operating 311 1-22
 - manual switch
 - operating on a tributary circuit pack 311 1-16
 - releasing on a tributary circuit pack 311 1-21
 - Manual Switch Complete alarm 543 5-45
 - Manual Switch Complete-Remote alarm 543 5-46
 - manually updating active alarms 543 2-7
 - map topology
 - adding a background image 520 5-27
 - adding a label 520 5-16
 - changing background color of a map 520 5-20
 - changing grid color of a map 520 5-20
 - changing label color of a map 520 5-20
 - clearing a single alarm balloon 520 5-22
 - clearing all alarm balloons 520 5-23
 - deleting a label 520 5-18
 - display options 520 5-33
 - displaying network element information 520 5-33
 - displaying the active alarms of a network element 520 5-36
 - displaying the shelf graphics of a network element 520 5-37
 - editing a label 520 5-17
 - logging in to a network element 520 5-24
 - logging in to a network element as a different user 520 5-25
 - logging out of a network element 520 5-26
 - modifying grid settings 520 5-21
 - moving a background image 520 5-31
 - moving a network element on a map 520 5-14
 - printing a map 520 5-38
 - removing a background image 520 5-32
 - removing a disabled network element or link on a map 520 5-12
 - map topology (continued)
 - removing all disabled items on a map 520 5-13
 - repositioning a label 520 5-19
 - resizing a background image
 - automatically 520 5-29
 - manually 520 5-30
 - retrieving a new map 520 5-3
 - retrieving a saved map 520 5-8
 - saving a map 520 5-6
 - selecting all nodes on a map 520 5-11
 - setting the default directory 520 5-7
 - showing or hiding a background image 520 5-28
 - zooming in and out on a map 520 5-15
 - materials required
 - adding a network element to a BLSR 224 2-263, 224 2-264
 - adding a network element to a UPSR 224 2-264
 - adding a new terminal network element to a linear network 224 2-263
 - adding an ADM network element to a linear network 224 2-263
 - converting 2-node UPSR to linear point-to-point 224 2-265
 - converting Full VT to VT assigned BLSR 224 2-265
 - converting linear point-to-point to 2-node UPSR 224 2-265
 - converting VT assigned to Full VT BLSR 224 2-265
 - DWDM reconfiguration procedures 224 3-91
 - removing a network element from a BLSR 224 2-264
 - removing a network element from a UPSR 224 2-264
 - removing a terminal network element from a linear network 224 2-264
 - removing an ADM network element from a linear network 224 2-264
 - upgrading line rate of fiber span 224 2-265
-

modem

- connecting to the shelf 201 3-189
- defining settings 302 2-14

moving BLSR configuration from NPx to NPx 320 6-49

N

NE Prov Script File Load Failed alarm 543 5-48

network diagram

- 2-node UPSR 224 2-194
 - adding a linear ADM node 224 2-46
 - adding a network element to a BLSR 224 2-95
 - adding a network element to a UPSR 224 2-82
 - adding a terminal network element to a linear network 224 2-71
 - linear point-to-point fiber span 224 2-195
 - logical UPSR with network element to be removed (over DWDM) 224 3-41
 - removing a network element from a BLSR 224 2-167
 - removing a network element from a linear network 224 2-139, 224 2-148
 - removing a network element from a UPSR 224 2-156
 - synchronization map
 - adding a network element to a BLSR 224 2-96
 - adding a network element to a UPSR 224 2-83
 - removing a network element from a BLSR 224 2-168
 - removing a network element from a UPSR 224 2-157
 - UPSR fiber span 224 2-184
- network element 520 4-2
- adding to a BLSR 224 2-84
 - adding to a BLSR over DWDM 224 3-61
 - adding to a linear network 224 2-2, 224 2-53
 - adding to a UPSR 224 2-74
 - adding to a UPSR over DWDM 224 3-19
 - commissioning 210 2-2
 - disconnecting from 302 2-41

network element (continued)

- displaying information 350 1-2
- editing
 - date and time 302 3-40
 - name 302 3-37
 - time zone 302 3-40
- logging in
 - automatically 302 2-30
 - manually 302 2-31
 - through DS1 service module (DSM) 302 2-34
 - using direct cable 302 2-32
- logging out 302 2-40
- provisioning a hardware terminal
 - loopback 222 2-53
 - removing from a BLSR 224 2-158
 - removing from a BLSR over DWDM 224 3-72
 - removing from a UPSR 224 2-150
 - removing from a UPSR over DWDM 224 3-32
 - removing from linear network 224 2-97, 224 2-141
- restoring to initial state 222 2-59
- retrieving
 - information 302 3-36
 - security 210 2-2
 - setting date 210 2-2
 - setting time 210 2-2
 - time of day synchronization 210 2-2
 - type, editing 302 3-42
- upgrading software
 - from local PC 302 6-58
 - over Ethernet 302 6-61
 - user account provisioning 210 2-2
- network element A cross-connects (DWDM) table 224 3-85
- network element A cross-connects table 224 2-250
- network element B cross-connects (DWDM) table 224 3-86
- network element B cross-connects table 224 2-251
- network element C cross-connects (DWDM) table 224 3-87
- network element C cross-connects table 224 2-252

-
- network processor
 - adding software from
 - OPC or network processor over direct cable 302 6-70
 - OPC or network processor over the network 302 6-68
 - PC over Ethernet 302 6-66
 - commissioning 210 2-5
 - daisy-chaining 201 3-187
 - deleting
 - shelf processor backups from 302 6-46, 302 6-47
 - software load 302 6-73
 - disconnecting from 302 2-41
 - editing
 - date and time 302 3-40
 - name 302 3-37
 - time zone 302 3-40
 - facility
 - adding 520 3-2
 - deleting 520 3-21
 - logging in
 - and configuring an X25 connection 302 2-10
 - using a modem 302 2-7
 - using direct cable 302 2-11
 - using the network 302 2-4
 - logging out 302 2-40
 - relocating 224 2-221
 - replacing 543 3-10
 - replacing with ILAN circuit pack 224 1-3
 - restarting 543 2-49
 - retrieving
 - information 302 3-36
 - software release list 302 6-72
 - security 210 2-5
 - time of day 210 2-5
 - upgrading software 302 6-55
 - user accounts 210 2-5
 - viewing software version 302 6-74
 - network processor TID table 224 2-202
 - Node ID mismatch alarm 543 5-49
 - node information, displaying 350 1-2
 - NP Ethernet LAN RJ-45 cable
 - assembly 201 5-34
 - pinout 201 5-34
 - NSAP
 - building an NSAP value 520 6-10
 - editing 520 6-10
 - using Build NSAP dialog box 520 6-10
- O**
- OAM Not Available alarm 543 5-50
 - OC12 Loopback Active alarm 543 5-53
 - OC12 Rx Line AIS alarm 543 5-73
 - OC12 Rx Loss of Frame alarm 543 5-75
 - OC12 Rx Loss of Signal alarm 543 5-78
 - OC12 Rx RFI alarm 543 5-81
 - OC12 Rx section trace mismatch alarm 543 5-83
 - OC12 Rx Signal Degrade alarm 543 5-85
 - OC12 Rx Signal Failure alarm 543 5-88
 - OC-12, testing signal continuity 222 2-18
 - OC192 Loopback Active alarm 543 5-53
 - OC192 Rx Line AIS alarm 543 5-109
 - OC192 Rx Loss of Frame alarm 543 5-111
 - OC192 Rx Loss of Signal alarm 543 5-114
 - OC192 Rx RFI alarm 543 5-118
 - OC192 Rx Section Trace Mismatch alarm 543 5-120
 - OC192 Rx Signal Degrade alarm 543 5-122
 - OC192 Rx Signal Failure alarm 543 5-125
 - OC-3, replacing with OC-3x4 circuit pack 224 1-14
 - OC3 Loopback Active alarm 543 5-53
 - OC3 Rx Line AIS alarm 543 5-54
 - OC3 Rx Loss of Frame alarm 543 5-57
 - OC3 Rx Loss of Signal alarm 543 5-60
 - OC3 Rx RFI alarm 543 5-63
 - OC3 Rx section trace mismatch alarm 543 5-65
 - OC3 Rx Signal Degrade alarm 543 5-67
 - OC3 Rx Signal Failure alarm 543 5-70
 - OC-3x4, testing signal continuity 222 2-18
 - OC48 Loopback Active alarm 543 5-53
 - OC48 Rx Line AIS alarm 543 5-91
 - OC48 Rx Loss of Frame alarm 543 5-93
 - OC48 Rx Loss of Signal alarm 543 5-96
 - OC48 Rx RFI alarm 543 5-99
 - OC48 Rx Section Trace Mismatch alarm 543 5-101
 - OC48 Rx Signal Degrade alarm 543 5-103
-

OC48 Rx Signal Failure alarm 543 5-106

OC-n

facility

alarm hierarchy 543 5-287

secondary states 350 2-4

office alarm cable

assembly 201 5-31

pinout 201 5-31

OMX

adding to an in-service DWDM

network 224 3-2

installation

connecting OMX+Fiber Manager 4CH
(NT0H32AE-HE, NT0H32AF-HF) to
OPTera Metro 3500 201 3-211

inspecting Fiber Manager (NT0H57BB)

container contents 201 3-201

inspecting OMX Shelf (NTN449ZW)

container contents 201 3-195

installing Fiber Manager equipment

drawer (NT0H57BB) 201 3-202

installing OMX shelf

(NTN449ZW) 201 3-197

installing OMX+Fiber Manager 4CH
equipment drawer (NT0H32AE-HE,
NT0H32AF-HF) 201 3-204

removing and installing OMX Shelf
(NTN449ZW) protective cover 201
3-200

removing and installing the protective
cover 201 3-200

OPE circuit pack

attaching to an existing RPR 320 5-22

installing 201 3-141, 201 3-149

replacing 543 3-15

operating, external controls 543 2-62

operational measurements

polling 510 1-22

retrieving 510 1-20

OPTera Connect DX bay, single shelf 201 3-1

OPTera Metro 3500 installation

grounding the shelf 201 3-69

inspecting shipping container contents 201
3-60

installing the shelf 201 3-63

OPTera Metro 3500 shelf

locking 201 3-185

unlocking 201 3-185

OPTera Packet Edge system

2 x GigE 201 3-149

4x100BT 201 3-141

4x100FX 201 3-141

optical connector

attaching to the optical interface 201 3-175

cleaning 201 4-9

optical interface circuit pack

autonomous messages, format 190 1-9

command response header, format 190 1-8

editing line SDTH 350 2-38

help for TL1 190 1-11

introduction to TL1 commands 190 1-3

operating forced optical line switch 311
1-27

operating lockout 311 1-28

operating manual optical line switch 311
1-26

replacing

in a BLSR 543 3-41

in a linear system 543 3-34

in a UPSR 543 3-38

specifications 224 2-265

TL1 message notation 190 1-6

TL1 message types 190 1-7

TL1 overview 190 1-1

optical power received (OPR)

definition 510 1-60

resetting baseline 510 1-41

optical power received normalized (OPRN),

definition 510 1-61

out-of-service

editing equipment state to 350 2-15

editing facility state to 350 2-25

P

Packet Edge circuit pack

installing 201 3-141, 201 3-149

replacing 543 3-15

upgrading FPGA load 302 6-64

-
- password
 - adding invalid 302 3-21
 - deleting invalid 302 3-23
 - displaying invalid 302 3-19
 - editing 302 3-17
 - password identifier (PID), definition 190 1-3
 - Path PM Threshold Exceeded alarm 543
 - 5-128
 - path switch, releasing 311 1-25
 - path trace
 - disabling 520 2-7
 - editing 520 2-8
 - enabling 520 2-7
 - procedures 520 2-1
 - retrieving 520 2-6
 - performance monitoring (PM)
 - collection, stopping 510 1-24
 - counts
 - clearing 510 1-25, 510 1-26
 - restarting 510 1-25, 510 1-26
 - editing the PM threshold crossing report
 - type 510 1-44
 - Ethernet operational measurements
 - parameter definitions 510 1-63
 - Facility PM counts table 510 1-45
 - facility PM counts, retrieving 510 1-3
 - DS1 510 1-4
 - DS3 510 1-6
 - DSM 510 1-5
 - EC-1 510 1-18
 - Ethernet 510 1-19
 - FC 510 1-19
 - history counts 510 1-27
 - OC-12 510 1-17
 - OC-192 510 1-17
 - OC-3 510 1-17
 - OC-48 510 1-17
 - STS-1 510 1-7
 - STS-12c 510 1-11
 - STS-24c 510 1-13
 - STS-3c 510 1-9
 - STS-48c 510 1-15
 - WAN 510 1-19
 - Facility PM thresholds table 510 1-45
 - performance monitoring (PM) (continued)
 - history counts
 - printing 510 1-28
 - retrieving 510 1-27
 - saving 510 1-28
 - operational measurements
 - polling 510 1-22
 - retrieving 510 1-20
 - parameters
 - by facility 510 1-54
 - definitions 510 1-56
 - descriptions 510 1-51
 - thresholds
 - default values 510 1-46
 - maximum values 510 1-46
 - thresholds, editing
 - default values 510 1-42
 - monitoring status 510 1-43
 - values 510 1-40
 - thresholds, retrieving
 - DS1 510 1-29
 - DS3 510 1-31
 - DSM 510 1-30
 - EC-1 510 1-38
 - Ethernet 510 1-39
 - FC 510 1-39
 - OC-12 510 1-37
 - OC-192 510 1-37
 - OC-3 510 1-37
 - OC-48 510 1-37
 - STS-1 510 1-32
 - STS-12c 510 1-34
 - STS-24c 510 1-35
 - STS-3 510 1-33
 - STS-48c 510 1-36
 - WAN 510 1-39
 - untimed counts
 - clearing 510 1-26
 - restarting 510 1-26
 - performing lamp tests 543 2-53
 - PLL Not Locked to Timing Ref. alarm 543
 - 5-134
 - power cable
 - assembly 201 5-13
 - connecting to the shelf 201 3-95
 - pinout 201 5-13
 - Power failure - A alarm 543 5-135
-

- Power failure - B alarm 543 5-135
- power module kit, installing 543 3-55
- power module, replacing 543 3-77
- Primary RADIUS Server Unavailable alarm 543 5-137
- Primary Security Gateway Unavailable alarm 543 5-138
- primary states
 - equipment 350 2-3
 - facility 350 2-3
- printing
 - active alarm details 543 2-9
 - Comm Log 302 4-8
 - event details 543 2-16
 - PM history counts 510 1-28
 - telnet terminal session 302 4-7
- protection
 - operating
 - forced line switch 311 1-27
 - forced path switch in UPSR 311 1-23
 - forced switch on a tributary circuit pack 311 1-18
 - lockout on optical interface circuit pack 311 1-28
 - lockout on tributary circuit pack 311 1-20
 - manual path switch 311 1-22
 - manual switch in 1+1 linear 311 1-26
 - manual switch on tributary circuit pack 311 1-16
 - releasing
 - optical interface line switch 311 1-30
 - path switch 311 1-25
 - tributary circuit pack 311 1-21
- protection exerciser
 - allowing to run as scheduled 311 1-46
 - inhibiting to run as scheduled 311 1-48
 - retrieving schedule 311 1-43
 - running manually 311 1-44
 - scheduling 311 1-40
- Protection Exerciser Failed alarm 543 5-139
- Protection Mode Mismatch alarm 543 5-141
- protection scheme
 - changing
 - from 1+1 linear to UPSR 311 1-6
 - from BLSR to UPSR 311 1-12
 - from UPSR to 1+1 linear 311 1-8
 - from UPSR to BLSR 311 1-10
 - deleting
 - 1+1 linear protection 311 1-6
 - retrieving 311 1-3
- Protection Scheme Mismatch alarm 543 5-143
- protection status, retrieving 311 1-15
- protection switch count (PSC), definition 510 1-62
- protection switch duration (PSD), definition 510 1-62
- Protection switch fail alarm 543 5-144
- protection switch mode
 - changing (1+1 linear) 311 1-4
 - retrieving 311 1-3
- protection switching
 - testing in a DWDM system 222 2-29
 - testing in a linear point-to-point configuration 222 2-25
 - testing in a non-DWDM system 222 2-21
 - testing in a UPSR 222 2-27
- provisioning
 - BLSR configuration 320 6-34
 - circuit pack
 - automatically 350 2-7
 - manually 350 2-9
 - cross-connects
 - bidirectional BLSR 320 4-2
 - bidirectional BLSR and linear spur 320 4-7
 - bidirectional BLSR with subtending UPSR 320 4-11
 - bidirectional linear configuration 320 2-2
 - bidirectional matched-node UPSRs 320 3-39
 - bidirectional subtending dual-homed dual link UPSRs 320 3-27
 - bidirectional subtending dual-homed single link UPSRs 320 3-33
 - bidirectional subtending single-homed UPSRs 320 3-21

-
- provisioning (continued)
 - cross-connects (continued)
 - bidirectional UPSR 320 3-3
 - bidirectional UPSR with linear spur 320 3-13
 - drop-and-continue linear configuration 320 2-5
 - hairpin 320 6-25
 - unidirectional drop-and-continue UPSR 320 3-9
 - unidirectional linear configuration 320 2-2
 - unidirectional matched-node UPSRs 320 3-42
 - unidirectional subtending dual-homed dual link UPSRs 320 3-30
 - unidirectional subtending dual-homed single link UPSRs 320 3-36
 - unidirectional subtending single-homed UPSRs 320 3-24
 - unidirectional UPSR 320 3-6
 - unidirectional UPSR with linear spur 320 3-17
 - DS1 service module (DSM) DS1x84 termination module (TM) manually 350 2-13
 - hardware terminal loopback 222 2-53
 - RPR (virtual) over Layer 1 core and subtending rings 320 5-14
 - RPR over a simple ring 320 5-2
 - RPR over Layer 1 subtending rings 320 5-7
 - software terminal loopback 222 2-56
 - provisioning data
 - restoring
 - from local PC to network processor over Ethernet 302 6-31
 - from local PC to shelf processor 302 6-5
 - from network processor to shelf processor 302 6-10
 - from OPC to network processor over OSI 302 6-36
 - from OPC to network processor over TCP/IP 302 6-42
 - restoring (continued)
 - from remote PC with FTP server to network processor 302 6-21
 - from UNIX workstation to network processor 302 6-26
 - saving
 - from all shelf processors in span of control to network processor 302 6-13
 - from network processor to OPC over OSI 302 6-34
 - from network processor to OPC over TCP/IP 302 6-40
 - from network processor to PC over Ethernet 302 6-29
 - from network processor to remote PC with FTP server 302 6-19
 - from network processor to UNIX workstation 302 6-24
 - from shelf processor to local PC 302 6-3
 - from shelf processor to network processor 302 6-8
 - PSC circuit pack
 - installing 201 3-129
 - replacing 543 3-45
 - PSX circuit pack
 - installing 201 3-129
 - replacing 543 3-47
 - PVC
 - changing a PVC to an SVC 520 3-13
 - changing an SVC to a PVC 520 3-11
 - editing the PVC parameter values 520 3-12
- ## R
- radio-frequency emissions 201 1-11, 210 1-5, 222 1-6
 - reconfiguration worksheets
 - Full VT to VT assigned 224 2-213
 - VT assigned to Full VT 224 2-203
 - releasing external controls 543 2-63
 - Remote Alarm(s) alarm 543 5-145
 - Remote Fail alarm 543 5-147
 - remote login session, starting from an OPTera Metro 3500 network element 302 2-17
-

removing

- DSM front cover 201 3-225
- grill/air deflector 201 3-183, 543 3-65
- network element from a BLSR 224 2-158
- network element from a BLSR over DWDM 224 3-72
- network element from a linear network 224 2-97, 224 2-141
- network element from a UPSR 224 2-150
- network element from a UPSR over DWDM 224 3-32
- SFP modules 201 3-152
- shelf front cover 201 3-181, 543 3-66
- traffic from UPSR span 224 3-81

replacing

- 2x100BT-P2P circuit pack 543 3-17
- 2xGigE circuit pack 543 3-15
- 2xGigE/FC-P2P circuit pack 543 3-18
- 4x100BT circuit pack 543 3-15
- 4x100FX circuit pack 543 3-15, 543 3-16
- cooling unit assembly 543 3-57
- cooling unit fan module 543 3-67
- cooling unit fan module, universal 543 3-75
- DS1 mapper 543 3-24
- DS1-I/O module on the DSM 543 3-84
- DS3VTx12 mapper 543 3-30
- DS3x12 mapper 543 3-30
- DS3x12e mapper 543 3-30
- DS3x3 mapper 543 3-30
- DS3x3 mapper with DS3x12 mapper 224 1-8, 224 1-14
- DSM DS1x84 TM mapper 543 3-26
- EC-1x12 circuit pack 543 3-32
- EC-1x3 circuit pack 543 3-32
- EC-1x3 circuit pack with EC-1x12 circuit pack 224 1-11
- fan module on the DS1 service module 543 3-54
- I/O module 543 3-88, 543 3-91
- ILAN circuit pack 543 3-13
- ILAN circuit pack with network processor 224 1-6
- LIF 543 3-79
- LOAM 543 3-79
- network processor 543 3-10

replacing (continued)

- network processor with ILAN circuit pack 224 1-3
 - OAM module on DSM 543 3-82
 - OC-3 with OC-3x4 circuit pack 224 1-14
 - optical interface circuit pack (BLSR) 543 3-41
 - optical interface circuit pack (linear system) 543 3-34
 - optical interface circuit pack (UPSR) 543 3-38
 - Packet Edge circuit pack 543 3-15
 - power module 543 3-77
 - PSC circuit pack 543 3-45
 - PSX 543 3-47
 - SFP modules 543 3-21, 543 3-23
 - shelf air filter 543 3-85
 - shelf processor 543 3-7
 - STX-192 circuit pack 543 3-51
 - universal cooling unit assembly 543 3-69
 - universal cooling unit fan module 543 3-75
 - VTX-48 circuit pack 543 3-48
 - VTX-48e circuit pack 543 3-48
- requirements
- general
 - for DWDM reconfiguration procedures 224 3-90
 - for reconfiguration procedures 224 2-253
 - specific
 - adding a network element to a BLSR 224 2-255
 - adding a network element to a DWDM ring 224 3-93
 - adding a network element to a UPSR 224 2-253, 224 2-254
 - converting 2-node UPSR to linear point-to-point 224 2-258
 - converting a UPSR to a UPSR over DWDM 224 3-92
 - converting Full VT to VT assigned BLSR 224 2-259
 - converting VT assigned to Full VT BLSR 224 2-258
 - removing a network element from a BLSR 224 2-256

-
- requirements (continued)
 - specific (continued)
 - removing a network element from a DWDM ring 224 3-94
 - removing a network element from a UPSR 224 2-256
 - upgrading span from OC-12 to OC-48 224 2-257
 - upgrading span from OC-3 to OC-12 224 2-256
 - reseating
 - circuit pack 543 3-4
 - restarting
 - circuit pack 543 2-45
 - facility PM counts 510 1-25
 - network processor 543 2-49
 - shelf processor 543 2-47
 - untimed PM counts 510 1-26
 - restoring
 - network element 222 2-59
 - provisioning data
 - from local PC to network processor over Ethernet 302 6-31
 - from local PC to shelf processor 302 6-5
 - from network processor to shelf processor 302 6-10
 - from OPC to network processor over OSI 302 6-36
 - from OPC to network processor over TCP/IP 302 6-42
 - from remote PC with FTP server to network processor 302 6-21
 - from UNIX workstation to network processor 302 6-26
 - traffic to UPSR span 224 3-83
 - retrieving 543 2-8
 - active alarms
 - by network element 543 2-3
 - details 543 2-8
 - from Shelf Level View 543 2-50
 - raised against disabled alarm points 543 2-27
 - alarm points
 - by class 543 2-25
 - by equipment type 543 2-26
 - alarm profile details 543 2-32
 - retrieving (continued)
 - alarm profiles
 - by alarm class 543 2-30
 - by equipment 543 2-31
 - by facility type 543 2-31
 - BLSR audit diagnostics 320 6-45
 - BLSR configuration 320 6-33
 - cross-connects 320 6-3
 - environmental alarm attributes 543 2-56
 - event details 543 2-15
 - event list 543 2-11
 - external control status 543 2-61
 - line SDTH 311 1-36
 - list of shelf processor backups on network processor 302 6-45
 - map 520 5-3
 - network element information 302 3-36
 - network processor information 302 3-36
 - network processor manual area address 520 3-16
 - network processor span of control 520 4-2
 - operational measurements 510 1-20
 - path SDTH 311 1-38
 - path trace messages 520 2-6
 - PM counts 510 1-3
 - DS1 facility 510 1-4
 - DS3 facility 510 1-6
 - DSM facility 510 1-5
 - EC-1 facility 510 1-18
 - Ethernet facility 510 1-19
 - FC facility 510 1-19
 - history 510 1-27
 - OC-12 facility 510 1-17
 - OC-192 facility 510 1-17
 - OC-3 facility 510 1-17
 - OC-48 facility 510 1-17
 - STS-1 facility 510 1-7
 - STS-12c facility 510 1-11
 - STS-24c facility 510 1-13
 - STS-3c facility 510 1-9
 - STS-48c facility 510 1-15
 - WAN facility 510 1-19
 - PM thresholds
 - DS1 facility 510 1-29
 - DS3 facility 510 1-31
 - DSM facility 510 1-30
 - EC-1 facility 510 1-38
-

retrieving (continued)
 PM thresholds (continued)
 Ethernet facility 510 1-39
 FC facility 510 1-39
 OC-12 facility 510 1-37
 OC-192 facility 510 1-37
 OC-3 facility 510 1-37
 OC-48 facility 510 1-37
 STS-1 facility 510 1-32
 STS-12c facility 510 1-34
 STS-24c facility 510 1-35
 STS-3 facility 510 1-33
 STS-48c facility 510 1-36
 WAN facility 510 1-39
 protection scheme 311 1-3
 protection status details 311 1-15
 protection switch mode 311 1-3
 saved map 520 5-8
 section trace messages 520 2-2
 security logs 302 3-29
 software release list on network
 processor 302 6-72
 synchronization data 310 1-2
 Rollover in Progress alarm 543 5-150
 routing
 optical fiber 201 3-166
 T1, T3, and Cat 5 UTP cabling to
 rear-facing I/O modules 201 3-158
 T1, T3, and Cat 5 UTP to front-facing I/O
 modules 201 3-156
 RPR (resilient packet ring)
 adding cross-connects 320 6-21
 attaching an OPE circuit pack 320 5-22
 deleting cross-connect 320 6-6
 provisioning over a simple ring 320 5-2
 provisioning over Layer 1 core and
 subtending rings 320 5-14
 provisioning over Layer 1 subtending
 rings 320 5-7
 RS-232 DCE DB25 cable
 assembly 201 5-28
 pinout 201 5-28
 RS-232 null modem cable
 assembly 201 5-11
 pinout 201 5-11
 running, script 302 7-14
 Rx Excessive Error Ratio alarm 543 5-151

Rx Loss of Data Synch alarm 543 5-155
 Rx Loss of Frame Delineation alarm 543
 5-158
 Rx Loss of Signal alarm 543 5-159
 Rx Signal Degrade alarm 543 5-162

S

safety 201 1-2
 circuit pack, static electricity 222 1-2
 equipment location 210 1-6, 222 1-6
 handling fiber 210 1-5, 222 1-5
 laser radiation 210 1-4, 222 1-4
 radio-frequency emissions 201 1-11, 210
 1-5, 222 1-6
 replacing fiber 210 1-5, 222 1-5
 saving
 active alarm details 543 2-10
 event details 543 2-17
 maps 520 5-6
 PM history counts 510 1-28
 provisioning data
 from all shelf processors in span of
 control to network processor 302
 6-13
 from network processor to OPC over
 OSI 302 6-34
 from network processor to OPC over
 TCP/IP 302 6-40
 from network processor to PC over
 Ethernet 302 6-29
 from network processor to remote PC
 with FTP server 302 6-19
 from network processor to UNIX
 workstation 302 6-24
 from shelf processor to local PC 302 6-3
 from shelf processor to network
 processor 302 6-8
 schedule parameters, exerciser 311 1-42
 scheduling a BLSR audit 320 6-45
 script
 building 302 7-6
 editing 302 7-11
 loading 302 7-10
 running 302 7-14

-
- SDCC 190 18-1
 - disabling lower layer 350 2-39
 - editing lower layer 350 2-40
 - editing upper layer 350 2-42
 - enabling lower layer 350 2-39
 - lower layer attributes 350 2-41
 - map 520 5-3
 - SDCC Link Failure alarm 543 5-166
 - SDTH
 - line
 - editing 311 1-37
 - retrieving 311 1-36
 - of an optical interface, editing 350 2-38
 - path
 - editing 311 1-39
 - retrieving 311 1-38
 - Secondary RADIUS Server Unavailable alarm 543 5-170
 - Secondary Security Gateway Unavailable alarm 543 5-171
 - secondary states
 - 2x100BT-P2P facility 350 2-6
 - DS1 facility 350 2-4
 - DS3 facility 350 2-5
 - EC-1 facility 350 2-5
 - equipment 350 2-3
 - GE/FC SFP facility 350 2-6
 - OC-n facility 350 2-4
 - Section PM Threshold Exceeded alarm 543 5-172
 - section trace
 - editing 520 2-4
 - procedures 520 2-1
 - retrieving 520 2-2
 - security
 - access level
 - Transaction Language 1 (TL1)
 - definition 190 1-4
 - clearing alarms 302 3-27
 - clearing alarms for customer managed network 302 3-35
 - editing default parameters 302 3-14
 - retrieving logs 302 3-29
 - selecting show in-service traffic rollover 320 6-51
 - setting up backup NPx for a BLSR 320 6-47
 - severely errored frame seconds (SEFS),
 - definition 510 1-56
 - severely errored frame/alarm indication signal seconds (SAS), definition 510 1-58
 - severely errored seconds (SES),
 - definition 510 1-56
 - SFP modules
 - installing 201 3-152
 - removing 201 3-152
 - replacing 543 3-21, 543 3-23
 - shelf 201 5-13
 - connecting a terminal or modem 201 3-189
 - connecting power cable 201 3-95
 - copying inventory information 302 5-10
 - graphics, displaying 302 5-2
 - grounding 543 3-63
 - installing and removing front cover 201 3-181
 - inventory, displaying 302 5-8
 - shelf air filter
 - installing 543 3-87
 - replacing 543 3-85
 - shelf alarms
 - connecting cables 201 3-101, 201 3-234
 - interface characteristics 201 3-101, 201 3-234
 - shelf equipment alarm hierarchy 543 5-292
 - shelf front cover
 - installing 543 3-66
 - removing 543 3-66
 - shelf processor
 - commissioning 210 2-2
 - installing software
 - from local PC 302 6-49
 - over Ethernet 302 6-52
 - replacing 543 3-7
 - restarting 543 2-47
 - retrieving list of backups on network processor 302 6-45
 - security 210 2-2
 - setting date 210 2-2
 - setting network element name 210 2-2
 - setting time 210 2-2
 - time of day synchronization 210 2-2
 - user account provisioning 210 2-2
 - viewing software version 302 6-75
-

- signal attributes
 - 2x100BT-P2P Ethernet facility 350 2-34
 - 2x100BT-P2P WAN facility 350 2-35
 - DS1 350 2-30
 - DS3 350 2-33
 - EC-1 350 2-33
 - editing for facility 350 2-28
 - GE/FC SFP Ethernet facility 350 2-36
 - GE/FC SFP FC facility 350 2-37
 - GE/FC SFP WAN facility 350 2-37
- signal continuity
 - testing in a DWDM system 222 2-29
 - testing in a linear point-to-point configuration 222 2-25
 - testing in a non-DWDM system 222 2-21
 - testing in a UPSR 222 2-27
- signal cross-connect, testing functionality and protection 222 2-5
- signal mapper, testing functionality and protection 222 2-5
- Site Manager
 - closing 302 2-42
 - starting 302 2-3
- SOC Software Version Mismatch alarm 543 5-179
- software
 - release
 - transferring from an OPC or network processor over direct cable 302 6-70
 - transferring from an OPC or network processor over the network 302 6-68
 - transferring from PC over Ethernet 302 6-66
 - upgrade
 - network element 190 22-1, 190 25-1
 - network processor (NPx) 190 22-1, 190 25-1
 - viewing version
 - on network processor 302 6-74
 - on shelf processor 302 6-75
- Software Configuration Unknown alarm 543 5-181
- Software Degradation alarm 543 5-182
- sorting
 - active alarms by network element 543 2-4
 - events 543 2-12
- source identifier (SID), definition 190 1-5
- SP Database Restore Fail alarm 543 5-183
- SP Version Mismatch alarm 543 5-184
- span of control, network processor
 - adding a network element 520 4-3
 - removing a network element 520 4-6
 - retrieving network elements 520 4-2
- specific requirements
 - adding a network element to a BLSR 224 2-255
 - adding a network element to a DWDM ring 224 3-93
 - adding a network element to a UPSR 224 2-253, 224 2-254
 - adding a new terminal network element to a linear network 224 2-254
 - adding an ADM network element to a linear network 224 2-253
 - converting 2-node UPSR to linear point-to-point 224 2-258
 - converting UPSR to a UPSR over DWDM 224 3-92
 - converting VT assigned to Full VT BLSR 224 2-258
 - Full VT to VT assigned BLSR 224 2-259
 - removing a network element from a BLSR 224 2-256
 - removing a network element from a DWDM ring 224 3-94
 - removing a network element from a UPSR 224 2-256
 - removing a terminal network element from a linear network 224 2-256
 - removing an ADM network element from a linear network 224 2-255
 - upgrading span from OC-12 to OC-48 224 2-257
 - upgrading span from OC-3 to OC-12 224 2-256
- split test access 520 7-12
- SPx circuit pack
 - installing 201 3-110
- SS bits mode, modifying 350 2-19
- SSM (synchronization status message),
 - setting 310 1-7

-
- starting
 - Comm Log 302 4-6
 - manual connection terminal session 302 4-5
 - remote login session
 - from an OPTera Metro 3500 network element 302 2-17
 - Site Manager 302 2-3
 - telnet terminal session
 - using a modem 302 4-3
 - using direct cable 302 4-4
 - using the network 302 4-2
 - TL1 Command Builder 302 7-2
 - static electricity, circuit pack 210 1-2
 - STS Rx AIS alarm 543 5-185
 - STS Rx Excessive BIP Error Rate alarm 543 5-188
 - STS Rx Loss of Alignment alarm 543 5-191
 - STS Rx Loss of Multiframe alarm 543 5-192
 - STS Rx Loss of Pointer alarm 543 5-194
 - STS Rx Loss of Sequence alarm 543 5-196
 - STS Rx Path Trace Mismatch alarm 543 5-197
 - STS Rx RFI alarm 543 5-199
 - STS Rx Signal Degrade alarm 543 5-201
 - STS Rx Signal Label Mismatch alarm 543 5-203
 - STS Rx Unequipped alarm 543 5-205
 - STS12C Rx AIS alarm 543 5-218
 - STS12C Rx Excessive BIP Error Rate alarm 543 5-220
 - STS12C Rx Loss of Pointer alarm 543 5-223
 - STS12C Rx Path Trace Mismatch alarm 543 5-197
 - STS12C Rx RFI alarm 543 5-199
 - STS12C Rx Signal Degrade alarm 543 5-201
 - STS12C Rx Signal Label Mismatch alarm 543 5-203
 - STS12C Rx Unequipped alarm 543 5-216
 - STS12C Unsupported Concatenated Service alarm 543 5-226
 - STS24C Rx AIS alarm 543 5-227
 - STS24C Rx Excessive BIP Error Rate alarm 543 5-229, 543 5-236
 - STS24C Rx Loss of Pointer alarm 543 5-232
 - STS24C Rx Path Trace Mismatch alarm 543 5-197
 - STS24C Rx RFI alarm 543 5-199
 - STS24C Rx Signal Degrade alarm 543 5-201
 - STS24C Rx Signal Label Mismatch alarm 543 5-203
 - STS24C Rx Unequipped alarm 543 5-216
 - STS3C Rx AIS alarm 543 5-207
 - STS3C Rx Excessive BIP Error Rate alarm 543 5-210
 - STS3C Rx Loss of Alignment alarm 543 5-191
 - STS3C Rx Loss of Multiframe alarm 543 5-192
 - STS3C Rx Loss of Pointer alarm 543 5-213
 - STS3C Rx Loss of Sequence alarm 543 5-196
 - STS3C Rx Path Trace Mismatch alarm 543 5-197
 - STS3C Rx RFI alarm 543 5-199
 - STS3C Rx Signal Degrade alarm 543 5-201
 - STS3C Rx Signal Label Mismatch alarm 543 5-203
 - STS3C Rx Unequipped alarm 543 5-216
 - STS-3c, testing signal continuity 222 2-18
 - STS48C Rx AIS alarm 543 5-234
 - STS48C Rx Loss of Pointer alarm 543 5-239
 - STS48C Rx RFI alarm 543 5-199
 - STS48C Rx Signal Degrade alarm 543 5-201
 - STS48C Rx Signal Label Mismatch alarm 543 5-203
 - STS48C Rx Unequipped alarm 543 5-216
 - STX-192 circuit pack
 - installing 201 3-110
 - replacing 543 3-51
 - SVC
 - changing a PVC to an SVC 520 3-13
 - changing an SVC to a PVC 520 3-11
 - editing the SVC parameter values 520 3-14
 - Switch mode mismatch alarm 543 5-241
 - synchronization
 - boundary
 - determining location of 224 2-218
 - moving 224 2-216
 - operating
 - BITS out switch 310 1-16
 - synchronization switch 310 1-9
-

synchronization (continued)
 parameters
 BITS in 310 1-12
 BITS out 310 1-15
 provisioning
 BITS in 310 1-10
 BITS out 310 1-13
 quality level, description 310 1-8
 retrieving data 310 1-2
 setting synchronization-status message
 (SSM) 310 1-7
 synchronizing a network element
 to external timing source 310 1-3
 to internal timing source 310 1-4
 to line-timing source 310 1-5

T

table

alarms observed
 adding a network element to a
 BLSR 224 2-269
 adding a network element to a
 UPSR 224 2-267
 Full VT to VT assigned BLSR 224
 2-275
 linear point-to-point to UPSR
 conversion 224 2-274
 OC-12 to OC-48 line rate upgrade 224
 2-273
 OC-3 to OC-12 line rate upgrade 224
 2-271
 removing a network element from a
 BLSR 224 2-269
 removing a network element from a
 UPSR 224 2-267
 VT assigned to Full VT BLSR 224
 2-275
 BLSR configuration 224 2-202
 final BLSR configuration data 224 2-249
 final section trace parameters 224 2-249
 final section trace parameters
 (DWDM) 224 3-84
 initial BLSR configuration data 224 2-249
 initial section trace parameters 224 2-249
 initial section trace parameters
 (DWDM) 224 3-84

table (continued)

linear configuration 224 2-47, 224 2-73,
 224 2-140, 224 2-149
 network element A cross-connects 224
 2-250
 network element A cross-connects
 (DWDM) 224 3-85
 network element B cross-connects 224
 2-251
 network element B cross-connects
 (DWDM) 224 3-86
 network element C cross-connects 224
 2-252
 network element C cross-connects
 (DWDM) 224 3-87
 network processor TID 224 2-202
 reconfiguration worksheet
 Full VT to VT assigned 224 2-213
 VT assigned to Full VT 224 2-203
 UPSR to UPSR over DWDM
 reconfiguration worksheet 224 3-88
 TAP 520 7-5, 520 7-7
 target identifier (TID), definition 190 1-5
 TARP
 adding an entry in TARP tables 520 6-4
 deleting an entry in TARP tables 520 6-7
 editing an entry in TARP tables 520 6-6
 editing configuration parameters 520 6-2
 performing echo function 520 6-8
 procedures 520 6-1
 TBOS
 adding a mapping assignment 520 1-2
 cable
 assembly 201 5-10
 pinout 201 5-10
 connecting cable 201 3-101, 201 3-234
 deleting a mapping assignment 520 1-4
 editing a mapping assignment 520 1-3
 procedures 520 1-1
 TBOS Connection Failure alarm 543 5-242
 telnet terminal session
 closing 302 4-9
 printing 302 4-7
 starting using a modem 302 4-3
 starting using direct cable 302 4-4
 starting using the network 302 4-2
 temporary account, creating 302 3-7

-
- terminal
 - connecting to the shelf 201 3-189
 - setting up 201 3-189
 - test access
 - cabling 520 7-2
 - components 520 7-2, 520 7-3
 - loss of association 520 7-4
 - modes 520 7-2, 520 7-12
 - Dual FAD, MONEF 520 7-11
 - Dual FAD, SPLTEF 520 7-15
 - Single FAD, MONE 520 7-11
 - Single FAD, MONF 520 7-11
 - Single FAD, SPLTA 520 7-14
 - Single FAD, SPLTE 520 7-14
 - Single FAD, SPLTF 520 7-14
 - monitor 520 7-8
 - session 520 7-8, 520 7-12
 - ports 520 7-5
 - provisioning TAPs 520 7-5
 - releasing 520 7-7, 520 7-16
 - session 520 7-16
 - TAPs 520 7-7
 - retrieving
 - connections 520 7-17
 - session information 520 7-17
 - setting up 520 7-2
 - split session 520 7-12
 - time out period 520 7-4
 - testing
 - functionality and protection 222 2-5
 - protection switching
 - DWDM system 222 2-29
 - non-DWDM system 222 2-21
 - point-to-point configuration 222 2-25
 - UPSR 222 2-27
 - signal continuity 222 2-18
 - DWDM system 222 2-29
 - non-DWDM system 222 2-21
 - point-to-point configuration 222 2-25
 - UPSR 222 2-27
 - Threshold AIS on BITSout-A alarm 543 5-244
 - Threshold AIS on BITSout-B alarm 543 5-244
 - time of day synchronization
 - daylight savings time 302 8-8
 - displaying servers 302 8-7
 - editing 302 8-2
 - setting up servers 302 8-4
 - synchronize 302 8-6
 - time zone offset or offset time 302 8-8
 - TL1 Command Builder
 - closing 302 7-3
 - starting 302 7-2
 - TL1 command description
 - ACT-USER 190 2-4
 - ADD-SOC 190 21-3
 - ALW-EX-OC12 190 11-4
 - ALW-EX-OC192 190 11-6
 - ALW-EX-OC3 190 11-3
 - ALW-EX-OC48 190 11-5
 - ALW-MSG-ALL 190 17-3
 - ALW-MSG-BROADCAST 190 17-4
 - ALW-SECU-CID 190 2-6
 - ALW-SECU-USER 190 2-7
 - AUD-BLSR 190 5-2
 - CANC-PROV 190 2-8
 - CANC-PROV-SOC 190 2-9
 - CANC-PROV-SP 190 2-10
 - CANC-RINGMAP 190 5-4
 - CANC-TL1SCRPT-NE 190 2-11
 - CANC-UPGRD 190 22-2
 - CANC-USER 190 2-12
 - CHG-ACCMD-STS1 190 15-3
 - CHG-ACCMD-STS12C 190 15-8
 - CHG-ACCMD-STS24C 190 15-10
 - CHG-ACCMD-STS3C 190 15-6
 - CHG-ACCMD-STS48c 190 15-12
 - CHG-ACCMD-T1 190 15-14
 - CHG-ACCMD-T3 190 15-16
 - CHG-ACCMD-VT1 190 15-18
 - CHK-PROV 190 2-13
 - CHK-PROV-SOC 190 2-15
 - CHK-PROV-SP 190 2-18
 - CHK-RINGMAP 190 5-5
 - CHK-UPGRD 190 22-3
 - CLR-ALM-SECU 190 2-21
 - CMMT-PROV 190 2-22
 - CMMT-PROV-SP 190 2-23
 - CMMT-RINGMAP 190 5-6
 - CMMT-ROLL-STS1 190 9-3
-

TL1 command description (continued)

CMMT-ROLL-STS12C 190 9-9
CMMT-ROLL-STS24C 190 9-12
CMMT-ROLL-STS3C 190 9-6
CMMT-ROLL-STS48C 190 9-15
CMMT-ROLL-VT1 190 9-17
CMMT-TL1SCRPT-NE 190 2-24
CMMT-UPGRD 190 22-4
CONN-TACC-STS1 190 15-20
CONN-TACC-STS12C 190 15-25
CONN-TACC-STS24C 190 15-27
CONN-TACC-STS3C 190 15-23
CONN-TACC-STS48C 190 15-29
CONN-TACC-T1 190 15-31
CONN-TACC-T3 190 15-33
CONN-TACC-VT1 190 15-36
CONN-TSTSIG-T1 190 10-3
DISC-TACC 190 15-39
DISC-TSTSIG-T1 190 10-5
DLT-ALM-PROFILE 190 17-5
DLT-BANNER 190 2-25
DLT-BLSRRING 190 5-7
DLT-CRS-STS1 190 16-3
DLT-CRS-STS12C 190 16-9
DLT-CRS-STS24C 190 16-11
DLT-CRS-STS3C 190 16-6
DLT-CRS-STS48C 190 16-13
DLT-CRS-VT1 190 16-15
DLT-EC1 190 7-4
DLT-EQPT 190 6-2
DLT-ETH 190 7-5
DLT-FAC 190 21-4
DLT-FC 190 7-6
DLT-FFP-OC12 190 7-8
DLT-FFP-OC192 190 7-11
DLT-FFP-OC3 190 7-7
DLT-FFP-OC48 190 7-9
DLT-IPT 190 8-2
DLT-IPTR 190 8-3
DLT-LLSDCC 190 18-2
DLT-OC12 190 7-14
DLT-OC192 190 7-16
DLT-OC3 190 7-13
DLT-OC48 190 7-15
DLT-PROV 190 2-26
DLT-PVC 190 21-5
DLT-RINGMAP 190 5-8

TL1 command description (continued)

DLT-ROLL-STS1 190 9-20
DLT-ROLL-STS12C 190 9-26
DLT-ROLL-STS24C 190 9-29
DLT-ROLL-STS3C 190 9-23
DLT-ROLL-STS48C 190 9-32
DLT-ROLL-VT1 190 9-34
DLT-SECU-ACCESS 190 2-28
DLT-SECU-BADPID 190 2-29
DLT-SECU-USER 190 2-30
DLT-T1 190 7-17
DLT-T3 190 7-18
DLT-UPGRD 190 22-5
ED-ALM-PROFILE 190 17-7
ED-BLSRRING 190 5-9
ED-CRS-STS1 190 16-18
ED-CRS-STS12C 190 16-26
ED-CRS-STS24C 190 16-29
ED-CRS-STS3C 190 16-22
ED-CRS-STS48C 190 16-32
ED-CRS-VT1 190 16-35
ED-DAT 190 2-31
ED-DFLT-AINS 190 7-19
ED-EC1 190 7-20
ED-ETH 190 7-21
ED-FC 190 7-24
ED-FFP-OC12 190 7-28
ED-FFP-OC192 190 7-32
ED-FFP-OC3 190 7-26
ED-FFP-OC48 190 7-30
ED-IP 190 21-6
ED-LLSDCC 190 18-3
ED-LLX25 190 21-7
ED-NETTYPE 190 3-2
ED-OC12 190 7-38
ED-OC192 190 7-44
ED-OC3 190 7-34
ED-OC48 190 7-41
ED-PMCONFIG-EC1 190 12-5
ED-PMCONFIG-ETH 190 12-7
ED-PMCONFIG-FC 190 12-9
ED-PMCONFIG-OC12 190 12-13
ED-PMCONFIG-OC192 190 12-17
ED-PMCONFIG-OC3 190 12-11
ED-PMCONFIG-OC48 190 12-15
ED-PMCONFIG-STS1 190 12-19
ED-PMCONFIG-STS12C 190 12-25

TL1 command description (continued)

ED-PMCONFIG-STS24c 190 12-28
 ED-PMCONFIG-STS3C 190 12-22
 ED-PMCONFIG-STS48c 190 12-30
 ED-PMCONFIG-WAN 190 12-32
 ED-PTX25 190 21-8
 ED-ROLL-STS1 190 9-37
 ED-ROLL-STS12C 190 9-43
 ED-ROLL-STS24C 190 9-46
 ED-ROLL-STS3C 190 9-40
 ED-ROLL-STS48C 190 9-49
 ED-ROLL-VT1 190 9-52
 ED-SECU-PID 190 2-32
 ED-SECU-USER 190 2-33
 ED-SITE-DSM 190 23-2
 ED-STS1 190 20-2
 ED-STS12C 190 20-6
 ED-STS24C 190 20-8
 ED-STS3C 190 20-4
 ED-SYS 190 7-47
 ED-T1 190 7-49
 ED-T3 190 7-54
 ED-TARP-CONFIG 190 13-2
 ED-TARP-TBL 190 13-5
 ED-TOD-MOD 190 2-36
 ED-ULSDCC 190 18-6, 190 21-10
 ED-ULX25 190 21-12
 ED-VC 190 21-15
 ED-WAN 190 7-56
 ENT-ALM-PROFILE 190 17-9
 ENT-BLSRRING 190 5-10
 ENT-CHALLENGE-RESPONSE 190
 2-38
 ENT-CRS-STS1 190 16-39
 ENT-CRS-STS12C 190 16-47
 ENT-CRS-STS24C 190 16-50
 ENT-CRS-STS3C 190 16-43
 ENT-CRS-STS48C 190 16-52
 ENT-CRS-VT1 190 16-54
 ENT-EC1 190 7-59
 ENT-EQPT 190 6-4
 ENT-ETH 190 7-61
 ENT-FAC 190 21-17
 ENT-FC 190 7-64
 ENT-FFP-OC12 190 7-68
 ENT-FFP-OC192 190 7-72
 ENT-FFP-OC3 190 7-66

TL1 command description (continued)

ENT-FFP-OC48 190 7-70
 ENT-IPT 190 8-4
 ENT-IPTR 190 8-5
 ENT-LLSDCC 190 18-8
 ENT-OC12 190 7-77
 ENT-OC192 190 7-81
 ENT-OC3 190 7-74
 ENT-OC48 190 7-79
 ENT-RINGMAP 190 5-11
 ENT-ROLL-STS1 190 9-55
 ENT-ROLL-STS12C 190 9-63
 ENT-ROLL-STS24C 190 9-66
 ENT-ROLL-STS3C 190 9-59
 ENT-ROLL-STS48C 190 9-69
 ENT-ROLL-VT1 190 9-72
 ENT-SECU-ACCESS 190 2-39
 ENT-SECU-BADPID 190 2-40
 ENT-SECU-USER 190 2-41
 ENT-T1 190 7-84
 ENT-T3 190 7-88
 EX-SW-OC12 190 11-9
 EX-SW-OC192 190 11-13
 EX-SW-OC3 190 11-7
 EX-SW-OC48 190 11-11
 INH-EX-OC12 190 11-16
 INH-EX-OC192 190 11-18
 INH-EX-OC3 190 11-15
 INH-EX-OC48 190 11-17, 190 11-18
 INH-MSG-ALL 190 17-11
 INH-MSG-BROADCAST 190 17-12
 INIT-COLD 190 19-2
 INIT-REG-ALL 190 12-36
 INIT-REG-EC1 190 12-40
 INIT-REG-ETH 190 12-44
 INIT-REG-FC 190 12-48
 INIT-REG-OC12 190 12-56
 INIT-REG-OC192 190 12-64
 INIT-REG-OC3 190 12-52
 INIT-REG-OC48 190 12-60
 INIT-REG-STS1 190 12-68
 INIT-REG-STS12C 190 12-75
 INIT-REG-STS24C 190 12-79
 INIT-REG-STS3C 190 12-72
 INIT-REG-STS48C 190 12-83
 INIT-REG-T1 190 12-87
 INIT-REG-T3 190 12-91

TL1 command description (continued)

INIT-REG-WAN 190 12-95
INIT-UPGRD-EQPT 190 6-7
INIT-WARM 190 19-3
INVK-RINGMAP 190 5-13
INVK-UPGRD 190 22-6
LOAD-REPLACE 190 22-8
LOAD-RINGMAP 190 5-14
LOAD-TL1SCRPT-NE 190 2-44
LOAD-UPGRD 190 22-9
OPR-ACO-ALL 190 17-13
OPR-BITSOUTSW 190 4-2
OPR-EXT-CONT 190 17-14
OPR-LAMP-TEST 190 23-5
OPR-LPBK-EC1 190 10-6
OPR-LPBK-ETH 190 10-8
OPR-LPBK-FC 190 10-10
OPR-LPBK-OC12 190 10-13
OPR-LPBK-OC192 190 10-15
OPR-LPBK-OC3 190 10-12
OPR-LPBK-OC48 190 10-14
OPR-LPBK-T1 190 10-16
OPR-LPBK-T3 190 10-18
OPR-PROTNSW-EQPT 190 11-19
OPR-PROTNSW-OC12 190 11-23
OPR-PROTNSW-OC192 190 11-27
OPR-PROTNSW-OC3 190 11-21
OPR-PROTNSW-OC48 190 11-25
OPR-PROTNSW-STS1 190 11-29
OPR-PROTNSW-STS12C 190 11-33
OPR-PROTNSW-STS24C 190 11-35
OPR-PROTNSW-STS3C 190 11-31
OPR-PROTNSW-STS48C 190 11-37
OPR-PROTNSW-VT1 190 11-39
OPR-SYNCSW 190 4-3
OPR-TARP-TEF 190 13-7
OPR-TOD-SYNC 190 2-47
REPT-INITZN 190 15-41
REPT-STAT 190 15-42
RLS-EXT-CONT 190 17-16
RLS-LPBK-FC 190 10-22
RLS-LPBK-OC12 190 10-24
RLS-LPBK-OC192 190 10-26
RLS-LPBK-OC3 190 10-23
RLS-LPBK-OC48 190 10-25
RLS-LPBK-T1 190 10-27
RLS-LPBK-T3 190 10-28

TL1 command description (continued)

RLS-PROTNSW-EQPT 190 11-41
RLS-PROTNSW-OC12 190 11-43
RLS-PROTNSW-OC192 190 11-46
RLS-PROTNSW-OC3 190 11-42
RLS-PROTNSW-OC48 190 11-44
RLS-PROTNSW-STS1 190 11-48
RLS-PROTNSW-STS12C 190 11-50
RLS-PROTNSW-STS24C 190 11-51
RLS-PROTNSW-STS3C 190 11-49
RLS-PROTNSW-STS48C 190 11-52
RLS-PROTNSW-VT1 190 11-53
RMV-EC1 190 7-90
RMV-EQPT 190 6-8
RMV-ETH 190 7-91
RMV-FC 190 7-92
RMV-OC12 190 7-94
RMV-OC192 190 7-96
RMV-OC3 190 7-93
RMV-OC48 190 7-95
RMV-SOC 190 21-18
RMV-T1 190 7-97
RMV-T3 190 7-98
RST-BANNER 190 2-48
RST-EC1 190 7-99
RST-EQPT 190 6-10
RST-ETH 190 7-100
RST-FC 190 7-101
RST-OC12 190 7-103
RST-OC192 190 7-105
RST-OC3 190 7-102
RST-OC48 190 7-104
RST-PROV 190 2-49
RST-PROV-SP 190 2-53
RST-T1 190 7-106
RST-T3 190 7-107
RTRV-ACTIVE-PROFILE 190 17-18
RTRV-ACTIVE-USER 190 2-56
RTRV-ALM-ALL 190 17-31
RTRV-ALM-ENV 190 17-34
RTRV-ALMID 190 17-40
RTRV-ALM-PROFILE 190 17-38
RTRV-AO 190 17-42
RTRV-AO-BROADCAST 190 17-45
RTRV-ATTR-CONT 190 17-47
RTRV-ATTR-CSA 190 2-58
RTRV-ATTR-ENV 190 17-50

TL1 command description (continued)

RTRV-ATTR-REMAUTH 190 2-60
 RTRV-AUD-BLSR 190 5-15
 RTRV-AUDIT-SECULOG 190 2-62
 RTRV-BACKPLANE 190 6-12
 RTRV-BANNER 190 2-48, 190 2-65
 RTRV-BITS-IN 190 4-4
 RTRV-BITS-OUT 190 4-6
 RTRV-BLSRRING 190 5-17
 RTRV-CEM-DSM 190 23-3
 RTRV-CHALLENGE 190 2-66
 RTRV-CHK-SUM 190 21-19
 RTRV-CLLI 190 2-67
 RTRV-COND-ALL 190 17-54
 RTRV-CONDATTR 190 17-57
 RTRV-CONFIG 190 21-21
 RTRV-CRS-STS1 190 16-58
 RTRV-CRS-STS12C 190 16-69
 RTRV-CRS-STS24C 190 16-74
 RTRV-CRS-STS3C 190 16-64
 RTRV-CRS-STS48C 190 16-78
 RTRV-CRS-VT1 190 16-81
 RTRV-DFLT-AINS 190 7-108
 RTRV-DFLT-PROFILE 190 17-60
 RTRV-EC1 190 7-110
 RTRV-EQPT 190 6-14
 RTRV-ETH 190 7-113
 RTRV-EXSCHED-OC12 190 11-57
 RTRV-EXSCHED-OC192 190 11-61
 RTRV-EXSCHED-OC3 190 11-54
 RTRV-EXSCHED-OC48 190 11-59
 RTRV-EXT-CONT 190 17-62
 RTRV-FAC 190 21-24
 RTRV-FC 190 7-120
 RTRV-FFP-OC12 190 7-125
 RTRV-FFP-OC192 190 7-129
 RTRV-FFP-OC3 190 7-123
 RTRV-FFP-OC48 190 7-127
 RTRV-HDR 190 2-68
 RTRV-HELP 190 2-69
 RTRV-INVENTORY 190 6-20
 RTRV-INVENTORY-FAN 190 6-25
 RTRV-INVENTORY-IO 190 6-27
 RTRV-IP 190 21-26
 RTRV-IPT 190 8-6
 RTRV-IPTR 190 8-8
 RTRV-LAST-SEQNUM 190 17-64

TL1 command description (continued)

RTRV-LLSDCC 190 18-10
 RTRV-LLX25 190 21-28
 RTRV-LPBK-EC1 190 10-29
 RTRV-LPBK-ETH 190 10-30
 RTRV-LPBK-FC 190 10-32
 RTRV-LPBK-OC12 190 10-36
 RTRV-LPBK-OC192 190 10-40
 RTRV-LPBK-OC3 190 10-34
 RTRV-LPBK-T1 190 10-41
 RTRV-LPBK-T3 190 10-43
 RTRV-NE-AOMSG 190 17-65
 RTRV-NETYPE (NP host) 190 3-5
 RTRV-NETYPE (SP host) 190 3-3
 RTRV-NTFCNCDE 190 17-68
 RTRV-OC12 190 7-136
 RTRV-OC192 190 7-144
 RTRV-OC3 190 7-131
 RTRV-OC48 190 7-140
 RTRV-PM-ABORT 190 12-111
 RTRV-PM-ALL 190 12-112
 RTRV-PMCONFIG-EC1 190 12-190
 RTRV-PMCONFIG-ETH 190 12-193
 RTRV-PMCONFIG-FC 190 12-196
 RTRV-PMCONFIG-OC12 190 12-202
 RTRV-PMCONFIG-OC192 190 12-208
 RTRV-PMCONFIG-OC3 190 12-199
 RTRV-PMCONFIG-OC48 190 12-205
 RTRV-PMCONFIG-STS1 190 12-211
 RTRV-PMCONFIG-STS12C 190 12-219
 RTRV-PMCONFIG-STS24c 190 12-222
 RTRV-PMCONFIG-STS3C 190 12-215
 RTRV-PMCONFIG-STS48c 190 12-225
 RTRV-PMCONFIG-WAN 190 12-228
 RTRV-PM-EC1 190 12-116
 RTRV-PM-ETH 190 12-121
 RTRV-PM-FC 190 12-126
 RTRV-PM-OC12 190 12-136
 RTRV-PM-OC192 190 12-146
 RTRV-PM-OC3 190 12-131
 RTRV-PM-OC48 190 12-141
 RTRV-PM-STS1 190 12-151
 RTRV-PM-STS12C 190 12-161
 RTRV-PM-STS24C 190 12-166
 RTRV-PM-STS3C 190 12-156
 RTRV-PM-STS48C 190 12-171
 RTRV-PM-T1 190 12-176

TL1 command description (continued)

RTRV-PM-T3 190 12-181
 RTRV-PM-WAN 190 12-186
 RTRV-PROTNSW-EQPT 190 11-63
 RTRV-PROTNSW-rr 190 11-66
 RTRV-PROV-LST 190 2-72
 RTRV-PTHTRC-STS1 190 20-10
 RTRV-PTHTRC-STS12C 190 20-15
 RTRV-PTHTRC-STS24C 190 20-17
 RTRV-PTHTRC-STS3C 190 20-13
 RTRV-PTX25 190 21-29
 RTRV-REMAUTH-ALTERNATE 190
 2-74
 RTRV-RINGMAP 190 5-19
 RTRV-ROLL-STS1 190 9-75
 RTRV-ROLL-STS12C 190 9-84
 RTRV-ROLL-STS24C 190 9-88
 RTRV-ROLL-STS3C 190 9-80
 RTRV-ROLL-STS48C 190 9-91
 RTRV-ROLL-VT1 190 9-94
 RTRV-RTG-TBL 190 3-7
 RTRV-SECU-ACCESS 190 2-75
 RTRV-SECU-ACSSTAT 190 2-76
 RTRV-SECU-BADPID 190 2-77
 RTRV-SECU-CID 190 2-78
 RTRV-SECU-DFLT 190 2-80
 RTRV-SECU-UPC 190 2-82
 RTRV-SECU-USER 190 2-84
 RTRV-SOC 190 21-31
 RTRV-SPACE 190 22-13
 RTRV-SW-VER 190 3-10
 RTRV-SYNCSTIN 190 4-9
 RTRV-SYS 190 7-148
 RTRV-T1 190 7-150
 RTRV-T3 190 7-155
 RTRV-TACC 190 15-43
 RTRV-TARP-CONFIG 190 13-9
 RTRV-TARP-TBL 190 13-11
 RTRV-TBOS 190 14-2
 RTRV-TH-ALL 190 12-231
 RTRV-TH-EC1 190 12-236
 RTRV-TH-ETH 190 12-238
 RTRV-TH-FC 190 12-240
 RTRV-TH-OC12 190 12-245
 RTRV-TH-OC192 190 12-251
 RTRV-TH-OC3 190 12-242
 RTRV-TH-OC48 190 12-248

TL1 command description (continued)

RTRV-TH-STS1 190 12-254
 RTRV-TH-STS12C 190 12-260
 RTRV-TH-STS24C 190 12-263
 RTRV-TH-STS3C 190 12-257
 RTRV-TH-STS48C 190 12-266
 RTRV-TH-T1 190 12-269
 RTRV-TH-T3 190 12-272
 RTRV-TH-WAN 190 12-275
 RTRV-TMG-MODE 190 4-11
 RTRV-TMREFIN 190 4-12
 RTRV-TMZONE 190 2-86
 RTRV-TOD-MODE 190 2-90
 RTRV-TOD-SER 190 2-92
 RTRV-TRC-OC12 190 20-21
 RTRV-TRC-OC192 190 20-25
 RTRV-TRC-OC3 190 20-19
 RTRV-TRC-OC48 190 20-23
 RTRV-ULSDCC 190 18-14, 190 21-32
 RTRV-ULX25 190 21-33
 RTRV-UPGRD 190 22-14
 RTRV-UPGRD-STATE 190 22-15
 RTRV-VC 190 21-35
 RTRV-WAN 190 7-157
 SAV-BANNER 190 2-95
 SAV-PROV 190 2-96
 SAV-PROV-SOC 190 2-100
 SAV-PROV-SP 190 2-102
 SCHED-EX-OC12 190 11-76
 SCHED-EX-OC192 190 11-80
 SCHED-EX-OC3 190 11-74
 SCHED-EX-OC48 190 11-78
 SEND-IMSG 190 2-105
 SET-ACTIVE-PROFILE 190 17-69
 SET-ATTR-CONT 190 17-71
 SET-ATTR-CSA 190 2-106
 SET-ATTR-ENV 190 17-73
 SET-ATTR-REMAUTH 190 2-108
 SET-ATTR-SECUDFLT 190 2-110
 SET-BANNER 190 2-113
 SET-BITS-IN 190 4-15
 SET-BITS-OUT 190 4-16
 SET-CHALLENGE-SECRET 190 2-114
 SET-CLLI 190 2-115
 SET-CONDATTR 190 17-76
 SET-DFLT-PROFILE 190 17-78
 SET-NTFCNCDE 190 17-80

-
- TL1 command description (continued)
- SET-REMAUTH-ALTERNATE 190 2-116
 - SET-SECU-ACSSTAT 190 2-117
 - SET-SID 190 2-118
 - SET-SYNCSTIN 190 4-18
 - SET-TBOS 190 14-4
 - SET-TH-ALL 190 12-277
 - SET-TH-EC1 190 12-278
 - SET-TH-ETH 190 12-281
 - SET-TH-FC 190 12-283
 - SET-TH-OC12 190 12-288
 - SET-TH-OC192 190 12-293
 - SET-TH-OC3 190 12-285
 - SET-TH-OC48 190 12-291
 - SET-TH-STS1 190 12-295
 - SET-TH-STS12C 190 12-300
 - SET-TH-STS24C 190 12-303
 - SET-TH-STS3C 190 12-297
 - SET-TH-STS48C 190 12-306
 - SET-TH-T1 190 12-309
 - SET-TH-T3 190 12-312
 - SET-TH-WAN 190 12-315
 - SET-TMG-MODE 190 4-20
 - SET-TMREFIN 190 4-21
 - SET-TMZONE 190 2-120
 - SET-TOD-SER 190 2-125
 - VALD-PROV 190 2-127
- TL1 Script file Failed alarm 543 5-247
- TL1 Script file Load in Progress alarm 543 5-248
- TOD Server has not responded to a request alarm 543 5-250
- TOD Threshold Exceeded alarm 543 5-252
- tools required
- adding a network element to a BLSR 224 2-259, 224 2-260
 - adding a network element to a UPSR 224 2-260
 - adding a new terminal network element to a linear network 224 2-260
 - adding an ADM network element to a linear network 224 2-259
 - converting 2-node UPSR to point-to-point linear 224 2-263
 - converting point-to-point linear to 2-node UPSR 224 2-262
- tools required (continued)
- DWDM reconfiguration procedures 224 3-91
 - removing a network element from a BLSR 224 2-262
 - removing a network element from a UPSR 224 2-262
 - upgrading line rate of a fiber span 224 2-262
- Traffic Squelched alarm 543 5-254
- Transaction Language 1 (TL1)
- autonomous messages, format 190 1-9
 - command interface, introduction 190 1-3
 - command response header, format 190 1-8
 - commands
 - editing 302 7-4
 - running 302 7-4
 - CTAG, definition 190 1-6
 - error codes and messages, definition 190 26-1
 - help syntax 190 1-11
 - message notation 190 1-6
 - message types 190 1-7
 - overview 190 1-1
 - password identifier, definition 190 1-3
 - security access level 190 1-4
 - source identifier, definition 190 1-5
 - standards compliance 190 1-1
 - target identifier, definition 190 1-5
 - user identifier, definition 190 1-3
 - user privilege codes, definition 190 1-4
- Transport Data Recovery Failed alarm 543 5-256
- tributary circuit pack
- operating forced switch 311 1-18
 - operating lockout 311 1-20
 - operating manual switch 311 1-16
 - releasing forced switch 311 1-21
- ## U
- Unable to Synchronize TOD alarm 543 5-257
- unavailable seconds (UAS), definition 510 1-57
- universal cooling unit assembly 543 3-72
- replacing 543 3-69
-

universal cooling unit fan module 543 3-73
 replacing 543 3-75
universal cooling unit plenum 543 3-74
unlocking channel identifiers 302 3-26
Unsupported Service - Path Trace alarm 543
 5-258
updating, events window 543 2-14
Upgrade Failed alarm 543 5-259
Upgrade Failed Slot n alarm 543 5-260
Upgrade in Progress alarm 543 5-262
upgrading
 fiber span from OC-12 to OC-48 line
 rate 224 2-176
 fiber span from OC-3 to OC-12 line
 rate 224 2-169
 FPGA load 302 6-64
 software
 on network element from local PC 302
 6-58
 on network element over Ethernet 302
 6-61
 on network processor 302 6-55
UPSR
 adding a node 224 2-74
 adding a node (over DWDM) 224 3-19
UPSR to UPSR over DWDM reconfiguration
 worksheet 224 3-88
user account
 adding 302 3-4
 deleting 302 3-16
 displaying details 302 3-3
 editing 302 3-10
user identifier (UID), definition 190 1-3
user privilege code (UPC)
 definition 190 1-4
user privilege level
 editing 302 3-10

V

Virtual Circuit Failure alarm 543 5-263
VT Rx AIS alarm 543 5-265
VT Rx Excessive BIP Error Rate alarm 543
 5-268
VT Rx Loss of Pointer alarm 543 5-271
VT Rx RFI alarm 543 5-274
VT Rx Signal Degrade alarm 543 5-276

VT Rx Signal Label Mismatch alarm 543
 5-279
VT Rx Unequipped alarm 543 5-281
VT1.5
 testing signal continuity 222 2-18
VTX Shelf ID Mismatch Detected alarm 543
 5-285
VTX-48 circuit pack
 installing 201 3-110
 replacing 543 3-48
VTX-48e circuit pack
 installing 201 3-110
 replacing 543 3-48

W

wait-to-restore period, changing 311 1-14
WAN
 facility
 2x100BT-P2P signal attributes 350 2-35
 editing 350 2-28
 GE/FC SFP signal attributes 350 2-37

X

X.25
 connecting cable 201 3-101
 editing 520 3-6

Nortel Networks

OPTera Metro 3500 Multiservice Platform

About the OPTera Metro 3500 NTP Library

Copyright © 2000–2003 Nortel Networks, All Rights Reserved

The information contained herein is the property of Nortel Networks and is strictly confidential. Except as expressly authorized in writing by Nortel Networks, the holder shall keep all information contained herein confidential, shall disclose the information only to its employees with a need to know, and shall protect the information, in whole or in part, from disclosure and dissemination to third parties with the same degree of care it uses to protect its own confidential information, but with no less than reasonable care. Except as expressly authorized in writing by Nortel Networks, the holder is granted no rights to use the information contained herein.

Nortel Networks, the Nortel Networks logo, the Globemark, OPTera, and Preside are trademarks of Nortel Networks.

Hewlett-Packard, HP, and HP-UX are trademarks of Hewlett-Packard Company.

Microsoft, Windows, and Windows NT are trademarks of Microsoft Corporation.

Solaris, Sun, Sun Blade, Sun Microsystems, and Ultra are trademarks of Sun Microsystems, Inc.

SPARC is a trademark of SPARC International, Inc.

Telcordia is a trademark of Telcordia Technologies, Inc.

323-1059-090

Standard Release 12.0 Issue 1

November 2003

Printed in Canada

