

INTERCONNECTING DEVICES, COMMON EQUIPMENT

615A PANEL

1. GENERAL

1.001 This addendum supplements Section 463-300-104, Issue 2. Place this pink sheet ahead of Page 1 of the section.

1.002 This addendum is issued to clarify the requirements for battery supplies used to provide dc power for the panel.

2. CHANGES TO SECTION

2.001 On Page 1, paragraph 2.04, add the following statement after the second sentence: The 108A IU can be mounted in the 615A panel only for PCA CD6, not for CDA.

2.002 On Page 2, add the following sentence at the end of paragraph 2.05: ***Talk battery is required for the 120-type IUs, while signal battery should be used for the other IUs.***

2.003 On Page 8, add new Table C.

2.004 On Page 9, add new Fig. 6.

TABLE C

POWER CONNECTIONS

VOLTAGE		615A PANEL*
120-TYPE IUs	OTHER IUs	
-24V TALK BAT.	-24V SIG BAT.	2D
24V GRD	24V GRD	4D
-48V TALK BAT. †	-48V SIG BAT.	10D
48V GRD	48V GRD	12D
±105V AC		6D
±105V GRD		8D

* Terminals on 66T1 connecting block.

† KS-15620, L22 (2-amp) or L23 (6-amp) rectifier is suitable for talk battery supply.

NOTICE

Not for use or disclosure outside the
Bell System except under written agreement

