

SINGLE-LINE, PUSHBUTTON DIAL, WALL TELEPHONES (STANDARD SIZE)

GENERAL DESCRIPTION

CONTENTS	PAGE
1. GENERAL DESCRIPTION	1
MODEL 3554** () 20	3
MODEL 3554** () 21	3
MODEL 3554** () 27/28	3
MODEL 3554** () 30	3
MODEL 3554** () 31	3
MODEL 3554** () 37/38	3
2. INSTALLATION	3
3. MAINTENANCE	3

1. GENERAL DESCRIPTION

1.01 This document covers the single-line, pushbutton dial, standard size, wall telephone. (See Figure 1.) A general description as well as information that is peculiar to single-line, pushbutton dial, standard size, wall telephones is included.

1.02 This section is reissued for the following reasons:

(a) Issue 3 adds feature code 27 to the full-modular (M) version of the single-line, pushbutton dial, standard size, wall telephones. Quarter-modular (Q) and full-modular (F) versions of the single-line, pushbutton dial, standard size, wall telephones have been manufacturing discontinued as well as the following:

- (1) Feature codes 28 and 38 telephones.
- (2) Color codes 05, 12, 43, 46, and 47.
- (3) Regular (R) dial telephones.
- (4) Tel-Pulse (T) dial telephones.



AW96-388

Figure 1: Single-Line, Pushbutton Dial, Wall Telephone

(b) Issue 2 corrected errors in the initial issue.

Note: Ordering information for manufacturing discontinued telephones has been removed; however, descriptive information has been retained as a reference for telephones still in service.

1.03 A replacement parts list and an exploded-view drawing for the telephones are contained in Section 50-554-104. Circuit labels appear in Section 50-554-105. Related documents of the CORTELCO Telephone Apparatus Practices Manual provide information on components.

1.04 The Model 3554 wall telephones are single-line, pushbutton dial, anti-sidetone type units that operate efficiently over a wide range of loop resistances and line impedances.

1.05 The Model 3554 wall telephones are identified by a coded label affixed to the bottom of the base plate. Refer to ordering information in Table A for an explanation of each code number.

TABLE A
ORDERING INFORMATION - TELEPHONES

CODE NUMBERS									
TELEPHONE CODE NUMBERS ARE FORMED IN SIX STEPS AS FOLLOWS:									
(1) Type of Instrument (See Part 1)	3554	44	O	BA	30	M			
(2) Color (See Part 2)									
(3) Version (See Part 3)									
(4) Ringer (See Part 4)									
(5) Special Feature (See Part 5)									
(6) Dial (See Part 6)									
PART 1 TYPE OF INSTRUMENT									
CODE	DESCRIPTION	COLOR OFFERED	VERSION OFFERED	RINGER OFFERED	FEATURE OFFERED	DIAL OFFERED			
3554	Single-Line, Pushbutton Dial, Standard Size, Wall Telephone	00, 09, 13, 15, 44, And 45	O	BA	30, 31, 37	M			
3554	Single-Line, Pushbutton Dial, Standard Size, Wall Telephone	(Available On All Models)	M	BA	20, 21, 27	M			
REFER TO INDIVIDUAL UNIT DESCRIPTION FOR COMPLETE DESCRIPTION OF FEATURE COMBINATIONS									
PART 2 COLORS		PART 3 VERSIONS		PART 4 RINGERS		PART 5 SPECIAL FEATURES		PART 6 DIALS	
CODE	COLORS	CODE	VERSIONS	CODE	RINGERS	CODE	SPECIAL FEATURES	CODE	DIAL
00	Black	O	Nonmodular	BA	Straight-Line	30	No Special Feature (Nonmodular)	M	Metropolitan (Letters & Numerals)
09	Ivory	M	Full-Modular			31	30 With 9-Foot Handset Cord		
13	Beige		(With Handset Cord)			37	30 With 90-Volt Message Waiting Lamp		
15	White					20	No Special Feature (Full-Modular)		
44	Light Ash					21	20 With 9-Foot Handset Cord		
45	Cocoa Brown					27	20 With 90-Volt Message Waiting Lamp		

AW86-508

1.06 The Model 3554 wall telephones are non-modular, quarter-modular, or full-modular versions. These versions are designated by a code letter in the telephone order number. (Refer to Table A.)

1.07 Nonmodular wall telephones include a hard-wired handset cord. This version is designated by the code letter O.

1.08 Quarter-modular version telephones (no longer available) include a hard-wired handset cord, and a modular plug is provided as part of the base assembly for inserting into a modular wall jack. This version is designated by the code letter Q.

1.09 Full-modular version telephones are available with or without a modular handset cord. However, all full-modular version telephones are equipped with jacks to accept the plugs of a modular handset cord, and a modular plug is provided as part of the base assembly for inserting into a modular wall jack. The full-modular version of the telephone with a modular handset cord, terminated on each end with modular plugs, is designated by the code letter M. The full-modular version without a modular handset cord (no longer available) is designated by the code letter F.

1.10 For Model 3354 wall telephones, feature codes 20, 21, and 27 pertain to modular units, while

feature codes 30, 31, and 37 pertain to nonmodular units.

1.11 The Model 3554 wall telephones are described in the following paragraphs. The circuit label drawings for these telephones are included in Section 50-554-105.

MODEL 3554 () 20**

1.12 The Model 3554** () 20 is a single-line, pushbutton dial, standard size, wall telephone. It provides no additional outstanding features.

MODEL 3554 () 21**

1.13 The Model 3554** () 21 is the same as the Model 3554** () 20 with the addition of a nine-foot handset cord.

MODEL 3554 () 27/28**

1.14 The Model 3554** () 27/28 is the same as the Model 3554** () 20 with the addition of a message waiting lamp. The lamp is used in PBX applications to indicate that the station user should contact the message center. The Model 3554** () 27 is equipped with a 90-volt indicator. The Model 3554** () 28 is equipped with a 125-volt indicator.

MODEL 3554 () 30**

1.15 The Model 3354** () 30 is a single-line pushbutton dial, standard size, wall telephone. This model provides no additional outstanding features.

MODEL 3554 () 31**

1.16 The Model 3554** () 31 is the same as the Model 3554** () 30 with the addition of a nine-foot handset cord.

MODEL 3554 () 37/38**

1.17 The Model 3554** () 37/38 is the same as the Model 3554** () 30 with the addition of a message waiting lamp. The lamp is used in PBX

applications to indicate that the station user should contact the message center. The Model 3554** () 37 is equipped with a 90-volt indicator. The Model 3554** () 38 is equipped with a 125-volt indicator.

1.18 Single-line wall telephones, such as the Model 3554** () 20, may be wired for use in a key system. This telephone provides connections through the hookswitch that allow ground on the A1 lead to be applied to key equipment by way of the A lead. The Model 3554** () 20 may be converted to A-lead control as follows:

- (a) Remove the line cord of the telephone by disconnecting the leads from the network.
- (b) Connect a four-conductor line cord in the following manner.
 - (1) Connect the RD (Ring) lead to network terminal L2.
 - (2) Connect the GN (Tip) lead to network terminal F.
 - (3) Connect the BK (A) lead to network terminal L1.
 - (4) Connect the YL (A1) lead to network terminal G.
- (c) Move the BK ringer lead from network terminal G to network terminal F.
- (d) Move the SL-WH hookswitch lead from network terminal F to network terminal G.

2. INSTALLATION

2.01 Since the modular versions of these telephones are equipped with modular plugs, installation consists of inserting this plug into an available wall jack. Refer to the appropriate circuit label for installation wiring of nonmodular units.

3. MAINTENANCE

3.01 For replacement parts information and for an exploded-view drawing of major assembly groups, refer to Section 50-554-104.