

555-7101-101

# CallPilot

## Planning and Engineering Guide

Product release 1.07

Standard 2.0

November 2000

---

---

**NORTEL**  
**NETWORKS™**

P0916384

# CallPilot

## Planning and Engineering Guide

---

|                     |               |
|---------------------|---------------|
| Publication number: | 555-7101-101  |
| Product release:    | 1.07          |
| Document release:   | Standard 2.0  |
| Date:               | November 2000 |

---

Copyright © 2000 Nortel Networks, All Rights Reserved

Printed in the United States of America

Information is subject to change without notice. Nortel Networks reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant.

The process of transmitting data and call messaging between the Meridian 1 and CallPilot is proprietary to Nortel Networks. Any other use of the data and the transmission process is a violation of the user license unless specifically authorized in writing by Nortel Networks prior to such use. Violations of the license by alternative usage of any portion of this process or the related hardware constitutes grounds for an immediate termination of the license and Nortel Networks reserves the right to seek all allowable remedies for such breach.

This page and the following page are considered the title page, and contain Nortel Networks and third-party trademarks

\*Nortel Networks, the Nortel Networks logo, the Globemark, and Unified Networks, BNR, CallPilot, DMS, DMS-100, DMS-250, DMS-MTX, DMS-SCP, DPN, Dualmode, Helmsman, IVR, MAP, Meridian, Meridian 1, Meridian Link, Meridian Mail, Norstar, SL-1, SL-100, Supernode, Symposium, Telesis, and Unity are trademarks of Nortel Networks.

ACCENT is a trademark of Accent Software International Ltd.

ACTION REQUEST SYSTEM and AR SYSTEM are trademarks of Remedy Corporation.

AMDEK is a trademark of Amdek Corporation.

ANSI is a trademark of the American National Standards Institute, Inc.

AT&T is a trademark of American Telephone and Telegraph Corporation.

ATRIA is a trademark of Pure Atria Corporation.

CASEWARE is a trademark of Caseware International, Inc.

CLEARCASE is a trademark of Rational Software Corporation.

CONTINUUS is a trademark of Continuus Software Corporation.

CRYSTAL REPORTS is a trademark of Seagate Software Inc.

EUDORA PRO is a trademark of QUALCOMM Inc.

FRAME, FRAMEBUILDER, FRAMEMAKER, and POSTSCRIPT are trademarks of Adobe Systems Incorporated.

HELVETICA is a trademark of Eltra Corporation.

HITACHI is a trademark of Hitachi Limited.

LOGITECH is a trademark of Logitech, Inc.

MACINTOSH and APPLE are trademarks of Apple Computer Inc.

MFA is a trademark of Astec International Ltd.

MICROSOFT, MS-DOS, POWERPOINT, WINDOWS, and WINDOWS NT are trademarks of Microsoft Corporation.

NOVELL is a trademark of Novell, Inc.

PCANYWHERE is a trademark of Symantec Corporation.

PROMARK and RHOBOT are trademarks of DMI Promark, Inc.

SLR4, SLR5, and TANDBERG are trademarks of Tandberg Data ASA.

SONY is a trademark of Sony Corporation.

SYBASE is a trademark of Sybase, Inc.

TIMES is a trademark of Heidelberger Druckmaschinen Aktiengesellschaft.

3COM is a trademark of 3Com Corporation.

UNIX is a trademark of X/Open Company Limited.

WINRUNNER is a trademark of Mercury Interactive Corporation.

# Publication history

## **November 2000**

The *CallPilot Planning and Engineering Guide* is released as Standard 2.0. This version documents Release 1.07 of CallPilot planning and engineering information. This edition makes all previous editions obsolete.

## **May 2000**

The *CallPilot Planning and Engineering Guide* is released as Standard 1.0. This version documents Release 1.07 of CallPilot planning and engineering information. This edition makes all previous editions obsolete.



# Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Getting started with planning and engineering</b>      | <b>11</b> |
|          | <b>Section A: About this guide</b>                        | <b>13</b> |
|          | Overview . . . . .  | 14        |
|          | What's new in Release 1.07?. . . . .                      | 15        |
|          | Skills you need. . . . .                                  | 16        |
|          | <b>Section B: About planning and engineering</b>          | <b>19</b> |
|          | Defining planning and engineering . . . . .               | 20        |
|          | Components in a CallPilot system. . . . .                 | 21        |
|          | Related information products . . . . .                    | 23        |
| <b>2</b> | <b>System configurations</b>                              | <b>27</b> |
|          | Overview . . . . .  | 28        |
|          | <b>Section A: About system configurations</b>             | <b>31</b> |
|          | Understanding the tower and rackmount platforms . . . . . | 32        |
|          | Understanding the 200i IPE platform . . . . .             | 36        |
|          | Understanding the 201i IPE platform . . . . .             | 38        |
|          | <b>Section B: Hardware and software configurations</b>    | <b>41</b> |
|          | CallPilot server . . . . .                                | 42        |
|          | Switches. . . . .   | 45        |
|          | Administrative PC . . . . .                               | 49        |
|          | Web Messaging server. . . . .                             | 52        |
|          | Desktop Messaging clients . . . . .                       | 55        |
|          | <b>Section C: Connectivity requirements</b>               | <b>59</b> |
|          | Meridian 1 . . . . .                                      | 60        |
|          | MSL-100/DMS-100. . . . .                                  | 63        |
|          | Lucent, Mitel, or Rolm . . . . .                          | 65        |
|          | Matra . . . . .   | 66        |
|          | Customer LAN . . . . .                                    | 67        |
| <b>3</b> | <b>Learning about CallPilot features</b>                  | <b>71</b> |
|          | Overview . . . . .  | 72        |

Application Builder . . . . . 74  
 Reporter . . . . . 76  
 Desktop and Web Messaging . . . . . 77  
 Networking . . . . . 78  
 Multimedia messaging . . . . . 81

**4 Determining system size 83**

Overview . . . . . 85

**Section A: About channel requirements 87**

An overview of channels . . . . . 88  
 Guidelines for determining channel requirements . . . . . 90

**Section B: Determining voice channel requirements 93**

Steps to follow in determining the number of voice channels . . . . . 94  
 To help you determine voice channel requirements . . . . . 96  
 Determining the busy hour activity . . . . . 98  
 Determining the activity of all voice services . . . . . 99  
 Determining network activity . . . . . 100  
 Determining Outcalling activity . . . . . 101  
 Determining the number of voice channels required . . . . . 102

**Section C: Determining fax channel requirements 105**

An overview of fax channels . . . . . 106  
 Determining the number of fax channels . . . . . 107  
 To help you determine fax channel requirements . . . . . 109  
 Determining the busy hour fax menu activity . . . . . 111  
 Determining the busy hour traffic for fax callback activity . . . . . 113  
 Determining the busy hour traffic for fax auto attendant . . . . . 114  
 Determining the busy hour fax messaging activity . . . . . 116  
 Calculating the number of fax channels required . . . . . 117  
 Calculating the number of fax channels for fax broadcasting activity . . . . . 118

**Section D: Determining speech-recognition channel requirements 121**

Determining the number of speech-recognition channels required . . . . . 122

**Section E: Determining the number of MPUs required 125**

Calculating the number of MPUs required . . . . . 126

**Section F: Determining storage hour requirements 129**

Steps to follow in estimating your storage hours . . . . . 130  
 To help you determine storage hour requirements . . . . . 131  
 Determining the mailbox storage requirements . . . . . 133

|          |   |            |
|----------|---|------------|
|          | Calculating storage hours for Application Builder . . . . .         | 136        |
|          | <b>Section G: Calculating system size</b>                           | <b>139</b> |
|          | Before you calculate your system size . . . . .                     | 140        |
|          | Calculating your system size . . . . .                              | 141        |
| <b>5</b> | <b>Engineering the server</b>                                       | <b>143</b> |
|          | Understanding the 200i server capacities . . . . .                  | 144        |
|          | Understanding the 201i server capacities . . . . .                  | 146        |
|          | Understanding the 702t server capacities . . . . .                  | 149        |
|          | Understanding the 1001rp server capacities . . . . .                | 152        |
| <b>6</b> | <b>Engineering the clients</b>                                      | <b>155</b> |
|          | Overview . . . . .  | 156        |
|          | <b>Section A: Engineering the administrative PC</b>                 | <b>157</b> |
|          | System requirements for Reporter . . . . .                          | 158        |
|          | System requirements for Application Builder . . . . .               | 160        |
|          | <b>Section B: Engineering the desktop client</b>                    | <b>161</b> |
|          | System requirements for the desktop client . . . . .                | 162        |
|          | <b>Section C: Calculating disk space requirements</b>               | <b>165</b> |
|          | To help you determine disk space requirements . . . . .             | 166        |
| <b>7</b> | <b>Selecting a site</b>   | <b>173</b> |
|          | Overview . . . . .  | 174        |
|          | Understanding space requirements for the CallPilot server . . . . . | 175        |
|          | CallPilot power supply requirements . . . . .                       | 178        |
|          | Environmental specifications for the CallPilot servers . . . . .    | 180        |
| <b>A</b> | <b>Traffic capacity tables</b>                                      | <b>185</b> |
|          | Types of traffic capacity tables . . . . .                          | 186        |
|          | CCS values and channel requirements table . . . . .                 | 187        |
| <b>B</b> | <b>Planning spares requirements</b>                                 | <b>193</b> |
|          | Planning spares for the CallPilot servers . . . . .                 | 194        |
|          | 200i server spares . . . . .  | 195        |
|          | 201i server spares . . . . .  | 197        |
|          | 702t server spares . . . . .  | 200        |

---

|   |            |
|---|------------|
| 1001rp server spares . . . . .  | 204        |
| Switch connectivity spares (tower and rackmount platforms) . . . . .  | 208        |
| IPE distributor support kits . . . . .                                | 210        |
| <br>  |            |
| <b>C Component list</b>   | <b>211</b> |
| <br>  |            |
| <b>D Site survey checklist</b>  | <b>213</b> |
| Planning your CallPilot system using a site survey checklist. . . . . | 214        |
| <br>  |            |
| <b>Index</b>  | <b>219</b> |

# Chapter 1

---

## Getting started with planning and engineering

### In this chapter

|  |           |
|--|-----------|
| <b>Section A: About this guide</b>               | <b>13</b> |
| Overview   | 14        |
| What's new in Release 1.07?                      | 15        |
| Skills you need                                  | 16        |
| <b>Section B: About planning and engineering</b> | <b>19</b> |
| Defining planning and engineering                | 20        |
| Components in a CallPilot system                 | 21        |
| Related information products                     | 23        |



# Section A: About this guide

## In this section

|                             |    |
|-----------------------------|----|
| Overview                    | 14 |
| What's new in Release 1.07? | 15 |
| Skills you need             | 16 |

# Overview

## Introduction

The *CallPilot Planning and Engineering Guide* provides descriptive information and instructions for selecting and planning your CallPilot system.

Before you can start planning, you must understand the key components that need to be provisioned and how these components interact with one another. This chapter provides a high-level overview of these concepts.

## Skills you need

Skills that might be helpful when planning your CallPilot system include the following:

- knowledge about Nortel Networks products
- knowledge about non-Nortel Networks switches
- Windows operating systems
- network management and client-server systems

See page 16 for more details.

## Other resources

To ensure a successful implementation, you should use both this guide and the resources identified on page 17.

# What's new in Release 1.07?

## Introduction

CallPilot now supports the following switches:

- MSL-100
- DMS-100 (Centrex)
- Matra (not available in North America)
- Lucent
- Mitel
- Rolm

The 201i platform replaces the 200i platform.

# Skills you need

## Introduction

You need certain skills and knowledge to use this guide effectively.

## Nortel Networks product knowledge

Knowledge of, or experience with, the following Nortel Networks products is helpful:

- Meridian 1
- MSL-100/DMS-100
- Meridian Mail
- CallPilot 1.06

## Experience or knowledge of non-Nortel Networks switches

Knowledge of, or experience with, the following non-Nortel Networks switches is helpful:

- Matra
- Lucent
- Mitel
- Rolm

## PC experience or knowledge

Knowledge of, or experience with, the following PC products is helpful:

- Microsoft Windows NT
- Microsoft Windows 95
- Microsoft Windows 98
- Microsoft Windows 2000

## Other experience or knowledge

Other types of experience or knowledge that might be useful include

- network management
- client-server systems
- flowcharting

## Other resources

The following documents and tools might be useful in engineering a CallPilot system:

- CallPilot 1.07 General Release Bulletin
- Meridian Client Compatibility Check utility
- Meridian Mail comparison
- Product Bulletins
- CallPilot Engineering Spreadsheet

To obtain the above resources, contact your Nortel Networks distributor. If you are a Nortel Networks distributor, you can obtain these documents from the CallPilot area of the Nortel Networks Information Center web site at <http://www.nortel.com/partnercenter>.



# Section B: About planning and engineering

## In this section

|                                   |    |
|-----------------------------------|----|
| Defining planning and engineering | 20 |
| Components in a CallPilot system  | 21 |
| Related information products      | 23 |

# Defining planning and engineering

## Introduction

The process of planning and engineering involves determining the best size, platform, and location for your CallPilot system. Worksheets and checklists are provided throughout this guide to help you with this task.

As a framework for beginning your planning and engineering activities, some possible questions to consider are listed below.

## Questions to consider

Consider these questions:

- Have you identified administrative PCs?
- Where will you locate the administrative PCs? What is the LAN connectivity for the PCs?
- Which of the three CallPilot servers will you use?
- Where will you locate the servers and how will you connect them?

Contents of this guide (including checklists and worksheets) can help you to find answers to these questions.

# Components in a CallPilot system

## Introduction

A CallPilot system consists of three key components: switch, server, and administrative PC. Desktop Messaging is an option that can be installed on desktop PCs. For Web Messaging, a web server is another optional component (supplied by the customer) that allows desktop PCs to access messages via web pages.

## Switch types

Switch types that are compatible with CallPilot include models of these switch families: Meridian 1, MSL-100, Matra, Lucent, Mitel, and Rolm. Complete compatibility details are outlined later in this guide.

## Server types and connection methods

The server can be a tower (702t), rackmount (1001rp), or an IPE (200i or 201i) platform. Based on the switch, the server connects using one of the following connectivity means:

- Meridian 1: Embedded LAN (ELAN) and IPE network loop through the MGate card
- MSL-100/DMS-100: T1 and SMDI link
- Lucent, Mitel, and Rolm: Digital Set Emulation (DSE)
- Matra: analog link

## Administrative and desktop PCs

The administrative PC maintains the server, switch, and CallPilot software.

The desktop PC with Desktop Messaging can download messages from the CallPilot server. A web server allows desktop users to access messages using a web browser.

## What needs to be provisioned?

The following components must be provisioned:

- CallPilot server
- administrative PC
- switch resources related to CallPilot
- desktop client PC, if the Desktop Messaging feature is required
- web server, if Web Messaging is required

# Related information products

## Introduction

The following CallPilot technical documents are stored on the CD-ROM that you receive with your system. You can search the entire suite of documentation online, or you can print part or all of a guide.

## Planning and engineering guides

Use these guides before you install CallPilot to help you plan your system, and to plan a migration of data from Meridian Mail to CallPilot.

### Document titles

---

*Planning and Engineering Guide*

*Meridian Mail to CallPilot Migration Utility Guide*

---

## Installation and configuration guides

These guides describe how to install hardware and software for the CallPilot server, client, and desktop messaging. Instructions for configuring the switch are also provided.

### Document titles

---

*200i Installation and Configuration Guide*

*201i Installation and Configuration Guide*

*702t Installation and Configuration Guide*

*1001rp Installation and Configuration Guide*

*Desktop Messaging Software Installation and Maintenance Guide*

---

## Administration guides

These guides provide specialized information to help you configure CallPilot, administer and maintain it, and use its features.

### Document titles

---

*Getting Started Quick Reference Card*

*Administrator's Guide*

*Reporter Guide*

*Application Builder Guide*

*Monitoring and Security for the Administrator*

---

## Networking guides

These guides describe how to plan, install, set up, and troubleshoot networking services.

### Document titles

---

*Network Planning Guide*

*AMIS Implementation and Administration Guide*

*Integrated AMIS Implementation and Administration Guide*

*NMS Implementation and Administration Guide*

*Enterprise Implementation and Administration Guide*

*VPIM Implementation and Administration Guide*

---

## End user guides

These guides are intended for end users of CallPilot, such as phoneset users and desktop messaging users.

### Document titles

---

*Multimedia Messaging User Guide*

*Speech Activated Messaging User Guide*

*Desktop Messaging Quick Reference Guide*

---

## Troubleshooting reference

This reference provides step-by-step troubleshooting procedures for CallPilot.

### Document title

---

*CallPilot Troubleshooting Reference*

---

## Using the online Help, guides, and tutorials

CallPilot contains three online sources for information:

- Online Help provides brief answers to the questions “What’s this?” and “How do I...?”
- Online guides provide detailed conceptual information, as well as information on how to perform detailed tasks.
- Online tutorials provide a complete product overview, as well as specific information on how to use Application Builder.

You can access all information using either the Help menu or Help buttons.

## **Contacting technical support**

Contact your distributor's technical support organization to get help with troubleshooting your system.

## **Contacting Nortel Networks**

If you have comments or suggestions for improving CallPilot and its documentation, contact Nortel Networks at the following web site address:

[http://www.nortelnetworks.com/callpilot\\_feedback](http://www.nortelnetworks.com/callpilot_feedback)

# Chapter 2

---

## System configurations

### In this chapter

|  |           |
|--|-----------|
| Overview   | 28        |
| <b>Section A: About system configurations</b>          | <b>31</b> |
| Understanding the tower and rackmount platforms        | 32        |
| Understanding the 200i IPE platform                    | 36        |
| Understanding the 201i IPE platform                    | 38        |
| <b>Section B: Hardware and software configurations</b> | <b>41</b> |
| CallPilot server                                       | 42        |
| Switches   | 45        |
| Administrative PC                                      | 49        |
| Web Messaging server                                   | 52        |
| Desktop Messaging clients                              | 55        |
| <b>Section C: Connectivity requirements</b>            | <b>59</b> |
| Meridian 1   | 60        |
| MSL-100/DMS-100  | 63        |
| Lucent, Mitel, or Rolm                                 | 65        |
| Matra  | 66        |
| Customer LAN   | 67        |

# Overview

## Introduction

This chapter provides an overview of the four system configurations supported by CallPilot.

Its purpose is to assist you in understanding the system, and the hardware and software components that must be provisioned.

## Supported server platforms

You can install CallPilot software on a tower (702t) or rackmount (1001rp) platform. The tower platform can connect to any of the supported switches. The rackmount platform can connect to any of the supported switches except Matra.

You can also install the CallPilot software on a server (200i or 201i) that resides in the Intelligent Peripheral Equipment (IPE) shelf on a Meridian 1 switch.

## Supported switches

Based on the server you choose, CallPilot supports the following switches:

- Meridian 1
- MSL-100
- DMS-100 (Centrex)
- Lucent
- Matra (not available in North America)
- Mitel
- Rolm

For information about the hardware and software requirements, see page 45. For information about the connectivity requirements, see Section C: “Connectivity requirements” on page 59.

## Administrative PC

CallPilot features, such as Reporter and Application Builder, are intended to run on the administrative PC. The administrative PC should be connected to the ELAN to administer the switch and the CallPilot server.

For more details, see page 49.

## Web Messaging server

If you are using the CallPilot Web Messaging feature, you need a Microsoft Internet Information Server (IIS) web server. For information about the minimum configuration requirements, see page 52.

## Desktop Messaging client

A PC running Windows 95, Windows 98, Windows 2000, or Windows NT can run the Desktop Messaging client that is available with CallPilot. The following Desktop Messaging clients are supported by CallPilot:

- Desktop Messaging for Microsoft Exchange/Outlook
- Desktop Messaging for Lotus Notes
- Desktop Messaging for Internet Mail clients
- Desktop Messaging for Novell GroupWise
- Desktop Messaging for Web Browsers

For information about the minimum configuration requirements, see page 55.



# Section A: About system configurations

## In this section

|   |    |
|---|----|
| Understanding the tower and rackmount platforms | 32 |
| Understanding the 200i IPE platform             | 36 |
| Understanding the 201i IPE platform             | 38 |

# Understanding the tower and rackmount platforms


## Introduction

You can install CallPilot software on a tower (702t) or rackmount (1001rp) platform. This section explains both of these configurations.

The tower and rackmount platforms support up to 96 DS0 channels and 96 Multimedia Processing Units (MPUs), and provide up to 1000 hours of storage.

## Network diagram

The tower and rackmount platforms have similar components but differ in server hardware. The following diagram shows a typical network setup using the tower platform and Meridian 1 switch. You can use a similar setup for a rackmount server. The ELAN is not supported by non-Meridian 1 switches.



G100895

## Switch

The tower or rackmount platform includes support for the switches identified in the following table:

| <b>Server type</b>    | <b>Switch components</b>       | <b>For more details, see</b> |
|-----------------------|--------------------------------|------------------------------|
| Tower (702t)          | ■ Meridian 1                   | ■ page 60                    |
|                       | ■ MSL-100 or DMS-100 (Centrex) | ■ page 63                    |
|                       | ■ Lucent                       | ■ page 65                    |
|                       | ■ Matra                        | ■ page 66                    |
|                       | ■ Mitel                        | ■ page 65                    |
|                       | ■ Rolm                         | ■ page 65                    |
| Rackmount<br>(1001rp) | ■ Meridian 1                   | ■ page 60                    |
|                       | ■ MSL-100 or DMS-100 (Centrex) | ■ page 63                    |
|                       | ■ Lucent                       | ■ page 65                    |
|                       | ■ Mitel                        | ■ page 65                    |
|                       | ■ Rolm                         | ■ page 65                    |

## Server and network connectivity

The server in the tower or rackmount configuration includes

- the CallPilot server (specifically the 702t or 1001rp) loaded with Windows NT Server 4.0, pcANYWHERE32 version 8, and an SQL Anywhere database  
Nortel Networks provides the server.
- modem (optional, for support purposes)
- Customer LAN (optional)
- laptop (for installation and maintenance purposes if no administrative PC is present at the customer site)

Based on the switch configuration, you require the following connectivity hardware for the CallPilot server:

| <b>Switch type</b>     | <b>Connectivity equipment</b>                           |
|------------------------|---|
| Meridian 1             | Hub, ELAN, MPB-16 Carrier Board, and MGate card         |
| MSL-100 or DMS-100     | SMDI Serial RS-232C line and Dialogic dual-span T1 card |
| Matra                  | MPB16-2T  |
| Lucent, Mitel, or Rolm | VTG VoiceBridge 2000                                    |

**Note:** Never connect a printer to the server.

## Client PCs

The client PCs include

- one web server PC
- one or more administrative PCs loaded with Windows 95, Windows 98, Windows 2000, or Windows NT Workstation 4.0
- one or more desktop client PCs loaded with third-party e-mail software packages (if the Desktop or Web Messaging software is purchased)

The customer supplies all client PCs.

# Understanding the 200i IPE platform


## Introduction

You can install CallPilot on an IPE platform (200i) that resides in a Meridian 1 or Option 11C switch. This section provides an overview of this configuration.

The IPE platform supports up to 24 DS0 channels and 24 MPUs, and provides 200 hours of storage.

## Network diagram

The following diagram shows a typical network setup with the 200i platform:



G100894

## Switch

Only the Meridian 1 switch is supported. For more details, see page 60.

## Server

The server component in the 200i configuration includes

- the 200i server loaded with Windows NT Server 4.0, pcANYWHERE32 version 8, and an SQL Anywhere database  
Nortel Networks provides the server.
- MPC-8 cards, which are part of the CallPilot server
- modem (for support purposes)
- ELAN
- customer LAN (CLAN, optional)
- Ethernet hub
- laptop (for installation and maintenance purposes, if no administrative PC is present at the customer site)

## Client PCs

The client PCs include

- one or more administrative PCs loaded with Windows 95, Windows 98, Windows 2000, or Windows NT Workstation 4.0
- one or more desktop client PCs loaded with third-party e-mail software packages  
You require these machines if Desktop Messaging software is purchased.

The customer supplies all client PCs.

# Understanding the 201i IPE platform


## Introduction

You can install CallPilot on an IPE platform (201i) that resides in a Meridian 1 or Option 11C switch. This section provides an overview of this configuration.

The IPE platform supports up to 24 DS0 channels and comes standard with 24 MPUs, and provides 200 hours of storage.

## Network diagram

The following diagram shows a typical network setup with the 201i platform:



G100894

## Switch

Only the Meridian 1 switch is supported. For more details, see page 60.

## Server

The server component in the 201i configuration includes

- the 201i server loaded with Windows NT Server 4.0, pcANYWHERE32 version 8, and an SQL Anywhere database  
Nortel Networks provides the server.
- MPC-8 cards, which are part of the CallPilot server
- modem (for support purposes)
- ELAN
- customer LAN (CLAN, optional)
- Ethernet hub
- laptop (for installation and maintenance purposes, if no administrative PC is present at the customer site)

## Client PCs

The client PCs include

- one or more administrative PCs loaded with Windows 95, Windows 98, Windows 2000, or Windows NT Workstation 4.0
- one or more desktop client PCs loaded with third-party e-mail software packages (if Desktop Messaging software is purchased)

The customer supplies all client PCs.



## Section B: Hardware and software configurations

### In this section

|                           |    |
|---------------------------|----|
| CallPilot server          | 42 |
| Switches                  | 45 |
| Administrative PC         | 49 |
| Web Messaging server      | 52 |
| Desktop Messaging clients | 55 |

# CallPilot server

## Introduction

This section summarizes the hardware and software requirements for the CallPilot server.

## Hardware

CallPilot is an application built on the CallPilot server hardware platform. The CallPilot platform for Release 1.07 consists of a tower chassis (702t), rackmount chassis (1001rp), or a server that fits into the IPE shelf of a Meridian 1 switch (200i or 201i). You can connect the 702t platform to any of the supported switches. You can connect the 1001rp platform to any of the supported switches except Matra.

## Software

The software configuration consists of the following items:

- the server operating system  
The CallPilot server uses the Windows NT Server 4.0 operating system with Service Pack 5.
- CallPilot software
- third-party software

## Compatibility with other products and environments

### Meridian Mail

CallPilot can coexist with Meridian Mail on the Meridian 1 switch. You can network CallPilot with Meridian Mail systems that use one or more of the following network protocols:

- AMIS-Analog Networking
- Enterprise Networking
- VPIM Networking using Meridian Mail Net Gateway

However, there are limitations. See page 80 for details.

### **Meridian 1 Multi-Tenant**

CallPilot supports users on a multi-tenant Meridian 1 switch as if they were on a single-tenant system. CallPilot

- does not know to which Meridian 1 tenant a user belongs
- has no administration or billing features by tenant

### **Custom Controlled Routing**

CallPilot can coexist on the same Meridian 1 switch as Custom Controlled Routing (CCR).

CallPilot does not support the CCR command, Give IVR.

### **Symposium applications**

CallPilot can coexist with Symposium Call Center Server 1.x and Symposium Express 1.0 or 2.0 on the same Meridian 1 switch and ELAN.

CallPilot does not support the following Symposium Call Center Server voice processing elements commands:

- Give IVR
- Give Broadcast Announcement
- Collect Digits
- Play Prompt
- Open...End Voice Session

Refer to Product Bulletin 99115 for details.

### **Internet Telephony Gateway**

AMIS-Analog and Enterprise Networking are supported with Internet Telephony Gateway (ITG) 1.1 (version 1.0.34 or later).

Network Message Service is not supported by ITG 1.1.

**Third-party Windows NT Server software and hardware**

Nortel Networks does not support the addition of any third-party Windows NT Server software or hardware to the CallPilot server. Installation of third-party Windows NT Server software or hardware can destabilize the system, degrade its mission of providing real-time call processing performance, and disrupt its Year 2000 (Y2K) conformance. For details, refer to Product Bulletin 99067, “CallPilot Unauthorized Hardware and Software.”

**See also**

For detailed information on the capacity of the servers, refer to Chapter 5, “Engineering the server.”

# Switches

## Introduction

This section identifies the switches that are supported by CallPilot.

## Meridian 1

The supported Meridian 1 platforms include

- Option 11C
- Option 11C Mini
- Option 81
- Options 51C through 81C

For North America, you need Release 23.55 or higher. For Europe, you need Release 24 or higher.

For information about the connectivity requirements, see “Meridian 1” on page 60.

## MSL-100 or DMS-100 (Centrex)

### Hardware requirements

For an MSL-100 switch, you must have a sufficient number of Line Side T1 cards for the number of channels purchased. Refer to the *Line Side T-1 Interface (LT1) for IPE Services Guide* (NTP 555-4001-022) for instructions on installing Line Side T1 cards.

**Note:** The Line Side T1 cards must be configured for ground start. CallPilot does not support loop start.

A DMS-100 switch requires an external channel bank to support Centrex service.

The switch must have either an IOC shelf with an NT1X89 card or an IOM to support the SMDI link to CallPilot.

**Software requirements**

The MSL-100 switch requires MSL-10 software or higher. The DMS-100 requires NA08 software or higher.

**See also**

For information about the connectivity requirements, see “MSL-100/DMS-100” on page 63.

**Lucent**

The Definity Generic 3 Lucent switch is supported through Digital Set Emulation (DSE).

**Software and line card requirements**

You need the Voice Mail Application option and one of the following software releases and line cards:

| <b>Software release</b> | <b>Line card</b> |
|-------------------------|------------------|
| G3V3+                   | TN2181 V7        |
| G3V6+                   | TN2224           |

**See also**

For information about the connectivity requirements, see “Lucent, Mitel, or Rolm” on page 65.

## Matra

All Matra switch models are supported.

### Software requirements

You need one of the following software releases:

- version 11.5F or later for Voice Messaging only (available on all models)
- version 11.6 for Voice, Fax, and ASR (available only on MC6501)
- version 12.2.1 or later for Voice, Fax, and ASR (available on all models)

### Analog line cards

You need one of the following loop-start analog line cards:

| Matra model | Supported line cards   |
|-------------|--|
| M6501       | <ul style="list-style-type: none"> <li>■ HJ2843A-LA4 (4 analog channels)</li> <li>■ HJ2763A-LA8 (8 analog channels)</li> </ul> |
| M6502       | <ul style="list-style-type: none"> <li>■ HJ3944A-LAE (32 analog channels)</li> </ul>   |
| M6504       | <ul style="list-style-type: none"> <li>■ HJ3806A-LAF (16 analog channels)</li> </ul>   |
| M6540       |  |
| M6550       |  |

### See also

For information about the connectivity requirements, see “Matra” on page 66.

## Mitel

The following table identifies the Mitel switches, software, and line cards that provide Digital Set Emulation (DSE):

| Switch        | Software       | Line card       |
|---------------|----------------|-----------------|
| SX-200D       | Lightware 15 + | Digital Line    |
| SX-200 Light  | Lightware 15 + | Digital Line    |
| SX-2000 Light | All M Streams  | DNI line: MC330 |
| SX-2000 S     | All M Streams  | DNI line: MC330 |
| SX-2000 VS    | All M Streams  | DNI line: MC330 |

### See also

For information about the connectivity requirements, see “Lucent, Mitel, or Rolm” on page 65.

## Rolm

You need the Message Waiting Interface option and one of the following Rolm switches that are supported through Digital Set Emulation (DSE):

| Switch      | Software         | Line card                    |
|-------------|------------------|------------------------------|
| 8000        | 8003 +           | RPI 1 and 2: 78011 and 78012 |
| 9000        | All versions     | RPI 1 and 2: 78011 and 78012 |
| 9751 (9005) | All versions     | RLI: 90678                   |
| 9751 (9006) | 9006.3 to 9006.4 | SLRM, SLRM2, SLRM3           |

### See also

For information about the connectivity requirements, see “Lucent, Mitel, or Rolm” on page 65.

# Administrative PC

## Introduction

This section provides the hardware and software requirements for the administrative PC. The administrative PC should be connected to the ELAN to administer the switch and the CallPilot server.

CallPilot features, such as Reporter and Application Builder, are intended to run on the administrative PC.

## Basic hardware specifications

The minimum hardware configuration is an Intel Pentium 90 MHz (or faster) PC with

- 32 Mbytes of RAM
- a hard disk drive with 160 Mbytes available with additional space available for Windows operations  
**Note:** The CallPilot software requires 160 Mbytes of space. Reporter requires additional hard disk space for the downloading and storing of data. Refer to Chapter 6, “Engineering the clients,” for more information on determining the disk space requirements.
- CD-ROM drive
- a voice/fax modem (optional) or one Ethernet Network Interface Card or Token Ring Network Interface Card. Connection to the ELAN requires an Ethernet Network Interface Card; connection to the CLAN requires either card.
- a 16-color VGA 640x480 monitor (256-color SVGA 800x600 is highly recommended)
- a sound card and microphone for recording custom prompts (optional)
- a Windows-compatible mouse

## Software configuration

The administrative PC software configuration consists of the following items:

- the operating system  
The administrative PC uses the Windows 95, Windows 98, Windows 2000, or Windows NT Workstation 4.0 operating system.
- CallPilot software

## Compatibility with other products and environments

### Operating systems

CallPilot administration clients are compatible with the following Windows operating systems:

- Windows 95a
- Windows 95b OEM Service Release 2
- Windows 98
- Windows 98 Second Edition
- Windows NT 4.0 (Service Pack 3 or higher)
- Windows 2000

CallPilot administration clients are not supported on PCs using the following operating systems:

- Windows 95a with Service Pack 1
- dual-boot configurations (Windows 95 and Windows NT)
- non-English versions of Windows
- Unix, Linux, or Mac OS

### Meridian Mail Reporter

CallPilot Reporter cannot coexist on the same PC as Meridian Mail Reporter.

**Note:** CallPilot Reporter only supports CallPilot. Meridian Mail Reporter supports only Meridian Mail.

**Meridian Administration Tools**

CallPilot administration clients can coexist on the same PC with Meridian Administration Tools (MAT) 6.6.

**MS Office 2000**

CallPilot administration, Reporter, and Application builder clients are compatible with Microsoft Office 2000.

**Novell Netware client**

CallPilot administration clients are compatible with Novell Netware client version 3.10.

**See also**

For more information on the administrative PC, refer to Chapter 6, “Engineering the clients.”

# Web Messaging server

## Introduction

If you are using the CallPilot Web Messaging feature, then the CallPilot Web Messaging software must be installed on a separate Windows NT server that is running Microsoft Internet Information Server (IIS).

## Hardware requirements

The Web Messaging server requires the following minimum hardware configuration:

- Pentium 166 MHz
- 64 Mbytes of RAM
- 10 Mbps network interface card

## Software specifications

The web messaging server requires the following software:

- Microsoft Windows NT 4 Server with Service Pack 3, 4, or 5
- Microsoft IIS version 4.0

## Web server considerations

You must consider a number of factors when installing Web Messaging that will influence the chosen configuration. It is not necessary for the server to be dedicated to providing Web Messaging. The same server can host other web pages or also provide standard network services, such as printing and file sharing.

As with any web server, you should monitor utilization following an installation or major change, such as adding more users. This provides useful insight into server utilization and also highlights a system overload.

Consider the following information when deciding on your Web Messaging server configuration:

- the number of clients that will be using this service
- other services running on your existing web server
- how messages are played
- acceptable response times
- the number of users that can be supported

### **Number of clients**

If this is the only desktop interface you are using, then it is likely that you will use Web Messaging more than you will use an e-mail server (such as Exchange) with a desktop client (such as Outlook).

### **Web server usage for other services**

If you know that your existing web server is already slow, then adding this additional functionality might overload it even more. Users are also more likely to receive sluggish response times.

### **How messages are played**

Users can play their messages on their PC speakers or headphones.

Alternatively, users can play their messages on the phoneset. This eliminates the burden of transporting and converting messages from the web server and network.

If messages are played via WAV, this generates considerable web server loads. When the user downloads a message in WAV format, the message is first transferred from CallPilot to the web server. Software on the web server transcodes the VBK file to WAV format, which is a CPU-intensive activity. If you know that users will be downloading messages in WAV format, then dedicating a fast server is necessary to ensure that users receive a reasonable response time.

An alternative that eliminates the load of transcoding VBK to WAV is for the users to download the CallPilot audio player. This audio player can play VBK encoded messages.

**Acceptable response times**

To provide acceptable response times to large user communities, you might need to provision two or more dedicated web servers.

If user response time is slow during the busy hour, you can monitor the level of activity on the web server to see if it is overloaded. Windows NT Performance Monitor can provide this information. The two main indicators to monitor are CPU usage and available memory. If the CPU usage (shown as Processor Time) is constantly above 90 percent for a number of minutes during the busy hour, then user response time is suffering. If memory availability (shown as Available Bytes) is ever below 4 Mbytes, then user response time is suffering.

**WAV downloads and the number of users who can be supported**

Testing shows that such a web server can effectively support between 500 to 800 active users if they are not downloading messages in WAV format and the server is only being used for Web Messaging. If WAV downloads occur frequently, then the system can only effectively support between 100 to 200 active users.

On new systems with additional RAM and processors, such as the PII 400 MHz, testing shows that a system can support up to as many as 3000 active users if they are not downloading messages in WAV format, and the server is only being used for Web Messaging. If WAV downloads occur frequently, then the web server can only support between 500 to 1000 active users.

# Desktop Messaging clients

## Introduction

A client PC running either Windows 95, Windows 98, Windows 2000, or Windows NT can run the Desktop Messaging client that is available with CallPilot.

## Hardware specifications

The minimum configuration should meet the following specifications:

- an IBM PC or compatible (Intel 486 or faster system)
- 16 Mbytes of RAM (32 Mbytes is highly recommended)
- a hard disk drive with 10 Mbytes available
- a CD-ROM (optional)
- 16-color VGA 640x480 (256-color SVGA 800x600 is highly recommended)
- a sound card, microphone, and speakers for recording and playback of messages (optional)
- a voice fax/modem (optional) or one Ethernet Network Interface Card or Token Ring Network Interface Card
- a Windows-compatible mouse

## Desktop Messaging clients

CallPilot supports the following Desktop Messaging clients:

- Desktop Messaging for Microsoft Exchange/Outlook
- Desktop Messaging for Lotus Notes
- Desktop Messaging for Internet Mail clients
- Desktop Messaging for Novell GroupWise
- Desktop Messaging for Web Browsers

### **Desktop Messaging for Microsoft Outlook**

The Microsoft Outlook client requires

- Microsoft Outlook 97 version 8.0
- Microsoft Outlook 98
- Microsoft Outlook 2000

### **Desktop Messaging for Lotus Notes**

The Lotus Notes client requires Lotus Notes version 4.5, 4.51, 4.6, 4.61, or 5.0.

### **Desktop Messaging for Internet Mail clients**

The Internet Mail client requires

- Microsoft Outlook 2000
- Microsoft Outlook 98 (running with Internet Explorer 4.01)
- Microsoft Outlook Express running with Internet Explorer 4.01 and service patch 1 (or later)
- Netscape Messenger (part of Netscape Communicator version 4.5 or later)
- Qualcomm Eudora Pro CommCenter (version 4.02 or 4.2)

### **Desktop Messaging for Novell GroupWise**

The Novell GroupWise client requires

- Groupwise 5.5 Service Pack 1
- Windows Messaging 4.0

### **Desktop Messaging for Web Browsers**

The Web Browser client requires

- Microsoft Internet Explorer version 3.x, 4.x, or 5.x on Windows 95, Windows 98, or Windows NT
- Netscape Navigator version 3.x or 4.x on Windows 95, Windows 98, or Windows NT

**See also**

For more information on the Desktop Messaging software available with CallPilot, refer to Chapter 3, “Learning about CallPilot features.”

For more information on the Desktop Messaging PC, refer to Chapter 6, “Engineering the clients.”



# Section C: Connectivity requirements

## In this section

|                        |    |
|------------------------|----|
| Meridian 1             | 60 |
| MSL-100/DMS-100        | 63 |
| Lucent, Mitel, or Rolm | 65 |
| Matra                  | 66 |
| Customer LAN           | 67 |

# Meridian 1

## Introduction

The CallPilot server connects to the Meridian 1 switch using an ELAN. The ELAN uses the TCP/IP protocol at a speed of 10 Mbps.

## Option 11C

The copper-connected Option 11C is not supported with CallPilot. If you are using a copper-connected Option 11C, you must upgrade to a Fiber Cabinet Option 11C to support the ELAN connection.

## Tower and rackmount connectivity requirements

The tower (702t) and rackmount (1001rp) platforms connect to the IPE network loops through the MGate card. Each MGate card resides in the Meridian 1 IPE shelf and is connected to an MPB16-4 card in the CallPilot server using a 10 m (32.5 ft) twisted pair cable.

The MGate card can support a maximum of 32 channels. A fully configured 96-channel tower or rackmount system requires three MGate cards.

The MPB16-4 board provides 16 MPU resources and DS0 channel connectivity to the Meridian 1 switch. It contains two embedded DSPs and connects to the PCI bus of the tower or rackmount server. Four MPC-8 cards are supplied with the MBP16-4 card for a total DSP capacity of 48 MPU.

## IPE platform connectivity requirements

The IPE platform occupies two slots in the Meridian 1 IPE shelf and interfaces with the network loops through the IPE backplane. From the Meridian 1 switch perspective, the IPE platform appears logically equivalent to an XDLC. The IPE (200i) platform contains one embedded DSP. When two MPC-8 cards are inserted into the IPE platform's faceplate, 24 DS0 channels are supported.

The IPE platform also occupies two slots in the Meridian 1 IPE shelf, but will present itself to the switch as two MGate cards. Unlike the 200i server, the 201i server connects to the backplane for both slots to gain access to the DS30X associated with the second slot. In addition to the faceplate connectors, this server also utilizes a breakout cable, which connects to the bulkhead I/O connector associated with the first slot. The IPE (201i) platform contains one embedded DSP and two factory-installed MPC-8 cards supporting 24 DS0 channels.

## ELAN requirements

CallPilot performs call control signaling to the Meridian 1 using the proprietary AML protocol (also used by Meridian Mail) running over an ELAN that runs outside the Meridian 1 cabinet. The bandwidth requirement is 10 Mbps.

You need the following items:

- MAU to 10BaseT transceiver to convert the MAU output of the Meridian 1 call processor to RJ-45 for 10BaseT connection to a hub
- Category 5 10BaseT cables for CallPilot, Meridian 1, and optional administrative PC connection to a hub
- Ethernet hub

The IPE platform ships with a 10BaseT Ethernet hub and transceiver. For the tower or rackmount platforms, you must supply your own equipment (or purchase it from Nortel Networks).

## Network recommendation

Based on the size and required administrative operations of an external network, you might decide that you want to internetwork the ELAN using routers, bridges, or switches.

Direct connection of the ELAN to external networks (such as the CLAN), or improper router, bridge, or switch device selection or configuration can adversely affect the call processing abilities of ELAN-based Meridian switches and CallPilot servers.

As a result, Nortel Networks does not recommend applying router and switching technologies to the ELAN.

# MSL-100/DMS-100

## Introduction

The MSL-100 or DMS-100 switch uses an SMDI link and T1 channels to exchange data with the CallPilot server.

## SMDI Link

The SMDI link is a data link between the second serial port (COM 2) on the CallPilot server and the MPC port on the switch. The SMDI link transports incoming call information and MWI control messages. If the CallPilot server is close to the switch (the criteria is listed in this section), then the SMDI link can be a direct cable connection between the server and the switch. For longer distances, use a modem connection.

The criteria for direct cable connection depends on whether the switch has an IOC shelf or an Input Output Module (IOM):

- With an IOC shelf, the CallPilot server must be within 15.25 m (50 ft) of the switch for a direct cable connection. Use a modem connection for longer distances.
- With an IOM, the CallPilot server must be within 230 m (750 ft) of the switch for a direct cable connection. Use a modem connection for longer distances.

The approved modem is the General DataComm 060A010-001 (North American AC version).

## Line Side T1 cards

Line Side T1 cards in the MSL-100 or DMS-100 switch send the voice and data signals to the CallPilot server.

## **Dialogic DTI/480SC board**

One or more DTI/480SC boards reside in the CallPilot server. Each DTI/480SC board supports up to two T1 links to the switch. Each T1 link supports up to 24 channels. Calls from the switch arrive at the DTI/480SC board and are passed to the MPB16-4 boards for call processing.

## **MPB16-4 board**

The MPB16-4 board provides 16 MPU resources, contains two embedded DSPs, and connects to the PCI bus of the tower or rackmount server. Four MPC-8 cards are supplied with the MPB16-4 board for a total DSP capacity of 48 MPU. The MPC-8 cards process the voice and data signals that pass through the DTI/480SC boards.

## **Channel bank for DMS-100**

For a DMS-100 switch, you require an appropriate channel bank.

# Lucent, Mitel, or Rolm

## Introduction

In this configuration, the Lucent, Mitel, or Rolm switch uses digital lines to exchange data with the CallPilot server.

## VB2000 card

One or more VB2000 cards reside in the CallPilot server. Each VB2000 card contains eight ports where the digital lines from the switch terminate.

When signals arrive from the switch, the VB2000 provides the interface that interprets them and passes them to the MPB16-4 board. When CallPilot transmits data to the switch, the VB2000 card converts it to emulate the signals sent by digital sets supported by that switch.

## MPB16-4 board

The MPB16-4 board provides 16 MPU resources, contains two embedded DSPs, and connects to the PCI bus of the tower or rackmount server. Four MPC-8 cards are supplied for a total DSP capacity of 48 MPU. The MPC-8 cards process the voice and data signals that pass through the VB2000 card.

## Line cards

For a list of supported line cards for each switch platform, see the following:

- Lucent on page 46
- Mitel on page 48
- Rolm on page 48

## Channel requirement for MWI signaling

MWI signaling to the Lucent, Mitel, or Rolm switch requires a voice channel dedication to MWI. This channel is not available for general traffic.

# Matra

## Introduction

In this configuration, the Matra switch uses analog lines to exchange data with the CallPilot server.

**Notes:** This product has not been approved for deployment in Norway because it does not meet isolation requirements in EN6950 Safety of Information Technology Equipment.

The Matra switch is not supported by the IPE or rackmount platforms.

## Tower platform connectivity requirements

The integration to the Matra switch is an analog integration. The MPB16-2T card in the CallPilot tower platform is connected to Matra loop-start analog line cards. For a list of supported analog line cards, see page 47.

The MPB16-2T board provides both DSP resources and channel connectivity over loop-start analog lines to the Matra switch. The MPB16-2T connects to the PCI bus of the tower platform and provides 32 MPUs and 16 analog lines (channels).

## Channel requirement for MWI signaling

MWI signaling to the Matra switch requires a voice channel dedication to MWI. This channel is not available for general traffic.

# Customer LAN

## Introduction

CLAN connectivity is required for:

- Unified Messaging
- VPIM networking
- SNMP Network Managers
- remote administrative clients (unless connecting to the ELAN through a router)

## Hardware requirements

You must provide your own LAN hub and associated cables for the connection of the switch to the CallPilot server. The customer supplies the LAN hub and required cables.

## Supported LAN topologies

CallPilot supports the CLAN topologies as identified in the following table:

| <b>CallPilot platforms</b> | Ethernet: 10 Mbps | Ethernet: 100 Mbps | Token Ring: 4 Mbps | Token Ring: 16 Mbps |
|----------------------------|-------------------|--------------------|--------------------|---------------------|
| 200i                       | ✓                 | ✓                  | ✓                  | ✓                   |
| 201i                       | ✓                 | ✓                  |                    |                     |
| 702t                       | ✓                 | ✓                  | ✓                  | ✓                   |
| 1001rp                     | ✓                 | ✓                  | ✓                  | ✓                   |

## Supported network protocols

CallPilot supports only the Windows TCP/IP protocol stack (Windows TCP/IP networking) on client PCs. CallPilot does not support Novell's IPX/SPX or TCP/IP protocol stack on client PCs. However, CallPilot can coexist on networks running both IPX/ SPX and other protocols as long as Windows TCP/IP is used for CallPilot client-server communication.

## CLAN traffic considerations

You must ensure that the CLAN has the appropriate bandwidth capacity to handle the traffic between the client PCs and the CallPilot server. When calculating bandwidth capacity calculations, consider the following facts:

| Traffic type  | Bandwidth   |
|---|---|
| Desktop traffic from CallPilot to a desktop client or the web server      | One minute of voice consumes 200 kbytes.<br>One page of fax averages 55 kbytes.   |
| Web Messaging traffic from the web server to the browser on the client PC | One minute of voice in WAV format consumes 60 kbytes.<br>One minute of voice in VBK format takes 130 kbytes.<br>One page of fax averages 40 kbytes. |
| VPIM Networking traffic   | One minute of voice consumes 330 kbytes.  |

### Data transfer rates

The following table identifies, per user, the average data transfer rates in Kbps:

| Traffic type            | Voice Messaging | Fax Messaging | Both |
|-------------------------|-----------------|---------------|------|
| Desktop Messaging       | 0.09            | 0.06          | 0.15 |
| Web Messaging using WAV | 0.12            | 0.10          | 0.22 |
| Web Messaging using VBK | 0.15            | 0.10          | 0.26 |

**Notes:**

- Voice messaging rates assume that 60 percent of the voice messages are transferred across the customer data network, and the remaining 40% are retrieved by phone.
- Fax messaging rates assume that 80 percent of the fax messages are transferred across the network and that fax messaging users retrieve their fax messages with either a Desktop or Web Messaging client. The other 20 percent are retrieved via fax machine.
- The transfer rates for Web Messaging files include the message transfer from CallPilot to the web server, and subsequent transfer from the web server to the web browser.
- Web Messaging with VBK (CallPilot's proprietary encoding) requires that the Nortel Networks voice player be installed on the client PC.



# Chapter 3

---

## Learning about CallPilot features

### In this chapter

|                           |    |
|---------------------------|----|
| Overview                  | 72 |
| Application Builder       | 74 |
| Reporter                  | 76 |
| Desktop and Web Messaging | 77 |
| Networking                | 78 |
| Multimedia messaging      | 81 |

# Overview

## Introduction

This chapter lists and describes the features available with CallPilot. Key features such as Reporter, Desktop Messaging, Application Builder, and networking are explained. This chapter is helpful if you are unfamiliar with the features provided with the CallPilot software.

## What features are available with CallPilot?

CallPilot provides a number of features to manage and monitor messaging activity. Key features include

- Application Builder
- Reporter
- Desktop and Web Messaging
- Networking
- Multimedia Messaging

## Application Builder

Application Builder is a graphical software program that gives the administrator the ability to create multimedia applications with both voice and fax functionality that callers can access by dialing telephone numbers.

## Reporter

Reporter is a software program that gives the administrator the ability to produce and print summarized and detailed reports about the use and functionality of the CallPilot system. To produce these reports, operational measurement (OM) information is downloaded from the CallPilot server and stored in a local database on the administrative PC.

## Desktop and Web Messaging

Desktop and Web Messaging give mailbox users access to their CallPilot messages from their PC. Users can play back or record voice messages on the PC if it is equipped with a sound card and microphone, or users can choose to use the telephone. Users can view fax messages on the PC or print them to a fax machine.

## Networking

Four types of networking solutions are supported by CallPilot:

- AMIS-Analog
- VPIM
- Enterprise
- Network Message Service (NMS)

## Multimedia Messaging

CallPilot supports voice and fax messaging that provides mailbox users with

- call answering
- express messaging
- mailbox logon

CallPilot also supports speech-activated messaging.

# Application Builder

## Introduction

Application Builder is a graphical software program that gives the administrator the ability to create multimedia applications with both voice and fax functionality that callers can access by dialing telephone numbers.

## Different levels of Application Builder

CallPilot provides two levels of Application Builder—basic and Application Builder with fax option.

Basic Application Builder gives the administrator the ability to create applications with only voice functionality.

Both voice and fax functionality are available with Application Builder with fax option.

## How to purchase Application Builder

Basic Application Builder software is packaged with the CallPilot software and is installed as part of the CallPilot installation on the administrative PC.

The customer can optionally purchase Application Builder with fax option.

## Platform availability

Basic and Application Builder with fax option are supported on all CallPilot platforms.

## Channel requirements

Application Builder requires voice channels for voice-supported applications, such as voice menus and announcements.

If Application Builder with fax option is purchased, fax channels must be provisioned.

For more information on calculating the number of voice and fax channels required to support Application Builder, refer to Chapter 4, “Determining system size.”

## Limits within Application Builder

Certain limits exist within Application Builder to restrict the number of items in an application. The following table details these limits:

| <b>Item</b>   | <b>Limit</b> |
|---|--------------|
| Number of Application Builder services                          | 2500         |
| Levels of services imported into an Application Builder service | 20           |
| Number of faxes stored in an Application Builder service        | 3000         |
| Number of voice prompts in an Application Builder service       | 3000         |

You can install and run Application Builder on more than one administrative PC.

## See also

For more information on calculating storage space required on the server, refer to Chapter 4, “Determining system size.”

# Reporter

## Introduction

Reporter is a software program that gives the administrator the ability to produce and print summarized and detailed reports about the use and functionality of the CallPilot system. To produce these reports, operational measurement (OM) information is downloaded from the CallPilot server and stored in a local database on the administrative PC.

## How to purchase Reporter

Reporter is packaged with CallPilot software and is installed as part of the CallPilot installation on the administrative PC.

## Platform availability

Reporter is supported on all CallPilot platforms.

## Number of servers that Reporter can access

A single administrative PC can download OMs from a maximum of 50 servers. A separate database is created on the administrative PC for the data downloaded from each of the servers. The maximum size of each of these databases is 550 Mbytes.

Consider the amount of time spent downloading, amount of data downloaded, time to generate reports, and available disk space when determining the number of servers that a single administrative PC running Reporter can accommodate.

## See also

For more information on calculating storage space required on the server, refer to Chapter 4, “Determining system size.”

For more information on calculating disk space required on the administrative PC, refer to Chapter 6, “Engineering the clients.”

# Desktop and Web Messaging

## Introduction

Desktop and Web Messaging give mailbox users access to their CallPilot messages from their PC. Users can play back or record voice messages on the PC if it is equipped with a sound card and microphone, or users can choose to use the telephone. Users can view fax messages on the PC or print them to a fax machine.

## How to purchase Desktop and Web Messaging

The Desktop and Web Messaging features are optional with the purchase of CallPilot.

## Limitations on the number of PCs running the software

There is no limit to the number of PCs that can run the Desktop Messaging software. There is, however, a limit on the number of mailbox users who can access the Desktop server at one time—a maximum of 1000 concurrent users on a 200i or 201i server, and 5000 concurrent users on a 702t or 1001rp server.

## LAN requirements

Nortel Networks recommends that the Desktop or Web Messaging client be connected to the Customer LAN.

## Platform availability

Desktop and Web Messaging are supported on the Windows 95, Windows 98, Windows 2000, and Windows NT 4.0 platforms.

## See also

For more information on engineering the Desktop or Web Messaging client, refer to Chapter 6, “Engineering the clients.”

# Networking

## Introduction

Four types of networking solutions are supported by CallPilot:

- AMIS-Analog
- VPIM
- Enterprise
- Network Message Service (NMS)

## How to purchase networking

When you purchase networking, all networking solutions, except for NMS, are available on your site.

During installation of CallPilot, you can select which networking solutions you want to install.

## AMIS-Analog Networking

AMIS-Analog Networking allows users to exchange messages with users of any voice messaging systems that support the AMIS protocol. This protocol is an industry-standard protocol for exchanging voice messages.

You can use AMIS-Analog Networking to network with other CallPilot systems, existing Meridian Mail systems, Norstar, or other third-party AMIS-compliant systems.

## VPIM Networking

VPIM Networking provides CallPilot with the capability to exchange multimedia messages with a standard data communications network. Messages can contain voice, fax, or both.

You can use VPIM Networking to network with other CallPilot systems, existing Meridian Mail Net Gateway (MMNG) systems, Norstar, or other third-party VPIM-compliant systems.

## **Enterprise Networking**

Enterprise Networking is Nortel Network's proprietary analog networking protocol for voice messages.

You can use Enterprise Networking to network with other CallPilot systems or existing Meridian Mail systems that support Enterprise Networking.

## **Network Message Service**

For Meridian 1 switches, Network Message Service (NMS) permits one CallPilot messaging server to provide messaging services to users on more than one switch location. In this configuration, a single server connected to one switch can provide services to a number of switches interconnected with the appropriate trunks.

## **Platform availability**

Enterprise, AMIS, and VPIM networking are supported on all CallPilot platforms.

## **Channel requirements**

All analog networking solutions can use voice channels.

Networking solutions can also use multimedia and speech recognition channels if the resources are available.

## Limits within networking

Certain limits exist within networking to restrict the number of sites. The following table details these limits:

| <b>Item</b>                               | <b>Limit</b> |
|---|--------------|
| Number of private network sites           | 500          |
| Number of CDP steering codes per location | 500          |
| Number of open VPIM network sites         | 500          |
| Number of NMS satellite locations         | 59           |

### See also

Refer to the *Network Planning Guide* for detailed information on selecting the type of networking appropriate for your site.

# Multimedia messaging

## Introduction

CallPilot supports voice and fax messaging that provides mailbox users with

- call answering
- express messaging
- mailbox logon
- outcalling (such as Remote Notification and Delivery to Telephone)

CallPilot also supports speech-activated messaging.

## How to purchase multimedia messaging

A customer can optionally purchase the voice messaging, fax messaging, and speech-recognition features. These features are enabled by mailbox.

## Limits within multimedia messaging

Certain limits exist within multimedia messaging to restrict the multimedia features:

- 99 personal distribution lists (PDL), with 200 entries per PDL
- 150 shared distribution lists (SDL) with up to 999 entries per SDL
- speech recognition for mailbox logon and navigation
- maximum number of mailboxes:
  - IPE platform: 8000
  - tower and rackmount platforms: 20 000

## Platform availability

All CallPilot platforms support multimedia messaging.

## Channel requirements

If a mailbox has fax messaging capability, fax channels are required.

**Note:** Each call that is forwarded to the fax messaging capable mailbox is serviced by a fax channel (the equivalent of two voice channels), regardless of whether or not the caller intends to leave a fax.

If a mailbox has speech-activated messaging capability, speech-recognition channels are required.

# Chapter 4

---

## Determining system size

### In this chapter

|   |            |
|---|------------|
| Overview  | 85         |
| <b>Section A: About channel requirements</b>                | <b>87</b>  |
| An overview of channels                                     | 88         |
| Guidelines for determining channel requirements             | 90         |
| <b>Section B: Determining voice channel requirements</b>    | <b>93</b>  |
| Steps to follow in determining the number of voice channels | 94         |
| To help you determine voice channel requirements            | 96         |
| Determining the busy hour activity                          | 98         |
| Determining the activity of all voice services              | 99         |
| Determining network activity                                | 100        |
| Determining Outcalling activity                             | 101        |
| Determining the number of voice channels required           | 102        |
| <b>Section C: Determining fax channel requirements</b>      | <b>105</b> |
| An overview of fax channels                                 | 106        |
| Determining the number of fax channels                      | 107        |
| To help you determine fax channel requirements              | 109        |
| Determining the busy hour fax menu activity                 | 111        |
| Determining the busy hour traffic for fax callback activity | 113        |

---

|   |            |
|---|------------|
| Determining the busy hour traffic for fax auto attendant              | 114        |
| Determining the busy hour fax messaging activity                      | 116        |
| Calculating the number of fax channels required                       | 117        |
| Calculating the number of fax channels for fax broadcasting activity  | 118        |
| <b>Section D: Determining speech-recognition channel requirements</b> | <b>121</b> |
| Determining the number of speech-recognition channels required        | 122        |
| <b>Section E: Determining the number of MPUs required</b>             | <b>125</b> |
| Calculating the number of MPUs required                               | 126        |
| <b>Section F: Determining storage hour requirements</b>               | <b>129</b> |
| Steps to follow in estimating your storage hours                      | 130        |
| To help you determine storage hour requirements                       | 131        |
| Determining the mailbox storage requirements                          | 133        |
| Calculating storage hours for Application Builder                     | 136        |
| <b>Section G: Calculating system size</b>                             | <b>139</b> |
| Before you calculate your system size                                 | 140        |
| Calculating your system size  | 141        |

# Overview

## Introduction

To determine an appropriate CallPilot system size, follow these steps:

1. Estimate the channel requirements.
2. Estimate the MPU requirements.
3. Estimate the storage size requirements.
4. Determine the platform required.

All of the above are automated when planning the customer order. In addition, you can use the CallPilot Engineering spreadsheet (Microsoft Excel) to perform these calculations. To obtain the spreadsheet, contact your Nortel Networks distributor. If you are a Nortel Networks distributor, you can obtain the spreadsheet from the CallPilot area of the Nortel Networks NIC web site at <http://www.nortelnetworks.com/partnercenter/>.

If you choose to perform manual calculations, this chapter helps you estimate the number of MPUs and hours of storage your CallPilot system requires, based upon the estimated system usage.

## Channel requirements

To ensure that your CallPilot system has the necessary processing power required to handle the volume and type of incoming calls, you must determine the number and type of channels required. To determine this, do the following:

1. Determine the type of channels required.
2. Determine the number of channels required for each media.

## MPU requirements

After you have calculated the number of voice, fax, and speech-recognition channels, you can determine the number of MPUs required by your CallPilot system.

After performing this calculation, you must calculate the additional hardware necessary to support the number of MPUs.

## Storage hour requirements

The storage hours your CallPilot system requires depend on the requirements for

- message storage, which includes stored messages and personal verifications
- voice services, which include voice menus, announcements, and fax definitions (all available with Application Builder)

**Note:** The storage space required for voice prompts is part of the CallPilot package and, therefore, is not counted in the storage hours figures.

## System size requirement

After you calculate the number of MPC-8 cards required for voice processing, and the number of storage hours required for messages and Application Builder, you can determine which platform supports your needs. See page 141.

# Section A: About channel requirements

## In this section

|   |    |
|---|----|
| An overview of channels                         | 88 |
| Guidelines for determining channel requirements | 90 |

# An overview of channels

## Introduction

To ensure that your CallPilot system has the necessary processing power required to handle the volume and type of incoming calls, you need to determine the number and type of channels required, and the hardware to support them. To determine this, do the following:

1. Determine the type of channels required.
2. Determine the number of channels required for each media.

This section provides an overview of MPC-8 cards, MPUs, and the different types of channels available with CallPilot.

## For Meridian Mail users

If you are upgrading from Meridian Mail to CallPilot, you will be familiar with determining the number of ports required. With CallPilot, a port now has two components—a channel and one or more MPUs.

## Definition: channels

There are three different types of channels to handle the various types of media supported by CallPilot:

- voice
- fax
- speech-recognition (ASR)

As part of planning and engineering your system, you must estimate how many voice, fax, and speech-recognition channels you require. You can configure channels for voice only, fax and voice, or speech-recognition with fax and voice.

**Definition: MPUs**

An MPU is a measure of Digital Signal Processing (DSP) processing power. It supports a session or connection of different media types (for example, voice, fax, and speech-recognition).

A voice channel requires one MPU, a fax channel requires two MPUs, and a speech-recognition channel requires four MPUs.

**Definition: MPC-8**

A Multimedia Processing Card (MPC-8) is a credit-card sized PC card that resides in the CallPilot server. It receives data from calls that arrive from the switch and processes the data as required.

Each MPC-8 has eight MPUs.

**MPUs and channels**

The number of MPUs required to process a call depends upon the type of call.

For example, one MPU can transport one voice call to a voice channel. Multiple MPUs, however, are required to transport one fax or one speech-recognition call to a channel, as shown in the following table:

| <b>Media channel type</b> | <b>Description</b>  |
|---------------------------|---|
| Voice                     | There is a one-to-one correspondence between voice channels and MPUs. |
| Fax                       | Fax media requires two MPUs.  |
| Speech-recognition        | Speech-recognition media requires four MPUs.                          |

# Guidelines for determining channel requirements

## Introduction

To help you with the task of determining your system size, this chapter uses specific guidelines that you should be familiar with before starting any of the calculations.

## Busy hour

Channel requirements are determined by using standard traffic engineering principles. One of these principles is the calculation of busy hour (BH) traffic, that is, the highest traffic hour for CallPilot.

To calculate busy hour traffic, you add the total call seconds (connect time) and divide by 100. Busy hour traffic is calculated in BH CCS (busy hour centa [hundred] call seconds).

When calculating busy hour traffic, keep in mind that, for a typical business, the busy hour usually occurs between 10:00 a.m. and 11:00 a.m. or between 2:00 p.m. and 3:00 p.m on weekdays. For individual businesses, the busy hour period can vary. You should be aware of these factors to engineer a system that can truly handle your peak traffic requirements.

## Channel requirements for specific switches

The key differences between sizing non-Meridian 1 switches versus Meridian 1 are as follows:

- CallPilot systems that are connected to Lucent, Mitel, Rolm, and Matra switches must dedicate one of their voice channels to MWI signaling. This means that the voice channel sizing must be adjusted for the loss of the MWI channel.

- Mitel, Rolm, and Matra switches do not support queuing for callers to busy channels. Callers to busy channels either receive busy treatment or are overflowed to a live (if answered) answering position. That is, these calls are blocked from accessing CallPilot channel resources. This effectively reduces the call carrying capacity of the channels. Consequently, Nortel Networks recommends that you use the Erlang B/P02 traffic table to provide an adequate grade of service.
- If you are using a switch that supports queuing (Meridian 1, MSL-100, and Lucent), Nortel Networks recommends that you use an Erlang C P.05 traffic table.

### Traffic tables to use when estimating channel requirements

The following table summarizes which traffic table to use to estimate the required channels by media and switch type. For the actual tables, see Appendix A, “Traffic capacity tables.”

#### Busy hour CCS (BHCCS) traffic capacity table type

| Switch and media type                      | Erlang C P.05 BHCCS (40 second AHT) | Erlang C P.05 BHCCS (adjust for one MWI channel) | Erlang B P.02 BHCCS | Erlang B P.02 BHCCS (adjust for one MWI channel) |
|--|-------------------------------------|--|---------------------|--|
| Meridian 1 and MSL-100 Voice, Fax, and ASR | ✓                                   |  |                     |  |
| Lucent Voice                               |                                     | ✓  |                     |  |
| Lucent Fax and ASR                         | ✓                                   |  |                     |  |
| Mitel, Rolm, Matra Voice                   |                                     |  |                     | ✓  |
| Mitel, Rolm, and Matra Fax and ASR         |                                     |  | ✓                   |  |

**Note:** These traffic tables are accounted for when using the automated method of planning the customer order. They are also accounted for when using the engineering spreadsheet that is available on the Nortel Networks NIC web page at <http://www.nortelnetworks.com/partnercenter/>.

## Section B: Determining voice channel requirements

### In this section

|   |     |
|---|-----|
| Steps to follow in determining the number of voice channels | 94  |
| To help you determine voice channel requirements            | 96  |
| Determining the busy hour activity                          | 98  |
| Determining the activity of all voice services              | 99  |
| Determining network activity                                | 100 |
| Determining Outcalling activity                             | 101 |
| Determining the number of voice channels required           | 102 |

# Steps to follow in determining the number of voice channels

## Introduction

There are four steps in calculating the number of voice channels for your system:

1. Determine the busy hour activity.
2. Determine the busy hour activity of all Application Builder services.
3. Determine the networking activity.
4. Estimate the outcalling activity.

This section provides an overview of these steps.

## Determine the busy hour

Your first step is to determine the busy hour messaging activity or connect time. This is the anticipated activity of CallPilot during the busy hour. For instructions on performing this task, see “Determining the busy hour activity” on page 98.

## Determine the busy hour activity of all CallPilot services

Your second step is to determine the busy hour activity of all services that use voice channels. This includes Application Builder services such as voice menus and automated attendant. For instructions on performing this task, see “Determining the activity of all voice services” on page 99.

## **Determine the networking activity**

Networking activity using voice channels might need to be calculated if networking is purchased. For instructions on performing this task, see “Determining network activity” on page 100.

If VPIM is the only networking solution installed, you do not need to determine the networking activity.

## **Estimate the Outcalling activity**

If Outcalling has been purchased, you must calculate the number of voice channels required for this service. For instructions on performing this task, see “Determining Outcalling activity” on page 101.

## **Determine the total number of channels**

Add the figures from the above four steps to obtain a total of the number of voice channels required.

# To help you determine voice channel requirements

## Introduction

A worksheet is provided to help you calculate the busy hour activity and the number of voice channels required.

## Worksheet

Complete the following worksheet to determine the number of voice channels your CallPilot system requires. The procedures on the following pages should help you complete the worksheet.

| <b>Busy hour system activity and channels required</b> |  | <b>Voice activity<br/>(Call-seconds)</b>                          |
|--|--|---|
| <b>1</b>   | <b>Voice Messaging activity</b>  | <b>1</b> <input style="width: 100px; height: 25px;" type="text"/> |
| <b>2</b>   | <b>Activity of all services (add 2a through 2d)</b>  | <b>2</b> <input style="width: 100px; height: 25px;" type="text"/> |
|  | 2a Voice Menu activity _____   |   |
|  | 2b Announcements activity _____  |   |
|  | 2c Auto attendant activity (if used during busy hour) _____  |   |
|  | 2d Fax on Demand callback menu _____   |   |
| <b>3</b>   | <b>Analog networking activity (if installed)</b>   | <b>3</b> <input style="width: 100px; height: 25px;" type="text"/> |
| <b>4</b>   | <b>Outcalling activity (if in use)</b>   | <b>4</b> <input style="width: 100px; height: 25px;" type="text"/> |
| <b>5</b>   | <b>Add lines 1 through 4.</b>  | <b>5</b> <input style="width: 100px; height: 25px;" type="text"/> |
| <b>6</b>   | <b>Divide line 5 by 100 to determine the total busy hour activity in CCS.</b>  | <b>6</b> <input style="width: 100px; height: 25px;" type="text"/> |
| <b>7</b>   | <b>Number of channels required.<br/>Look up the CCS recorded in line 6 in Appendix A, "Traffic capacity tables," to determine the number of voice channels required.</b> | <b>7</b> <input style="width: 100px; height: 25px;" type="text"/> |

# Determining the busy hour activity

## Introduction

Follow this procedure to determine the busy hour voice messaging activity. Record the result in box 1 on the worksheet.

## To determine the busy hour messaging activity

- 1 Estimate the average connection time per registered user during the busy hour.

This includes both the time the mailbox user is logged on to CallPilot and the time callers use to leave messages for that user.

The normal range is 30 to 60 seconds per user. A reasonable assumption is 40 seconds per user.

- 2 Determine the number of voice messaging users.
- 3 Multiply the result of step 1 by the result of step 2.
- 4 Record the result in box 1 of the worksheet.

## Example

If the average connection time is 40 seconds and you have 1000 CallPilot users at your site, the total seconds of voice messaging activity is 40 000.

# Determining the activity of all voice services

## Introduction

Services that use voice channels include Application Builder, Voice Menus, Voice Call Answering, and Voice Messaging. It is important to analyze your specific services since many services vary widely in the number of calls requiring processing and in the holding times of those calls.

## To calculate the busy hour activity

- 1 Estimate the average length of a call during the busy hour.  
The type of service determines the average length. For an information-type menu, a reasonable assumption is 60 seconds per call. An automated attendant has a much smaller average call length in the range of 15–30 seconds.
- 2 Estimate the number of calls during the busy hour.
- 3 Multiply the result of step 1 by the result of step 2.  
The result is the estimated busy hour activity for that particular service.
- 4 Record the total.
- 5 Repeat steps 1 through 4 for each service (that is, voice menus and announcements).
- 6 Record the result in the appropriate step 2 box of the worksheet.
- 7 Repeat steps 1 through 6 for each service.

# Determining network activity

## Introduction

AMIS and Enterprise Networking use voice channels to send and receive messages. To calculate the networking activity, follow the procedure in this section. A typical assumption is that networking traffic increases overall voice messaging traffic by five percent. For more information on planning for networking, see the *Network Planning Guide*.

## To determine the networking activity

- 1 Multiply the result in box 1 of the worksheet by 0.05.
- 2 Record the result in box 3 of the worksheet.

# Determining Outcalling activity

## Introduction

Outcalling (which collectively refers to the Remote Notification, Delivery to Fax, and Delivery to Telephone services) can be used in different ways by different organizations, so channel requirements vary from one organization to the next. You must consider how your site will use Outcalling, especially during the busy hour.

## Determining how your site will use Outcalling

Voice channel requirements for Outcalling can be limited or unlimited depending on how this service is used at your site. The following table provides several scenarios for using Outcalling:

| <b>IF</b>  | <b>THEN</b>  |
|--|--|
| only a small number of users will be using Delivery to Telephone, Remote Notification, or both         | the effect of these services on your overall system requirements will be small and can be ignored at this point.                             |
| the Delivery to Telephone service will be restricted to low-traffic periods (for example, after-hours) | the service should have no impact on your system requirements.   |
| a large number of users will be accessing Delivery to Telephone, Remote Notification, or both          | estimate what the usage will be in CCS and record it in box 4 of the worksheet. Use the same voice message holding time as you used earlier. |

# Determining the number of voice channels required

## Introduction

After estimating the busy hour activity for the voice services supported by CallPilot, you can calculate the total number of voice channels required. Follow the procedures in this section to determine the number of voice channels required.

## Assumptions for determining voice messaging use

While usage patterns differ from customer to customer, you can make assumptions about typical use of the system. The following assumptions allow typical business traffic estimation for a given user population:

- 25% of the time is at busy hour traffic (approximately 2 hours).
- 5% of the time is at greater than busy hour traffic (approximately 25 minutes).
- 70% of the time is at less than 75% of busy hour traffic (approximately 5 hours and 35 minutes).
- The average call-holding time is 40 seconds for voice messaging.
- Typically, a maximum of 20% of logon calls use messaging features.
- The busy hour traffic is 13% of the average daily traffic. The amount of traffic generated in one 24-hour period is equivalent to 7.69 hours of busy hour traffic.

**To determine the number of voice channels required**

- 1** Add the totals from the previous procedures and record the result in box 5 of the worksheet.
- 2** Divide the result in box 5 by 100 to get the estimated busy hour voice activity in centa (hundred) call seconds (CCS). Record the result in box 6.
- 3** Refer to the traffic capacity table provided in Appendix A, "Traffic capacity tables," to determine the number of channels required.

From the table, find the CCS calculated in step 2. The corresponding value in the column labeled "Number of channels" is the number of channels required to accommodate the estimated total system activity. Record the result in box 7.



# Section C: Determining fax channel requirements

## In this section

|  |     |
|--|-----|
| An overview of fax channels  | 106 |
| Determining the number of fax channels                               | 107 |
| To help you determine fax channel requirements                       | 109 |
| Determining the busy hour fax menu activity                          | 111 |
| Determining the busy hour traffic for fax callback activity          | 113 |
| Determining the busy hour traffic for fax auto attendant             | 114 |
| Determining the busy hour fax messaging activity                     | 116 |
| Calculating the number of fax channels required                      | 117 |
| Calculating the number of fax channels for fax broadcasting activity | 118 |

# An overview of fax channels

## Introduction

The number of fax channels your site requires depends on how you plan to offer multimedia services. The options available are same call delivery and callback delivery.

## Same call delivery

With same call delivery, a caller who has accessed a voice menu with fax items can select and receive a fax during the same call (that is, using the same line). For this type of voice menu service, the voice menu must run on a fax channel. Only a fax channel can provide both the voice and fax services required for a voice menu with same call fax delivery.

Similarly, fax announcements that use same call delivery (a caller reaches the announcement service, hears a greeting, and receives a fax in the same call) must use a fax channel.

To calculate traffic requirements for voice menus with fax items (same call delivery), refer to “Determining the busy hour traffic for fax callback activity” on page 113. To calculate the traffic requirements for a fax announcement service with same call delivery, refer to “Determining the busy hour traffic for fax auto attendant” on page 114.

## Callback delivery

With callback delivery, the caller who has accessed a voice menu with fax items must provide a fax number for the fax delivery. After the caller completes the call, CallPilot uses a fax channel to deliver or send the selected fax items to the specified fax number.

# Determining the number of fax channels

## Introduction

There are four steps in calculating the number of fax channels for your system:

1. Determine the busy hour for voice menus with fax items.
2. Determine the busy hour for fax callback.
3. Determine the connect time for fax announcements.
4. Determine the busy hour for fax messaging activity.

If fax broadcasting is used at a customer site, you must also estimate the number of channels required to support this service.

This section provides an overview of these steps.

## Determine the busy hour for voice menus that offer fax menu items

Your first step is to determine the busy hour activity or connect time for voice menus that offer faxes as one or more menu items. For instructions on performing this task, see page 111.

## Determine the busy hour activity for fax callback deliveries

Your second step is to determine the busy hour activity for fax delivery to a fax number specified by a caller. For instructions on performing this task, see page 113.

## Determine the connect time for fax announcements

Fax announcements that deliver the fax during the same call require a fax channel. Calculate the total busy hour connect time for this type of announcement. For instructions on performing this task, see page 114.

## **Determine the busy hour for fax messaging**

Mailbox users who are configured for fax messaging require a fax channel to receive, print, or send faxes. Calculate the busy hour activity for fax messaging by following the procedure on page 116.

## **Determine the total number of channels**

Add the figures from the above four steps to obtain a total of the number of fax channels.

If Fax Broadcasting is used, you must take into consideration the number of channels required to support this service.

# To help you determine fax channel requirements

## Introduction

A worksheet is provided to help you calculate the busy hour activity and the number of fax channels required.

## Worksheet

Complete the following worksheet to determine the number of fax channels your CallPilot system requires. The procedures on the following pages should help you complete the worksheet.

| <b>Fax busy hour system activity and channels required</b> |  | <b>Activity<br/>(Call-seconds)</b>                                |
|--|--|---|
| <b>1</b>   | <b>Voice menus with fax items (same call delivery)</b>   | <b>1</b> <input style="width: 100px; height: 20px;" type="text"/> |
| <b>2</b>   | <b>Fax callback activity</b>   | <b>2</b> <input style="width: 100px; height: 20px;" type="text"/> |
| <b>3</b>   | <b>Fax announcement activity (same call delivery)</b>  | <b>3</b> <input style="width: 100px; height: 20px;" type="text"/> |
| <b>4</b>   | <b>Fax messaging activity</b>  | <b>4</b> <input style="width: 100px; height: 20px;" type="text"/> |
| <b>5</b>   | <b>Add lines 1 through 4.</b>  | <b>5</b> <input style="width: 100px; height: 20px;" type="text"/> |
| <b>6</b>   | <b>Divide line 5 by 100 to determine the total activity in CCS.</b>  | <b>6</b> <input style="width: 100px; height: 20px;" type="text"/> |
| <b>7</b>   | <b>Number of fax channels required.<br/>Look up the CCS recorded in line 6 in Appendix A, "Traffic capacity tables," to determine the number of fax channels required.</b> | <b>7</b> <input style="width: 100px; height: 60px;" type="text"/> |
| <b>8</b>   | <b>Number of channels dedicated to Multicast to Fax</b>  | <b>8</b> <input style="width: 100px; height: 20px;" type="text"/> |

# Determining the busy hour fax menu activity

## Introduction

With the Fax on Demand feature, you can set up voice menus that offer faxes as some of the menu items. A caller who reaches a fax voice menu can select faxes to receive. If the caller is calling from a phone line that is also connected to a fax machine, the fax can be delivered during the same call (same call delivery).

Follow this procedure to estimate the call connect time for fax voice menus during the busy hour. Record the result in box 1 on the worksheet.

## To determine the call connect time

- 1 Select a fax voice menu and estimate the average duration of calls during the busy hour.

When estimating this duration, include the following:

- time to listen to the menu greeting
  - time to listen to the voice menu and select as many faxes as required
  - time to receive “same call” faxing instructions
  - time to transmit the faxes selected
    - about 12 seconds to establish protocol
    - 40 seconds per page in normal resolution; 80 seconds per page in fine resolution
    - about 10 seconds to complete the fax delivery (that is, end protocol/disconnect)
- 2 Estimate the number of calls to this menu during the busy hour. This depends on the specific function of the fax voice menu in your organization.
  - 3 Multiply the result of step 1 by the result of step 2 to determine the estimated total activity generated from this fax voice menu during the busy hour.

- 4 Record the total.
- 5 Repeat steps 1 through 4 for each fax voice menu.
- 6 Add all the voice menu totals together and record the result in box 1 of the worksheet.

# Determining the busy hour traffic for fax callback activity

## Introduction

A voice menu with fax items might require the caller to specify a fax number to receive the selected faxes. With this type of voice menu, CallPilot uses a fax channel to call the specified fax number and deliver the selected faxes.

The voice menu and fax selection part of the process can use a voice channel or fax channel. Only the actual fax delivery call requires a fax channel.

## To estimate the total busy hour connect time for fax callback deliveries

- 1 Estimate the average duration of fax callback delivery calls during the busy hour. When estimating this duration, include the following:
  - 10 seconds to set up the call
  - 14 seconds to answer the call
  - 12 seconds to establish the protocol
  - 40 seconds per page in normal resolution; 80 seconds per page in fine resolution
  - 10 seconds to complete the fax delivery (that is, end protocol/disconnect)
- 2 Estimate the number of fax callback deliveries during the busy hour.
- 3 Multiply the result of step 1 by the result of step 2 to determine the estimated total connect time used by fax callback deliveries in the busy hour.
- 4 Record the result in box 2 on the worksheet.

# Determining the busy hour traffic for fax auto attendant

## Introduction

A fax announcement service that requires the caller to enter a fax callback number requires a fax channel only for the callback delivery. For these types of announcements, refer to “Determining the number of voice channels required” on page 102. To estimate the traffic generated by the actual fax delivery, see the section “Determining the busy hour traffic for fax callback activity” on page 113.

A fax announcement service that delivers the fax during the same call (no callback number is required) must use a fax channel for the entire call. Follow the procedure in this section to estimate the connect time for these types of announcements.

## To estimate the connect time for fax announcements with same call delivery

- 1 Select a fax announcement and estimate the average duration of calls to this fax announcement during the busy hour.

When estimating this duration, include the following:

- time to listen to prompts and instructions and to enter the number
  - time to transmit the fax
    - about 12 seconds to establish protocol
    - 40 seconds per page in normal resolution; 80 seconds per page in fine resolution
    - about 10 seconds to complete the fax delivery (that is, end protocol/disconnect)
- 2 Estimate the number of calls to the announcement during the busy hour. This depends on the specific function of this fax announcement in your organization.

- 3** Multiply the result of step 1 by the result of step 2 to determine the estimated total activity generated during the busy hour.
- 4** As the fax must be delivered as well, estimate delivery time by including the time to transmit the fax and multiplying by step 2.
- 5** Add the step 3 and step 4 totals together and record the result in box 3 of the worksheet.

# Determining the busy hour fax messaging activity

## Introduction

Mailbox users who are configured for fax messaging require a fax channel to receive, print, or send faxes. A fax channel is not required to access a mailbox to listen to voice messages or to listen to the print status of a fax message.

Fax messaging users who are also Desktop Messaging users can view and print faxes using their desktop as opposed to using CallPilot to print their fax messages.

## To estimate the busy hour fax messaging activity

- 1 Estimate the average duration of calls to receive an incoming fax message. A typical estimate for a three-page fax in normal resolution is 142 seconds. For the same fax in fine resolution, a typical estimate is 262 seconds.
- 2 Estimate the number of fax messaging users who will receive fax messages during the busy hour. This depends upon whether you anticipate the fax users at the site to be heavy users of fax messaging.
- 3 Estimate the number of fax messaging users who print fax messages during the busy hour. If you use the auto print feature at the site, this value will be approximately the same as the number received.
- 4 Multiply the result of step 1 by step 2.
- 5 Multiply the result of step 1 by step 3.
- 6 Add step 4 and step 5 and record the result in box 4 of the worksheet.

# Calculating the number of fax channels required

## Introduction

After estimating the busy hour activity for the fax services supported by CallPilot, you can calculate the total number of fax channels required.

## Assumptions for determining fax messaging use

While usage patterns differ from customer to customer, you can make assumptions about typical use of the system. The following assumptions allow typical business traffic estimation for a given user population:

- The average fax message received is three pages and is received in normal resolution.
- The holding time for an average fax message is 142 seconds per call.

## To calculate the number of fax channels required

- 1 Add the totals from the previous procedures and record the result in box 5.
- 2 Divide the result in box 5 by 100 to get the estimated busy hour fax activity in centa (hundred) call seconds (CCS), and record the result in box 6 of the worksheet.
- 3 Determine the number of fax channels required based on the estimated busy hour fax activity.

Refer to the traffic capacity table provided in Appendix A, "Traffic capacity tables," to determine the number of channels required.

- 4 Record the result in box 7 of the worksheet.

# Calculating the number of fax channels for fax broadcasting activity

## Introduction

Fax broadcasting is an industry standard term used to describe sending a fax to many destinations. CallPilot has a service called Multicast to Fax that supports fax broadcasting activities. It is distinguished from Delivery to Fax (DTF) service to prevent using DTF channels when a fax broadcast is sent. If a CallPilot system is also using Fax on Demand (FOD), fax call answering, and fax buffering mailbox type service, it is important that broadcasting does not degrade the quality of service from those services.

If Multicast to Fax is not used at a customer site, there is no need to perform the calculations below.

If Multicast to Fax will be used, Nortel Networks strongly recommends that you use the service during off-peak hours or establish a maximum number of channels for this service in the SDN table (if there are other fax services competing for fax channels). The following procedure shows you how to calculate the maximum number of fax channels.

## To calculate the number of fax channels

- 1 Estimate the average duration of a delivery to a single recipient. Each call takes
  - 10 seconds to set up the call
  - 14 seconds to answer the call
  - 12 seconds to establish the protocol
  - 40 seconds per page (normal resolution) or 80 seconds per page (fine resolution)
  - 10 seconds to complete the delivery

- 2 Estimate the average number of recipients in a fax broadcast.
- 3 Multiply the result of step 1 by step 2 and then divide by 100 to get the average CCS required by a broadcast.
- 4 Estimate the number of fax broadcasts in a day.
- 5 Multiply the result of step 3 by step 4 to get the total number of CCS required to deliver broadcast messages per day.
- 6 Experiment with the following calculation to determine the delivery time window you want to achieve with the maximum number of fax channels available for Multicast to Fax service. Record the result in box 8 of the fax worksheet.  
$$\text{(Total CCS of delivery) / (number of channels dedicated * 36) * 60 minutes}$$
$$= \text{delivery time in minutes}$$

## Example

If you calculated a CCS of 63, the amount of time to send the message to 50 recipients is as follows:

1 channel provides 36 CCS per hour  $(63/36) * 60 = 105$  minutes to deliver

2 channels provide 72 CCS per hour  $(63/72) * 60 = 53$  minutes to deliver

4 channels provide 144 CCS per hour  $(63/144) * 60 = 26$  minutes to deliver



## **Section D: Determining speech-recognition channel requirements**

### **In this section**

Determining the number of speech-recognition channels required 122

# Determining the number of speech-recognition channels required

## Introduction

The number of speech-recognition channels you require depends upon the number of users who use the speech activated messaging service. As this service is provided to enable mailbox access for those who work outside the office, busy hour for those channels might be outside normal office hours, particularly if the user accesses the messages while commuting.

To determine the number of speech-recognition channels required, calculate the average amount of time it takes to log on to a mailbox and play back messages using speech-recognition services.

## Assumptions for determining speech-recognition messaging use

While usage patterns differ from customer to customer, you can make assumptions about typical use of the system. The following assumption allows typical business traffic estimation for a given user population:

- The average call time is 100 seconds for land line calls. This includes only the time that users call in to retrieve their messages. It does not include call answering times.

## Worksheet

Complete the following worksheet to determine the number of speech-recognition channels your CallPilot system requires. The procedures below should help you to complete the worksheet.

| <b>Speech recognition busy hour<br/>system activity and channels required</b> |  | <b>Activity<br/>(Call-seconds)</b>                                |
|---|--|---|
| <b>1</b>  | <b>Messaging activity</b>  | <b>1</b> <input style="width: 100px; height: 20px;" type="text"/> |
| <b>2</b>  | <b>Divide line 1 by 100 to determine the total activity in CCS.</b>  | <b>2</b> <input style="width: 100px; height: 20px;" type="text"/> |
| <b>3</b>  | <b>Number of speech recognition channels required.<br/>Look up the CCS recorded in line 2 in Appendix A, "Traffic capacity tables," to determine the number of speech recognition channels required.</b> | <b>3</b> <input style="width: 100px; height: 60px;" type="text"/> |

## To determine the number of speech-recognition channels

- 1** Estimate the average connection time per registered user during the busy hour.  
  
This includes both the time the mailbox user is logged on to CallPilot and the time used to play back messages. The normal range is 75 to 120 seconds per user. A reasonable assumption is 100 seconds per user.
- 2** Determine the number of speech-recognition users.
- 3** Multiply the result of step 1 by the result of step 2 and record the results in box 1 of the worksheet.
- 4** To calculate the CCS, divide the result of step 3 by 100 and record the result in box 2.
- 5** Refer to the traffic capacity table provided in Appendix A, "Traffic capacity tables," to determine the number of channels required.  
  
From the table, find the CCS listed in box 2 of the worksheet. The corresponding value in the column labeled "Number of channels" is the number of channels required to accommodate the estimated total system activity.
- 6** Record the result in box 3 of the worksheet.



# Section E: Determining the number of MPUs required

## In this section

Calculating the number of MPUs required

126

# Calculating the number of MPUs required

## Introduction

After you have calculated the number of voice, fax, and speech-recognition channels, you can determine the number of MPUs required by your CallPilot system.

After performing this calculation, you must calculate the additional hardware necessary to support the number of MPUs.

## Worksheet

Complete the following worksheet to calculate the number of MPUs your CallPilot system requires.

| <b>MPUs required for voice, fax, and speech recognition services</b> |   |          |                      |
|--|---|----------|----------------------|
| <b>1</b>   | <b>Number of channels required for voice services</b>                     | <b>1</b> | <input type="text"/> |
| <b>2</b>   | <b>Number of channels required for fax services multiplied by 2</b>       | <b>2</b> | <input type="text"/> |
| <b>3</b>   | <b>Number of channels required for speech recognition multiplied by 4</b> | <b>3</b> | <input type="text"/> |
| <b>4</b>   | <b>Add lines 1 through 3.</b>   | <b>4</b> | <input type="text"/> |

## To determine the number of MPUs required

- 1 Copy the figure from box 6b on the voice channel worksheet into box 1 on the above worksheet.
- 2 Multiply the figure from box 8 on the fax channel worksheet by 2. Record the result in box 2 on the above worksheet.

**Note:** Since every fax channel requires 2 MPUs, you must multiply the number of channels by 2 to get the number of MPUs.

- 3 Multiply the figure from box 3 on the speech-recognition worksheet by 4. Record the result in box 3.

**Note:** Since every speech-recognition channel requires 4 MPUs, you must multiply the number of channels by 4 to get the number of MPUs.

- 4 Add boxes 1 through 3 together. Record the result in box 4.

This figure is the number of MPUs required.

## Example

If you have calculated that your platform requires 8 voice channels, 4 fax channels, and 2 speech-recognition channels, you require the following number of MPUs:

| <b>Number of channels</b> | <b>Number of MPUs<br/>(steps 1 through 3 of the above procedure)</b> |
|---------------------------|--|
| 8 voice                   | 8 MPUs   |
| 4 fax                     | $4 \times 2 = 8$ MPUs  |
| 2 speech-recognition      | $2 \times 4 = 8$ MPUs  |

Add together the total number of MPUs ( $8 + 8 + 8 = 24$  MPUs).

## To determine the hardware required

DSPs and channel connectivity are provided as follows:

- IPE platform: one embedded DSP providing 8 MPUs, and two MPC-8 cards providing 16 MPUs (for a maximum of 24 MPUs)
- tower and rackmount platforms: on MPB-16 boards

The boards provide capacity as follows:

- Each MPB16-4 board contains two embedded DSPs (providing 16 MPUs) and comes packaged with four MPC-8 cards (each providing 8 MPUs) for a maximum of 48 MPUs.
- Each MPB16-2T contains capacity for 32 MPUs.

| IF you are using   | AND you need      | THEN   |
|--|-------------------|--|
| the IPE (200i and 201i) platform   |                   | a maximum of 24 MPUs are supported (and provided with the base package). |
| the rackmount platform with analog connectivity (for example, with a Matra switch) | more than 32 MPUs | you need two MPB16-2T boards.  |
| a tower or rackmount platform with digital connectivity                            | more than 48 MPUs | you need two MPB16-4 boards.   |

**Notes:** You can insert a maximum of two MPB16-2T or MPB16-4 boards into the tower and rackmount platforms.

The IPE (201i) platform has 4 MPC card sockets, but only two are supported with this version of CallPilot.

# Section F: Determining storage hour requirements

## In this section

|   |     |
|---|-----|
| Steps to follow in estimating your storage hours  | 130 |
| To help you determine storage hour requirements   | 131 |
| Determining the mailbox storage requirements      | 133 |
| Calculating storage hours for Application Builder | 136 |

# Steps to follow in estimating your storage hours

## Introduction

The storage hours your CallPilot system requires depend on the requirements for

- message storage, which includes stored messages and personal verifications
- voice services, which include voice menus, announcements, and fax definitions (all available with Application Builder)

## Determining your message storage requirements

Your first step is to determine the total message storage time required for the mailbox users at your site. Total message storage time depends on

- the number of mailbox users
- average storage per user (for messages and personal verifications)

To determine this value, follow the procedures in “Determining the mailbox storage requirements” on page 133.

## Determining the Application Builder storage requirements

The number of storage hours required by Application Builder applications depends upon the number of prompts and the number of fax pages in an application.

To determine this value, follow the procedures in “Calculating storage hours for Application Builder” on page 136.

# To help you determine storage hour requirements

## Introduction

A worksheet is provided to help you calculate the number of storage hours required by your CallPilot system.

## Worksheet

Complete the following worksheet to determine the number of hours of storage your CallPilot system requires. The procedures on the following pages should help you complete the worksheet.

| <b>Storage hours required</b> |  | <b>Hours of storage</b>  |
|-------------------------------|--|--|
| <b>1</b>                      | <b>Message storage time</b>                                    | <b>1</b> <input style="width: 100px; height: 20px;" type="text"/>  |
| <b>2</b>                      | <b>Personal verification storage time</b>                      | <b>2</b> <input style="width: 100px; height: 20px;" type="text"/>  |
| <b>3</b>                      | <b>Greeting storage time</b>                                   | <b>3</b> <input style="width: 100px; height: 20px;" type="text"/>  |
| <b>4</b>                      | <b>Recorded PDL titles storage time</b>                        | <b>4</b> <input style="width: 100px; height: 20px;" type="text"/>  |
| <b>5</b>                      | <b>Fax storage time</b>  | <b>5</b> <input style="width: 100px; height: 20px;" type="text"/>  |
| <b>6</b>                      | <b>Add lines 1 through 5.</b>                                  | <b>6</b> <input style="width: 100px; height: 20px;" type="text"/>  |
| <b>7</b>                      | Storage hours for prompts                                      | <b>7</b> _____   |
| <b>8</b>                      | Storage for fax pages  | <b>8</b> _____   |
| <b>9</b>                      | Add lines 7 and 8.   | <b>9</b> _____   |
| <b>10</b>                     | <b>Add lines 6 and 9 to determine the total storage hours.</b> | <b>10</b> <input style="width: 100px; height: 20px;" type="text"/> |

# Determining the mailbox storage requirements

## Introduction

The number of hours required for storage of messages and personal verifications is determined from the number of mailbox users and how many minutes of storage each user requires.

For those mailboxes that support fax messaging, additional storage should be provided depending on the number of pages of fax that each user requires.

## To determine the voice message storage time

- 1 Estimate the total number of mailbox users.
- 2 Estimate the average number of minutes of storage each user requires. The minimum storage time that is allowed per user is 1 minute. If each user uses an average of 10 minutes of storage time and the average message length is 30 seconds, then approximately 20 messages can be stored per user.
- 3 Multiply the result of step 1 by the result of step 2.
- 4 Multiply the result of step 3 by 1.2 (to add a 20% safety margin).
- 5 Divide by 60 to convert the storage time to hours.
- 6 Record the result in box 1 of the worksheet.

## To determine personal verification storage time

- 1 Assume approximately 3.5 seconds per personal verification.
- 2 Multiply the result of step 1 by the estimated number of mailbox users.
- 3 Divide the result of step 2 by 60 to convert the storage time to hours. Therefore, if there are 1000 mailbox users, required storage time is  $1000 \times 3.5 = 3500$  seconds or approximately 1.0 hour.
- 4 Record the result in box 2 of the worksheet.

## To determine the personal greeting storage hours

- 1 Assume 3 greetings (internal, external, and temporary), each approximately 10 seconds long, for a total of 30 seconds per user.
- 2 Multiply the result of step 1 by the estimated number of mailbox users.
- 3 Divide the result of step 2 by 60 to convert the storage time to hours. For example, if there are 1000 mailbox users, required storage time is  $1000 \times 30 = 30\,000$  seconds or approximately 8.3 hours.
- 4 Record the result in box 3 of the worksheet.

## To determine the PDL title storage hours

- 1 Estimate approximately 3.5 seconds per recorded PDL title. Although a user can create up to 99 PDL titles, a typical user has only a few. Estimate approximately 2 recorded PDL titles per user for a total of 7 seconds per user.
- 2 Multiply the result of step 1 by the estimated number of mailbox users.
- 3 Divide the result by 60 to convert the storage time to hours. For example, if there are 1000 mailbox users, required storage time is  $1000 \times 7.0 = 7000$  seconds or approximately 2.0 hours.
- 4 Record the result in box 4 of the worksheet.

## To determine the fax messaging storage time

- 1 Estimate the total number of fax messaging users.
- 2 Estimate the number of fax pages each user requires. For example, if the average message size is 3 pages, and if users have up to 10 fax messages, 30 fax pages are required per user.
- 3 Multiply the result of step 2 by 0.3 to convert fax pages to the equivalent minutes of storage. If you are accepting fine resolution messages at your site, use 0.6 as the conversion factor.
- 4 Multiply the result of step 1 by step 3 to get the total number of minutes of storage required.
- 5 Divide by 60 to convert to hours of storage.
- 6 Record the result in box 5 of the worksheet.

**To calculate the total hours of storage required for mailboxes**

Add the storage times from the above three procedures and record the result in box 6 of the worksheet.

# Calculating storage hours for Application Builder

## Introduction

Application Builder applications can contain both voice and fax media and are stored in the same volume as users' mailboxes.

Since there is no limit on the amount of data that can be in an application, you should estimate the number of application prompts and the number of fax pages.

## To estimate the number of prompts

- 1 Estimate the average number of prompts you plan to have in an application.
- 2 Multiply the result by the number of applications you estimate you will have on your CallPilot system.
- 3 Record the result on line 7 of the worksheet.

## To determine the fax storage hours

- 1 Estimate the total number of normal resolution fax pages you plan to have in an application.
- 2 Multiply the result of step 1 by 0.3 to get the total number of minutes of storage required.
- 3 Estimate the total number of fine resolution fax pages you plan to have in an application.
- 4 Multiply the result of step 3 by 0.6 to get the total number of minutes of storage required.
- 5 Add the totals from steps 2 and 4 to get the total fax storage requirements in minutes.
- 6 Multiply the totals by the number of applications you estimate you will have on your CallPilot system.
- 7 Divide the storage time by 60 to convert to hours of storage.

- 8 Record the result on line 8 of the worksheet.

### **To calculate the total hours of storage required for Application Builder**

Add the storage hours calculated above to obtain the total storage hours for Application Builder applications. Record the result in line 9 of the worksheet.



## Section G: Calculating system size

### **In this section**

|                                       |     |
|---------------------------------------|-----|
| Before you calculate your system size | 140 |
| Calculating your system size          | 141 |

# Before you calculate your system size

## Introduction

Before you calculate the required system size, familiarize yourself with the following disk space guidelines.

## Disk volume VS1

All systems have a disk volume VS1 (Volume Server 1). This volume is used for personal verifications, messages, and Application Builder voice and fax media.

If the hours of storage available on VS1 are enough to satisfy the expected requirements, then the above-mentioned data can be stored on VS1.

## User volumes

If all of the personal verifications, messages, and Application Builder voice and fax media cannot fit on VS1, then any additional messages and Application Builder data can be stored on hard drives VS102 and VS103.

# Calculating your system size

## Introduction

At this point, you should have calculated

- the number of channels required for voice processing
- the number of storage hours required for messages and Application Builder

**Note:** The storage space required for voice prompts is part of the CallPilot package and, therefore, is not counted in the storage hours figures.

## To calculate the system size

Refer to the following table to determine the size of system you require:

| <b>Server platform</b> | <b>Number of disks</b> | <b>Number of storage hours</b> | <b>Maximum number of channels</b> |
|------------------------|------------------------|--------------------------------|-----------------------------------|
| 200i (IPE)             | 1                      | 200                            | 24                                |
| 201i (IPE)             | 1                      | 200                            | 24                                |
| 702t (tower)           | 3                      | 1000                           | 96                                |
| 1001rp (rackmount)     | 3                      | 1000                           | 96                                |



# Chapter 5

---

## Engineering the server

### In this chapter

|  |     |
|--|-----|
| Understanding the 200i server capacities   | 144 |
| Understanding the 201i server capacities   | 146 |
| Understanding the 702t server capacities   | 149 |
| Understanding the 1001rp server capacities | 152 |

# Understanding the 200i server capacities

## Introduction

You should be familiar with the capacities of the 200i server to ensure your selection meets the requirements of your site.

## Platform capacities

The 200i server is limited in the number of voice, fax, and speech recognition channels it can support, as well as in the number of mailboxes. The following table summarizes the capacities of each server:

| <b>Platform feature</b>                  | <b>Limits</b>                      |
|--|------------------------------------|
| Storage hours                            | 200                                |
| Number of voice channels                 | 24                                 |
| Number of fax channels                   | 12                                 |
| Number of speech-recognition channels    | 6                                  |
| Number of mailboxes                      | 8000                               |
| Number of voice prompt languages         | 6                                  |
| Number of speech recognition languages   | 3                                  |
| Number of Desktop Messaging mailboxes    | 1000                               |
| RAID (Level 1, hardware, mirroring only) | Not supported                      |
| Disks                                    | Not hot-swappable<br>Not redundant |

## Switch connectivity

The 200i server provides a maximum of 24 channels through the server connection to the Option 11C or Meridian 1 IPE shelf backplane. Both servers occupy two slots.

From the switch perspective, the 200i server appears logically equivalent to one XDLC.

## DSP configurations

The server contains one embedded DSP providing support for eight channels. Twenty-four channels are supported by inserting two MPC-8 cards into the server's faceplate. (Each MPC-8 card provides eight channels.)

## Disk and volume capacities

There is one system volume (VS1) on each CallPilot server, and it is always found on the system disk. VS1 contains system prompts, user personal verifications, network message queues, and user mailboxes.

The 200i server supports a single IDE hard drive. The following table identifies the disk size and storage capacity for each server:

| <b>Platform</b> | <b>Hours of storage</b> |
|-----------------|-------------------------|
| 200i            | 200                     |

## Data port provisioning

Only one COM port is available on the 200i server (identified as COM1). You can use it for remote support, download of Reporter data, or operation of MAT.

Connection to the COM port is provided by a 9-pin RS-232 connector as follows:

- 200i server: on the external I/O breakout panel

Neither server has a parallel port. In contrast to the other CallPilot servers, the dongle is embedded on the motherboard.

# Understanding the 201i server capacities

## Introduction

You should be familiar with the capacities of the 201i server to ensure your selection meets the requirements of your site.

## Platform capacities

The 201i server is limited in the number of voice, fax, and speech recognition channels it can support, as well as in the number of mailboxes. The following table summarizes the capacities of each server:

| <b>Platform feature</b>                  | <b>Limits</b>                      |
|--|------------------------------------|
| Storage hours                            | 200                                |
| Number of voice channels                 | 24                                 |
| Number of fax channels                   | 12                                 |
| Number of speech-recognition channels    | 6                                  |
| Number of mailboxes                      | 8000                               |
| Number of voice prompt languages         | 6                                  |
| Number of speech recognition languages   | 3                                  |
| Number of Desktop Messaging mailboxes    | 1000                               |
| RAID (Level 1, hardware, mirroring only) | Not supported                      |
| Disks                                    | Not hot-swappable<br>Not redundant |

## Switch connectivity

The 201i server provides a maximum of 24 channels through the server connection to the Option 11C or Meridian 1 IPE shelf backplane. Both servers occupy two slots.

From the switch perspective, the 200i server appears logically equivalent to one XDLC. The 201i server appears as two MGate cards.

## DSP configurations

The server contains one embedded DSP providing support for eight channels. Twenty-four channels are supported by inserting two MPC-8 cards into the server's faceplate. (Each MPC-8 card provides eight channels.)

**Note:** The 201i server provides four MPC-8 card slots. However, only two are supported in this release.

## Disk and volume capacities

There is one system volume (VS1) on each CallPilot server, and it is always found on the system disk. VS1 contains system prompts, user personal verifications, network message queues, and user mailboxes.

The 201i server supports a single IDE hard drive. The following table identifies the disk size and storage capacity for each server:

| Platform | Hours of storage |
|----------|------------------|
| 201i     | 200              |

## Data port provisioning

Only one COM port is available on the 201i server (identified as COM1). You can use it for remote support, download of Reporter data, or operation of MAT.

Connection to the COM port is provided by a 9-pin RS-232 connector as follows:

- 201i server: on the multi I/O cable

Neither server has a parallel port. In contrast to the other CallPilot servers, the dongle is embedded on the motherboard.

# Understanding the 702t server capacities

## Introduction

You should be familiar with the capacities of the 702t server to ensure they meet the requirements of your site.

## Platform capacities

The 702t server is limited in the number of voice, fax, and speech recognition channels it can support as well as the number of mailboxes. The following table summarizes the capacities of the server:

| <b>Platform feature</b>                  | <b>Limit</b>                              |
|--|---|
| Storage hours                            | 1000                                      |
| Number of voice channels                 | 96  |
| Number of fax channels                   | 48  |
| Number of speech-recognition channels    | 24  |
| Number of mailboxes                      | 20 000                                    |
| Number of storage hours for services     | 1000                                      |
| Number of voice prompt languages         | 6   |
| Number of speech recognition languages   | 3   |
| Number of Desktop Messaging mailboxes    | 5000                                      |
| RAID (Level 1, hardware, mirroring only) | Supported (optional)                      |
| Disks                                    | Not hot-swappable<br>Redundant (optional) |
| Power supply, fans                       | Not redundant or<br>hot-swappable         |

## MPC-8 cards and MPB-16 carrier boards

The 702t server supports the MPB-16 carrier board, which has two onboard MPC-8 sections. There are four additional slots on the board into which you can insert a total of 4 MPC-8 cards for a total of 48 channels per carrier board. You can insert a maximum of two carrier boards into the server.

A single carrier board provides two DS30x connections, each of which is connected to an MGate card in the switch. Each MGate card provides 32 channels. Therefore, for 96 channels, you require three MGate cards.

## Number of disks

The following table shows the recommended size of the hard drives available for the different storage configurations:

| <b>Hours of storage</b> | <b>Disk 1 (Gbyte)</b> | <b>Disk 2 (Gbyte)</b> | <b>Disk 3 (Gbyte)</b> |
|-------------------------|-----------------------|-----------------------|-----------------------|
| up to 1000              | 4                     | 4                     | 4                     |

## Volume capacities

There is one system volume (VS1) on each CallPilot server, and it is always found on the system disk. User volumes VS102 and VS103 are placed on separate hard drives that are configured on the server. The following table shows the recommended number of mailboxes available for the different storage configurations:

| <b>Volume</b> | <b>Storage hours</b> | <b>Maximum number of mailboxes</b> |
|---------------|----------------------|------------------------------------|
| VS1           | 200                  | 8000                               |
| VS102         | 600                  | 18 000                             |
| VS103         | 1000                 | 20 000                             |

## Data port provisioning

On the 702t server, the parallel port is dedicated to the dongle, a keycode security device.

There are two serial ports, one of which is used to support an external modem. The other port is retained as a spare.

## LAN connectivity

You can install one Ethernet card or one Token Ring card in the 702t server. The following cards are supported:

- 10/100 Mbps PCI Ethernet card
- PCI Token Ring card
- ISA 10 Mbps Ethernet card
- ISA Token Ring card

# Understanding the 1001rp server capacities

## Introduction

You should be familiar with the capacities of the 1001rp server to ensure they meet the requirements of your site.

## Platform capacities

The 1001rp server is limited in the number of voice, fax, and speech recognition channels it can support, as well as in the number of mailboxes. The following table summarizes the capacities of the server:

| <b>Platform feature</b>                  | <b>Limit</b>                   |
|--|--------------------------------|
| Storage hours                            | 1000                           |
| Number of voice channels                 | 96                             |
| Number of fax channels                   | 48                             |
| Number of speech-recognition channels    | 24                             |
| Number of mailboxes                      | 20 000                         |
| Number of voice prompt languages         | 6                              |
| Number of speech recognition languages   | 3                              |
| Number of Desktop Messaging mailboxes    | 5000                           |
| RAID (Level 1, hardware, mirroring only) | Standard                       |
| Disks                                    | Hot-swappable and<br>redundant |
| Power supply, fans                       | Redundant<br>Hot-swappable     |

## MPC-8 cards and MPB-16 carrier boards

The 1001rp server supports the single MPB-16 carrier board, which has two onboard MPC-8 sections. There are four additional slots on the board into which you can insert a total of four MPC-8 cards for a total of 48 channels per carrier board. You can insert a maximum of two carrier boards into the server.

A single carrier board provides two DS30x connections, each of which is connected to an MGate card in the switch. Each MGate card provides 32 channels. Therefore, for 96 channels, you require three MGate cards.

## Number of disks

The following table shows the recommended size of the hard drives available for the different storage configurations:

| <b>Hours of storage</b> | <b>Disk 1 (Gbyte)</b> | <b>Disk 2 (Gbyte)</b> | <b>Disk 3 (Gbyte)</b> |
|-------------------------|-----------------------|-----------------------|-----------------------|
| up to 1000              | 4                     | 4                     | 4                     |

## Volume capacities

There is one system volume (VS1) on each CallPilot server, and it is always found on the system disk. You can find user volumes VS102 and VS103 on separate hard drives that are configured on the server. The following table shows the recommended number of mailboxes available for the different storage configurations:

| <b>Volume</b> | <b>Storage hours</b> | <b>Maximum number of mailboxes</b> |
|---------------|----------------------|------------------------------------|
| VS1           | 200                  | 8000                               |
| VS102         | 600                  | 18 000                             |
| VS103         | 1000                 | 20 000                             |

## Data port provisioning

On the 1001rp server, the parallel port is dedicated to the dongle, a keycode security device.

There are two serial ports, one of which is used to support an external modem. The other port is retained as a spare.

# Chapter 6

---

## Engineering the clients

### In this chapter

|   |            |
|---|------------|
| Overview  | 156        |
| <b>Section A: Engineering the administrative PC</b>   | <b>157</b> |
| System requirements for Reporter                      | 158        |
| System requirements for Application Builder           | 160        |
| <b>Section B: Engineering the desktop client</b>      | <b>161</b> |
| System requirements for the desktop client            | 162        |
| <b>Section C: Calculating disk space requirements</b> | <b>165</b> |
| To help you determine disk space requirements         | 166        |

# Overview

## Introduction

To help you engineer the client PCs (administrative PC and Desktop Messaging PC), you must understand the LAN connectivity and disk space requirements for both machines. This chapter provides procedures for estimating the disk space requirements and establishing the necessary network connectivity.

## Software

CallPilot software contains several software components (for example, Reporter and Application Builder) that are intended to run on administrative PCs connected to a CallPilot server.

The Desktop Messaging software can run on a separate PC that is intended for a mailbox user.

## LAN connections

The administrative PC can be connected to both an ELAN or a CLAN.

The Desktop Messaging PC should be connected to a CLAN to ensure a high quality of service for telephony applications on the ELAN.

## See also

For more information on the hardware specifications for the administrative and desktop client PCs, refer to Chapter 2, “System configurations.”

# Section A: Engineering the administrative PC

## In this section

|   |     |
|---|-----|
| System requirements for Reporter            | 158 |
| System requirements for Application Builder | 160 |

# System requirements for Reporter

## Introduction

Reporter is a software program that gives the administrator the ability to produce and print summarized and detailed reports about the use and functionality of the CallPilot system. To produce these reports, operational measurement information is downloaded from the CallPilot server and stored in a local database on the administrative PC.

## Storage of operational measurements on the administrative PC

A single administrative PC can store operational measurements from a maximum of 50 servers. A database is created on the administrative PC for each server.

## Disk space requirements

Reporter requires disk space on the administrative PC for

- OM data collected from one or more servers
- storage of generated reports
- temporary files created during report generation (approximately 14 Mbytes)

The disk space requirements for the database depend on

- the amount of call traffic received
- the number of days operational measurement data is stored in a database (between 5 and 180 days)
- the number of servers a single PC can access

**Note:** The database has an upper limit of 550 Mbytes per system. If this limit is exceeded, the number of days that data is stored in the database must be reduced.

For more information on calculating disk space, refer to “To help you determine disk space requirements” on page 166.

## **LAN requirements**

Reporter can be connected to an ELAN or a CLAN. It can also be accessed by a modem using PPP.

# System requirements for Application Builder

## Introduction

Application Builder is a graphical software program that gives the administrator the ability to create multimedia applications with both voice and fax functionality. Callers can access the applications by dialing telephone numbers.

## Disk space requirements

Application Builder requires disk space on the administrative PC for

- Application Builder software (approximately 20 Mbytes)
- temporary working space while working on an application
- WAV and TIFF-F files that can reside on the PC and be imported into an application

If you want to estimate the amount of disk space that might be required for WAV and TIFF files, use the following measurements:

- 1 minute of WAV = 1 Mbyte
- 1 page of fax = 40 kbytes in normal resolution and 80 kbytes in fine resolution

For more information on calculating disk space, refer to “To help you determine disk space requirements” on page 166.

## LAN requirements

Application Builder can be connected to either an ELAN or a CLAN.

## **Section B: Engineering the desktop client**

### **In this section**

System requirements for the desktop client

162

# System requirements for the desktop client

## Introduction

Desktop Messaging gives mailbox users access to their CallPilot messages from their PC. They can play back or record voice messages on the PC if it is equipped with a sound card and microphone. Users can also choose to use the telephone. They can view fax messages on the PC or print them to a fax machine.

## Disk space requirements

The following items require additional disk space and should be included when planning the disk space requirements:

| <b>Item</b>  | <b>Approximation</b>   |
|--|--|
| Temporary working space                              | approximately 40 kbytes per page of fax (normal resolution) and 80 kbytes per page of fax (high resolution)  |
| Address Book information                             | approximately 10 kbytes per 100 users on the system  |
| Saving a local copy of the message to another folder | approximately 40 kbytes per page of fax (normal resolution) and 80 kbytes per page of fax (high resolution)<br>Estimate approximately 960 kbytes per minute of voice in a message. |

For more information on calculating disk space, refer to “To help you determine disk space requirements” on page 166.

## **LAN requirements**

The Desktop Messaging client should be connected to the CLAN to ensure a high quality of service for telephony applications on the ELAN.

The Desktop Messaging feature generates approximately 0.047 kbps of LAN traffic per user during the busy hour.



## **Section C: Calculating disk space requirements**

### **In this section**

To help you determine disk space requirements

166

# To help you determine disk space requirements

## Introduction

A worksheet is provided to help you estimate the amount of disk space you will need on the administrative PC and the Desktop Messaging client to support the CallPilot software and the data downloaded for Reporter.

## Worksheet

Use the following worksheet to determine disk space requirements for the client PCs. For an explanation of the boxes shown on the worksheet, refer to “To determine disk space requirements” on page 168.

| <b>Client PC disk space required</b> |   | <b>Disk space<br/>(Mbytes)</b> |
|--------------------------------------|---|--------------------------------|
| <b>1</b>                             | <b>CallPilot software</b><br><b>Note:</b> Approximately 25 Mbytes of temporary space is required for software installation. | <b>1</b><br><br><b>125</b>     |
| <b>2</b>                             | <b>Reporter data</b>  | <b>2</b><br><br>               |
|                                      | 2a Temporary file space   | <b>2a</b><br><br><b>20</b>     |
|                                      | 2b Optional space for saving report output  | <b>2b</b><br><br><b>5</b>      |
|                                      | 2c Database for each CallPilot system   | <b>2c</b><br><br>              |
| <b>3</b>                             | <b>Total disk space for administrative PC</b>   | <b>3</b><br><br>               |
| <b>4</b>                             | <b>Desktop Messaging client PC</b>  | <b>4</b><br><br>               |
|                                      | 4a Software and online guides   | <b>4a</b><br><br>              |
|                                      | 4b Storage for voice<br>(minutes of voice *1 Mbyte/minute)  | <b>4b</b><br><br>              |
|                                      | 4c Storage for fax<br>(pages of fax *80 kbytes/page)  | <b>4c</b><br><br>              |
| <b>5</b>                             | <b>Total disk space for Desktop Messaging client PC</b>   | <b>5</b><br><br>               |

## To determine disk space requirements

- 1 The amount of space required by the CallPilot OA&M software is estimated to be 125 Mbytes. This includes the following:
  - approximately 25 Mbytes of temporary space for software installation
  - CallPilot client software
  - Application Builder
  - Reporter (does not include database)
  - online documentation
  - Adobe Acrobat Reader (to view the documentation)
- 2 The amount of space required by Reporter is estimated as follows:
  - temporary file space: 20 Mbytes
  - optional space for saving Reporter output: 5 Mbytes

The size of the database for each CallPilot system at the customer site is calculated by using the following equations:

$$824 + (6.05 * \text{Busy Hour CCS}) = \text{kbytes of data/day}$$

$$(\text{Days stored} + 1) * \text{kbytes of data/day} = \text{Database size}$$

Days stored = the number of days data is to be stored in the database

- 3 The amount of space required by the Desktop Messaging client is as follows:
  - Client software and online guides: 10 Mbytes
  - Storage for fax messages is calculated as number of pages of fax in a message multiplied by 80 kbytes per page.
  - Storage for voice messages is calculated as number of minutes in the message multiplied by 1 Mbyte per minute.

## Reporter download sizes

The following table shows sample Reporter download sizes on a daily basis. Use this table when calculating the busy hour CCS in step 2:

| <b>Channels</b> | <b>Busy hour CCS</b> | <b>kbytes of data/day</b> |
|-----------------|----------------------|---------------------------|
| 12              | 274                  | 2482                      |
| 24              | 652                  | 4769                      |
| 36              | 1049                 | 7170                      |
| 48              | 1455                 | 9627                      |
| 60              | 1867                 | 12 159                    |
| 72              | 2282                 | 14 630                    |
| 84              | 2630                 | 16 736                    |
| 96              | 3120                 | 19 700                    |

## Example for estimating disk space requirements

The following example uses the worksheet to calculate the disk space requirements for a customer site. An example of the completed worksheet appears on page 171.

### Assumptions

The customer requirements are as follows:

- The customer is purchasing CallPilot client software and Desktop Messaging software.
- Two CallPilot systems exist at the customer site. One is a 24-channel system and the other is a 48-channel system. Ten days of storage are required for Reporter data.
- The customer expects to store 10 minutes of voice messages on the Desktop Messaging client PC.
- The customer expects to store 10 pages of fax messages on the Desktop Messaging client PC.

**Example**

Based on these assumptions, the worksheet on page 171 summarizes the calculations you must perform to determine the disk space requirements for this example.

In this example, the busy hour CCS is calculated by using the table provided in “Reporter download sizes” on page 169.

To calculate the database for the 24-channel system, perform the following calculation:

$$(10 + 1) * 4769 = 52\,459$$

$$824 + (6.05 * 652) = 4769 \text{ kbytes of data/day}$$

To calculate the database for the 48-channel system, perform the following calculation:

$$(10 + 1) * 9267 = 105\,897$$

$$824 + (6.05 * 14552) = 9627 \text{ kbytes of data/day}$$

## Completed worksheet example

| <b>Client PC disk space required</b> |   | <b>Disk space</b>           |
|--------------------------------------|---|-----------------------------|
| <b>1</b>                             | <b>CallPilot software</b><br><b>Note:</b> Approximately 25 Mbytes of temporary space is required for software installation. | <b>1</b><br><br><b>125</b>  |
| <b>2</b>                             | <b>Reporter data</b>  | <b>2</b><br><br>            |
|                                      | 2a Temporary file space   | <b>2a</b><br><br><b>20</b>  |
|                                      | 2b Optional space for saving report output  | <b>2b</b><br><br><b>5</b>   |
|                                      | 2c Database for 24-channel system   | <b>2c</b><br><br><b>52</b>  |
|                                      | Database for 48-channel system  | <b>2c</b><br><br><b>106</b> |
| <b>3</b>                             | <b>Total disk space for administrative PC</b>   | <b>3</b><br><br><b>283</b>  |
| <b>4</b>                             | <b>Desktop Messaging client PC</b>  | <b>4</b><br><br>            |
|                                      | 4a Software and online guides   | <b>4a</b><br><br><b>10</b>  |
|                                      | 4b Storage for voice<br>(minutes of voice *1 Mbyte/minute)  | <b>4b</b><br><br><b>10</b>  |
|                                      | 4c Storage for fax<br>(pages of fax *80 kbytes/page)  | <b>4c</b><br><br><b>1</b>   |
| <b>5</b>                             | <b>Total disk space for Desktop Messaging client PC</b>   | <b>5</b><br><br><b>21</b>   |



# Chapter 7

---

## Selecting a site

### In this chapter

|   |     |
|---|-----|
| Overview  | 174 |
| Understanding space requirements for the CallPilot server | 175 |
| CallPilot power supply requirements                       | 178 |
| Environmental specifications for the CallPilot servers    | 180 |

# Overview

## Introduction

This chapter provides guidelines on selecting an appropriate site for your CallPilot system. It describes specific space, power, and environmental requirements to help with your planning activities.

## Space requirements

Take into account that the physical space occupied by the CallPilot server, administrative PC, and ELAN equipment is part of your planning activities. This section provides guidelines to help you determine adequate space for the servers.

## Power requirements

You must consider the power supply requirements for the CallPilot server as part of your planning activities.

## Environmental considerations

Also consider the environmental requirements of the CallPilot servers when planning an adequate location for the servers.

# Understanding space requirements for the CallPilot server

## Introduction

Take into account that the physical space occupied by the 1001rp server is part of your planning activities. This section provides guidelines for determining that adequate space is provided for the servers.

## Space requirements for the 1001rp server

Front and rear access room is required for servicing of rack components. Situate the rack cabinet in an area with enough space for the front and rear cabinet doors to open and close, and allow extra access room for service or removal of any rack-mounted component.

## Switch room space planning

When you plan for the incremental space and mounting needed for the CallPilot server and peripherals, you must consider the space required in the switch room.

### ELAN

Ensure there is sufficient space for the Ethernet hub and cables.

### IPE server

The IPE server occupies two slots in the IPE shelf. You must also ensure there is sufficient space for the following:

- mounting and space
- I/O breakout panel (2001 server)
- multi-I/O cable (201i server)
- modem
- tape drive
- monitor, keyboard, mouse (although these cannot be permanently connected)

**Tower server**

The tower server is freestanding. The dimensions are

- height: 49.02 cm (19.3 in.)
- chassis width: 21.08 cm (8.3 in.) (10 in. with feet)
- depth: 44.96 cm (17.7 in.)

The clearance is

- front: 21.59 cm (8.5 in.)
- rear: 12.7 cm (5 in.)
- side: 7.62 cm (3 in.)

The weight of a loaded system with six SCSI drives, six populated boards, one CD-ROM drive, one floppy drive, and one tape drive is 22.05 kg (48.50 lbs).

The cable from the tower server to the Meridian 1 IPE shelf is 10 m (33 ft) in length.

You must ensure that there is sufficient space for the following items:

- modem
- monitor
- keyboard
- mouse

**Rackmount server**

The rackmount server goes into a customer-supplied 47.5 cm (19 in.) shelf. The dimensions are

- height: 31 cm (12.25 in.)
- width:
  - with the rackmount faceplate: 48.3 cm (19 in.)
  - without the rackmount faceplate: 42.88 cm (17 in.)
- depth:
  - server body: 48.3 cm (19 in.)
  - with handles: 53.3 cm (21 in.)

The weight of a loaded system with six SCSI drives, one CD-ROM drive, one floppy drive, and one tape drive is 45.5 kg (92 lbs).

The cable from the rackmount server to the Meridian 1 IPE shelf is 10 m (33 ft) in length.

You must ensure there is sufficient space for the following items:

- modem
- monitor
- keyboard (with integrated mouse track-ball)

## **Administrative PC**

If the administrative PC is connected to the ELAN, it must be 100 m (330 ft) or less from the ELAN hub.

# CallPilot power supply requirements

## Introduction

You must consider the power supply requirements for the CallPilot server as part of your planning activities. This section defines the requirements.

## General requirements

Locate the CallPilot server in an area that is

- not subject to static electricity
- not subject to vibration
- away from a sprinkler system, water, steam, or other liquid-carrying pipes
- physically safe for personnel and equipment
- not subject to electromagnetic interference (EMI)

Sources of EMI include

- broadcast stations
- radar
- mobile communications
- high-voltage power lines
- power tools
- office machines, such as photocopiers

## CallPilot server power requirements

The three types of servers require different power inputs and usage. The following table summarizes the power requirements:

| Device | Power input        | Power usage |
|--------|--------------------|-------------|
| 702t   | 120V AC<br>240V AC | 300 W       |

| <b>Device</b>       | <b>Power input</b>                    | <b>Power usage</b> |
|---------------------|---------------------------------------|--------------------|
| 1001rp AC           | 120V AC<br>240V AC                    | 400 W              |
| 1001rp DC           | 48V, 20 amp DC<br>See the note below. |                    |
| 200i                | provided by the M1 IPE                | 40 W               |
| 201i                | provided by the M1 IPE                | 40 W               |
| ELAN hub            | 110 V                                 | 1.8 W              |
| external tape drive | 110 V                                 | 7.2 W              |
| MGate card          | provided by the M1 IPE                | 5 W                |
| modem               |                                       | 10 W               |
| monitor             | 110 VAC                               | 90 W               |

**Note:** If you are using the Nortel Networks MFA150 rectifier (which comes with 30 A breakers, two 20 A breakers in the Spare Circuit Breaker Kit, 20 A [P0729846]), it must be configured to supply the two 20 A DC circuits for the rackmount server.

# Environmental specifications for the CallPilot servers

## Introduction

Consider the environmental requirements of the CallPilot servers when planning an adequate location for the servers.

**Note:** Switch environment specifications should be considered first before the server environment specifications.

## Specifications for the 200i server

The proper temperature and humidity are important for the longevity of the server. The following table summarizes the key specifications:

| Parameter   | Condition                      | Specification   |
|-------------|--------------------------------|---|
| Temperature | Recommended temperature        | 15°C (59°F) to 30°C (86°F)                            |
|             | Absolute temperature           | 10°C (50°F) to 45°C (113°F)                           |
|             | Long-term storage temperature  | -20°C (-4°F) to 60°C (140°F)                          |
|             | Short-term storage temperature | -40°C (-40°F) to 70°C (158°F)<br>(less than 72 hours) |
|             | Change rate temperature        | less than 1°C (33.8°F) per three minutes              |

| <b>Parameter</b> | <b>Condition</b>                    | <b>Specification</b>  |
|------------------|-------------------------------------|---|
| Humidity         | Recommended relative humidity       | 20% to 55% RH (non-condensing)  |
|                  | Absolute relative humidity          | 20% to 80% RH (non-condensing)  |
|                  | Long-term storage relative humidity | 5% to 95% RH (at -40°C [-40°F] to 70°C [158°F] respectively) (non-condensing) |

## Specifications for the 201i server

The proper temperature and humidity are important for the longevity of the server. The following table summarizes the key specifications:

| <b>Parameter</b> | <b>Condition</b>               | <b>Specification</b>                               |
|------------------|--------------------------------|--|
| Temperature      | Recommended temperature        | 15°C (59°F) to 30°C (86°F)                         |
|                  | Absolute temperature           | 10°C (50°F) to 45°C (113°F)                        |
|                  | Long-term storage temperature  | -20°C (-4°F) to 60°C (140°F)                       |
|                  | Short-term storage temperature | -40°C (-40°F) to 70°C (158°F) (less than 72 hours) |
|                  | Change rate temperature        | less than 1°C (33.8°F) per three minutes           |

| <b>Parameter</b> | <b>Condition</b>                    | <b>Specification</b>  |
|------------------|-------------------------------------|---|
| Humidity         | Recommended relative humidity       | 20% to 55% RH (non-condensing)  |
|                  | Absolute relative humidity          | 20% to 80% RH (non-condensing)  |
|                  | Long-term storage relative humidity | 5% to 95% RH (at -40°C [-40°F] to 70°C [158°F] respectively) (non-condensing) |

## Specifications for the 1001rp server

The proper temperature, humidity, and altitude are important for the longevity of the server. The following table summarizes the key specifications:

**Note:** The Non-operating label under the Condition column refers to the specification during shipping, storage, or both.

| <b>Parameter</b> | <b>Condition</b> | <b>Specification</b>                                   |
|------------------|------------------|--|
| Temperature      | Operating        | 5°C (41°F) to 35°C (95°F)                              |
|                  | Non-operating    | -40°C (-40°F) to 70°C (158°F)                          |
| Humidity         | Operating        | 5% to 95% at 40°C (104°F) (non-condensing)             |
|                  | Non-operating    | 0% to 95% at 40°C (104°F) (non-condensing)             |
| Shock            | Operating        | 1.25 Gs, 10 ms (10.0 Gs, 11 ms in appropriate chassis) |
|                  | Non-operating    | 30.0 Gs, 10 ms (40.0 Gs, 11 ms in appropriate chassis) |

---

| <b>Parameter</b> | <b>Condition</b> | <b>Specification</b>  |
|------------------|------------------|---|
| Vibration        | Operating        | 0.25 Gs at 5 Hz to 100 Hz (1.5 Gs over 5 Hz to 100 Hz in appropriate chassis) |
|                  | Non-operating    | 5 Gs at 5 Hz to 100 Hz  |
| Altitude         | Operating        | 4572 m (15 000 ft)  |
|                  | Non-operating    | 15 240 m (50 000 ft)  |

---



# Appendix A

---

## Traffic capacity tables

### In this appendix

|   |     |
|---|-----|
| Types of traffic capacity tables          | 186 |
| CCS values and channel requirements table | 187 |

# Types of traffic capacity tables

## Introduction

When calculating the number of channels you need on your CallPilot system, be aware that there are differences between sizing non-Meridian 1 switches versus Meridian 1 switches. The key differences are identified in “Channel requirements for specific switches” on page 90.

## Types of tables to use

The following table identifies the type of table to use for your CallPilot system and switch type. The actual tables begin on page 187.

### Busy hour CCS (BHCCS) traffic capacity table type

| Switch and media type                      | Erlang C P.05 BHCCS (40 second AHT) | Erlang C P.05 BHCCS (adjust for one MWI channel) | Erlang B P.02 BHCCS | Erlang B P.02 BHCCS (adjust for one MWI channel) |
|--|-------------------------------------|--|---------------------|--|
| Meridian 1 and MSL-100 Voice, Fax, and ASR | ✓                                   |  |                     |  |
| Lucent Voice                               |                                     | ✓  |                     |  |
| Lucent Fax and ASR                         | ✓                                   |  |                     |  |
| Mitel, Rolm, Matra Voice                   |                                     |  |                     | ✓  |
| Mitel, Rolm, and Matra Fax and ASR         |                                     |  | ✓                   |  |

# CCS values and channel requirements table

## Introduction

This section provides traffic capacity tables to use when calculating channel requirements.

## Before using this table

To determine which column of the following table to use when calculating channel requirements, refer to “Types of tables to use” on page 186.

### CCS values

| Number of channels | Erlang C P.05 GOS | Erlang C P.05 (adjusted for one MWI channel) | Erlang B P.02 GOS | Erlang B P.02 (adjusted for one MWI channel) |
|--------------------|-------------------|--|-------------------|--|
| 1                  | 2                 | < 2  | 1                 | < 1  |
| 2                  | 14                | 2  | 8                 | 1  |
| 3                  | 32                | 14   | 22                | 8  |
| 4                  | 54                | 32   | 40                | 22   |
| 5                  | 77                | 54   | 60                | 40   |
| 6                  | 103               | 77   | 83                | 60   |
| 7                  | 129               | 103  | 106               | 83   |
| 8                  | 156               | 129  | 131               | 106  |
| 9                  | 184               | 156  | 157               | 131  |
| 10                 | 213               | 184  | 183               | 157  |
| 11                 | 242               | 213  | 210               | 183  |
| 12                 | 271               | 242  | 238               | 210  |

**CCS values**

| <b>Number of channels</b> | <b>Erlang C P.05 GOS</b> | <b>Erlang C P.05 (adjusted for one MWI channel)</b> | <b>Erlang B P.02 GOS</b> | <b>Erlang B P.02 (adjusted for one MWI channel)</b> |
|---------------------------|--------------------------|---|--------------------------|---|
| 13                        | 301                      | 271   | 267                      | 238   |
| 14                        | 331                      | 301   | 295                      | 267   |
| 15                        | 362                      | 331   | 325                      | 295   |
| 16                        | 392                      | 362   | 356                      | 325   |
| 17                        | 424                      | 392   | 386                      | 356   |
| 18                        | 455                      | 424   | 416                      | 386   |
| 19                        | 486                      | 455   | 447                      | 416   |
| 20                        | 518                      | 486   | 477                      | 447   |
| 21                        | 550                      | 518   | 508                      | 477   |
| 22                        | 582                      | 550   | 539                      | 508   |
| 23                        | 614                      | 582   | 570                      | 539   |
| 24                        | 646                      | 614   | 602                      | 570   |
| 25                        | 678                      | 646   | 633                      | 602   |
| 26                        | 711                      | 678   | 665                      | 633   |
| 27                        | 744                      | 711   | 697                      | 665   |
| 28                        | 776                      | 744   | 729                      | 697   |
| 29                        | 809                      | 776   | 761                      | 729   |
| 30                        | 842                      | 809   | 793                      | 761   |
| 31                        | 875                      | 842   | 825                      | 793   |

**CCS values**

| <b>Number of channels</b> | <b>Erlang C P.05 GOS</b> | <b>Erlang C P.05 (adjusted for one MWI channel)</b> | <b>Erlang B P.02 GOS</b> | <b>Erlang B P.02 (adjusted for one MWI channel)</b> |
|---------------------------|--------------------------|---|--------------------------|---|
| 32                        | 908                      | 875   | 857                      | 825   |
| 33                        | 941                      | 908   | 890                      | 857   |
| 34                        | 974                      | 941   | 922                      | 890   |
| 35                        | 1008                     | 974   | 955                      | 922   |
| 36                        | 1041                     | 1008  | 987                      | 955   |
| 37                        | 1074                     | 1041  | 1020                     | 987   |
| 38                        | 1108                     | 1074  | 1053                     | 1020  |
| 39                        | 1141                     | 1108  | 1086                     | 1053  |
| 40                        | 1175                     | 1141  | 1119                     | 1086  |
| 41                        | 1209                     | 1175  | 1152                     | 1119  |
| 42                        | 1242                     | 1209  | 1185                     | 1152  |
| 43                        | 1276                     | 1242  | 1218                     | 1185  |
| 44                        | 1310                     | 1276  | 1252                     | 1218  |
| 45                        | 1344                     | 1310  | 1285                     | 1252  |
| 46                        | 1378                     | 1344  | 1318                     | 1285  |
| 47                        | 1412                     | 1378  | 1352                     | 1318  |
| 48                        | 1445                     | 1412  | 1385                     | 1352  |
| 49                        | 1479                     | 1445  | 1418                     | 1385  |
| 50                        | 1513                     | 1479  | 1452                     | 1418  |

## CCS values

| Number of channels | Erlang C P.05 GOS | Erlang C P.05 (adjusted for one MWI channel) | Erlang B P.02 GOS | Erlang B P.02 (adjusted for one MWI channel) |
|--------------------|-------------------|--|-------------------|--|
| 51                 | 1548              | 1513   | 1486              | 1452   |
| 52                 | 1582              | 1548   | 1519              | 1486   |
| 53                 | 1616              | 1582   | 1553              | 1519   |
| 54                 | 1650              | 1616   | 1587              | 1553   |
| 55                 | 1684              | 1650   | 1620              | 1587   |
| 56                 | 1718              | 1684   | 1654              | 1620   |
| 57                 | 1753              | 1718   | 1688              | 1654   |
| 58                 | 1787              | 1753   | 1722              | 1688   |
| 59                 | 1821              | 1787   | 1756              | 1722   |
| 60                 | 1856              | 1821   | 1790              | 1756   |
| 61                 | 1890              | 1856   | 1824              | 1790   |
| 62                 | 1924              | 1890   | 1858              | 1824   |
| 63                 | 1959              | 1924   | 1892              | 1858   |
| 64                 | 1993              | 1959   | 1926              | 1892   |
| 65                 | 2028              | 1993   | 1960              | 1926   |
| 66                 | 2062              | 2028   | 1994              | 1960   |
| 67                 | 2097              | 2062   | 2028              | 1994   |
| 68                 | 2131              | 2097   | 2063              | 2028   |
| 69                 | 2166              | 2131   | 2097              | 2063   |

**CCS values**

| <b>Number of channels</b> | <b>Erlang C P.05 GOS</b> | <b>Erlang C P.05 (adjusted for one MWI channel)</b> | <b>Erlang B P.02 GOS</b> | <b>Erlang B P.02 (adjusted for one MWI channel)</b> |
|---------------------------|--------------------------|---|--------------------------|---|
| 70                        | 2200                     | 2166  | 2131                     | 2097  |
| 71                        | 2235                     | 2200  | 2165                     | 2131  |
| 72                        | 2269                     | 2235  | 2200                     | 2165  |
| 73                        | 2304                     | 2269  | 2234                     | 2200  |
| 74                        | 2339                     | 2304  | 2268                     | 2234  |
| 75                        | 2373                     | 2339  | 2303                     | 2268  |
| 76                        | 2408                     | 2373  | 2337                     | 2303  |
| 77                        | 2443                     | 2408  | 2372                     | 2337  |
| 78                        | 2477                     | 2443  | 2406                     | 2372  |
| 79                        | 2512                     | 2477  | 2441                     | 2406  |
| 80                        | 2547                     | 2512  | 2475                     | 2441  |
| 81                        | 2582                     | 2547  | 2510                     | 2475  |
| 82                        | 2616                     | 2582  | 2544                     | 2510  |
| 83                        | 2651                     | 2616  | 2579                     | 2544  |
| 84                        | 2686                     | 2651  | 2613                     | 2579  |
| 85                        | 2721                     | 2686  | 2648                     | 2613  |
| 86                        | 2756                     | 2721  | 2682                     | 2648  |
| 87                        | 2791                     | 2756  | 2717                     | 2682  |
| 88                        | 2825                     | 2791  | 2752                     | 2717  |

**CCS values**

| <b>Number of channels</b> | <b>Erlang C P.05 GOS</b> | <b>Erlang C P.05 (adjusted for one MWI channel)</b> | <b>Erlang B P.02 GOS</b> | <b>Erlang B P.02 (adjusted for one MWI channel)</b> |
|---------------------------|--------------------------|---|--------------------------|---|
| 89                        | 2860                     | 2825  | 2786                     | 2752  |
| 90                        | 2895                     | 2860  | 2821                     | 2786  |
| 91                        | 2930                     | 2895  | 2856                     | 2821  |
| 92                        | 2965                     | 2930  | 2891                     | 2856  |
| 93                        | 3000                     | 2965  | 2925                     | 2891  |
| 94                        | 3035                     | 3000  | 2960                     | 2925  |
| 95                        | 3070                     | 3035  | 2995                     | 2960  |
| 96                        | 3105                     | 3070  | 3030                     | 2995  |

# Appendix B

---

## Planning spares requirements

### In this appendix

|  |     |
|--|-----|
| Planning spares for the CallPilot servers                  | 194 |
| 200i server spares   | 195 |
| 201i server spares   | 197 |
| 702t server spares   | 200 |
| 1001rp server spares                                       | 204 |
| Switch connectivity spares (tower and rackmount platforms) | 208 |
| IPE distributor support kits                               | 210 |

# Planning spares for the CallPilot servers

## Introduction

This section lists the parts and assemblies that can be ordered for replacement and spares. It also shows the estimated Annual Failure Rate (AFR) in percentage.

**Note:** When ordering a replacement dongle, you must also include the ordering code for an Upgrade (NTZE4002 A0809123).

## Definition: Annual Failure Rate

The AFR is the percentage of the parts that are expected to fail in a year. The following formula converts AFR to a Mean Time Between Failure (MTBF):

$$\text{MTBF (years)} = 1 / \text{AFR \%}$$

### Example

If the AFR % is 2%, then the MTBF =  $1 / .02 = 50$  years.

## 200i server spares

| Component                                       | CPC             | PEC             | AFR %    |
|---|-----------------|-----------------|----------|
| Base system                                     | A0641449        | NTRH14AA        | 2        |
| Hard drive power cable                          | P0684414        | P0684414        | –        |
| 4 Gbyte IDE hard drive                          | A0731186        | NTRH9049        | 2        |
| 128 Mbyte DIMM                                  | A0738130        | A0738130        | 2        |
| Hard drive data cable                           | A0661097        | NTRH16BA        | –        |
| Option 11 SCSI cable                            | A0767359        | NTRH1407        | –        |
| Meridian 1 faceplate SCSI cable                 | A0769733        | NTRH1408        | –        |
| Meridian 1 bulkhead SCSI cable                  | A0769774        | NTRH1409        | –        |
| 4.3 m (14 ft) shielded Ethernet cable           | A0769310        | A0769310        | –        |
| <b>200i breakout panel assembly</b>             | <b>A0688377</b> | <b>NTRH09AA</b> | <b>–</b> |
| 1.8 m (6 ft) breakout panel interconnect cable  | A0726955        | NTRH0910        | –        |
| 4.6 m (15 ft) breakout panel interconnect cable | A0765601        | NTRH0911        | –        |
| <b>CLAN Token Ring connection kit</b>           | <b>A0739898</b> | <b>NTUB51AA</b> | <b>1</b> |
| Token Ring adapter PCMCIA                       | A0683742        | NTRH9040        | 1        |
| Token Ring cabling                              | A0742083        | NTRH1406        | –        |
| <b>CLAN Ethernet connection kit</b>             | <b>A0739900</b> | <b>NTUB52AA</b> | <b>1</b> |
| Ethernet adapter PCMCIA                         | A0683741        | NTRH9039        | 1        |
| Internal Ethernet cabling                       | A0730304        | NTRH1405        | –        |

| <b>Component</b>                            | <b>CPC</b>      | <b>PEC</b>      | <b>AFR %</b> |
|---|-----------------|-----------------|--------------|
| <b>External SCSI 4-Gbyte tape drive kit</b> | <b>A0739901</b> | <b>NTUB53AA</b> | <b>1</b>     |
| External SCSI tape drive (4 Gbytes)         | A0683740        | NTRH9038        | 1            |
| SCSI cable                                  | A0372864        | NTAK1305        | –            |
| Data cartridge                              | A0780247        | A0780247        | 3            |
| SCSI adapter                                | A0769312        | A0769312        | –            |
| Cleaning cartridge                          | A0627875        | A0627875        | 3            |
| <b>Recovery kit</b>                         | <b>A0739902</b> | <b>NTUB54AA</b> | <b>1</b>     |
| CD-ROM kit                                  | A0744832        | NTUB59AA        | 1            |
| MAS flash recovery PC card                  | A0744464        | NTRH9055        | 1            |
| <b>Monitor peripheral kit</b>               | <b>A0739905</b> | <b>NTUB56AA</b> | <b>0.2</b>   |
| 14" monitor                                 | A0663896        | NTRH9011        | 0.2          |
| Keyboard                                    | A0993898        | NTRH9013        | 0.2          |
| Mouse                                       | A0663899        | NTRH9014        | 0.2          |

## 201i server spares

| Component                               | CPC             | PEC             | AFR % |
|---|-----------------|-----------------|-------|
| <b>201i server base hardware</b>        | –               | –               | –     |
| 201i server                             | A0774802        | NTRH30AA        | 2     |
| CallPilot 1.07 keycode package          | A0805067        | NTUB14AC        | –     |
| ATA66 hard drive                        | A0822235        | A0822235        | –     |
| MPC-8                                   | A0639034        | NTRH01AA        | 2     |
| <b>Hardware accessories</b>             | –               | –               | –     |
| 10BaseT hub                             | A0663902        | NTRH9017        | 0.5   |
| 10BaseT transceiver MAU                 | A0795886        | NTRH9069        | 0.5   |
| Option 11 SCSI cable                    | A0767359        | NTRH1407        | –     |
| Meridian 1 faceplate SCSI cable         | A0769733        | NTRH1408        | –     |
| Multi I/O cable - dual Ethernet         | A0789694        | NTRH0912        | NA    |
| Meridian 1 unfiltered ring/tip cable    | A0812878        | NTRH3501        | –     |
| Meridian 1 bulkhead SCSI cable          | A0827498        | NTRH1410        | –     |
| 14 ft shielded Ethernet cable           | A0769310        | A0769310        | –     |
| <b>Base server software</b>             | <b>A0811164</b> | <b>NTUB20AD</b> | –     |
| Windows NT 4.0 OS Recovery CD-ROM       | A0744465        | NTRH8027        | –     |
| CallPilot Master Driver CD-ROM Bootable | A0811040        | NTRH8101        | –     |
| CallPilot 1.07 Server Software CD-ROM   | A0805235        | NTUB40AC        | –     |

| <b>Component</b>                            | <b>CPC</b>      | <b>PEC</b>      | <b>AFR %</b> |
|---|-----------------|-----------------|--------------|
| CallPilot 1.07 Admin Client<br>CD-ROM       | A0795747        | NTUB41AC        | –            |
| CallPilot 1.07 Desktop Messaging<br>CD-ROM  | A0805370        | NTUB42AC        | –            |
| CallPilot 1.07 PEP Software<br>CD-ROM       | A0805372        | NTUB43AC        | –            |
| CallPilot 1.07 Language Prompts<br>CD-ROM   | A0811170        | NTUB44BC        | –            |
| CallPilot 1.07 Web Messaging<br>CD-ROM      | A0805374        | NTUB45AC        | –            |
| <b>External SCSI 4 Gbyte tape drive kit</b> | <b>A0739901</b> | <b>NTUB53AA</b> | <b>1</b>     |
| External SCSI tape drive                    | A0683740        | NTRH9038        | –            |
| External SCSI tape drive cable              | A0820829        | NTRH3502        | –            |
| Data cartridge                              | A0780247        | A0780247        | –            |
| SCSI adapter                                | A0769312        | A0769312        | 3            |
| Cleaning cartridge                          | A0627875        | A0627875        | 3            |

| <b>Component</b>                        | <b>CPC</b>      | <b>PEC</b>      | <b>AFR %</b> |
|---|-----------------|-----------------|--------------|
| <b>CD-ROM Kit</b>                       | <b>A0744832</b> | <b>NTUB59AA</b> | <b>1</b>     |
| Hardware assembly—portable CD-ROM drive | A0683739        | NTRH9037        | 1            |
| External SCSI drive cable               | A0820829        | NTRH3502        | —            |
| <b>Monitor peripheral kit</b>           | <b>A0739905</b> | <b>NTUB56AA</b> | <b>0.2</b>   |
| 14" monitor                             | A0663896        | NTRH9011        | 0.2          |
| Keyboard                                | A0993898        | NTRH9013        | 0.2          |
| Mouse                                   | A0663899        | NTRH9014        | 0.2          |
| <b>Modem kit</b>                        | <b>A0744831</b> | <b>NTUB16AA</b> | <b>1</b>     |
| Modem                                   | A0663901        | NTRH9016        | 1            |
| Modem cabling                           | A0601464        | A0601464        | —            |
| <b>Ethernet cables</b>                  | <b>—</b>        | <b>—</b>        | <b>—</b>     |
| .6 m (2 ft) Ethernet cable              | A0648374        | A0648374        | —            |
| 1.25 m (4 ft) Ethernet cable            | A0648372        | A0648372        | —            |
| 2.1 m (7 ft) Ethernet cable             | A0648375        | A0648375        | —            |
| 3 m (10 ft) Ethernet cable              | A0648377        | A0648377        | —            |
| 4.6 m (15 ft) Ethernet cable            | A0648378        | A0648378        | —            |
| 7.7 m (25 ft) Ethernet cable            | A0648379        | A0648379        | —            |

## 702t server spares

| Component                         | CPC             | PEC             | AFR % |
|-----------------------------------|-----------------|-----------------|-------|
| <b>702t base hardware package</b> | –               | –               | –     |
| 300 W power supply                | A0741561        | A0741561        | 1.5   |
| Fan module assembly               | A0741576        | A0741576        | 0.5   |
| Floppy drive                      | A0662019        | NTRH9004        | 0.5   |
| Floppy cable                      | A0741572        | A0741572        | –     |
| IDE CD-ROM drive                  | A0680752        | NTRH9035        | 0.5   |
| IDE cable to CD-ROM               | A0806019        | A0806019        | –     |
| Pentium II 450 Mhz CPU (2)        | A0761148        | A0761148        | 0.6   |
| 128 Mbyte DIMM (2)                | A0744456        | A0744456        | 2     |
| 9 Gbyte SCSI disk (3)             | A0741778        | NTRH9054        | 2     |
| Wide SCSI cable                   | A0788129        | A0788129        | –     |
| Wide SCSI terminator              | A0766997        | A0766997        | –     |
| 9 drop SCbus cable                | A0788131        | A0788131        | –     |
| Dongle adapter                    | A0731666        | A0731666        | 0.2   |
| CallPilot 1.07 keycode package    | A0805067        | NTUB14AC        | –     |
| 7.7 m (25 ft) Ethernet cable      | A0648379        | A0648379        | –     |
| <b>Base server software</b>       | <b>A0811166</b> | <b>NTUB22AD</b> | –     |
| Emergency Repair Disk (blank)     | A0682962        | NT3R9501        | –     |
| Windows NT 4.0 Install Diskettes  | A0747562        | NTRH8033        | –     |

| <b>Component</b>                           | <b>CPC</b>      | <b>PEC</b>      | <b>AFR %</b> |
|--|-----------------|-----------------|--------------|
| Windows NT 4.0 OS Recovery<br>CD-ROM       | A0744465        | NTRH8027        | –            |
| CallPilot Master Driver CD-ROM<br>Bootable | A0811040        | NTRH8101        | –            |
| CallPilot 1.07 Server Software<br>CD-ROM   | A0805235        | NTUB40AC        | –            |
| CallPilot 1.07 Admin Client<br>CD-ROM      | A0795747        | NTUB41AC        | –            |
| CallPilot 1.07 Desktop Messaging<br>CD-ROM | A0805370        | NTUB42AC        | –            |
| CallPilot 1.07 PEP Software<br>CD-ROM      | A0805372        | NTUB43AC        | –            |
| CallPilot 1.07 Language Prompts<br>CD-ROM  | A0811170        | NTUB44BC        | –            |
| CallPilot 1.07 Web Messaging<br>CD-ROM     | A0805374        | NTUB45AC        | –            |
| <b>Internal tape drive kit</b>             | <b>A0739904</b> | <b>NTUB55AA</b> | <b>1</b>     |
| Tape drive                                 | A0678778        | NTRH9034        | 1            |
| Cleaning cartridge                         | A0677506        | A0677506        | 3            |
| Data cartridge                             | A0677508        | A0677508        | 3            |
| M/M Wide-Nar SCSI adapter                  | A0729069        | A0729069        | –            |
| F/F Wide-Nar SCSI adapter                  | A0684822        | A0684822        | –            |
| Twisted wide SCSI cable                    | A0788129        | A0788129        | –            |
| Wide SCSI terminator                       | A0766997        | A0766997        | –            |

| <b>Component</b>                                    | <b>CPC</b>      | <b>PEC</b>      | <b>AFR %</b> |
|---|-----------------|-----------------|--------------|
| <b>700 series RAID kit</b>                          | <b>A0739908</b> | <b>NTUB58AA</b> | <b>1</b>     |
| SCSI RAID controller                                | A0833400        | NTRH9076        | 2            |
| 9 Gbyte SCSI disk (3)                               | A0741778        | NTRH9054        | 2            |
| Wide SCSI cable                                     | A0788129        | A0788129        | –            |
| Wide SCSI terminator                                | A0766997        | A0766997        | –            |
| <b>Modem kit</b>                                    | <b>A0744831</b> | <b>NTUB16AA</b> | <b>1</b>     |
| Modem   | A0663901        | NTRH9016        | 1            |
| Modem cabling                                       | A0601464        | A0601464        | –            |
| <b>Monitor peripheral kit</b>                       | <b>A0739905</b> | <b>NTUB56AA</b> | <b>0.2</b>   |
| 14" monitor   | A0663896        | NTRH9011        | 0.2          |
| Keyboard  | A0993898        | NTRH9013        | 0.2          |
| Mouse   | A0663899        | NTRH9014        | 0.2          |
| <b>General parts</b>                                | <b>–</b>        | <b>–</b>        | <b>–</b>     |
| Meridian Mail to CallPilot Migration Tape (S/W)     | A0805432        | NTUB24AB        | –            |
| MPC-8   | A0639034        | NTRH01AA        | 2            |
| MPB16-4 DSP carrier card (512TS)                    | A0765614        | NTRH20AB        | 2            |
| MPB16-4 DSP carrier card (1024TS)<br>(MSL-100 only) | A0772417        | NTRH20BA        | 2            |
| 100BaseT Ethernet adapter                           | A0680753        | NTRH9036        | 0.2          |
| Token Ring adapter PCI                              | A0663895        | NTRH9010        | 0.2          |

| <b>Component</b>              | <b>CPC</b> | <b>PEC</b> | <b>AFR %</b> |
|-------------------------------|------------|------------|--------------|
| 10BaseT hub                   | A0663902   | NTRH9017   | 0.5          |
| 10BaseT transceiver MAU       | A0795886   | NTRH9069   | 0.5          |
| 700 Series DC power converter | A0673987   | NTRH9032   | 0.2          |
| <b>Ethernet cables</b>        | –          | –          | –            |
| .6 m (2 ft) Ethernet cable    | A0648374   | A0648374   | –            |
| 1.25 m (4 ft) Ethernet cable  | A0648372   | A0648372   | –            |
| 2.1 m (7 ft) Ethernet cable   | A0648375   | A0648375   | –            |
| 3 m (10 ft) Ethernet cable    | A0648377   | A0648377   | –            |
| 4.6 m (15 ft) Ethernet cable  | A0648378   | A0648378   | –            |
| 7.7 m (25 ft) Ethernet cable  | A0648379   | A0648379   | –            |

# 1001rp server spares

| Component                           | CPC      | PEC      | AFR % |
|-------------------------------------|----------|----------|-------|
| <b>AC and DC platform spares</b>    | –        | –        | –     |
| Hot-swappable fan                   | A0681326 | A0681326 | 0.5   |
| Alarm status module                 | A0681164 | A0681164 | 0.2   |
| Rack rails                          | A0797941 | A0797941 | –     |
| Floppy drive                        | A0662019 | NTRH9004 | 0.5   |
| 256 Mbyte SDRAM                     | A0813446 | A0813446 | 2     |
| 9 Gbyte disk—hot swappable (6)      | NTRH9053 | A0741777 | 2     |
| IDE CD-ROM drive                    | A0680752 | NTRH9035 | 0.5   |
| Video card adapter                  | A0683743 | NTRH9041 | 0.2   |
| 100BaseT Ethernet adapter           | A0680753 | NTRH9036 | 0.2   |
| SCSI RAID controller                | A0663892 | NTRH9007 | 2     |
| Twisted wide SCSI cable             | A0788129 | A0788129 | –     |
| 9 drop SCbus cable                  | A0788131 | A0788131 | –     |
| Dongle adapter                      | A0731666 | A0731666 | 0.2   |
| 7.7 m (25 ft) Ethernet cable        | A0648379 | A0648379 | –     |
| CallPilot 1.07 keycode package      | A0805067 | NTUB14AC |       |
| <b>AC rackmount platform spares</b> | –        | –        | –     |
| 500 W AC power supply (2)           | A0805434 | A0805434 | 1.5   |

| <b>Component</b>                                | <b>CPC</b>      | <b>PEC</b>      | <b>AFR %</b> |
|---|-----------------|-----------------|--------------|
| <b>DC rackmount platform spares</b>             | –               | –               | –            |
| 300 W DC power supply                           | A0723663        | A0723663        | 1.5          |
| DC power cord                                   | A0725949        | A0725949        | –            |
| PDU   | A0676108        | A0676108        | –            |
| <b>Dual Pentium III SBC</b>                     | <b>A0793321</b> | <b>NTRH9068</b> | <b>2</b>     |
| Floppy cable                                    | A0685305        | A0685305        | –            |
| Cable harness for first and second serial ports | A0826698        | A0826698        | –            |
| IDE cable to CD-ROM                             | A0806019        | A0806019        | –            |
| <b>Base server software</b>                     | <b>A0811166</b> | <b>NTUB22AD</b> | –            |
| Emergency Repair Disk (blank)                   | A0682962        | NT3R9501        | –            |
| Windows NT 4.0 Install Disk                     | A0747562        | NTRH8033        | –            |
| Windows NT 4.0 OS Recovery CD-ROM               | A0744465        | NTRH8027        | –            |
| CallPilot Master Driver CD-ROM Bootable         | A0811040        | NTRH8101        | –            |
| CallPilot 1.07 Server Software CD-ROM           | A0805235        | NTUB40AC        | –            |
| CallPilot 1.07 Admin Client CD-ROM              | A0795747        | NTUB41AC        | –            |
| CallPilot 1.07 Desktop Messaging CD-ROM         | A0805370        | NTUB42AC        | –            |
| CallPilot 1.07 PEP Software CD-ROM              | A0805372        | NTUB43AC        | –            |

| <b>Component</b>                                    | <b>CPC</b>      | <b>PEC</b>      | <b>AFR %</b> |
|---|-----------------|-----------------|--------------|
| CallPilot 1.07 Language Prompts<br>CD-ROM           | A0811170        | NTUB44BC        | –            |
| CallPilot 1.07 Web Messaging<br>CD-ROM              | A0805374        | NTUB45AC        | –            |
| <b>Internal tape drive kit</b>                      | <b>A0739904</b> | <b>NTUB55AA</b> | <b>1</b>     |
| Tape drive  | A0678778        | NTRH9034        | 1            |
| Cleaning cartridge                                  | A0677506        | A0677506        | 3            |
| Data cartridge                                      | A0677508        | A0677508        | 3            |
| M/M Wide-Nar SCSI adapter                           | A0729069        | A0729069        | –            |
| F/F Wide-Nar SCSI adapter                           | A0684822        | A0684822        | –            |
| Twisted wide SCSI cable                             | A0788129        | A0788129        | –            |
| Wide SCSI terminator                                | A0766997        | A0766997        | –            |
| <b>Modem kit</b>                                    | <b>A0744831</b> | <b>NTUB16AA</b> | <b>1</b>     |
| Modem   | A0663901        | NTRH9016        | 1            |
| Modem cabling                                       | A0601464        | A0601464        | –            |
| <b>General parts</b>                                | <b>–</b>        | <b>–</b>        | <b>–</b>     |
| 14" monitor   | A0663896        | NTRH9011        | 0.2          |
| Keyboard  | A0726973        | NTRH9048        | 0.2          |
| MPC-8   | A0639034        | NTRH01AA        | 2            |
| MPB16-4 DSP carrier card (512TS)                    | A0765614        | NTRH20AB        | 2            |
| MPB16-4 DSP carrier card (1024TS)<br>(MSL-100 only) | A0772417        | NTRH20BA        | 2            |
| Token Ring adapter PCI                              | A0663895        | NTRH9010        | 0.2          |

| <b>Component</b>                                   | <b>CPC</b> | <b>PEC</b> | <b>AFR %</b> |
|--|------------|------------|--------------|
| 100BaseT Ethernet adapter                          | A0680753   | NTRH9036   | 0.2          |
| 10BaseT transceiver MAU                            | A0795886   | NTRH9069   | 0.5          |
| 10BaseT hub  | A0663902   | NTRH9017   | 0.5          |
| Meridian Mail to CallPilot Migration<br>Tape (S/W) | A0805432   | NTUB24AB   | –            |
| <b>Ethernet cables</b>                             | –          | –          | –            |
| .6 m (2 ft) Ethernet cable                         | A0648374   | A0648374   | –            |
| 1.25 m (4 ft) Ethernet cable                       | A0648372   | A0648372   | –            |
| 2.1 m (7 ft) Ethernet cable                        | A0648375   | A0648375   | –            |
| 3 m (10 ft) Ethernet cable                         | A0648377   | A0648377   | –            |
| 4.6 m (15 ft) Ethernet cable                       | A0648378   | A0648378   | –            |
| 7.7 m (25 ft) Ethernet cable                       | A0648379   | A0648379   | –            |

## Switch connectivity spares (tower and rackmount platforms)

| Component                                       | CPC             | PEC             | AFR %    |
|---|-----------------|-----------------|----------|
| <b>CallPilot to Lucent (2 Wire) Integration</b> | <b>A0787958</b> | <b>NTZE29BA</b> | <b>1</b> |
| VTG VB2009                                      | A0774945        | NTRH9060        | 1        |
| 30.8 m (100 ft) switch board cable              | A0766163        | A0766163        | –        |
| <b>CallPilot to Siemens/Rolm Integration</b>    | <b>A0787959</b> | <b>NTZE29CA</b> | <b>1</b> |
| VTG VB2002                                      | A0774940        | NTRH9057        | 1        |
| 30.8 m (100 ft) switch board cable              | A0766163        | A0766163        | –        |
| <b>CallPilot to Mitel Integration</b>           | <b>A0787960</b> | <b>NTZE29DA</b> | <b>1</b> |
| VTG VB2007                                      | A0774944        | NTRH9059        | 1        |
| 30.8 m (100 ft) switch board cable              | A0766163        | A0766163        | –        |
| <b>CallPilot to Meridian 1 Integration</b>      | <b>A0787957</b> | <b>NTZE29AA</b> | <b>1</b> |
| Mgate card                                      | A0767356        | NTRB18CA        | 1        |
| MGate dual connect cable                        | A0767358        | NTRH2013        | –        |
| Single DS30XV interconnect cable                | A0767357        | NTRH2012        | –        |
| <b>CallPilot to Matra Integration Kit</b>       | <b>A0806050</b> | <b>NTZE29GA</b> | <b>2</b> |
| MPC-8 (2)                                       | A0639034        | NTRH01AA        | 2        |
| MPB16-2T carrier card                           | A0804626        | NTRH21CA        | 2        |
| Analog loop start cable                         | A0790467        | NTRH0914        | –        |

| <b>Component</b>                                       | <b>CPC</b>      | <b>PEC</b>      | <b>AFR %</b> |
|--|-----------------|-----------------|--------------|
| <b>CallPilot to Nortel Networks SL-100 Integration</b> | <b>A0787961</b> | <b>NTZE29EA</b> | <b>1</b>     |
| Dialogic DT1/480SC DualSpan T1                         | A0788895        | NTRH9065        | 1            |
| T1 cable   | A0788107        | A0788107        | –            |
| Modem for SMDI link in T1 application                  | A0620530        | A0620530        | 0.2          |
| Modem cabling  | A0601464        | A0601464        | –            |
| VTG adapter cable                                      | A0788198        | A0788198        | –            |
| 9 drop SCbus cable (used for DSE connectivity kit)     | A0788131        | A0788131        | –            |
| CT to CT bus cable (used for NTZE29GA kit)             | A0790468        | NTRH0915        | –            |

# IPE distributor support kits

## Introduction

This section identifies the hardware distributors use to install, support, and recover CallPilot IPE systems.

| Description                            | CPC             | PEC             | AFR %      |
|--|-----------------|-----------------|------------|
| <b>Recovery kit (200i server only)</b> | <b>A0739902</b> | <b>NTUB54AA</b> | <b>1</b>   |
| CD-ROM kit                             | A0744832        | NTUB59AA        | 1          |
| MAS flash recovery PC card             | A0744464        | NTRH9055        | 1          |
| <b>Monitor peripheral kit</b>          | <b>A0739905</b> | <b>NTUB56AA</b> | <b>0.2</b> |
| 14" monitor                            | A0663896        | NTRH9011        | 0.2        |
| Keyboard                               | A0993898        | NTRH9013        | 0.2        |
| Mouse                                  | A0663899        | NTRH9014        | 0.2        |

### Notes:

- The 201i server contains a read-only disk operating system (ROM-DOS) that enables you to perform a system recovery and build. For more details, refer to *Part 5: 201i Server Maintenance and Diagnostics* in the *CallPilot 201i Installation and Configuration Guide*.
- The monitor kit (monitor, mouse, and keyboard) is needed only for initial installation of the IPE platform. To conform with EMI regulations, remove it after installation.

# Appendix C

---

## Component list

For component lists for each CallPilot server platform, refer to the *Models and Ordering Procedures* product bulletin.

To obtain this document, contact your Nortel Networks distributor. If you are a Nortel Networks distributor, you can obtain this document from the CallPilot area of the Nortel Networks Information Center web site at <http://www.nortel.com/partnercenter/>.



# Appendix D

---

## Site survey checklist

### In this appendix

Planning your CallPilot system using a site survey checklist

214

# Planning your CallPilot system using a site survey checklist

## To plan for a CallPilot system

Use the following checklist to help you plan for a CallPilot system:

### 1. General information

#### End User

Name: \_\_\_\_\_

Address: \_\_\_\_\_

City, State/Province: \_\_\_\_\_

Country, Zip/Postal Code: \_\_\_\_\_

Telephone number: \_\_\_\_\_

Primary contact: \_\_\_\_\_

Secondary contact: \_\_\_\_\_

#### Distributor

Name: \_\_\_\_\_

Address: \_\_\_\_\_

City, State/Province: \_\_\_\_\_

Country, Zip/Postal Code: \_\_\_\_\_

Telephone number: \_\_\_\_\_

Primary contact: \_\_\_\_\_

Secondary contact: \_\_\_\_\_

---

## 2. Delivery information

---

City, State/Province: \_\_\_\_\_

Country, Zip/Postal Code: \_\_\_\_\_

Telephone number: \_\_\_\_\_

Primary contact: \_\_\_\_\_

Secondary contact: \_\_\_\_\_

Vehicle restrictions: \_\_\_\_\_

Hours of delivery: \_\_\_\_\_

Security clearance: \_\_\_\_\_

Freight company: \_\_\_\_\_

Delivery constraints: \_\_\_\_\_

---

## 3. Switch configuration

---

Meridian 1 model (see below for other types of switches): \_\_\_\_\_

Meridian 1 serial number: \_\_\_\_\_

Memory (check one):

|                                    |                                     |
|------------------------------------|-------------------------------------|
| <input type="checkbox"/> 24 Mbytes | <input type="checkbox"/> 80 Mbytes  |
| <input type="checkbox"/> 48 Mbytes | <input type="checkbox"/> 96 Mbytes  |
| <input type="checkbox"/> 64 Mbytes | <input type="checkbox"/> 112 Mbytes |

Average Real-Time Utilization: \_\_\_\_\_ %

Over a period of hours, days, weeks, or months: \_\_\_\_\_

MSL-100 model: \_\_\_\_\_

MSL-100 serial number: \_\_\_\_\_

Lucent model: \_\_\_\_\_

Matra model: \_\_\_\_\_

Rolm model: \_\_\_\_\_

Mitel model: \_\_\_\_\_

Current software release: \_\_\_\_\_

**4. CallPilot system sizing considerations  
(Refer to Chapter 4, "Determining system size," in this guide for the following information.)**

Number of channels required (voice, fax,  
and speech recognition): \_\_\_\_\_

Number of MPC-8 cards required: \_\_\_\_\_

Number of MPB-16 boards required: \_\_\_\_\_

Number of storage hours required: \_\_\_\_\_

**5. CallPilot optional features desired**

Primary language: \_\_\_\_\_

Secondary language: \_\_\_\_\_

Extra/alternate language (3): \_\_\_\_\_

Extra/alternate language (4): \_\_\_\_\_

Extra/alternate language (5): \_\_\_\_\_

Extra/alternate language (6): \_\_\_\_\_

(Contact your Nortel Networks representative for a list of available languages.)

AMIS Networking:  Yes  No

Enterprise networking:  Yes  No

|                                      |                              |                             |
|--------------------------------------|------------------------------|-----------------------------|
| VPIIM Networking:                    | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| NMS locations:                       | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Application Builder with fax option: | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Desktop messaging client:            | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Fax messaging mailboxes:             | <input type="checkbox"/> Yes | <input type="checkbox"/> No |
| Speech recognition mailboxes:        | <input type="checkbox"/> Yes | <input type="checkbox"/> No |

---

### 6. Administrative PC and Desktop Messaging clients

---

Primary individual/group responsible for installation of Desktop Messaging client software:

Distributor  
 Mailbox user  
 Customer's Information System department

Primary individual/group responsible for installation of CallPilot software on administrative PC:

Distributor  
 Customer's Information System department

---

### 7. Network changes

---

IP address of CallPilot server: \_\_\_\_\_.

Subnet mask for CallPilot server on ELAN (Meridian 1 only): \_\_\_\_\_.

IP address for connection of server to CLAN: \_\_\_\_\_.

Primary individual/group responsible for configuring CallPilot server:

Distributor  
 System administrator  
 Customer's Information System department

LAN connection for CallPilot:             10BaseT             Token Ring 4 Mbps  
     100BaseT             Token Ring 16 Mbps

When will the CLAN drop for the CallPilot be available? \_\_\_\_\_

Is TCP/IP available from CallPilot server to all administrative and messaging clients?     Yes             No

**8. Enter third-party e-mail or GroupWare Messaging system installed:**

|  | Number of users: |
|--|------------------|
| <input type="checkbox"/> e-mail or GroupWare                                   | _____            |
| <input type="checkbox"/> Microsoft Exchange                                    | _____            |
| <input type="checkbox"/> Microsoft Outlook97                                   | _____            |
| <input type="checkbox"/> Lotus Notes   | _____            |
| <input type="checkbox"/> Novell Groupwise                                      | _____            |
| <input type="checkbox"/> Microsoft Outlook Express<br>(Internet e-mail client) | _____            |
| <input type="checkbox"/> Netscape Messenger<br>(Internet e-mail client)        | _____            |
| <input type="checkbox"/> Qualcomm Eudora<br>(Internet e-mail client)           | _____            |
| <input type="checkbox"/> Microsoft Outlook 98<br>(Internet e-mail mode)        | _____            |

# Index

## Numerics

- 1001rp server
  - data port provisioning 154
  - environmental specifications 182
  - number of disks 153
  - platform capacities 152
  - power supply requirements 178
  - space requirements 175
  - volume capacities 153
- 200i server
  - components 36, 38
  - data port provisioning 145, 147
  - environmental specifications 180, 181
  - platform capacities 144, 146
  - power supply requirements 179
- 201i server
  - relative humidity 178
  - temperatures 178
- 702t server
  - data port provisioning 151
  - platform capacities 149
  - power supply requirements 178
  - volume capacities 150

## A

- administrative PC, configuration 49
- AMIS Networking 78
- AML link 69
- Application Builder 74
  - disk space requirements 160
  - storage requirements 130, 136

## B

- busy hour
  - definition 90
  - determining
    - Application Builder voice services 99
    - fax auto attendant 114

- fax callback activity 113
- fax menu activity 111
- fax messaging activity 116
- voice channels 98

## C

- callback delivery 106
- CallPilot system planning 214
- channel requirements
  - fax channels, calculating 117
  - for Application Builder 74
  - for Fax Broadcasting 117
  - for Multimedia messaging 82
  - for Networking 79
  - guidelines for estimating 90
  - voice channels, determining 103
- channel, definition 88
- client PC
  - components 35, 37, 39
  - disk space requirements, determining 166
  - LAN connections
    - 156
  - components in a CallPilot system 22
- configuration
  - administrative PC 49
  - Desktop Messaging client 52
  - IPE platform 36, 38
  - rackmount platform 32
  - tower platform 32
- customer LAN 67

## D

- Desktop Messaging client
  - disk space requirements 162
  - e-mail packages supported 29, 55
  - for Internet Mail 56
  - for Lotus Notes 56
  - for Microsoft Exchange/Outlook 56
  - for web browsers 56

- hardware requirements 55
- how to purchase 77
- LAN requirements 77
- disk space requirements
  - for Application Builder 160
  - for Desktop Messaging client 162
  - for Reporter 158

## E

- Embedded LAN 60
- Enterprise Networking 79

## F

- fax channels, determining 107
- Fax on Demand 111

## H

- hard disk drive
  - administrative PC requirements 49
  - Desktop Messaging client requirements 55
- Help, online 25
- humidity, 201i server 178

## M

- Meridian 1 switch 45
- Meridian Application Server
  - components 34, 37, 39
  - hardware components 42
- MPB-16 boards, determining how many are required 128
- MPB16-4 carrier board 64, 65
- MPC-8 cards
  - definition 89
- MPUs
  - calculating 127
  - definition 89
- multimedia messaging 81

## N

- Network Message Service (NMS) Networking 79
- networking limits 80

## O

- online Help 25
- outcalling activity 101

## P

- Personal Distribution List limits 81
- planning a CallPilot system 214

## R

- rackmount platform 32
- RAID 144, 146, 149, 152
- RAM requirements
  - for the administrative PC 49
  - for the Desktop Messaging client 55
- related information products 23
- relative humidity, 201i server 178
- Reporter 76
  - disk space requirements 158

## S

- same call delivery 106
- Shared Distribution Lists limits 81
- speech-recognition channels, determining 123
- storage hours, determining 130
- storage requirements
  - for Application Builder 130, 136
  - for messages 130, 133
- switches, supported 45
- system size, calculating 141

**T**

temperatures, 201i server 178  
tower platform 32

**V**

voice channels, determining 94  
Volume VS1 140  
Volume VS102 140  
Volume VS103 140  
VPIM Networking 78

**W**

worksheets  
    CallPilot system, planning 214  
    fax channels, determining 109  
    MPUs, determining 126  
    speech-recognition channels, determining 122  
    storage hours, determining 131  
    voice channels, determining 96



\*Nortel Networks, the Nortel Networks logo, the Globemark, and Unified Networks, BNR, CallPilot, DMS, DMS-100, DMS-250, DMS-MTX, DMS-SCP, DPN, Dualmode, Helmsman, IVR, MAP, Meridian, Meridian 1, Meridian Link, Meridian Mail, Norstar, SL-1, SL-100, Supernode, Symposium, Telesis, and Unity are trademarks of Nortel Networks.

ACCENT is a trademark of Accent Software International Ltd.

ACTION REQUEST SYSTEM and AR SYSTEM are trademarks of Remedy Corporation.

AMDEK is a trademark of Amdek Corporation.

ANSI is a trademark of the American National Standards Institute, Inc.

AT&T is a trademark of American Telephone and Telegraph Corporation.

ATRIA is a trademark of Pure Atria Corporation.

CASEWARE is a trademark of Caseware International, Inc.

CLEARCASE is a trademark of Rational Software Corporation.

CONTINUUS is a trademark of Continuus Software Corporation.

CRYSTAL REPORTS is a trademark of Seagate Software Inc.

EUDORA PRO is a trademark of QUALCOMM Inc.

FRAME, FRAMEBUILDER, FRAMEMAKER, and POSTSCRIPT are trademarks of Adobe Systems Incorporated.

HELVETICA is a trademark of Eltra Corporation.

HITACHI is a trademark of Hitachi Limited.

LOGITECH is a trademark of Logitech, Inc.

MACINTOSH and APPLE are trademarks of Apple Computer Inc.

MFA is a trademark of Astec International Ltd.

MICROSOFT, MS-DOS, POWERPOINT, WINDOWS, and WINDOWS NT are trademarks of Microsoft Corporation.

NOVELL is a trademark of Novell, Inc.

PCANYWHERE is a trademark of Symantec Corporation.

PROMARK and RHOBOT are trademarks of DMI Promark, Inc.

SLR4, SLR5, and TANDBERG are trademarks of Tandberg Data ASA.

SONY is a trademark of Sony Corporation.

SYBASE is a trademark of Sybase, Inc.

TIMES is a trademark of Heidelberger Druckmaschinen Aktiengesellschaft.

3COM is a trademark of 3Com Corporation.

UNIX is a trademark of X/Open Company Limited.

WINRUNNER is a trademark of Mercury Interactive Corporation.

# CallPilot

## Planning and Engineering Guide

Toronto Information Products  
Nortel Networks  
522 University Avenue, 14th Floor  
Toronto, Ontario, Canada  
M5G 1W7

Copyright © 2000 Nortel Networks, All Rights Reserved

Information is subject to change without notice. Nortel Networks reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant.

The process of transmitting data and call messaging between the Meridian 1 and CallPilot is proprietary to Nortel Networks. Any other use of the data and the transmission process is a violation of the user license unless specifically authorized in writing by Nortel Networks prior to such use. Violations of the license by alternative usage of any portion of this process or the related hardware constitutes grounds for an immediate termination of the license and Nortel Networks reserves the right to seek all allowable remedies for such breach.

The preceding page contains Nortel Networks and third-party trademarks.

|                     |               |
|---------------------|---------------|
| Publication number: | 555-7101-101  |
| Product release:    | 1.07          |
| Document release:   | Standard 2.0  |
| Date:               | November 2000 |

Printed in the United States of America

**NORTEL**  
**NETWORKS™**