

**555-7101-305**

# **CallPilot**

## **Integrated AMIS Networking Implementation and Administration Guide**

Product release 2.5

Standard 1.0

October 2003

---

---

**NORTEL**  
**NETWORKS™**



# CallPilot

## Integrated AMIS Networking Implementation and Administration Guide

---

Publication number:	555-7101-305
Product release:	2.5
Document release:	Standard 1.0
Date:	October 2003

---

Copyright © 2003 Nortel Networks, All Rights Reserved

Information is subject to change without notice. Nortel Networks reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant.

The process of transmitting data and call messaging between the CallPilot server and the switch or system is proprietary to Nortel Networks. Any other use of the data and the transmission process is a violation of the user license unless specifically authorized in writing by Nortel Networks prior to such use. Violations of the license by alternative usage of any portion of this process or the related hardware constitutes grounds for an immediate termination of the license and Nortel Networks reserves the right to seek all allowable remedies for such breach.

This page and the following page are considered the title page, and contain Nortel Networks and third-party trademarks.

Nortel Networks, the Nortel Networks logo, the Globemark, and Unified Networks, BNR, CallPilot, DMS, DMS-100, DMS-250, DMS-MTX, DMS-SCP, DPN, Dualmode, Helmsman, IVR, MAP, Meridian, Meridian 1, Meridian Link, Meridian Mail, Norstar, SL-1, SL-100, Succession, Supernode, Symposium, Telesis, and Unity are trademarks of Nortel Networks.

3COM is a trademark of 3Com Corporation.

ACCENT is a trademark of Accent Software International Ltd.

ADOBE is a trademark of Adobe Systems Incorporated.

AMDEK is a trademark of Amdek Corporation.

AT&T is a trademark of American Telephone and Telegraph Corporation.

ATLAS is a trademark of Quantum Corporation.

ATRIA is a trademark of Pure Atria Corporation.

CASEWARE is a trademark of Caseware International, Inc.

CONTINUUS is a trademark of Continuus Software Corporation.

CRYSTAL REPORTS is a trademark of Seagate Software Inc.

DEFINITY is a trademark of Avaya Inc.

DIALOGIC, INTEL and VOICEBRIDGE are trademarks of Intel Corporation.

DIVX is a trademark of DivXNetworks, Inc.

EUDORA and QUALCOMM are trademarks of Qualcomm, Inc.

eTrust and InoculatelT are trademarks of Computer Associates Think Inc.

DIRECTX, EXCHANGE.NET, FRONTPAGE, INTERNET EXPLORER, LINKEXCHANGE, MICROSOFT, MICROSOFT EXCHANGE SERVER, MS-DOS, NETMEETING, OUTLOOK, POWERPOINT, VISUAL STUDIO, WINDOWS, WINDOWS MEDIA, and WINDOWS NT are trademarks of Microsoft Corporation.

GROUPWISE and NOVELL are trademarks of Novell Inc.

HITACHI is a trademark of Hitachi Limited.

LOGITECH is a trademark of Logitech, Inc.

LUCENT is a trademark of Lucent Technologies, Inc.

MATRA is a trademark of Matra Hachette.

MCAFFEE and NETSHIELD are trademarks of McAfee Associates, Inc.

MYLEX is a trademark of Mylex Corporation.

NET2PHONE is a trademark of Net2Phone, Inc.

NETOPIA is a trademark of Netopia, Inc.

NETSCAPE COMMUNICATOR is a trademark of Netscape Communications Corporation.

NOTES is a trademark of Lotus Development Corporation.

NORTON ANTIVIRUS and PCANYWHERE are trademarks of Symantec Corporation.

POWERQUEST is a trademark of PowerQuest Corporation.

PROMARK and RHOBOT are trademarks of DMI Promark, Inc.

QUICKTIME is a trademark of Apple Computer, In.

RADISYS is a trademark of Radisys Corporation.

ROLM is a trademark of Siemens ROLM Communications Inc.

SLR4, SLR5, and TANDBERG are trademarks of Tandberg Data ASA.

SONY is a trademark of Sony Corporation.

SYBASE is a trademark of Sybase, Inc.

TEAC is a trademark of TEAC Corporation.

UNIX is a trademark of X/Open Company Limited.

US ROBOTICS, the US ROBOTICS logo, and SPORTSTER are trademarks of US Robotics.

WINAMP is a trademark of Nullsoft, Inc.

WINRUNNER is a trademark of Mercury Interactive Corporation.

WINZIP is a trademark of Nico Mark Computing, Inc.

# Publication history

**October 2003**

Standard 1.0 issue of the CallPilot 2.5 *Integrated AMIS Networking Implementation and Administration Guide*.



# Contents

<b>1</b>	<b>About CallPilot</b>	<b>11</b>
	<b>About this guide</b>	<b>13</b>
	Overview . . . . .	14
	Skills you need. . . . .	15
	How this guide is organized . . . . .	16
	Related information products . . . . .	18
	Conventions . . . . .	24
	<b>Finding your way around CallPilot</b>	<b>25</b>
	Connecting to CallPilot . . . . .	26
	Multi-administrator access . . . . .	34
	Error handling in property sheets . . . . .	36
	Using the online Help . . . . .	39
<b>2</b>	<b>Getting started</b>	<b>43</b>
	<b>About Integrated AMIS Networking</b>	<b>45</b>
	Overview . . . . .	46
	CallPilot and Integrated AMIS Networking . . . . .	51
	<b>Implementing Integrated AMIS Networking</b>	<b>55</b>
	Overview . . . . .	56
	Implementation in a complex messaging network . . . . .	60
	<b>How Integrated AMIS Networking works</b>	<b>61</b>
	About Integrated AMIS Networking messages. . . . .	62
	About Integrated AMIS Networking parameters . . . . .	64
	About AMIS Networking parameters . . . . .	68
	Understanding Integrated AMIS Networking settings . . . . .	71
	<b>How Integrated AMIS Networking handles messages</b>	<b>73</b>
	Overview . . . . .	74
	What the MTA does . . . . .	76
	What the ANA does. . . . .	79
	How a message is transferred . . . . .	80

	<b>Coordinating with the system administrator</b>	<b>81</b>
	Overview . . . . .	82
	Assigning a Restriction/Permission List for AMIS Networking messages . .	86
<b>3</b>	<b>Gathering information</b>	<b>87</b>
	<b>Information required</b>	<b>89</b>
	Overview . . . . .	90
	Switch information . . . . .	91
	Information required from switch. . . . .	93
	Evaluating the switch information . . . . .	96
	Information from other sites . . . . .	97
	Messaging network representation . . . . .	98
<b>4</b>	<b>Configuring the switch for Integrated AMIS Networking</b>	<b>101</b>
	<b>Configuring the switch</b>	<b>103</b>
	Overview . . . . .	104
	SDN Table and Integrated AMIS Networking . . . . .	106
	Adding and configuring SDNs . . . . .	112
	Phantom DNs and Integrated AMIS Networking . . . . .	116
<b>5</b>	<b>Configuring CallPilot for Integrated AMIS Networking</b>	<b>119</b>
	<b>About configuring CallPilot</b>	<b>121</b>
	Overview . . . . .	122
	Configuration summary . . . . .	123
	Message delivery parameters—AMIS 1 tab . . . . .	126
	Message delivery parameters—AMIS 2 tab . . . . .	131
	Configuring the message delivery parameters . . . . .	135
	Enabling AMIS Networking functionality . . . . .	137
	Creating a loopback mailbox . . . . .	140
<b>6</b>	<b>Adding sites to Integrated AMIS Networking</b>	<b>143</b>
	<b>About the messaging network</b>	<b>145</b>
	Overview . . . . .	146
	Configuration and other networking solutions . . . . .	147

	<b>Configuring the local site</b>	<b>151</b>
	Overview . . . . .	152
	Configuring the local messaging server . . . . .	154
	Configuring the local prime switch location . . . . .	159
	Configuring ESN information . . . . .	165
	Configuring CDP information . . . . .	169
	<b>Adding and configuring a remote site</b>	<b>173</b>
	Overview . . . . .	174
	Configuring a remote messaging server . . . . .	175
	Configuring a remote prime switch location . . . . .	184
	Configuring a remote satellite switch location . . . . .	195
	Recording a spoken name . . . . .	199
	Importing a spoken name . . . . .	201
	Non-CallPilot remote sites . . . . .	203
	Meridian Mail remote sites . . . . .	205
	Norstar Voice Mail remote sites . . . . .	206
<b>7</b>	<b>Testing and backing up Integrated AMIS Networking</b>	<b>207</b>
	<b>Tests and backups</b>	<b>209</b>
	Integrated AMIS Networking test suite . . . . .	210
	Call routing test . . . . .	212
	Local SDN test . . . . .	213
	Quick SDN test . . . . .	215
	Loopback test . . . . .	217
	End-to-end test . . . . .	219
	Backing up Integrated AMIS Networking . . . . .	222
<b>8</b>	<b>Maintaining Integrated AMIS Networking</b>	<b>223</b>
	<b>About maintaining Integrated AMIS Networking</b>	<b>225</b>
	Overview . . . . .	226
	Maintain a network history . . . . .	228
	Printing configuration information . . . . .	229
	<b>Regularly scheduled maintenance tasks</b>	<b>231</b>
	Reviewing OM reports and alerts . . . . .	232
	<b>As-required maintenance tasks</b>	<b>233</b>
	Overview . . . . .	234
	Modifying the configuration of Integrated AMIS Networking . . . . .	236
	Disabling and enabling Integrated AMIS Networking . . . . .	238

Modifying message delivery parameters . . . . . 241  
 Modifying the channel resource allocation. . . . . 243  
 Add, modify, or delete remote sites . . . . . 245  
 Locating an item in the tree view . . . . . 247  
 Modifying a remote site configuration . . . . . 248  
 Deleting items in the tree view . . . . . 251  
 Modifying dialing plan information . . . . . 254

**9 Troubleshooting Integrated AMIS Networking 255**

**About troubleshooting Integrated AMIS Networking 257**  
 Overview. . . . . 258  
 Determine if Integrated AMIS is disabled . . . . . 260  
 Reviewing Alarm and Event reports. . . . . 261  
 Reviewing Operational Measurement reports . . . . . 262

**Determining if problems are switch-related 263**  
 Switch-related problems . . . . . 264  
 Call trace test . . . . . 265  
 Link diagnostic test. . . . . 267

# chapter 1

---

## About CallPilot

This chapter introduces CallPilot, the powerful multimedia messaging system from Nortel Networks. CallPilot offers a single solution for managing many types of information, including voice mail, fax-mail, e-mail, telephone calls, conferencing, calendars, directories, and call logs.

CallPilot enables you to get all the information you need from one source, whether through display-based telephone sets, your wireless set, your Windows desktop computer, a speech recognition interface, or another personal communications device.

### In this chapter

<a href="#"><u>About this guide</u></a>	13
<a href="#"><u>Finding your way around CallPilot</u></a>	25



# About this guide

## In this section

<u>Overview</u>	14
<u>Skills you need</u>	15
<u>How this guide is organized</u>	16
<u>Related information products</u>	18
<u>Conventions</u>	24

# Overview

## Introduction

The *Integrated AMIS Networking Implementation and Administration Guide* provides the information and procedures that are necessary to implement the Integrated Audio Messaging Interchange Specification (AMIS) Networking.

## Assumptions

This guide assumes that the Meridian Application Server has been correctly installed and is operational. If the application has not been installed, then install it before proceeding. For installation instructions, refer to the hardware installation guide appropriate to your server type.

If the server has been installed but is not operational, refer to the *Maintenance and Diagnostics Guide* for information on troubleshooting your system.

# Skills you need

## Introduction

You need certain skills and knowledge to use this guide effectively.

## Nortel Networks product knowledge

Knowledge of, or experience with, the following Nortel Networks products will assist you:

- previous releases of CallPilot
- Meridian Mail

## PC experience or knowledge

Knowledge of, or experience with, the following PC products will be of assistance. This guide does not document the following functionality:

- Microsoft Windows NT
- Microsoft Windows 95
- Microsoft Windows 2000

## Other experience or knowledge

Other types of experience or knowledge that may be of use include the following:

- switch configuration and operation (especially trunk group access restrictions [TGARs] and network classes of service [NCOS])
- network management
- client-server systems
- flowcharting
- troubleshooting

# How this guide is organized

## Introduction

The *Integrated AMIS Networking Implementation and Administration Guide* is organized in the sequence of tasks required to successfully implement Integrated AMIS Networking for CallPilot. Start at the beginning of the guide and work your way through it until all required tasks are completed.

## Contents

This guide contains the following chapters.

Chapter title	Description
<u><a href="#">Chapter 1, About CallPilot</a></u>	This chapter describes how to work with the CallPilot interface and how to use this guide.
<u><a href="#">Chapter 2, Getting started</a></u>	<p>This chapter provides an overview of Integrated AMIS Networking.</p> <p>This chapter describes the features supported by Integrated AMIS Networking and how Integrated AMIS Networking works.</p> <p>This chapter also provides a high-level overview of the tasks that are performed during implementation.</p>
<u><a href="#">Chapter 3, Gathering information</a></u>	This chapter explains how to gather the information required to implement Integrated AMIS Networking.
<u><a href="#">Chapter 4, Configuring the switch for Integrated AMIS Networking</a></u>	This chapter explains how to configure the switch for Integrated AMIS Networking.
<u><a href="#">Chapter 5, Configuring CallPilot for Integrated AMIS Networking</a></u>	<p>This chapter describes how to configure CallPilot for Integrated AMIS Networking.</p> <p>This chapter describes every box that must be completed and provides detailed procedures.</p>

<b>Chapter title</b>	<b>Description</b>
<u>Chapter 6. Adding sites to Integrated AMIS Networking</u>	<p>This chapter describes how to configure the local site. This chapter also describes how to add and configure every site in the messaging network that uses Integrated AMIS Networking to exchange messages with local sites.</p> <p>This chapter describes every box that must be completed and provides detailed procedures.</p>
<u>Chapter 7. Testing and backing up Integrated AMIS Networking</u>	<p>This chapter describes how to test the implementation of Integrated AMIS Networking to ensure that it is properly configured. This chapter also describes how to perform a backup of the system.</p>
<u>Chapter 8. Maintaining Integrated AMIS Networking</u>	<p>This chapter explains how to perform both regularly scheduled maintenance tasks and as-required maintenance tasks.</p>
<u>Chapter 9. Troubleshooting Integrated AMIS Networking</u>	<p>This chapter provides information to identify and solve problems with Integrated AMIS Networking.</p>

---

# Related information products

## Introduction

The following CallPilot technical documents are stored on the CD-ROM that you receive with your system. The documents are also available from the following sources:

- CallPilot Manager
- My CallPilot
- the Nortel Networks Partner Information Center (PIC) at <http://my.nortelnetworks.com>

You require a user ID and a password to access the PIC. If you do not have a PIC account, click Register to request an account. It can take up to 72 hours to process your account request.

You can print part or all of a guide, as required.

**Note:** To order the documents that are available in printed format, contact your Nortel Networks sales representative.

## Planning and migration guides

Use these guides before you install CallPilot to help plan your system, or to plan a migration of data from Meridian Mail to CallPilot:

<b>Document title</b>	<b>NTP number</b>
<i>Installation and Configuration Planner</i>	—
<i>Planning and Engineering Guide</i>	555-7101-101
<i>What's New Guide</i>	555-7101-901

## Installation and configuration guides

The following guides describe how to install the following:

- CallPilot server hardware and software
- desktop messaging and My CallPilot software

Document title	NTP number
<i>Desktop Messaging and My CallPilot Installation Guide</i>	555-7101-505
<p><i>Installation and Configuration Guide</i> for your server model</p> <p>This is a binder that contains the following five documents:</p> <ul style="list-style-type: none"> <li>■ <i>Part 1: Installation and Maintenance Overview</i></li> <li>■ <i>Part 2: &lt;Server model&gt; Server Hardware Installation</i></li> <li>■ <i>Part 3: &lt;Switch name&gt; and CallPilot Server Configuration</i></li> <li>■ <i>Part 4: Software Installation and Maintenance</i></li> <li>■ <i>Part 5: &lt;Server model&gt; Server Maintenance and Diagnostics</i></li> </ul>	Refer to the <i>CallPilot Installation and Configuration</i> binder for NTP numbers.

## Administration guides

The following guides provide specialized information to help you configure, administer, and maintain CallPilot, and use its features:

Document title	NTP number
<i>Administrator's Guide</i>	555-7101-301
<i>Reporter Guide</i>	555-7101-310
<i>Application Builder Guide</i>	555-7101-325

<b>Document title</b>	<b>NTP number</b>
<i>Desktop Messaging and My CallPilot Administration Guide</i>	555-7101-503
<i>Meridian Mail to CallPilot Migration Utility Guide</i>	555-7101-801

## Networking guides

The following guides describe how to plan, install, set up, and troubleshoot the CallPilot networking services:

<b>Document title</b>	<b>CallPilot release</b>	<b>NTP number</b>
<i>Networking Enhancements Guide</i>	2.0	555-7101-507
<i>Networking Planning Guide</i>	1.0	555-7101-100
<i>NMS Implementation and Administration Guide</i>	1.0	555-7101-302
<i>AMIS Networking Implementation and Administration Guide</i>	1.0	555-7101-303
<i>Enterprise Networking Implementation and Administration Guide</i>	1.0	555-7101-304
<i>Integrated AMIS Networking Implementation and Administration Guide</i>	1.0	555-7101-305
<i>VPIM Implementation and Administration Guide</i>	1.0	555-7101-306

**Note:** For instructions on how to configure the networking services on CallPilot, refer to the CallPilot Manager online Help.

## End user guides

The following guides are intended for CallPilot end users, such as telephone set users and desktop messaging users:

### **Document titles**

---

*Unified Messaging Quick Reference Card*

*Unified Messaging Wallet Card*

*Unified Messaging What's New Card*

*Command Comparison Cards*

*Menu Interface Quick Reference Card*

*Alternative Command Interface Quick Reference Card*

*Multimedia Messaging User Guide*

*Speech Activated Messaging User Guide*

*Desktop Messaging User Guides*

*My CallPilot User Guide*

---

## Troubleshooting

The *CallPilot Troubleshooting Reference* describes symptoms that can appear on all CallPilot server platforms, and describes ways to resolve them.

The *CallPilot Troubleshooting Reference* is intended for Nortel Networks distributors and technical support representatives; therefore, it is not part of the customer documentation package. Nortel Networks continually updates the *CallPilot Troubleshooting Reference*, which is available from the Nortel Networks Partner Information Center (PIC) at <http://my.nortelnetworks.com>.

You require a user ID and a password to access the PIC. If you do not have a PIC account, click Register to request an account. It can take up to 72 hours to process your account request.

**Note:** If you are not a Nortel Networks distributor, then contact your Nortel Networks technical support representative for assistance.

## Using online sources

### CallPilot administration online Help

The CallPilot Manager and CallPilot Reporter software contain administration online Help areas that provide access to

- technical documentation in Acrobat PDF format
- online Help topics in HTML format

To access online information, use either of the following methods:

- Click the orange Help button at the top of any page to access the Administration Help area.
- Click the grey Help button on any page to display a topic that relates to the contents of the page.

For more information about using these Help systems, access the CallPilot Manager Help, open the Getting Started book, and click “Navigating CallPilot Manager Help.”

The Application Builder software contains a Windows Help system as well as context-sensitive Help (available by clicking the ? button and then a field or label).

### **CallPilot end-user online Help**

The My CallPilot software contains a Useful Information area that provides access to the end-user guides in PDF format.

To access online Help for the currently selected My CallPilot tab, click the Help button on the upper-right corner of the My CallPilot page.

Desktop messaging provides product-specific Windows Help for groupware clients (Microsoft Outlook, Novell GroupWise, and Lotus Notes). The stand-alone version of CallPilot Player also provides addressing and troubleshooting information for Internet mail clients.

### **Contacting technical support**

Contact your distributor's technical support organization to get help with troubleshooting your system.

# Conventions

## Commands documented in procedures

As in many other Windows-based applications, in CallPilot you can execute a command in several ways. For example, to copy text you can choose any of the following methods:

- Select Copy from the Edit menu.
- Click the Copy button on the toolbar.
- Type the keyboard shortcut Control + C.

The procedures in this guide use only the first method: selecting a command from a menu.

## Navigation information in procedures

A **Getting there** statement precedes each procedure in this guide. This statement summarizes the steps you must take to navigate to the window or tab where you carry out the procedure.

All **Getting there** statements start at the Nortel System Management Interface (SMI) window. This assumes that you logged on and selected the appropriate system. Each item mentioned after the Nortel SMI window represents an icon, window or tab that makes up the path to the final destination.

### Example

To define special mailboxes, such as the broadcast mailbox, you must be on the Mailboxes tab.

### **Getting there** Nortel SMI > Meridian Application Server > CallPilot > Message Administration

After you double-click Messaging Administration, the Message Administration Properties sheet displays. Click the Mailboxes tab.

# Finding your way around CallPilot

## **In this section**

<a href="#"><u>Connecting to CallPilot</u></a>	26
<a href="#"><u>Multi-administrator access</u></a>	34
<a href="#"><u>Error handling in property sheets</u></a>	36
<a href="#"><u>Using the online Help</u></a>	39

# Connecting to CallPilot

## Introduction

To perform administrative tasks, or to build or work with CallPilot applications, you must first connect to the Meridian Application Server (the MAS server). The MAT Navigator and the System Management Interface (SMI) work together to give you access to your system and sites.


## Selecting a system-the MAT Navigator

The first step in logging in is to launch the MAT Navigator, which has its own password. The MAT Navigator connects your administration client to the MAS server. It displays all your sites and systems and enables you to select one to work on.



## Selecting a program—the System Management Interface (SMI)


When you select a system from the MAT Navigator, you are prompted for a second password. At this point, the SMI window for the selected system or site displays.



The SMI gives you quick and easy access to your system or sites. The SMI uses a navigation tree to display the system's hierarchy. In the tree, icons represent the folders and programs. Double-click a folder icon to view its contents. Folders can contain programs and other folders. Double-click a program icon to run the associated program.

### Selecting an object-list views

When you launch certain programs, the first thing you see is a list view. The list view displays all the objects of a certain type (such as mailbox classes) that are currently defined in the system. The list view includes predefined objects as well as those defined by an administrator. From the list view window, you can select a specific object to work on.



### **Viewing and changing properties**

Select an object and display its properties by

- double-clicking it or
- single-clicking it and selecting Properties from the File menu
- right-clicking it and selecting Properties from the popup menu

### **Entering data and choosing options-property sheets**

A property sheet is displayed when you view an object selected from a list view. Certain programs, such as Messaging Administration, display a property sheet immediately after launching. Property sheets have one or more tabs. Each tab has fields, referred to as boxes, in which you can type data or from which you can select options.

Most CallPilot property sheets look like the following:

**Basic Users - Mailbox Classes Properties** [?] [X]

Mailbox | Call handling | Media | Remote Notification | RPLs

Name: Basic Users

Comment: Basic Users

Storage

Voice storage limit: 0003 minutes

Delete read messages (voice): after: 05 days

Delete read messages (fax): after: 05 days

Block call answering when mailbox is full

Retain copy of sent messages

Revert DN set by telset


Max composed message length: 03:00 mm:ss

Max call answering message length: 02:00 mm:ss

Language for automated services: system primary

Save Cancel Print Help

Some property sheets are divided into two panes. When a box is checked in the left pane, the selected capabilities are enabled and you can access the associated tabs. Select a tab by clicking its name in the left pane or by clicking the tab in the right pane. These property sheets look like this:



### Mandatory boxes

If the name of a box is underlined, the box is mandatory, and you must fill it in. You cannot save if any mandatory boxes are empty.

## Common buttons

The following buttons appear on most property sheets:

Button	Description
Save	Saves all changes made on any of the tabs in a property sheet and closes the property sheet. Therefore, save only when you have made the necessary changes on all tabs.
Cancel	Closes the property sheet without saving any changes.
Print	Prints the contents of all tabs in the property sheet.
Help	Displays Help for the current tab. From this overview Help topic, you can access other Help topics, the index, and the search function.

## Using the toolbar buttons

For easier access, some of the more common tasks, such as Print and Save, are represented as buttons on the toolbar.

The following buttons are used throughout CallPilot. Buttons or icons specific to certain CallPilot functions, such as backups and archives, are documented in the relevant chapters.

Toolbar button	Description
	Saves any changes you have made and then transfers all the application's data to the server.
	Opens the Print dialog box and prints the active file or the objects you specify.
	Deletes the object you select.

Toolbar button	Description	
	Displays the properties of the object you select.	
	Displays the Help topics window.	
		Explains the next menu item or screen object you click. In a window, there is an arrow. On tabs or in dialog boxes, there is no arrow.
		Opens the New dialog box, where you identify the properties of the object you are creating. The button looks different in different applications.
		Displays the Open dialog box, where you select an object to open. The button is different in different applications.
	Reloads the current page and displays the changes you have made.	
	Enables you to select how the system displays icons.	

# Multi-administrator access

## Introduction

You can create multiple administrator accounts to make administering CallPilot easier and more efficient. Multiple accounts enable administration responsibilities to be distributed among a number of people. Therefore, certain administrators can specialize in certain tasks, such as maintaining users, performing backups, analyzing reports, or creating multimedia services.

## Access classes

For security reasons, administrators should be given access only to those parts of the system that relate to their role. For example, an administrator who is responsible only for creating multimedia services should have access only to Application Builder and the Service Directory Number Table.

Each administrator account is assigned an access class. An access class is a list of the parts of the system and the level of access allowed. The access levels are as follows:

- create/delete (enables an administrator to delete objects such as users and services)
- edit
- view
- none

For example, an administrator may be able to create or delete objects in Application Builder but only view User Templates.

## Simultaneous access

Multiple administrators can log in to CallPilot at the same time without overwriting other work.

If you are the first to log in to a particular resource, such as a specific mailbox class or user profile, and another administrator tries to access the same resource, a dialog box appears to inform you of the other administrator. At this point, you can do one of the following:

- Keep editing.
- Save your changes, and release the resource to the other administrator.
- Cancel your changes, and release the resource to the other administrator.

If you do not respond to this prompt within two minutes—because you are away from the terminal, for example—the system releases the resource so that others can access it. If this happens, all your unsaved changes are lost.

An administrator who accesses a resource that is currently being edited sees a read-only view of the property sheet in which all boxes are dimmed. This indicates that the resource is currently locked. The administrator is not notified when the resource is released, but must try to access the property sheet again to see whether its status has changed.

If a user tries to log on to a mailbox while an administrator is changing the profile, the user is unable to log on and receives a message that says the mailbox is in use.

## Refreshing screens

Because multiple administrators can access the same database at the same time, a Refresh command is available from the View menu to ensure that the view you are seeing is the most up-to-date.

For example, if you are viewing a list of users when another administrator deletes a user, the only way to see the change is to refresh the screen. You should, therefore, refresh the screen regularly.

# Error handling in property sheets

## Introduction

If you make certain types of errors while entering data, you are not able to save your changes until you correct the errors. For example, if you leave a mandatory box empty, you receive a message prompting you to fix it.

**Note:** These errors do not show up in the Event Browser or Alarm Monitor because the errors relate only to data entry and are not operational problems.

## How error handling works

There are two types of error messages.

### Type 1

If you get this type of error message, click OK, and then fix the problem described in the message before you try to save again.




## Type 2


If you get this type of error message, click OK to see a list of errors.



Double-click an error from the list. Your cursor is automatically placed in the box where the error was made so that you can correct it.



For example, if you double-click the second error, the Remote notification tab is displayed, with the cursor in the Target number box.



# Using the online Help

## Introduction

While administering or maintaining CallPilot, you may have questions about the purpose of certain boxes and buttons, or need more information about completing certain tasks. Online Help provides brief answers to the questions "What's this?" and "How do I...?"


## Context-sensitive Help

If you need to know the purpose of a particular box or button, use context-sensitive Help.

### To access context-sensitive Help

- 1 Click the  icon in a window or the  icon on a tab or in a dialog box.
- 2 Point to the box or button for which you want more information, and click.

**Result:** A pop-up description of the selected object is displayed.




## Procedures

If you need to know how to do something, you can access procedures to lead you through a task.

### High-level tasks

In some cases, high-level tasks take you through longer procedures. These tasks also provide you with navigation to the step-by-step procedures they include.

For example, setting up Delivery to Telephone requires several procedures. The high-level task summarizes these procedures. You click the gray buttons within the task to open the step-by-step procedures. The high-level task remains on your screen so that you can continue to use it to move through the procedures.



## Overview topics

Overview topics provide brief descriptions of tabs, features, and the tasks carried out from the tabs. However, the online guides contain more detailed feature descriptions.

### To access overview topics

Click the Help button on a tab.

## To find information in Help

You can look up procedures and overview topics in the following ways:

- 1 From the Help menu, select Help Topics.  
**Note:** You can also press F1 on the keyboard.
- 2 Go to one of the following tabs:
  - To see the table of contents of all the Help topics, select the Contents tab.
  - To look up a subject alphabetically, select the Index tab.
  - To do a full-text search to find topics that contain the words you enter, select the Find tab.

## chapter 2

---

# Getting started

Integrated AMIS Networking is one of the networking solutions offered by CallPilot. Integrated AMIS Networking uses the industry-standard AMIS analog protocol to exchange messages with AMIS-compliant systems that are configured in the local network database.

This chapter introduces Integrated AMIS Networking and provides a basic overview of the Integrated AMIS Networking implementation process.

### In this chapter

<u>About Integrated AMIS Networking</u>	45
<u>Implementing Integrated AMIS Networking</u>	55
<u>How Integrated AMIS Networking works</u>	61
<u>How Integrated AMIS Networking handles messages</u>	73
<u>Coordinating with the system administrator</u>	81



# About Integrated AMIS Networking

## **In this section**

<u>Overview</u>	46
<u>CallPilot and Integrated AMIS Networking</u>	51

# Overview

## Introduction


Integrated AMIS Networking is one of the networking solutions offered by CallPilot. This chapter introduces Integrated AMIS Networking and provides a basic overview of its implementation process.

You must be familiar with the basic concepts of messaging networks, dialing plans, and protocols. To review these concepts, consult the *Networking Planning Guide*.

## Definition: Integrated AMIS Networking

Integrated AMIS Networking is a CallPilot networking solution that is used to exchange messages between users at different sites in a private messaging network.

The following diagram is a conceptual illustration of how Integrated AMIS Networking works.



G100949.ej

## AMIS protocol

Integrated AMIS Networking uses the industry-standard analog Audio Messaging Interchange Specification (AMIS) protocol. Because it is standard protocol, AMIS can exchange messages with all AMIS-compliant messaging systems, regardless of vendor.

The AMIS protocol uses dual-tone multifrequency (DTMF) signaling. DTMF signaling is a global standard. Therefore, you can use Integrated AMIS Networking outside of North America.

**Note:** There are both analog and digital versions of the AMIS protocol, but CallPilot uses only the analog version. Therefore, AMIS refers to AMIS-Analog throughout this guide.

## Comparison with AMIS Networking

AMIS Networking is another networking solution offered by CallPilot. This solution also uses the AMIS protocol.

AMIS Networking is designed primarily for the exchange of messages with sites that are not part of the private messaging network. When a site is not included in the private messaging network, it is called an open site.

Integrated AMIS Networking, however, is used to exchange messages with sites that are part of the private messaging network. When a site is included in the private messaging network, it is called an integrated site.

Because Integrated AMIS Networking uses the AMIS protocol, it can also be used to send messages to open sites.

## Key terms

The following terms are used throughout this guide:

Term	Definition
Open	<ul style="list-style-type: none"> <li>■ Not defined in the network database</li> <li>■ Not part of the private messaging network, in most cases</li> </ul>
Integrated	<ul style="list-style-type: none"> <li>■ Defined in the network database</li> <li>■ Part of the private messaging network</li> </ul>
Network administrator	<ul style="list-style-type: none"> <li>■ Individual responsible for implementing and maintaining a site in the private messaging network</li> </ul>

**Note:** The term “virtual node,” which was used in Meridian Mail documentation, is replaced by the term “integrated site.”

## Relationship with AMIS Networking


The capability to exchange messages with open sites is inherent within Integrated AMIS Networking. That is, if you have Integrated AMIS Networking implemented on your local site, local users can send messages to other sites within the private messaging network, as well as to open sites.

## Complex network with Integrated AMIS Networking

You can implement Integrated AMIS Networking on a complex messaging network that combines several networking solutions. A messaging network is often both open and private, combining various protocols.

The following diagram illustrates a complex network that includes Network Message Service (NMS), Enterprise Networking, AMIS Networking, and Integrated AMIS Networking.

Because Enterprise Networking is implemented in this messaging network, every site has a unique site ID number.



G101139.e

While the sites have more than one networking solution implemented, only one protocol is used between any two sites (for example, Site 4 and Site 2 must agree on which protocol to use).

In this example, Site 1 implements VPIM Networking to exchange messages with an open site. Since the VPIM protocol is not used by Site 1 to communicate with any other site within the private messaging network, Site 1 does not implement Integrated AMIS Networking.

## When to use this guide

Use the *Integrated AMIS Networking Implementation and Administration Guide* if you use the AMIS protocol to exchange messages with integrated sites. You can also use this guide if you use the AMIS protocol to exchange messages with open sites.

If you use the AMIS protocol to exchange messages with open sites only, use the *AMIS Networking Implementation and Administration Guide*.

# CallPilot and Integrated AMIS Networking

## Introduction

Integrated AMIS Networking supports most of the features offered by CallPilot.

## Integrated AMIS Networking features

The following table lists the CallPilot features that are supported by Integrated AMIS Networking.

For detailed information about CallPilot features, consult the *Basic Administration Guide*.

CallPilot feature	Supported	Notes
Call Sender	Yes	Call Sender can be used for both call answering and composed messages from Integrated AMIS Networking users if <ul style="list-style-type: none"> <li>■ the mailbox numbering plan follows the dialing plan, or</li> <li>■ a remote user is added for the network user</li> </ul>
Names Across the Network	No	
Name Addressing	Yes	This feature is available if users at the remote site are defined as remote users at the local site.
Name Dialing	Yes	This feature is available if users at the remote site are defined as remote users at the local site.
Personal Distribution Lists	Yes	Integrated AMIS Networking addresses can be included in a user's PDL.

<b>CallPilot feature</b>	<b>Supported</b>	<b>Notes</b>
Shared Distribution Lists	Yes	A remote user is required. A network address cannot be entered into the Shared Distribution List unless the address corresponds to a remote user.
Multiple Recipients	No	
Reply To	No	
Reply All	No	A message has only one recipient.
User's Actual Personal Verification	Yes	The user's actual personal verification is not carried across sites.
Administrator-Recorded Personal Verification	No	An administrator can record a personal verification for remote users who are defined at the local site.
Remote Site Spoken Names	Yes	A spoken name can be recorded for each remote switch location during configuration.
Private Tag	No	AMIS does not support private message tags. For this reason, messages tagged as private are returned to the sender with a non-delivery notification.
Acknowledgment Tag	Yes	Acknowledgment tags indicate that the message was delivered to the remote system, not that it was listened to.
Urgent Tag	Yes	Users can tag a message as urgent, and the system treats it as urgent for prioritizing delivery. However, the recipient of an urgent message does not know it was tagged as urgent.

<b>CallPilot feature</b>	<b>Supported</b>	<b>Notes</b>
Economy Tag	Yes	Users can tag a message as economy, and the system treats it as economy for prioritizing delivery. However, the recipient of an urgent message does not know it was tagged as economy.
Received Time Announced	Yes	The time when the message was deposited into the mailbox is announced to the recipient.
Sent Time Announced	No	
120-Minute Messages	No	Message body length is limited to eight minutes. Messages longer than eight minutes are not sent, and a non-delivery notification is sent to the originator.
Sender's Name (Text)	Yes	
Recipient's Name (Text)	Yes	If the recipients are defined as remote users, their names are provided.
Message Subject (Text)	No	
Sender's Department	No	
Timed Delivery	Yes	



# Implementing Integrated AMIS Networking

## **In this section**

<u>Overview</u>	56
<u>Implementation in a complex messaging network</u>	60

# Overview

## Introduction

Planning is critical to successfully implement Integrated AMIS Networking. Before you begin to implement Integrated AMIS Networking, you must understand the basic implementation process and know what information to provide.

The process for planning the implementation of a CallPilot networking solution is described in detail in the *Networking Planning Guide*. The following overview assumes that you are familiar with this description.

## Before you begin

The following assumptions are made:

- The switch is installed and configured.
- Sufficient trunks that connect the switch to a public switch are available.
- CallPilot is installed and configured, except for networking.
- If it is part of the local site, Network Message Service (NMS) is fully implemented.
- If implementation is an upgrade from Meridian Mail, all legacy information is available or is migrated.
- Contact is made with the network administrators of the remote sites.

Fulfill all of these requirements before you continue with the implementation of Integrated AMIS Networking.

## Implementation steps

To implement Integrated AMIS Networking, you must complete the following steps:

- Gather information for the network.
- Configure the switch for Integrated AMIS Networking.
- Configure CallPilot for Integrated AMIS Networking.
- Configure CallPilot for AMIS Networking if this functionality is also required.
- Add and configure the sites that use Integrated AMIS Networking to the local network database.
- Test and back up the network.

## Gather information for the network

The first step in implementing Integrated AMIS Networking is to gather the information required during the configuration. You must gather information about

- the switch configuration
- the remote sites

You must also create a network representation.

### Gather information from the switch

Much of the information you need to implement Integrated AMIS Networking is available in the switch database.

For example, before you begin to implement networking, the switch is set up to make telephone calls to all the remote sites. The dialing plan exists in the switch database. You must reflect the dialing plan settings when you configure CallPilot for networking.

Ask the administrator who is responsible for the switch configuration to provide this dialing plan information.

## **Create the messaging network representation**

You need information about the other sites in the messaging network to create a messaging network representation.

You must create a detailed representation. This representation, which is your blueprint for implementation, shows the relationship between all sites.

## **Configure the switch**

The switch must be set up and configured at your site before you begin to implement Integrated AMIS Networking. However, you must check the configuration and ensure that it is properly configured for Integrated AMIS Networking.

The only additional switch configuration necessary for Integrated AMIS Networking is the creation and setting of phantom DNSs.

## **Configure CallPilot**

The network database contains information about your messaging network. When you configure CallPilot, you add information to the network database. You must add the following information to configure CallPilot:

- general information about the message delivery configuration
- detailed information about the local site: information about how the server handles messages and how the switch handles messages
- detailed information about each remote site that communicates with the local site using Integrated AMIS Networking

## **Validate the configuration**

When you implement Integrated AMIS Networking, you add configuration information about the messaging servers and switch locations to your network database.

Before you add this information, CallPilot validates the information to ensure that there are no conflicts.

## Keep records

As you plan and implement Integrated AMIS Networking, it is important to keep detailed records about your site.

These records

- Provide a source of information for support personnel.
- Share information about the site with other network administrators.

## Test the network

When you complete the configuration of Integrated AMIS Networking, you perform a test suite. This test suite ensures that the configuration is correct and that Integrated AMIS Networking is working properly.

## Back up the network

When you successfully complete the test suite, you perform a backup. The backup ensures that no configuration information is lost in the event of system failure.

## See also

If you need additional information about the general implementation process, consult the *Networking Planning Guide*.

The *Networking Planning Guide* provides a more detailed discussion about the preliminary requirements, how to create network diagrams, and how to maintain a network history.

# Implementation in a complex messaging network

## Introduction

Integrated AMIS Networking is usually part of a complex messaging network that combines several CallPilot networking solutions.

## Order of implementation

If you are implementing any other CallPilot networking solutions on your site, you will make the process easier to understand and manage by following the correct order of implementation.

The implementation of each networking solution builds upon earlier implementations. Information is often configured only once, and all subsequent networking solutions that are implemented use this configuration.

## Recommended order

The recommended order for implementation is

- Network Message Service (NMS)—if the local site is an NMS site
- Integrated AMIS Networking
- Enterprise Networking
- VPIM Networking

### AMIS Networking

If your local site exchanges messages with both integrated and open sites, implement Integrated AMIS Networking only. Integrated AMIS Networking also contains the functionality of AMIS Networking.

Implement AMIS Networking by following the procedures in the *AMIS Networking Implementation and Administration Guide* only if your local site exchanges messages with open sites exclusively.

# How Integrated AMIS Networking works

## In this section

<a href="#"><u>About Integrated AMIS Networking messages</u></a>	62
<a href="#"><u>About Integrated AMIS Networking parameters</u></a>	64
<a href="#"><u>About AMIS Networking parameters</u></a>	68
<a href="#"><u>Understanding Integrated AMIS Networking settings</u></a>	71

# About Integrated AMIS Networking messages

## Introduction

You use Integrated AMIS Networking to exchange messages with sites in a messaging network. When you implement Integrated AMIS Networking, you configure the system to handle these messages in a particular way.

An understanding of the basic components of a message makes the implementation process and configuration of CallPilot easier to understand.

## Integrated AMIS Networking message

Every Integrated AMIS Networking message contains two parts:

- a message header
- the recorded message

### Message header

The message header transmits to the receiving site with DTMF signals. The header contains the following information:

- the sender's address (which includes the system access number and the mailbox number)
- the recipient's address (mailbox number)
- the system access number
- the type of message (regular, acknowledgment, or non-delivery notification [NDN])
- the priority applied to the message (private, urgent, or acknowledgment)

### Message body

The recorded message and spoken name are played over the voice port of the sending site and are recorded by the receiving site. The recorded message contains the following information:

- the voice portion of the message
- any attachments

## Message priorities

The sender can assign a message priority to an Integrated AMIS Networking message. There are three priorities:

- economy
- standard
- urgent

One message priority, usually standard, is the default. Users must assign another message priority manually.

### Configuration required for each message priority

The message priority tag that is assigned to a message determines how CallPilot handles the message.

When you implement Integrated AMIS Networking, you configure the scheduling parameters that determine how messages with different message priority tags are handled.

In general, you send economy messages during lower long-distance toll charge periods. You send urgent messages quickly, with the emphasis on speed rather than cost.

# About Integrated AMIS Networking parameters

## Introduction

You set Integrated AMIS Networking parameters during the implementation process. These parameters work with internal CallPilot settings to control how Integrated AMIS Networking works.

Before you begin the implementation process, you must understand these parameters and decide on their settings.

## Parameters set during implementation

CallPilot uses scheduling parameters to determine when to send messages to remote sites. CallPilot uses the following scheduling parameters:

- batch threshold
- stale times
- economy message priority delivery start and stop times

## Parameter default values

CallPilot provides default settings for all scheduling parameters. The default values are based on typical requirements.

To ensure a quick implementation process, use these default values.

After your system is operational, monitor usage to determine if the default settings are serving the needs of your users. You can modify the scheduling parameters whenever users' needs change.

For all default values, see “Defaults” on page 124.

## Batch threshold

The batch threshold is the number of standard and urgent messages that are held in queue waiting for delivery to a single remote site. When you send messages in batches, you make more efficient use of system resources. However, to ensure that messages awaiting delivery are not held too long in the queue, the holding time overrides the batch threshold. A message is held in a batch until either the batch threshold is exceeded or the holding time for standard or urgent messages is reached.

Batch thresholds apply only to standard and urgent messages.

## Holding time

Holding time is the period of time that a message is held in queue before CallPilot attempts delivery. CallPilot holds a message in queue while it awaits the arrival of more messages for the same destination. This bulk sending makes more efficient use of the system.

However, to ensure that messages are always delivered in a timely fashion and do not wait too long for the arrival of additional messages, they are held for only a set period of time. This is the holding time.

CallPilot computes the holding time internally, based on the stale time.

### Standard message holding time

The holding time for standard messages is one-third of the stale time for standard messages.

### Urgent message holding time

The holding time for urgent messages is one-tenth of the stale time for urgent messages.

## Stale time

Stale time determines how long an undeliverable message is held within the system before being returned to the sender with a non-delivery notification (NDN).

You set stale times independently for economy, standard, and urgent messages. Typically, the stale time for a standard message is longer than the stale time for an urgent message, because it may be critical for a user to know that an urgent message was not delivered.

The following examples are based upon an Integrated AMIS Networking site that uses the default values.

### Example 1

Milo Feinstein sends a standard message. The message is held in the queue awaiting the arrival of three more messages. However, when the message has waited in queue for 40 minutes (the holding time for standard messages), the message is sent.

### Example 2

Ronnie Prakesh and Philippe Dumont are users at the same site. Ronnie sends three standard messages for users at the remote site in Newmarket. Her messages are held in the queue. Philippe sends a message to a user at the same remote site. The batch threshold is reached, and all four messages are sent.

### Example 3

Barney Gumbolski sends an urgent message. It is held in queue. No other messages for the same remote site arrive within six minutes (the holding time for urgent messages). Barney's urgent message is sent.

## **Economy delivery start and stop times**

Economy messages are handled differently from standard and urgent messages. Economy messages are collected and are sent only during designated times, rather than held in queues.

The delivery start and stop times determine when the system sends economy messages to their destinations.

Economy messages usually have a start time that corresponds to the beginning of lower-rate telephone charges, and a stop time set to the resumption of regular rates.

### **Example**

The following example is based on an Integrated AMIS Networking site that uses the current default values.

At 8:00 a.m., Marge Sampson sends an economy message to a remote site. The message is held in queue until the economy delivery start time. The message is held in queue for a total of 16 hours. The economy message stale time is large enough to take this into account.

# About AMIS Networking parameters

## Introduction

The functionality of AMIS Networking is inherent within Integrated AMIS Networking. When you implement Integrated AMIS Networking, you decide if the local site can use this functionality, which enables users to exchange messages with open sites.

If your local site uses the AMIS Networking functionality, you must also configure the Open AMIS parameters that determine how messages to open sites are handled.

## Why these parameters are important

The Open AMIS parameters are important because they determine how CallPilot sends AMIS messages to open sites.

Since Open AMIS messages can incur long-distance toll charges, it is especially important that you consider how these parameters are set.

## Open AMIS parameters

The parameters that apply to Open AMIS messages are

- economy message stale time
- Open AMIS compose prefix
- economy delivery start and stop times
- Open AMIS delivery times

## Economy message stale time

The economy message stale time for Open AMIS messages functions in the same way as the economy message stale time for Integrated AMIS messages.

## Open AMIS compose prefix

The Open AMIS compose prefix is a number that alerts CallPilot that the rest of the number to be entered is an AMIS address.

The AMIS compose prefix must not conflict with any other prefixes used in the system, such as the name dialing prefix or the VPIM prefix.

### Example

A local user logs in to CallPilot and enters 75 to compose a message. The user enters the Open AMIS compose prefix (in this example, 13). The system is alerted that this message is being addressed to an open site. The user enters the system access number and the mailbox number to complete the address.

## Economy delivery start and stop times

The economy delivery start and stop times for Open AMIS messages are similar in concept to the times for integrated AMIS economy messages.

However, because Open AMIS messages may incur long-distance toll charges, you must set these carefully.

Open AMIS economy messages often have a delivery start time that corresponds to the start of lower long-distance toll charges and a stop time that corresponds to the resumption of regular rates.

### Possible conflicts

The various scheduling parameters may conflict with each other. Therefore, when you set the Open AMIS delivery times, ensure that messages cannot become stale before they are delivered.

## Open AMIS delivery times

The Open AMIS delivery times determine the hours when Open AMIS messages are delivered during business days and nonbusiness days.

In some countries, these settings have legal ramifications. Open AMIS messages are directed to telephones automatically. If you address the message incorrectly, the unintended recipient may be disturbed at an inappropriate time. Therefore, computer-generated calls, such as Open AMIS messages, are legally allowed only during specific times of the business day.

If your country has these regulations in place, configure the Open AMIS delivery times to conform to the regulations.

# Understanding Integrated AMIS Networking settings


## Introduction

Sites within the messaging network that use Integrated AMIS Networking to communicate use system access numbers (SANs) and networking connection DNs to initiate and establish sessions.

## Relationship of a system access number to a connection DN

The following diagram shows the relationship of a system access number to a connection DN.

A system access number becomes a connection DN in the network database record of a remote messaging server.



G100990.eps

## How connection DNs work

The system access number uniquely identifies a site that uses Integrated AMIS Networking.

When you send a message to an integrated site, the local site looks up the connection DN for that remote site and initiates the network call. The local site identifies itself to the remote site by including its own system access number in the message header.

The receiving site takes that system access number and searches its own network database for a connection DN that matches the system access number.

### **If a match is found**

The receiving site identifies the sending site if it finds a connection DN that matches the system access number it received. When the recipient listens to the message, the sending site is identified.

### **If a match is not found**

If the receiving site does not find a connection DN that matches the system access number it received, it treats the message as an Open AMIS message sent from a remote site that is not part of the private messaging network. When the recipient listens to the message, the sending site is identified only as an open site.

## Coordinated information

You must coordinate the information you need to exchange messages. A local site must gather information from every remote site with which it intends to exchange messages. You must give your local system access number to remote network administrators. These administrators enter your local system access number as a connection DN when they configure your site as a remote site in their network databases.

# How Integrated AMIS Networking handles messages

## In this section

<u>Overview</u>	74
<u>What the MTA does</u>	76
<u>What the ANA does</u>	79
<u>How a message is transferred</u>	80

# Overview

## Introduction

The scheduling parameters that you configure during the implementation of Integrated AMIS Networking work with internal CallPilot networking settings. These internal settings are controlled by the

- Message Transfer Agent (MTA)
- Analog Networking Agent (ANA)

This brief overview provides a general understanding of how Integrated AMIS Networking handles messages to help you interpret Alarm and Event reports.

## MTA responsibilities

The MTA provides many of the basic maintenance functions required by CallPilot networking. The MTA is responsible for the following services:

- Queue outgoing network messages.
- Determine when to begin sending messages to a remote system.
- Receive incoming messages for delivery to local users.
- Collect networking traffic Operational Measurements (OM) reports.

To ensure the timely handling of messages, the MTA wakes up CallPilot every minute.

When it wakes up, the MTA does the following:

- initiates calls to remote sites
- checks for stale messages
- checks if any sites are in error status

### **MTA Monitor**

The MTA Monitor continuously watches the performance of the MTA. The MTA Monitor provides detailed information and is useful for regular maintenance and troubleshooting.

For complete information about the MTA Monitor and how it is used, consult the relevant section in the *Support Tools Guide*.

### **ANA responsibilities**

The ANA send messages to and from remote systems.

There is one ANA for every active port used during an Integrated AMIS Networking session.

### **Main steps of message transfer**

There are three main steps in the message transfer process:

- The Message Transfer Agent determines if the message is ready for transfer.
- The Analog Networking Agent completes a communication process, known as handshaking, with the receiving site.
- The message, which consists of the message header and the message body, is transferred.

# What the MTA does


## Introduction

The Message Transfer Agent (MTA) handles most aspects of message transmission for CallPilot.

## How MTA and ANA handle messages

The following diagram is a graphical representation of how CallPilot handles Integrated AMIS Networking messages.

The diagram shows the activity of both the MTA and the ANA in message handling.



G100969.eps

As the diagram indicates, the MTA handles most of the processing. Every minute, a scheduler wakes the MTA. The MTA scans the message queue for each destination, and checks the status of messages awaiting delivery. This scan determines if there are valid messages, according to the system parameter configuration. The MTA then determines if the valid messages are ready for delivery, according to the set system parameters.

Once the MTA determines that a transmission session is needed, it seeks a method of delivery from the call router. The ANA assumes responsibility for delivering the message.

# What the ANA does

## Introduction

The Analog Networking Agent (ANA) works with the MTA to handle messages.

## How the ANA sets up calls

The ANA calls a remote site and delivers messages.

CallPilot originates a network call to the receiving site using the connection directory number (DN) defined for that site. The switch places the call according to switch call-processing parameters.

If the call is successful, the call terminates on the networking connection DN at the receiving site.

### **If the call is not successful**

If the call fails due to a busy or no-answer condition, CallPilot waits until the next wake-up interval before it attempts the call again. If three consecutive attempts fail, CallPilot places the receiving site into error status and an alarm is generated, depending on the nature of the problem.

CallPilot waits for one hour before it repeats the three-call attempt cycle.

### **When connection is established**

When connection between the sending and receiving sites is established, ANA initiates a communication process known as handshaking.

# How a message is transferred

## Introduction

After the ANA successfully establishes a message transfer session, the message transfer begins.

The message contains the message header and the recorded message.

## Message transfer process

The following table describes how messages are transferred:

The sending site	The receiving site
uses DTMF tones to send the message header to the integrated site. The message header contains:	receives the DTMF tones, interprets the tones, and creates the message.
<ul style="list-style-type: none"> <li>■ the sender’s mailbox number without location prefixes</li> <li>■ the sender’s system access number</li> <li>■ the recipient’s mailbox without location prefixes</li> </ul>	
plays the voice portion of the message across a voice port.	records the message body and adds it to the message.
repeats these steps for each message the sending site must send.	repeats these steps for each message.
<b>Note:</b> The maximum number of messages in a transfer session is five.	
terminates the message transfer session.	hangs up.

# Coordinating with the system administrator

## In this section

<u>Overview</u>	82
<u>Assigning a Restriction/Permission List for AMIS Networking messages</u>	86

# Overview

## Introduction

If the local site uses the AMIS Networking functionality that is inherent within Integrated AMIS Networking, and if you allow local users to send messages to open sites, you must establish user access.

You must carefully control user access, because long-distance toll charges may be incurred when messages are sent to open sites.

## Levels of control

There are two basic levels of control:

- When you define message delivery parameters, you define general system-wide controls over AMIS Networking messages.
- However, when you define different classes of users with basic administration, you define the access level individual users have to AMIS Networking.

## Basic administration

Basic administration tasks include setting up the following:

- users
- mailboxes
- mailbox classes
- Restriction/Permission Lists (if messages are sent to open sites)

### See also

For detailed information on each basic administration task, consult the *Basic Administration Guide*.

## Purpose of basic administration

With basic administration you can be more precise about how you want AMIS Networking to be used.

This precision is important because AMIS Networking can send messages outside of the private messaging network, which may result in long-distance toll charges. Therefore, controlling the access of users can result in considerable cost savings.

### Example: Basic administration settings

You implement Integrated AMIS Networking and enable AMIS Networking as well. You configure your site to send and receive AMIS Networking messages. However, you restrict this ability to specific groups of users only.

## Mailbox class settings


You control a user's access to AMIS Networking, in part, by the mailbox class to which the user is assigned.

The following options for each mailbox class are available only if AMIS Networking is implemented:

- default message priority—standard or economy
- permission for exchange of messages with open sites
- Restriction/Permission List for open messages, if you allow users to send messages to open sites

You must set the AMIS Networking options for each mailbox class.

**Getting there** Nortel SMI > Meridian Application Server > User Administration > Mailbox Classes > Call Handling tab



**To set the default message priority**

To set the default message priority as standard, select Standard.

To set the default message priority as economy, select Economy.

## **To control the exchange of open networked messages**

- 1** To enable this mailbox class to send messages to open sites, select the Compose/send check box.
- 2** To enable this mailbox class to receive messages from open sites, select the Receive check box.
- 3** If you have enabled this mailbox class to send messages to open sites, set the Restriction/Permission List.

For instructions on how to set a Restriction/Permission List, see “Assigning a Restriction/Permission List for AMIS Networking messages” on page 86.

# Assigning a Restriction/Permission List for AMIS Networking messages

## Introduction

If you allow local users to exchange messages with open sites, create any necessary Restriction/Permission Lists for AMIS Networking. A Restriction/Permission List defines any restrictions to access and also lists any exceptions to these restrictions.

### Example

Local users can send messages to open sites. However, you want to ensure that different classes of users can send messages only to specific sites. Users with a manager-level mailbox class can send messages to any site. Users with a summer student mailbox class can send messages to any open site that does not incur long-distance toll charges.

## Purpose

A Restriction/Permission List provides additional security and prevents unauthorized long-distance toll charges.

## Creating a Restriction/Permission List

Usually, you will assign a pre-existing Restriction/Permission List. However, if no pre-existing list satisfies your requirements for AMIS protocol messages, you can create a new list.

## See also

For detailed procedures on creating a Restriction/Permission List, consult the *Basic Administration Guide*.

## chapter 3

---

# Gathering information

This chapter describes how to gather the information required to implement Integrated AMIS Networking. This chapter provides a checklist for all information that is needed about the switch configuration.

This chapter also describes how to gather information about the other sites in the messaging network, and how to convert this information into a messaging network representation.

### **In this chapter**

Information required

89



# Information required

## In this section

<u>Overview</u>	90
<u>Switch information</u>	91
<u>Information required from switch</u>	93
<u>Evaluating the switch information</u>	96
<u>Information from other sites</u>	97
<u>Messaging network representation</u>	98

# Overview

## Introduction

Before you can begin to implement Integrated AMIS Networking, gather the information you require. You will speed up the implementation process if you have this information before you begin. When you analyze the information and look for inconsistencies and incompleteness, you ensure that potential problems are resolved.

### Required information

You must gather two types of information:

- local site information, especially about the switch configuration information and dialing plan
- messaging network information that is provided by all remote sites

## Why gather information?

The gathered information is used to

- Identify the sites in the messaging network.
- Identify how the sites relate to each other.
- Identify the dialing plan used by each switch in the network.
- Determine if the dialing plan on one or more switches in the network must be modified to support the networking solutions of CallPilot.
- Create a messaging network representation.
- Prepare for CallPilot configuration.

## Information about open sites

If local users exchange messages with open sites, gather the system access numbers of these open sites.

You also need the system access number of at least one open site that you can use when you test your implementation. Coordinate with the administrator of a remote open site before you begin to test the implementation.

# Switch information

## Introduction

When you begin to implement Integrated AMIS Networking, the switch is already correctly installed and configured, and is operational for CallPilot.

This means that the switch is set up for dialing among the sites in the messaging network. The dialing plans that are configured on the switch for making telephone calls between sites are also used to exchange messages among sites.

You must check the configuration to make sure it is suitable for Integrated AMIS Networking.

## Gathering dialing plan information

You need the dialing plan information that is configured on the switch. You must know the dialing plan used in the messaging network and how all sites dial one another.

The easiest way to gather this information is to ask the switch technician or system administrator.

### **Gathering information directly from the switch**

Gathering information directly from the switch is not recommended. The information that you require is found on several switch configuration files called overlays. Finding the information can be difficult and time-consuming.

If you must gather the information from the switch, consult your switch documentation for the proper procedures and detailed descriptions of the information in each overlay.

## **Confirming settings**

Usually, when the switch is configured, the switch technician addresses the impact of messaging on the switch.

However, to ensure that there will be no problems, you must confirm that the configuration suits the needs of Integrated AMIS Networking and can handle your anticipated volume of traffic.

If you discover that changes are necessary, you must complete these changes before you proceed with the implementation of Integrated AMIS Networking.

# Information required from switch

## Introduction

You must gather information about the switch. You must verify that the switch supports networking. You use some of the information, such as dialing plan information, to configure CallPilot.

Gather information from

- the local prime switch location
- the remote switch locations (prime and satellite)

**Note:** If the local site is an NMS site, you must also gather information from each satellite switch location. For instructions on how to gather this information, consult the *NMS Implementation and Administration Guide*.

## Gather information about used features only

Most of the information that you gather from the switch is related to the dialing plan.

Gather information about a dialing plan only if a dialing plan is being used. Do not gather the information if the dialing plan is installed on the switch but is not currently being used.

**Example:** Your switch has both ESN and CDP installed. However, only ESN is used. Do not gather CDP information.

## Local prime switch location information checklist

You need the following information from the switch configuration:

- name or physical location of switch (useful to name the switch location on CallPilot)
- dialing plan used
  - Electronic Switched Network (ESN)
  - Coordinated Dialing Plan (CDP)
  - hybrid dialing plan, combining ESN and CDP
  - another dialing plan, such as public switched telephone network
- if ESN or hybrid dialing plan is used:
  - ESN access code
  - ESN location codes
    - local switch location
    - remote switch locations
  - overlap of location codes with extension numbers
- if CDP or hybrid dialing plan is used:
  - CDP steering codes
    - local switch location
    - remote switch location
  - overlap of steering codes with extension numbers
- confirmation that sufficient trunks are available for anticipated networking traffic
- confirmation that restrictions are suitable for networking (for example, trunk group access restrictions [TGAR])
- range of extension numbers used at the local site (for example, 7000–7999)
- information about existing CDNs and phantom DNs that are defined on the switch

## Remote switch location information checklist

For each remote site in the messaging network, you need the following information about each switch location (prime and satellite):

- name or physical location of switch (useful to name the switch location on CallPilot)
- dialing plan used
  - Electronic Switched Network (ESN)
  - Coordinated Dialing Plan (CDP)
  - hybrid dialing plan, combining ESN and CDP
  - another dialing plan, such as public switched telephone network
- if ESN or hybrid dialing plan is used:
  - ESN access code
  - verify the ESN location codes
    - local switch location
    - remote switch locations
  - overlap of location codes with extension numbers
- if CDP or hybrid dialing plan is used:
  - CDP steering codes
    - local switch location
    - remote switch location
  - overlap of steering codes with extension numbers
- range of extension numbers used at the local site (for example, 7000–7999)
- confirmation that all extension numbers at this switch location can be dialed *directly* from the local switch
- confirmation that all extension numbers at this switch location can be dialed in the *same* way

# Evaluating the switch information

## Introduction

When you have the dialing plan information from all switches in the messaging network, review the information to ensure that you do not have to make any changes to switch configurations.

## Mandatory requirement

The dialing plans of all switches in the network must have a uniform, or standardized, dialing plan.

A uniform dialing plan means that users on all switches dial the same way to reach the same recipient.

There is only one exception to this rule: ESN access codes can be different.

You need a uniform dialing plan to dial users on other switches within the messaging network and at public sites.

A uniform dialing plan offers the following benefits:

- The network is easier to configure and maintain.
- Future growth of the network is allowed.

## Configuring dialing plan information

You need extensive switch programming experience to configure dialing plan information on a switch.

### **ATTENTION!**

---

If you determine that changes to the dialing plan configuration are necessary, ask a switch technician to confirm your conclusion and make the necessary changes.

## See also

You can find detailed information on dialing plan configuration in your switch documentation.

# Information from other sites

## Introduction

Implementation of a networking solution is a coordinated effort. Many decisions must be made before implementation begins.

Gather the following information before you begin to implement Integrated AMIS Networking:

- site names
- Enterprise site IDs, if Enterprise Networking is implemented in the messaging network
- fully qualified domain names (FQDNs) of servers
- the protocol used between the local site and all remote sites
- the dialing plan used between the local site and all remote sites
- connection DNs for each site that uses the AMIS protocol to exchange messages with the local site

If any remote sites are NMS sites, also gather the following information for each satellite switch location:

- switch location name
- switch type
- location ID

# Messaging network representation

## Introduction

A messaging network representation provides a complete summary of your messaging network. This representation contains information about each of the sites and indicates the relationship between each pair of sites.

If sufficiently detailed, a messaging network representation is the primary source of information for implementing a messaging network.

The more detail you can supply, the easier you will find the implementation process.

A diagram is the most suitable form of representing most messaging networks. A spreadsheet is more appropriate for large messaging networks.

## Definition: Messaging network diagram

A messaging network diagram is a graphical representation of your network. It includes the following types of information:

- all sites in the network
- the protocols implemented at each site
- the protocol used between sites
- location codes and names
- dialing plan information

## Definition: Messaging network spreadsheet

A spreadsheet is more appropriate for representing a large messaging network. It provides the same information as the diagram.

## Benefits

There are many benefits to creating a representation of your messaging network. A representation

- offers a clear view of how your network is connected
- gathers all the required information in one source
- provides a useful means of planning future modifications
- helps during the analysis of traffic issues
- reveals areas for improvement
- provides support personnel with a concise, clear view of your network

## Coordinating efforts

Administrators of other sites must provide much of the information for your network representation. For example, you need to know the site name and other information of every site.

Although each site administrator creates a representation, ideally one site administrator should create a final version to distribute to all sites. This ensures that the representation is comprehensive and that each site uses the same information for implementation.

## Protecting the representation

Your network representation contains sensitive information. Keep it properly stored and protected as part of standard security procedures.

## See also

For detailed instructions on how to create a network representation, as well as for several examples, consult the relevant section in the *Networking Planning Guide*.



## chapter 4

---

# Configuring the switch for Integrated AMIS Networking

This chapter describes how to configure the switch to implement Integrated AMIS Networking. This chapter introduces the concepts that are necessary to understand the configuration process and provides detailed configuration procedures.

### **In this chapter**

Configuring the switch

103



# Configuring the switch

## In this section

<u>Overview</u>	104
<u>SDN Table and Integrated AMIS Networking</u>	106
<u>Adding and configuring SDNs</u>	112
<u>Phantom DNs and Integrated AMIS Networking</u>	116

# Overview

## Introduction

The switch provides the call handling for CallPilot.

When you implement Integrated AMIS Networking, the switch is already installed and configured, and is operational. It is ready for the implementation of Integrated AMIS Networking.

There are two steps in the configuration process. On the server, you must set up inbound and outbound service directory numbers (SDNs) for Integrated AMIS Networking. On the switch, you must set up phantom directory numbers (DNs).

## Before you begin

Review the information that you gathered. Confirm the settings to ensure that they are correct.

Before you begin to implement Integrated AMIS Networking, complete and test any required changes to the switch settings.

## How the switch views an Integrated AMIS Networking call

The switch handles an Integrated AMIS Networking message from the local site to a remote site like any other outbound telephone call.

The switch is already configured to handle outbound telephone calls.

## Integrated AMIS Networking requirements

Like all services, however, Integrated AMIS Networking needs a route that connects the messaging server and the switch.

Integrated AMIS Networking requires only one additional configuration on the switch. A phantom DN is required.

**See also**

For detailed information about the switch, consult your switch documentation.

For information about how CallPilot works with the switch and how the switch must be configured, consult the relevant section in the *Advanced Administration Guide*.

# SDN Table and Integrated AMIS Networking

## Definition: SDN

A service directory number (SDN) is a number that enables a user to access a CallPilot service. Each SDN must be unique so that CallPilot can identify the requested service and play the appropriate prompts.

## SDN Table

The system automatically creates the Service Directory Number Table during the initial installation of CallPilot. The SDN Table lists all SDNs and provides details about their settings.

CallPilot uses the SDN Table to map directory numbers (DNs) to services. The SDN Table lists both inbound and outbound SDNs.

## Inbound and outbound SDNs

CallPilot requires both inbound and outbound SDNs.

You must manually add an inbound SDN. An outbound SDN is created automatically if Integrated AMIS Networking is installed. Both the inbound and the outbound SDNs require additional configuration.

### Inbound SDNs

For most services, an inbound SDN is a number that a user enters to access a service. However, the Integrated AMIS Networking inbound SDN is not a directly dialable number. A remote system dials this SDN when it delivers an Integrated AMIS Networking message.

### Outbound SDNs

CallPilot uses an outbound SDN to make the requested service available. An outbound SDN consists of the word OUTBOUND and a number.

## Example: SDN Table

The following illustration shows an SDN Table that lists both inbound and outbound Integrated AMIS Networking SDNs.

Service DN	Application Name	Media Type	Minimum Channels	Maximum Channels	Comments
4750	Voice Messaging	Voice	0	Default Max.	
4751	Multimedia Messag...	Fax	0	Default Max.	
4763	Enterprise Network...	Voice	0	Default Max.	
4764	AMIS Networking	Voice	0	Default Max.	
4765	Fax Item Maintena...	Fax	0	Default Max.	Shared with AMIS & EN.
8899	Multimedia Messag...	Fax	0	Default Max.	
OUTBOUND10	AMIS Networking	Voice	0	Default Max.	
OUTBOUND11	Multimedia Messag...	Voice	0	Default Max.	
OUTBOUND15	Multimedia Messag...	Fax	0	Default Max.	
OUTBOUND18	Multimedia Messag...	Voice	0	Default Max.	
OUTBOUND6	Multimedia Messag...	Voice	0	Default Max.	
OUTBOUND7	Multimedia Messag...	Voice	0	Default Max.	
OUTBOUND8	Multimedia Messag...	Fax	0	Default Max.	
OUTBOUND9	Enterprise Network...	Voice	0	Default Max.	

If another service shares the inbound Integrated Networking SDN, that service appears in the SDN Table.

When you review an SDN Table, the only way you know if an SDN is shared is by the description. For this reason, the description of the SDN should mention that it is shared with the inbound Integrated AMIS Networking SDN.

## SDN numbers

An SDN must be unique, but it is not randomly selected. CallPilot uses SDNs to map numbers to services. There are also important relationships between the SDN and other numbers used by the system.

### Relationship of SDN to other numbers

The CallPilot SDN setup echoes the DN settings on the switch.

An important relationship exists between the inbound SDN and the local system access number (SAN), and the phantom DN on the switch. For example,

- The inbound Integrated AMIS Networking SDN = 7400.
- The phantom DN for Integrated AMIS Networking = 7400.
- The Integrated AMIS Networking local SAN = 1-416-597-7400.

The Integrated AMIS inbound SDN on CallPilot must correspond to the Integrated AMIS phantom DN on the switch. Before you create an SDN for Integrated AMIS Networking, confirm the phantom DN on the switch.

To view the phantom DN setting, consult the gathered switch information.

## Phantom DNs

There are two ways to create an Integrated AMIS Networking phantom DN on the switch:

- Define a new phantom DN for Integrated AMIS Networking.
- Share an existing phantom DN of specific services.

## Media type

To process a call, Integrated AMIS Networking needs access to a channel. A channel provides a connection between the switch and the Digital Signal Processor (DSP) cards on the CallPilot server.

CallPilot supports three channel types. Each type corresponds to different media:

- voice
- fax
- speech recognition

Integrated AMIS Networking can use all three channel types. However, a voice channel is recommended. By default, CallPilot automatically assigns a voice port to Integrated AMIS Networking.

## Minimum and maximum channels

You must determine the channel resources for both inbound and outbound Integrated AMIS Networking SDNs.

Every service, including Integrated AMIS Networking, requires channel resources to process calls. Channel resources are the number of channels that Integrated AMIS Networking has available. Channel resources are set as minimum and maximum values. The minimum value is the number of channels that is always reserved for the exclusive use of the service.

This setting is important because, if you incorrectly allocate channel resources, users may experience delays in reaching requested services.

### **Example: Channel allocation**

Your system has 96 available channels. You decide to dedicate a minimum of 5 channels and a maximum of 30 channels to Integrated AMIS Networking. If the system handles only 5 Integrated AMIS Networking calls each day, a more appropriate allocation is a minimum of 1 channel and maximum of 3 channels.

## Examples: How to use inbound and outbound Integrated AMIS Networking SDNs

The following examples describe a network that consists of two sites, and show how to use the inbound and outbound Integrated AMIS Networking SDNs to provide services.


In these examples, it is important to distinguish between messages sent by users and calls made by the CallPilot system itself.

### Example 1: Shared SDN

This example illustrates how to use a shared inbound SDN.

Howard wants to send a message to Joy in Chicago. He enters 6060, which is directed to the SDN for Integrated Voice/Fax. The request is directed to CallPilot, which routes it to the outbound Integrated AMIS Networking SDN. The system in Philadelphia calls the remote SAN of the system in Chicago, 64447080, and the two systems complete the required handshaking before the message is transferred.

The Voice Menu SDN, which is shared with the inbound Integrated AMIS Networking SDN, receives the message. The Voice Menu SDN is set to act when it receives an AMIS initiator tone. The message is directed to Joy's mailbox.




G100994.eps

## Example 2: Unique SDN

This example illustrates how to use an inbound Integrated AMIS Networking SDN that is not shared.

Joy wants to send a message to Howard in Philadelphia. She enters 7070, which is directed to the SDN for Integrated Voice/Fax. The request is directed to CallPilot, which routes it to the outbound Integrated AMIS Networking SDN. The system in Chicago calls the remote SAN of the system in Philadelphia, 63386080, and the two systems complete the required handshaking before the message is transferred. The inbound Integrated AMIS Networking SDN receives the message and directs it to Howard's mailbox.



G100992.eps

## See also

For detailed information on SDNs and SDN Tables, consult the relevant sections in the *Advanced Administration Guide*.

# Adding and configuring SDNs

## Integrated AMIS Networking SDNs

Integrated AMIS Networking requires an outbound SDN and an inbound SDN.

### Outbound SDN

An outbound SDN is created automatically when you install Integrated AMIS Networking. You can modify the default channel resource allocation.

### Inbound SDN

An inbound SDN is not created automatically. There are two ways to set up an inbound SDN:

- Create a new inbound SDN.
- Share an inbound SDN with certain other services.

The choice depends on your administrative requirements.

<b>Do this</b>	<b>If the primary concern is</b>
Create new SDNs.	Operational Measurement reports must be precise for each service.
Share SDNs with other services.	A shortage of DNs exists or is likely to exist.

## Services that can share an inbound SDN with Integrated AMIS Networking

Integrated AMIS Networking can share the inbound SDN of the following services:

- Announcement Service
- Enterprise Networking
- Fax Information Service
- Voice Menu

- Time of Day Controller
- Thru-Dial

**Getting there** Nortel SMI > Meridian Application Server > System Configuration > Service Administration > Service Directory Number

## To add and configure a new inbound SDN

- 1 From the SDN Table, select New from the File menu.

**Result:** The New Inbound Service Directory Number Properties dialog box appears.

The screenshot shows a dialog box titled "New Inbound Service Directory Number Properties - CallPilot on MAS...". It has three tabs: "General", "Session Profile", and "Callback Handling". The "General" tab is selected. The dialog contains the following fields and controls:

- Service DN:** A text input field.
- Application:** A section containing:
  - Application ID:** A text input field with the value "10".
  - Application Name:** A dropdown menu showing "AMIS Networking".
- Multimedia Channels and Media:** A section containing:
  - Media Type:** A dropdown menu showing "Voice".
  - Minimum Channels:** A text input field with the value "0".
  - Maximum Channels:** A text input field with the value "0".
  - Use Default Maximum:** An unchecked checkbox.
- Comments:** A large text area with a scroll bar.
- Buttons:** "Save", "Cancel", and "Help" buttons at the bottom.

- 2 On the General tab, enter the SDN number in the Service DN box.

**Note:** This number must correspond to a CDN or phantom DN on the switch.

- 3 Select an application from the Application Name list.

**Result:** The corresponding application ID appears in the Application ID box.

- 4 Select the type of channel required by the service in the Media Type list.

- 5 If you want to reserve a minimum number of channels for the service, enter the number in the Minimum Channels box.
- 6 Do one of the following:
  - Select the Use Default Maximum box. This is the recommended option.
  - Enter the maximum number of channels that a service can use at one time in the Maximum Channels box.

**Note:** The maximum number of channels cannot exceed the total number of channels available on the server. If you enter a number larger than the total number of channels, a warning box appears asking you to change the number.
- 7 Enter any comments in the Comments box.
- 8 Click Save to add the SDN to the SDN Table.

## To share an existing inbound SDN with Integrated AMIS Networking

- 1 Select an existing inbound SDN that can be shared with Integrated AMIS Networking from the SDN Table.
- 2 On the File menu, click New.

**Result:** The New Inbound Service Directory Number Properties dialog box appears.
- 3 On the General tab, in the Comments box, insert a brief comment that the SDN is shared with Integrated AMIS Networking.

**Tip:** This comment appears in the final column of the SDN Table and is the easiest way to determine which SDN is shared with Integrated AMIS Networking.

- 4 Click the Session Profile tab.

The screenshot shows a dialog box titled "New Inbound Service Directory Number Properties - CallPilot on MAS...". It has three tabs: "General", "Session Profile", and "Callback Handling". The "Session Profile" tab is selected. The dialog contains the following fields and controls:

- Session time limit: 10 minutes (with up/down arrows)
- Maximum invalid password entries: 10 (with up/down arrows)
- Mailbox number: (empty text field)
- Act on AMIS/Enterprise networking initiator tone
- Language: English(American) (dropdown menu)
- Fax setting section:
  - Fax selections: Maximum number: 5 (with up/down arrows)
  - Page limit for fax items: 40 (with up/down arrows)
  - Sender fax number: (empty text field)
  - Sponsor fax item: Import... (button)
  - Billing DN: (empty text field)
  - Page transmission error handling:  Continue  Retransmit
  - Fax delivery options: Callback (dropdown menu)

At the bottom of the dialog are three buttons: "Save", "Cancel", and "Help".

- 5 Select the Act on AMIS/Enterprise networking initiator tone box.

**Note:** You select this option only for the SDN that is being shared with the inbound Integrated AMIS SDN.

- 6 Click Save to add the shared SDN to the SDN Table.

# Phantom DNs and Integrated AMIS Networking

## Switch setting required for Integrated AMIS Networking

SDNs on the server have a direct correspondence to phantom directory numbers (DNs) on the switch.

If you create a new SDN for Integrated AMIS Networking, you need a phantom DN for Integrated AMIS Networking. If you share an existing SDN for Integrated AMIS Networking with an existing service, Integrated AMIS Networking also shares the phantom DN of that service.

## Integrated AMIS Networking uses DNs

To access a CallPilot service, a user enters a unique dialable number. The dialable number is known as a directory number (DN). There are different types of DNs, including extension numbers and telephone numbers.

The switch uses the DN to route the call to the requested service.

### Example

A user enters a DN, 7505, to access Remote Notification.

## Switch and DNs

All DNs that you use to access a service correspond to a setting on the switch. To handle calls in sequence of arrival, the system places calls in a queue, depending on the call type.

The switch has as many as three queues, called controlled directory number (CDN) queues, which you use for the following types of services:

- Voice Messaging
- Fax Call Answering
- Speech Recognition Messaging

Each CDN queue is associated with a dialable number known as the CDN. A user can dial the service directly by entering the CDN.

**Example**

The CDN of Voice Messaging is 7400. A user can dial 7400 to reach Voice Messaging. The call is placed into the queue.

**Phantom DNs**

While there are queues for three types of services, CallPilot users usually have many individual services available within each type. These services are also dialable.

To offer more than three services, the switch uses phantom DNs.

A phantom DN is a unique dialable number that is routed to one of the CDN queues.

A phantom DN is not a randomly selected number. There is a direct correspondence between the local system access number (SAN) for Integrated AMIS Networking and the phantom DN.

If Integrated AMIS Networking shares an existing phantom DN, check that the phantom DN is configured to forward messages to the correct CDN queue. For Integrated AMIS Networking, the phantom DN should forward messages to the Voice Messaging CDN queue.

**Example**

The phantom DN for Express Messaging is 7401. A user dials 7401 and expects to reach the requested service. However, the switch routes the phantom DN to the appropriate CDN queue (in this case, Voice Messaging) before the service is provided.

**Integrated AMIS Networking phantom DN**

Integrated AMIS Networking requires a phantom DN for incoming messages.

However, unlike other phantom DNs, it is not dialed by a local user when exchanging a message with an Integrated AMIS Networking site. The system uses this number when an Integrated AMIS Networking message must be sent to a remote site.

Users at remote sites also use the phantom DN when they make a call to a local system.

## Ways to create the phantom DN

There are two ways to create a phantom DN for Integrated AMIS Networking:

- Use a unique phantom DN. Most switch technicians create additional phantom DNs for use by services like Integrated AMIS Networking.
- Share an existing phantom DN. If Integrated AMIS Networking shares a service directory number (SDN) with another service, it also shares the phantom DN of the service.

## See also

For a detailed description of how the switch is configured for CallPilot, consult the *Advanced Administration Guide*.

## chapter 5

---

# Configuring CallPilot for Integrated AMIS Networking

This chapter describes how to configure CallPilot to implement Integrated AMIS Networking.

The chapter introduces the concepts that are necessary to understand the configuration process and provides detailed descriptions of configuration procedures.

### **In this chapter**

[About configuring CallPilot](#)

121



# About configuring CallPilot

## In this section

<a href="#"><u>Overview</u></a>	122
<a href="#"><u>Configuration summary</u></a>	123
<a href="#"><u>Message delivery parameters—AMIS 1 tab</u></a>	126
<a href="#"><u>Message delivery parameters—AMIS 2 tab</u></a>	131
<a href="#"><u>Configuring the message delivery parameters</u></a>	135
<a href="#"><u>Enabling AMIS Networking functionality</u></a>	137
<a href="#"><u>Creating a loopback mailbox</u></a>	140

# Overview

## Configuring CallPilot

The implementation of Integrated AMIS Networking requires additional configuration of CallPilot. This configuration determines how Integrated AMIS Networking exchanges messages with other sites in the messaging network.

To configure CallPilot for Integrated AMIS Networking, you must

- Confirm CallPilot administration settings.
- Define Integrated AMIS Networking information.
- Create a loopback mailbox.

### **ATTENTION!**

---

You must perform each step in the configuration process in the order presented.

## Before you begin

Complete the switch configuration before you configure CallPilot.

If your Integrated AMIS Networking site is an NMS network, NMS should be configured and tested.

# Configuration summary

## Introduction

The Integrated AMIS Networking message delivery configuration determines how Integrated AMIS Networking handles messages.

You provide this information on two tabs of the Message Delivery Configuration dialog box:

- AMIS 1
- AMIS 2

## Required information

When you complete the AMIS 1 and AMIS 2 tabs, the following are required:

- enabled outgoing and incoming Integrated AMIS Networking
- defined local AMIS system access number
- batch threshold
- economy delivery times
- stale times

## See also

For a general overview of how Integrated AMIS Networking uses this information, see the section “How Integrated AMIS Networking works” on page 61.

## Open AMIS boxes

As you configure the Integrated AMIS Networking message delivery information, you will see several boxes for configuring Open AMIS.

If users at the local site exchange messages with open sites, you must also configure the Open AMIS boxes.

## Defaults

CallPilot provides default settings for the message delivery configuration. The default values are based on typical requirements.

To simplify the process of implementing Integrated AMIS Networking, use the default values. After your system is operational, monitor usage and performance to determine if the default settings are sufficient. You can modify the settings whenever users' needs change.

<b>Parameter</b>	<b>Current default</b>
Batch threshold	4 messages
Stale time for standard messages	2 hours
Holding time for standard messages	40 minutes (calculated internally, based on stale time settings)
Stale time for urgent messages	60 minutes
Holding time for urgent messages	6 minutes (calculated internally, based on stale time settings)
Stale time for economy messages	6 hours
Delivery start time for economy messages	6:00 p.m.
Delivery stop time for economy messages	11:00 p.m.

## **Suggested process**

You should read through this section on configuring Integrated AMIS Networking information. The settings that you select determine how efficiently your system handles Integrated AMIS Networking messages.

Ideally, know how you are going to complete the required information before you begin the configuration.

## **Before you begin**

You must properly configure the inbound and outbound SDNs for Integrated AMIS Networking before you configure Integrated AMIS Networking.

# Message delivery parameters—AMIS 1 tab

## Introduction

To implement Integrated AMIS Networking you must set the parameters that CallPilot uses to deliver messages.

These parameters are set on the Message Delivery Configuration AMIS 1 and AMIS 2 tabs.

## AMIS 1 tab

The following shows the Message Delivery Configuration—AMIS 1 tab.

The screenshot shows a dialog box titled "Message Delivery Configuration - CallPilot on MAS Server - T...". It has four tabs: "AMIS 1", "AMIS 2", "Enterprise", and "SMTP / VPIM". The "AMIS 1" tab is selected.

Inside the dialog, there are two checked checkboxes: "Outgoing AMIS Networking" and "Incoming AMIS Networking".

Below these is a section for "Local AMIS System Access Number". It contains two radio buttons: "Public network" (unselected) and "Private network" (selected). To the right of the "Public network" radio button are three input fields labeled "Country", "Area / City", and "Number". To the right of the "Private network" radio button is a single input field.

Below this section is a "Collect" field with a spinner box set to "1" and the text "messages before sending ( Batch Threshold )".

At the bottom is a "Stale Times" section with four time input fields (hh:mm) and spinners:

- Standard: 2:00 hh:mm
- Economy Open AMIS: 23:59 hh:mm
- Urgent: 1:00 hh:mm
- Economy Integrated AMIS: 23:59 hh:mm

At the very bottom of the dialog are four buttons: "Save", "Cancel", "Print", and "Help".

## Outgoing and incoming AMIS

If Integrated AMIS Networking is installed on your system, the following options are enabled by default:

- Outgoing AMIS Networking
- Incoming AMIS Networking

These boxes restrict the use of Integrated AMIS Networking. They also restrict the use of AMIS Networking.

If you do not want local users to send outbound Integrated AMIS Networking messages, clear the Outgoing AMIS Networking option.

If you do not want local users to receive inbound Integrated AMIS Networking messages, clear the Incoming AMIS Networking option.

To completely disable Integrated AMIS Networking, clear both options.

## Local AMIS system access number

CallPilot requires a system access number (SAN) to initiate and establish network calls.

The system access number uniquely identifies an Integrated AMIS Networking site in a messaging network.

There are two types of system access number:

- public network
- private network

### Public network local AMIS system access number

If your site has a public network system access number, your site can be reached from the public telephone switch network and the private messaging network.

The use of a public network system access number allows more systems to connect to your site.

### **Private network local AMIS system access number**

If your site has a private network system access number, your site can be reached only from the private messaging network.

Use a private network system access number if your messaging network is not connected to, or plans to connect to, systems over the public telephone switched network.

The use of a private network system access number is uncommon.

### **Batch threshold**

When you batch messages, you send messages that are intended for a single destination in a group. This method makes more efficient use of the system than if you send each message separately.

The batch threshold defines the maximum number of messages intended for a single destination that can be queued before CallPilot begins to send the messages.

The batch threshold applies only to standard and urgent message types.

The batch threshold overrides the CallPilot holding times.

### **Stale times**

Stale time is the period of time that CallPilot holds an undelivered message before it considers the message undeliverable and returns it to the sender with a non-delivery notification (NDN). In the period before a message is considered stale, CallPilot makes repeated attempts at delivery.

Stale time is expressed as a time period, such as 10 minutes or 5 hours.

Separate stale times are set for economy, standard, and urgent messages. The stale time for urgent messages should be the shortest time, because it is critical to know if an urgent message is not delivered.

Set a stale time for economy Open AMIS messages if local users send AMIS Networking messages to open sites.

## Stale time settings affect holding times

CallPilot uses stale time settings to calculate holding times.

The holding time is the period of time that a message is held in queue before an attempt is made to send it.

### Urgent messages

For urgent messages, the holding time is one-third of the stale time.

For example, if you set the urgent stale time to 30 minutes, the urgent message holding time is automatically set to 10 minutes.

### Standard messages

For standard messages, the holding time is one-tenth of the stale time.

For example, if you set the standard stale time to 5 hours, the standard message holding time is automatically set to 30 minutes.

## Holding times interact with the batch threshold

The interaction of the holding time and the batch threshold ensures that messages are delivered in a timely and efficient manner. A message is sent when the batch threshold is reached or when the holding time is reached, whichever is sooner.

# Message delivery parameters—AMIS 2 tab


## Introduction

You complete the configuration of the Integrated AMIS Networking delivery parameters on the AMIS 2 tab.

Complete this tab for Integrated AMIS Networking. Complete all Open AMIS fields to enable the functionality of AMIS Networking.

### AMIS 2 tab

The following shows the Message Delivery Configuration—AMIS 2 tab.



## Open AMIS compose prefix

If users are exchanging messages with open sites, provide the Open AMIS compose prefix. This number alerts the system that the number about to be entered is an Open AMIS address.

The Open AMIS compose prefix must not conflict with any other prefixes used in the system, such as the name dialing prefix or the VPIM prefix.

## Economy delivery start and stop times

An economy message is a message that a user tags for economy delivery.

Economy messages are treated differently from standard and urgent messages. Economy messages are collected through the day and sent only during designated times, rather than held in queues. The delivery start and stop times determine when the system sends economy messages to their destinations.

Economy messages often have a start time set to the beginning of lower-rate telephone services, and a stop time set to the resumption of regular rates.

Set two delivery times for economy messages:

- start time
- stop time

### Example

If the telephone rate is lower between 11:00 p.m. and 6:00 a.m., set the start time at 11:00 p.m. and the stop time at 5:55 a.m.

## Open AMIS delivery times

If local users send AMIS Networking messages to sites that are not part of the messaging network, you must define the Open AMIS delivery times.

Open AMIS delivery times determine how AMIS Networking messages are handled during business and nonbusiness days. In some countries, these settings have legal ramifications.

Open AMIS Networking messages are considered computer-generated calls. Since they are sent to recipients who are not part of the private messaging network, there is a risk of disturbing the wrong recipient.

For this reason, many countries legally allow computer-generated calls only during set times of the business day.

If your country has these regulations in place, configure the Open AMIS delivery times.

If your country does not have these regulations, or if your local site does not send AMIS Networking messages to sites that are not part of the messaging network, do not configure the Open AMIS delivery times.

# Configuring the message delivery parameters

## Introduction

You must configure the parameters that determine how your system handles messages.

You configure these parameters on the Message Delivery Configuration AMIS 1 and AMIS 2 tabs.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration > AMIS 1 tab

## To configure Integrated AMIS Networking parameters

- 1 To enable your site to send outgoing Integrated AMIS Networking messages, ensure that the Outgoing Integrated AMIS Networking check box is selected.
- 2 To enable your site to receive incoming Integrated AMIS Networking messages, ensure that the Incoming Integrated AMIS Networking check box is selected.
- 3 Select the type of network used by the local AMIS system access number.
- 4 If you use a public network system access number, enter the country code, the area/city code, and the system access number.  
  
If you use a private system access number, enter the number used to dial the local site.
- 5 Enter the batch threshold in the Collect (number of) messages before sending (Batch Threshold) box.
- 6 Enter the stale times for each message type:
  - Standard
  - Urgent
  - Economy Integrated AMIS
- 7 To continue the configuration, click the AMIS 2 tab.

- 8 Enter the Integrated AMIS economy delivery start and stop times in the Start Time and Stop Time boxes.
- 9 To enable AMIS Networking functionality, complete the Open AMIS boxes on the AMIS 1 and AMIS 2 tabs, as described in “Enabling AMIS Networking functionality” on page 137.

For Integrated AMIS Networking functionality only, click Save.

**Result:** The information is validated and saved to the network database.

# Enabling AMIS Networking functionality

## Introduction

If your local site sends messages to open sites you must configure all Open AMIS boxes.


**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration > AMIS 1 tab

## To configure AMIS Networking

- 1 On the AMIS 1 tab, enter the Open AMIS stale time.
- 2 On the AMIS 2 tab, enter the Open AMIS compose prefix for AMIS Networking capabilities.
- 3 Enter the economy delivery start and stop times.

- 4 Click the Define Open AMIS delivery times button for AMIS Networking capability.

**Result:** The Delivery Times dialog box appears.



- 5 In the Business Days column, select the days of the week that are normal business days for your organization.
- 6 In the Non Business Days column, select the days of the week that are considered nonbusiness days for your organization.
- 7 Enter the Business Days delivery start and stop times in the Delivery Time from: and to: boxes.
- 8 Enter the nonbusiness days delivery start and stop times in the Delivery Time from: and to: boxes.

**9** Click Save.

**Result:** The Delivery Times dialog box closes and you return to the AMIS 2 tab. The information is validated and saved in the network database.

## What's next?

After you configure CallPilot for Integrated AMIS Networking, create a loopback mailbox.

Every site in the messaging network requires a loopback mailbox that remote network administrators can use to test their systems. You will use the loopback mailboxes created by remote network administrators to complete your testing.

Although it is not mandatory, it is recommended that you create a loopback mailbox at this time.

# Creating a loopback mailbox

## Introduction

When you implement Integrated AMIS Networking, create a loopback mailbox. Although it is not mandatory to create the loopback mailbox at this time, completing this task now will save you considerable time later.

## Definition: Loopback mailbox

A loopback mailbox is a mailbox that is created at each site in a messaging network. You use a loopback mailbox to test the capability of a site.

To test that a site can send a message to a remote site, a message is sent to the loopback mailbox. The loopback mailbox automatically returns the message to the sender.

Remote sites use your loopback mailbox to test their systems. You use the loopback mailboxes of each remote site to test your system.

Since each site requires a loopback mailbox, create one now so that the testing can proceed without interruption.

## Loopback mailbox requirements

A loopback mailbox is not a real mailbox because it does not collect messages. It bounces messages back to the sender. However, the loopback mailbox number must be unique and cannot conflict with any other mailbox number.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Messaging Administration Properties > Mailboxes tab

### To create a loopback mailbox

- 1 In the Networking Loopback mailbox box, enter the mailbox number.
- 2 Click Save.

**Result:** The information is validated and saved to the database.

### Announce the loopback mailbox

Remote network administrators test their implementation by sending an Integrated AMIS Networking message to your loopback mailbox. Announce the loopback mailbox number to all remote sites.

Similarly, gather the loopback mailbox numbers from the network administrators of all other remote sites.

### Using the loopback mailbox

A remote administrator addresses a test message to a loopback mailbox using the protocol and dialing plans specified for use between the two sites.

For example, you create a loopback mailbox, 9999, on Site 6. Integrated AMIS Networking is used between Site 4 and Site 6. The ESN dialing plan is used, and the ESN prefix to address Site 6 from Site 4 is 3555. Therefore, to address your loopback mailbox, the network administrator at Site 4 enters 35559999.

### See also

For more information on creating mailboxes and assigning them a class of service, consult the *Advanced Administration Guide*.



## chapter 6

---

# Adding sites to Integrated AMIS Networking

This chapter describes how to define the sites in the messaging network that exchange messages with the local site using Integrated AMIS Networking.

This chapter describes how to configure the local messaging server and prime switch location. It also explains how to add and configure remote messaging servers and switch locations.

### **In this chapter**

<u>About the messaging network</u>	145
<u>Configuring the local site</u>	151
<u>Adding and configuring a remote site</u>	173



# About the messaging network

## In this section

<u>Overview</u>	146
<u>Configuration and other networking solutions</u>	147

# Overview

## Introduction

A CallPilot messaging network consists of a local site and one or more remote sites.

All sites in your private messaging network with which your local site exchanges messages must appear in the Messaging Network Configuration tree view. If a remote site is part of the messaging network, but the local site does not exchange messages with that remote site using Integrated AMIS Networking, you do not add it to the tree view during the implementation of VPIM Networking.

To implement Integrated AMIS Networking, configure the local site and add and configure all remote sites that will transfer messages with the local site using Integrated AMIS Networking.

### **ATTENTION!**

---

It is strongly recommended that you complete each step in the configuration process in the order presented.

## See also

Sites are configured in the Messaging Network Configuration tree view. For an overview of how to work with the tree view, consult the relevant section in the *Networking Planning Guide*.

## Before you begin

You should have already configured the Message Delivery Configuration dialog box for Integrated AMIS Networking.

If your local site is an NMS site, NMS should be configured and tested.

Your messaging network representation should be complete and available. This representation provides a blueprint for the implementation process.

# Configuration and other networking solutions

## Introduction

If any other CallPilot networking solution is installed on your local system, much of the local messaging server and the local switch configuration work is already complete.

## Configuring the local messaging server and switch location

If another networking solution is installed on the local site, the local messaging server and prime switch location configuration is almost entirely complete. You must only confirm the settings and enter the information that is specifically required to implement Integrated AMIS Networking.

## NMS local site

If your local site is an NMS site, implement and test NMS before you begin to implement Integrated AMIS Networking.

If NMS is installed, the NMS satellite switch locations for the local site appear in the Messaging Network Configuration tree view below the local prime switch location.


## Remote sites

If another CallPilot networking solution is implemented on your system, remote sites may already be added and configured. These sites appear in the Messaging Network Configuration tree view. These sites communicate with the local site using the other networking solution.

When you implement Integrated AMIS Networking, you must add and configure the remote sites that will communicate with your local site using Integrated AMIS Networking. These sites appear in the tree view only as you add them.

### Example: Implementing Integrated AMIS Networking

In this example, you are the network administrator of Site 6. Working with the network administrators of the other sites, you have created a diagram of your messaging network. Note that many details are removed from this network diagram for clarity.



G101139.e

Your local site has the following networking solutions: Integrated AMIS Networking, AMIS Networking (available because Integrated AMIS Networking is implemented), NMS, and Enterprise Networking.

Since you are following the recommended order of implementation, you have implemented and tested NMS.

To implement Integrated AMIS Networking, you add the following remote sites to your network database because you use the AMIS protocol to exchange messages with them:

- Site 3
- Site 4
- Site 5—satellite switches are also added

Your site is set up to exchange messages with an open site that is not part of your messaging network. When you set the Integrated AMIS Networking message delivery configuration parameters, you also complete all Open AMIS boxes.

After you implement and test Integrated AMIS Networking, you implement Enterprise Networking. During this implementation, you add Site 1 and Site 2 to the Messaging Network Configuration tree view because you use the Enterprise Networking protocol to exchange messages with these sites.



# Configuring the local site

## In this section

<a href="#"><u>Overview</u></a>	152
<a href="#"><u>Configuring the local messaging server</u></a>	154
<a href="#"><u>Configuring the local prime switch location</u></a>	159
<a href="#"><u>Configuring ESN information</u></a>	165
<a href="#"><u>Configuring CDP information</u></a>	169

# Overview

## Introduction

When CallPilot is initially installed on your system, a local messaging server and local switch location are automatically added to the Messaging Network Configuration tree view.

## Local messaging server name

By default, both the local messaging server and the prime switch location are assigned the name “Untitled.” Assign new names to the local messaging server and the prime switch location during configuration.

The local site receives its name from the name assigned to the local messaging server.

## Configuration

You must configure the local messaging server. To configure a messaging server, you save general information about the messaging server, such as name and description, to the network database.

The local messaging server is configured on the General tab of the Local Server Properties dialog box.

## SMTP/VPIM Server FQDN

The SMTP/VPIM Networking Server FQDN box is enabled only if VPIM Networking is installed on your system. It is configured during the implementation of VPIM Networking.

However, if the box is enabled on the General tab, you must enter a placeholder in the box or you will be unable to close the tab and save the information to the network database.

While implementing Integrated AMIS Networking, enter a placeholder in this box. You will replace this placeholder with the correct server FQDN when you implement VPIM Networking.

## **Configuring the local server if another messaging solution is implemented**

If you have implemented another CallPilot networking solution on your local system, you have already completed the local messaging server configuration.

No additional configuration is required for Integrated AMIS Networking.


# Configuring the local messaging server

## Introduction

You must configure the local messaging server to implement Integrated AMIS Networking.

If another networking solution is implemented, the configuration of the local messaging server is complete. You must only check the information.

The local messaging server is configured on the Local Server Properties—General tab.



## **Name**

By default, both the local messaging server and the prime switch location are assigned the name “Untitled.” Assign new names during configuration.

The messaging server is usually given a name that corresponds to its geographic location.

### **Local site name**

The name given to the local messaging server becomes the name of the local site.

## **Server type**

The local messaging server is always CallPilot.

## **Description**

Provide a brief description of the messaging server, or implementation notes, such as when the server was configured or who completed the configuration, in the Description box.

## **Send Messages to all other Servers**

The Send Messages to all other Servers check box determines if the local site can send messages to integrated remote sites in the messaging network.

This check box is selected by default and is cleared only under exceptional circumstances.

When cleared, the local messaging server does not send messages to any integrated remote site using any protocol. Messages can still be sent to open remote sites.

### **When to clear this option**

This option lets you quickly disable messaging from your local site. Clear this check box in emergency situations.

## Restricting messages to individual sites

Clearing the Send Messages to all other Servers check box is a quick way to disable the system.

You restrict the sending of messages to each remote site separately.

To prohibit the local messaging server from sending messages to a particular remote site, clear the Send Messages to this Server check box on the Remote Messaging Server Properties—General tab.

For example, your messaging network has six sites. You do not want to send messages to one of these sites. You select the Send Messages to all other Servers option while you configure the local messaging server. You clear the Send Messages to this Server box while you configure the remote server to which you do not want to send messages.

**Note:** When the Send Messages to all other Servers box is cleared, users can still send messages to open sites using the VPIM and AMIS protocols.

## Add/Update Remote Users on this Server

The Names Across the Network feature is available with Enterprise Networking only.

The Add/Update Remote Users on this Server check box enables the Names Across the Network feature to work with Enterprise Networking.

If enabled, this check box was configured during the implementation of Enterprise Networking.

## Enterprise Site ID

The Enterprise Site ID box is enabled only if Enterprise Networking is implemented on your local messaging server.

If the Enterprise Site ID box is enabled, the Local Messaging Server Properties—General tab cannot be closed, and the information cannot be saved to the network database unless the Enterprise Site ID box contains some information.

If you do not know the Enterprise site ID, enter a valid placeholder and enter the correct ID when you implement Enterprise Networking.

## Receive Message Text Info

The Receive Message Text Info check box is enabled only if Enterprise Networking is installed on your local messaging server. Configure this box when you implement Enterprise Networking.

## Server FQDN

The Server FQDN box is enabled only if VPIM Networking is installed on your local messaging server. The server FQDN is entered while you implement VPIM Networking.

However, the Local Server Properties—General tab cannot be closed and the information cannot be entered into the network database unless the Server FQDN box contains some information.

If you know the server FQDN, enter it while you implement Integrated AMIS Networking. Otherwise, enter a placeholder that you can replace while you implement VPIM Networking.

For example, enter “FQDN\_goes\_here.” A clearly marked placeholder reminds you to replace the information when you implement VPIM Networking.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration

## To configure the local messaging server

- 1 In the Messaging Network Configuration tree view, select the local messaging server.

- 2 On the File menu, click Open.

**Result:** The Local Server Properties—General tab appears.

- 3 To change the name of the local messaging server, enter a new name in the Name box.

**Tip:** The name given to the local messaging server is also the name of the local site.

**Note:** The server type is always CallPilot and cannot be changed.

- 4 In the Description box, enter details about the local messaging server.

- 5 To send messages to all other sites in the messaging network, ensure that the Send Messages to all other Servers box is selected.

**Note:** The Add/Update Remote Users on this Server check box is enabled if Enterprise Networking is installed. Configure this setting when you implement Enterprise Networking.

- 6 If Enterprise Networking is installed, enter the Enterprise Site ID number for the local messaging server or a valid placeholder.

**Note:** The Receive Message Text Info check box is enabled only if Enterprise Networking is installed. Configure this setting when you implement Enterprise Networking.

- 7 If VPIM Networking is installed, the Server FQDN box is enabled. Enter the FQDN or a valid placeholder.

- 8 Click Save.

**Result:** The information is validated and saved to the network database.

## What's next?

After you configure the local messaging server, you must configure the local prime switch location.

# Configuring the local prime switch location

## Introduction

You must configure the local prime switch location to implement Integrated AMIS Networking.

The final step in configuring the local site for Integrated AMIS Networking is to configure the local prime switch location.

## If any other networking solution is implemented

If another networking solution is implemented on the local site, the local prime switch location configuration is already configured.

You must check the current configuration information. Make any necessary modifications.

## If NMS is implemented

If NMS is implemented on the local site, the information required for the local switch location configuration is already complete.

All satellite switch locations attached to the local prime switch location are also already installed.


## If no other networking solution is implemented

If no other networking solution is implemented on the local site, you must complete the General tab. You may have to complete the ESN tab or the CDP tab, or both, depending on the dialing plan used on your local switch location.

## Where the prime switch location is configured

The local prime switch location is configured on the Prime Switch Location Properties dialog box, which has four tabs:

- General
- ESN
- CDP
- SMTP/VPIM



### General tab

Complete the General tab no matter what dialing plan your site uses.

### ESN tab

Complete the ESN tab if the local site uses the ESN or a hybrid dialing plan.

**CDP tab**

Complete the CDP tab if the local site uses the CDP or a hybrid dialing plan.

**SMTP/VPIM tab**

The SMTP/VPIM tab is enabled only if VPIM Networking is installed on your local switch location.

You complete the SMTP/VPIM tab during the implementation of VPIM Networking.

**General tab**

The following explain all boxes on the General tab.

**Name**

Every switch location needs a name that is unique within the messaging network. Usually, this name is the same as the name of the messaging server. This ensures that the identity of the switch location within the network is immediately apparent. A geographic name is common.

For example, if a messaging server is named “Moscow,” the prime switch location is usually also named “Moscow.”

By default, the local prime switch location is given the name “Untitled.” This name must be changed.

**Description**

The Description box is useful for short notes, reminders, or comments about the switch location.

You might find it useful to specify your switch model, the date of the switch configuration, or contact information for the switch technician.

**Enterprise Location ID**

The Enterprise Location ID box is not enabled for the prime switch location.

**Note:** The location ID for the prime switch location is always 0 and cannot be changed.

## Spoken Name Recorded

If your local site is not an NMS site, the Spoken Name Recorded check box is not enabled.

If your site is an NMS site, the Spoken Name Recorded check box was configured during the NMS implementation.

## Dialing plan information

You need detailed information about the dialing plan used by the local site when you configure the local prime switch location.

### Dialing plans for dialing to this location

You must specify which of the following dialing plans is used to dial to the local switch location:

- ESN
- CDP
- hybrid that combines ESN and CDP
- another dialing plan (such as PSTN)

When you configure the local prime switch location, you specify the dialing plan that is used to dial to the local site.

**Note:** If you use ESN anywhere in the messaging network, you must select ESN because you need an ESN access code.

## Mailbox specifications

The following boxes are dynamically enabled and disabled depending on the dialing plan you have specified for the local prime switch location:

- Mailbox addressing follows dialing plan
- Mailbox prefixes

### Mailbox addressing follows dialing plan

The Mailbox addressing follows dialing plan check box is available only if NMS is installed on the local messaging server. If NMS is implemented, this check box should be properly configured already.

## Mailbox prefixes

A mailbox prefix is a leading string of digits that uniquely identifies a mailbox number as belonging to a particular site.

If the local site does not have NMS installed, the mailbox prefixes are never required for the local prime switch location.

If the local site does have NMS installed, the mailbox prefix, or prefixes, are already properly configured.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration

## To configure the local prime switch location

- 1 In the Messaging Network Configuration tree view, select the local prime switch location.
- 2 On the File menu, click Open.  
**Result:** The Messaging Network Configuration—Prime Location Properties—General tab appears.
- 3 To change the name of the local prime switch location, enter a name in the Name box.
- 4 In the Description box, enter details about the local prime switch location.  
**Note:** The Enterprise Location ID is always 0 and cannot be changed.
- 5 Confirm the status of the Spoken Name Recorded box.  
**Note:** This box is enabled only if NMS is installed and was completed during the implementation of NMS.
- 6 Specify the dialing plan used to dial the local prime switch location. Select the
  - ESN check box if ESN is used
  - CDP check box if CDP is used
  - ESN and CDP check boxes if a hybrid dialing plan is used**Note:** Leave both check boxes clear if another dialing plan, such as PSTN, is used.

- 7 The Mailbox addressing follows dialing plan box and the Mailbox prefixes boxes are enabled only if NMS is implemented locally. If enabled, they are already configured.
- 8 Determine whether you must complete another tab. If not, click Save to close the dialog box.
- 9 Select another tab to continue the configuration.

## What's next?

### **If the local site uses an ESN, CDP, or hybrid dialing plan**

After you complete the General tab, you must complete the ESN tab, or the CDP tab, or both tabs, depending on the dialing plan used.

### **If the local site uses another dialing plan**


If your local site uses another dialing plan, such as PSTN, you have completed the configuration of your local prime switch location.

# Configuring ESN information

## Introduction

If the local prime switch location uses either an ESN dialing plan or a hybrid dialing plan, you must complete the ESN tab.

You must provide the ESN access codes and ESN location codes. These are combined to create the ESN prefix.



The screenshot shows a dialog box titled "Local Prime Switch - Prime Location Properties" with a tabbed interface. The "ESN" tab is selected. The dialog contains the following elements:

- Four tabs: "General", "ESN", "CDP", and "SMTP / VPIM".
- A text label: "ESN Access Code used by this location:" followed by an empty text input field.
- A text label: "ESN Location Codes:"
- A table with two columns: "Location Code" and "Overlap". The table body is currently empty.
- Three buttons on the right side: "Add New...", "Open...", and "Remove".
- Four buttons at the bottom: "Save", "Cancel", "Print", and "Help".

## See also

For a description of the ESN dialing plan and how it works, consult the *Networking Planning Guide*.

## **ESN Access Code used by this location**

The ESN access code is used to access ESN routing in the same way that an access code, such as 9, is used to dial out to the public network from a private network.

Typically, all switches in a messaging network use the same ESN access code.

## **ESN Location Codes**

An ESN location code is a routing prefix that identifies a location within a network. It is usually three digits long, but can be up to ten digits long.

You must also indicate the number of digits in the ESN location code that overlap the mailbox number.

The ESN Location Codes list contains all ESN location codes currently assigned and indicates the overlap between the ESN location code and the mailbox directory numbers.

ESN location codes can be added, modified, or deleted at any time. The ESN location codes must always match the dialing plan configuration on the switch.

### **ESN location code capacity**

The maximum number of ESN location codes for a switch location is 30.

### ESN location code overlap

When you are entering the dialing plan information for the local site, you must calculate the number of digits in the ESN prefix that overlap the digits in the local extension.

If there is overlap between the rightmost digit or digits of the location code and the leftmost digit or digits of the extension number, enter the amount of overlap.

The following table provides examples of ESN location code overlap.


Access code	Location code	Extension number	Number dialed by users at other sites	Overlap
6	338	8300	63388300	0
6	338	8300	6338300	1
6	300	8000-8999	63008300-63008999	0
6	302	25000-26999	63025000-63026999	1

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration > Local Prime Switch Location Properties > ESN tab

## To configure the ESN information

- 1 Enter the ESN access code.
- 2 To add a new location code, click the Add New button.

**Result:** The New ESN Location Code Properties dialog box appears.



- 3 In the Location Code box, enter the location code.
- 4 In the Overlap box, enter the number of digits in the mailbox number that overlap the location code.
- 5 Click Save.

**Result:** The location code and overlap are validated and appear in the ESN Location Codes list on the ESN tab.

- 6 Repeat steps 3–5 for each ESN location code required.
- 7 When you have finished configuring the ESN information, determine if you must configure CDP information.
  - If yes, click the CDP tab.
  - If no, click Save to validate the ESN information and save it to the database.

## What's next?


If your local prime switch location uses the hybrid dialing plan, click the CDP tab to continue configuring the local prime switch location.

# Configuring CDP information

## Introduction

If the local switch location uses either a CDP dialing plan or a hybrid dialing plan, complete the CDP tab.

You must provide the CDP steering codes.



## See also

For a general description of the CDP dialing plan and how it works, consult the *Networking Planning Guide*.

## CDP Steering Codes

A CDP steering code is a site prefix that identifies the local site within the network. Therefore, a CDP prefix must be unique for all switches in the messaging network.

CDP steering codes are determined by the switch technician.

The CDP steering codes defined on the switch are entered on CallPilot because the system must be able to identify the steering code in the mailbox number to determine the site.

The CDP Steering Codes list box contains all CDP steering codes currently assigned to the switch location. The list box also indicates the overlap between the CDP steering codes and the mailbox directory numbers.

CDP steering codes can be added, modified, or deleted.

### CDP steering code capacity

The maximum number of CDP steering codes for a switch location is 500.

### CDP steering code overlap

When entering the dialing plan information, you must calculate the number of digits in the CDP steering code that overlap the digits of the local extension.

If there is overlap between the last digit or digits of the steering code and the first digit or digits of the extension number, enter the amount of overlap.

Normally, the steering code overlaps with the first few digits of a local extension number.

The following table provides three examples of CDP steering code overlap.


Steering code	Extension number	Number dialed by users at other sites	Amount of overlap
22	22345	2222345	0
22	22345	222345	1
22	22345	22345	2

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration > Local Prime Switch Location Properties > CDP tab

## To configure the CDP information

- 1 Click the Add New button.

**Result:** The New CDP Steering Code Properties dialog box appears.



- 2 In the Steering Code box, enter the steering code.
- 3 In the Overlap box, enter the number of digits in the mailbox number that overlap the steering code.
- 4 Click Save.

**Result:** The steering code and overlap are validated and appear in the CDP Steering Code list box on the CDP tab.

- 5 Repeat steps 1–4 for each CDP steering code required.
- 6 When you have added all necessary CDP steering codes, click Save.

**Result:** The information is validated and saved to the network database.

## What's next?

You have completed the configuration of the local site and are ready to begin adding and configuring remote sites.



# Adding and configuring a remote site

## In this section

<a href="#"><u>Overview</u></a>	174
<a href="#"><u>Configuring a remote messaging server</u></a>	175
<a href="#"><u>Configuring a remote prime switch location</u></a>	184
<a href="#"><u>Configuring a remote satellite switch location</u></a>	195
<a href="#"><u>Recording a spoken name</u></a>	199
<a href="#"><u>Importing a spoken name</u></a>	201
<a href="#"><u>Non-CallPilot remote sites</u></a>	203
<a href="#"><u>Meridian Mail remote sites</u></a>	205
<a href="#"><u>Norstar Voice Mail remote sites</u></a>	206

# Overview

## Introduction

When you implement Integrated AMIS Networking, you add to the Messaging Network Configuration tree view all the remote sites that use Integrated AMIS Networking to exchange messages with the local site.

Every remote site added to the tree view must be configured.

## Information required

The information that you enter when configuring a remote site reflects the information that is configured for that site in its own local network database. For example, you enter the name of that site and its FQDN. You must get this information from the remote network administrator.

But configuring a remote site is not simply copying the information provided by the remote site. You also enter information that reflects how your local site will communicate with that remote site. For example, for each remote site you decide whether your local site sends messages to this particular remote server.

## Main steps

There are three main steps to adding a remote site to your local network database. For each remote site, you must add and configure

- the remote messaging server
- the remote prime switch location
- the remote satellite switch locations, if the remote site is an NMS site

## Network representation

Much of the information that you must provide while configuring a remote messaging server is contained in the network diagram or spreadsheet.

# Configuring a remote messaging server

## Introduction

When CallPilot is initially installed on your system, your local site, consisting of a local messaging server and a local prime switch location, is automatically added into the Messaging Network Configuration tree view.

However, you must manually add each remote site that exchanges messages with the local site using Integrated AMIS Networking into the Messaging Network Configuration tree view. Both the remote messaging server and the remote prime switch location must be configured.

The following tabs must be completed for each remote messaging server:

- Remote Messaging Server Properties—General tab
- Remote Messaging Server Properties—Connection Information tab


## Remote servers and other networking solutions

If you have implemented another CallPilot networking solution on your system, you have already added remote sites to the Messaging Network Configuration tree view.

The process of adding a remote site is essentially the same regardless of the networking solution being implemented. However, when you add remote sites during the implementation of Integrated AMIS Networking there are important differences to consider.

## Remote Messaging Server Properties—General tab

The Remote Messaging Server Properties—General tab contains detailed information about the remote messaging server and defines how the local site and the remote site exchange messages.



### Name

You should assign the remote messaging server the same name that was assigned to it by its local network administrator. This correspondence in naming sites makes the network easier to administer and maintain because all network administrators use the same names for the same sites.

For example, if a remote site calls itself Connecticut, you should name it Connecticut when you add it to the Messaging Network Configuration tree view.

**Server type**

The remote messaging server can be any of the following types:

- CallPilot (CallPilot)
- Meridian Mail Net Gateway (MMNG)
- Norstar Voice Mail (Norstar)
- Meridian Mail
- Other

**Description**

Provide a brief description of the remote messaging server or useful notes, such as when the messaging server was configured or who completed the configuration.


**Send Messages to this Server**

The Send Messages to this Server check box interacts with the Send Messages to all other Servers check box on the Local Messaging Server Properties—General tab.

When you configured the local messaging server, you decided if you wanted the local messaging server to send messages to all remote messaging servers. This option is selected by default and is cleared under exceptional circumstances only.

However, you can still stop the delivery of messages to specific remote messaging servers. The Send Messages to this Server check box enables you to block the delivery of messages from your local messaging server to a particular remote site.

**Example:** In the following diagram, Helsinki is configured to deliver messages to all other sites. However, the network database records for Paris and Cairo specify that messages are not sent to these remote sites. Messages are sent to Lammi and Korso-Rekola. Therefore, while the potential exists for sending messages to both remote sites, only two sites in the messaging network receive messages from Helsinki.



G100995.eps

### Send local user information to this Server

The Send local user information to this Server check box determines if the Names Across the Network feature is used with this remote site. If enabled, this feature was configured during the implementation of Enterprise Networking.

### **Enterprise Site ID**

The Enterprise Site ID box is enabled only if Enterprise Networking is installed on the local site.

All remote sites connected to a site that has Enterprise Networking installed must have an Enterprise site ID, regardless of the actual protocol used with the site.

Therefore, if Enterprise Networking is installed locally, when implementing Integrated AMIS Networking, you must enter the site ID for all remote sites, even those that exchange messages with the local site using the AMIS protocol.

Consult the network representation for the correct Enterprise site IDs.

### **Send Message Text Info to this Server**

This check box applies only to remote sites that use Enterprise Networking to exchange messages with the local site. For remote sites that use Integrated AMIS Networking, this box is not applicable.


### **Server FQDN**

If VPIM Networking is installed on your local site, the VPIM Networking Server FQDN box is enabled.

However, since your local site transfers messages with this remote site using Integrated AMIS Networking, a Fully Qualified Domain Name (FQDN) of the remote server is not required.

## Remote Messaging Server—Connections tab

The configuration of a remote messaging server continues on the Connections tab.



### Network protocol

When implementing Integrated AMIS Networking, you must specify that the protocol used by the local site to exchange messages with this remote site is AMIS.

To use a particular protocol, both sites must have the same networking solution installed and implemented.

If a remote site is not configured to use the same protocol as the local site, the following occurs when the local site attempts to send a message:

- The message is not delivered.
- An error message is generated.
- The remote site is put into error status on the local system.

## Integrated AMIS Networking connection DNs

When CallPilot initiates a call to a remote site, it uses the networking connection DN that is specified for the remote site in your network database.

You can define up to three DNs. DN1 is mandatory. DN2 and DN3 are optional.

At least one connection DN must be the Integrated AMIS Networking system access number for the remote site, as defined on the AMIS 1 tab of the Message Delivery Configuration Properties dialog box of the remote site.

You should include the system access number of the remote site on the network representation. If you do not have the system access number, contact the administrator of the remote site.

The connection DNs are entered in a format that is dialable from the local site. Connection DN1 should be the least expensive means of calling the remote site. For example, if you use the ESN dialing plan between the sites, use the ESN prefix for connection DN1 and the PSTN number for connection DN2.

The system always uses DN1 to reply to a message from the remote site, unless it encounters problems. If the system does encounter a problem, it attempts to contact the remote site using another DN.

## See also


For a general discussion of how connection DNs are used, consult “Understanding Integrated AMIS Networking settings” on page 71.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration

## To configure a remote messaging server

- 1 In the Messaging Network Configuration tree view, select Remote Server Maintenance.
- 2 On the File menu, click New > Messaging Server.  
**Result:** The Remote Messaging Server Properties dialog box appears.
- 3 On the General tab, in the Name box, enter the name of the remote messaging server.
- 4 Select the server type from the Server type box.

- 5 In the Description box, enter details about the remote messaging server.
- 6 To enable the local messaging server to send messages to this remote messaging server, ensure that the Send Messages to this Server box is selected.
- 7 If an Enterprise site ID is required, enter the unique site ID number of the remote messaging server or a valid placeholder.
- 8 To continue configuring the remote messaging server, click the Connections tab.
- 9 From the Network protocol list, select AMIS.  
**Result:** The Define buttons become enabled.
- 10 Click the Define button for DN1.  
**Result:** The New DN dialog box appears.



- 11 Enter the required DN.
  - For a public network, enter a public DN.
  - For a private network, enter a private DN.
- 12 Click Save.  
**Result:** The DN appears in the Connection DNs box on the Connections tab.
- 13 Repeat steps 9–12 for each connection DN.  
**Note:** DN1 is mandatory. At least one DN must be the system access number of the remote site.

If you are defining more than one connection DN, list them in order of cost. Connection DN1 should be the least expensive means of contacting the remote site.

- 14 Click Save.

**Result:** The information is validated and entered into the network database.

## What's next?

After you add information about the remote messaging server into your local network database, you must also add information about the remote prime switch location.

# Configuring a remote prime switch location

## Introduction

When you added a remote messaging server to the Message Network Configuration tree view, a corresponding prime switch location was added.

A remote prime switch location must be configured. This process is almost identical to configuring the local prime switch location.

## Remote Prime Switch Location Properties dialog box

The remote prime switch location is configured on the Remote Prime Switch Location Properties dialog box, which has four tabs:

- General
- ESN
- CDP
- SMTP/VPIM

### General tab

Completing the General tab is mandatory.

### ESN tab

Complete the ESN tab if an ESN or hybrid dialing plan is used with this remote site.

### CDP tab

Complete the CDP tab if a CDP or hybrid dialing plan is used with this remote site.

### SMTP/VPIM tab

Because your local site is not using VPIM Networking to transfer messages with this remote site, do not complete the SMTP/VPIM tab.

## Remote Prime Switch Location Properties—General tab

The screenshot shows a dialog box titled "Remote Site Prime Switch - Prime Location Properties" with a "General" tab selected. The dialog contains the following fields and controls:

- Name:** A text box containing "Remote Site Prime Switch".
- Description:** An empty text box.
- Enterprise Location ID:** A numeric field with "0" and a dropdown arrow.
- Spoken Name Recorded:** A field with "No" and buttons for "Record..." and "Import...".
- Dialing and addressing:** A section containing:
  - Dialing plans for dialing to this location:** Two checkboxes, "ESN" (checked) and "CDP" (unchecked).
  - Mailbox addressing follows dialing plan:** A checked checkbox.
  - Mailbox prefixes:** Two empty text boxes.
  - Dialing prefix:** One empty text box.
- Buttons:** "Save", "Cancel", "Print", and "Help" at the bottom.

### Name

Assign a unique name to each switch location. The name should correspond to the switch location to make the location easy to identify. A street or city name is a good choice.

The remote switch location is automatically given the name of the remote server that was added to the Messaging Network Configuration tree view. This name can be changed.

### Description

Enter short notes or comments about the remote switch location in this box.

## Enterprise Location ID

The Enterprise Location ID box is enabled only if Enterprise Networking is implemented on the local site.

A location ID is required for all remote sites if Enterprise Networking is installed locally, even if another protocol is used to exchange messages with this site.

The location ID of the prime switch location is set to 0 by default and cannot be changed.

## Spoken Name Recorded

When local users compose a message to this remote site or use the playback feature to determine the sender of a message, they hear a message that identifies the sender. The content of the message depends on whether a spoken name for that remote site is recorded.

If a spoken name is recorded, voice mail users hear the location name followed by the local mailbox directory number.

**Example:** “Dallas, Mailbox 2346”

### Spoken name not recorded

If a spoken name is not recorded, local users hear a full mailbox address that does not identify the sender’s site by name.

For example, for an ESN switch location, users hear the ESN location prefix followed by the local mailbox directory number.

**Example:** “Mailbox 6444 2346”

### When a spoken name is not desirable

You may decide that you do not want local users to hear a spoken name for a particular remote site. For example, if CDP is used for messaging with this remote site and the mailbox numbers follow the dialing plan, you may decide that a recorded spoken name is unnecessary. In this case, do not record or import a spoken name.

### Ways to add a spoken name recording

There are two ways to add a spoken name recording: record a spoken name directly by clicking the Record button, or import a prerecorded message.

## Dialing plan information

Provide general information on the dialing plan used by the switch.

The dialing plan boxes have complex interactions. They are dynamically enabled or disabled depending on the choices made. Complete all enabled boxes.

### Dialing plans for dialing to this location

You must specify which dialing plan is used to dial this remote switch location from the local switch location. There are four possible dialing plans:

- ESN
- CDP
- hybrid combining ESN and CDP
- another (such as PSTN)

### Mailbox addressing follows dialing plan

When a mailbox follows the dialing plan, a user dials and addresses a message to a recipient in the same way. There are two ways to achieve this correspondence:

- A user's mailbox number and extension number are the same.
- The addressing plan and the dialing plan are the same.

If either situation is true, select the Mailbox addressing follows dialing plan check box.

Clear this option if users at the site do not dial and address recipients in the same way.

**Example:** If the local ESN prefix is 6222 and the local mailbox is 1234, remote users can dial the local user with the number 62221234, which is the ESN prefix and the mailbox number combined.

**Example:** If the CDP steering code is 22 and the local mailbox is 1234, remote users can dial the local user with the number 221234, which is the steering code and the mailbox number combined.

## Mailbox prefixes

Mailbox prefixes are used by local users to address users at a remote site if mailboxes at the remote site do not follow the dialing plan.

A mailbox prefix must be provided if the mailbox does not follow the dialing plan or if another dialing plan, such as PSTN, is used.

A mailbox prefix does not have to overlap with local mailbox numbers. Two mailbox prefixes can be entered. Either prefix can be used to address any mailbox at the local site. Normally, however, only one prefix is required.

Usually, the mailbox prefix is a shortcut. A mailbox prefix can be any number as long as it does not conflict with other network data.

A mailbox prefix can also be the entire telephone number of the site, including country code, city/area code, and exchange.

**Example:** If the mailbox prefix is 22 and the mailbox number of a local user is 6565, users at other switches address the local user by dialing 226565.

## Dialing prefix

A dialing prefix is needed if the local site uses another dialing plan, such as PSTN, and users at your local site use dialing prefix to reach users at this remote site.

Usually, if the Dialing prefix box is enabled, you enter the prefix.

In a few cases, a dialing prefix is not needed. For example, if the mailbox number, without the mailbox prefix, can be dialed directly, a dialing prefix is not needed. This situation is rare because most systems use at least some sort of access code.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration

## To configure a remote prime switch location

- 1 In the Messaging Network Configuration tree view, select the remote prime switch location.
- 2 On the File menu, select Properties.

**Result:** The Remote Prime Switch Location Properties dialog box appears.

- 3 On the General tab, in the Name box, enter the name of the remote prime switch location.
- 4 In the Description box, enter details about the switch location.  
**Note:** The Enterprise Location ID is always set to 0 for remote prime switch locations and cannot be changed.
- 5 If needed, click Record to record a spoken name for the site, or click Import to import a prerecorded spoken name.  
**Note:** For instructions on how to record a spoken name, see “Recording a spoken name” on page 199.  
For instructions on how to import a spoken name, see “Importing a spoken name” on page 201.
- 6 Specify the dialing plan used to dial the remote site. Select the
  - ESN check box if ESN is used
  - CDP check box if CDP is used
  - ESN and CDP check boxes if a hybrid dialing plan is used**Note:** Leave both check boxes clear if you use another dialing plan, such as PSTN.
- 7 Indicate if mailbox addressing follows the dialing plan.
- 8 If necessary, enter the mailbox prefix or prefixes.
- 9 If necessary, enter the dialing prefix.

## ESN information

If the remote prime switch location uses an ESN or hybrid dialing plan, complete the ESN tab.

The procedure for configuring the ESN information for a remote prime switch is identical to the procedure used for the local prime switch location.

**Note:** You must provide the ESN access code used at the remote site. Do not enter the access code used locally.

For a review of the ESN access codes, ESN location codes, and overlap, consult “Configuring ESN information” on page 165.

## To configure the ESN information

- 1 Open Message Delivery Configuration > Switch Location > ESN tab.


The screenshot shows a dialog box titled "Remote Site Prime Switch - Prime Location Properties" with a standard Windows window border. It has four tabs: "General", "ESN", "CDP", and "SMTP / VPIM". The "ESN" tab is selected. Inside the dialog, there is a text label "ESN Access Code used by this location:" followed by an empty text input field. Below this is a section titled "ESN Location Codes:" containing a table with two columns: "Location Code" and "Overlap". The table is currently empty. To the right of the table are three buttons: "Add New...", "Open...", and "Remove". At the bottom of the dialog are four buttons: "Save", "Cancel", "Print", and "Help".

Location Code	Overlap
---------------	---------

- 2 Enter the ESN access code.

- 3 To add a new location code, click the Add New button.

**Result:** The New ESN Location Code Properties dialog box appears.



- 4 In the Location Code box, enter the location code.
- 5 In the Overlap box, enter the number of digits in the mailbox number that overlap the location code.
- 6 Click Save.  
**Result:** The location code and overlap are validated and appear in the ESN Location Codes box on the ESN tab.
- 7 Repeat steps 3–6 for each ESN location code required.
- 8 When you have finished configuring the ESN information, determine if you must configure CDP information. If yes, click the CDP tab. If no, click Save.

## What's next?

If your remote prime switch location uses the hybrid dialing plan, click the CDP tab to continue configuring the local prime switch location.

If the local prime switch location uses only the ESN dialing plan, click Save to validate the configuration information and save it to the network database.

## **CDP information**

If a CDP dialing plan or a hybrid dialing plan is used to connect the local site to the remote site, complete the CDP tab.

Configuring the CDP information for a remote prime switch location is identical to configuring the local prime switch location.

For a review of the CDP steering codes and overlap, consult “Configuring CDP information” on page 169.


## To configure the CDP information

- 1 Open Message Delivery Configuration > Switch Location > CDP tab.



- 2 Click the Add New button.

**Result:** The New CDP Steering Code Properties dialog box appears.



- 3 In the Steering Code box, enter the steering code.
- 4 In the Overlap box, enter the number of digits in the mailbox number that overlap the steering code.
- 5 Click Save.  
**Result:** The steering code and overlap are validated and appear in the CDP Steering Codes box on the CDP tab.
- 6 Repeat steps 2–5 for each CDP steering code required.
- 7 When you have added all necessary CDP steering codes, click Save.  
**Result:** The information is validated and added to the network database.

## What's next?

You have completed the configuration of the remote prime switch location.

Click Save to validate the information and save it to the network database.

The Remote Prime Switch Location Properties dialog box closes, and you return to the Messaging Network Configuration tree view.

# Configuring a remote satellite switch location

## Introduction

If a remote site is an NMS site, you must add and configure each of its satellite switch locations. This information is saved to the local network database.

Although a prime switch location is added automatically when a remote site is added to the Messaging Network Configuration tree view, you must manually add each satellite switch location of a remote NMS site.

## Capacity

An NMS site can have up to 59 satellite switch locations.

## Organization

When you add a satellite switch location, this location appears in the Messaging Network Configuration tree view. Satellite switch locations are listed alphabetically below the prime switch location.

## Where to configure a satellite switch location

To configure a satellite switch location, complete the General tab of the Remote Satellite Switch Location Properties dialog box.

You must also complete the tabs that correspond to the dialing plan used by the local site.

### **ESN tab**

Complete the ESN tab if you use an ESN or hybrid dialing plan.

### **CDP tab**

Complete the CDP tab if you use a CDP or hybrid dialing plan.

## Spoken Name Recorded

When local users compose a message to a remote satellite switch location or use the playback feature to hear who sent a message, the name of the switch location is played.

If a spoken name is not recorded, local users hear the full DN, such as “Mailbox 64441234.” If a recording of the spoken name is available, local users hear the switch location name followed by the mailbox number, such as “Milan 1234.” You can either record a message using the telephone or import a prerecorded WAV file.

When a recording of the spoken name is available, Yes appears in the Spoken Name Recorded box.

If you do not want your local users to hear the name of this satellite switch location when composing messages or using playback, do not record a message. For example, if you are using CDP to transfer messages to the site and mailbox numbers follow the dialing plan, you may feel that a spoken name is unnecessary.

## Dialing plan interaction

The dialing plan boxes are dynamically enabled or disabled depending on the choices made. Complete all enabled fields.

## See also

Configuring a satellite switch location for a remote site is identical to configuring a remote prime switch location for a remote site.

For a review, consult “Configuring a remote prime switch location” on page 184.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration

## To configure a remote satellite switch location

- 1 On the Messaging Network Configuration tree view, highlight the remote messaging server.
- 2 On the File menu, select New > Switch location.

**Result:** The Satellite Switch Location Properties dialog box appears.

The screenshot shows a dialog box titled "Remote Site Satellite Switch - Satellite Location Properties". It has four tabs: "General", "ESN", "CDP", and "SMTP / VPIM". The "General" tab is selected. The fields are as follows:

- Name:** Remote Site Satellite Switch
- Description:** (empty)
- Enterprise Location ID:** 1
- Spoken Name Recorded:** No, with buttons for "Record..." and "Import..."
- Dialing and addressing section:**
  - Dialing plans for dialing to this location:
    - ESN
    - CDP
  - Mailbox addressing follows dialing plan
  - Mailbox prefixes:** (two empty input boxes)
  - Dialing prefix:** (one empty input box)

At the bottom are buttons for "Save", "Cancel", "Print", and "Help".

- 3 In the Satellite Switch Location Properties dialog box, complete the General tab.

**Note:** For detailed instructions on how to record a spoken name, consult "Recording a spoken name" on page 199. For detailed instructions on how to import a spoken name, consult "Importing a spoken name" on page 201.

- 4 Complete the ESN tab and the CDP tab as required.

- 5 Click Save.

**Result:** The information is validated and the satellite switch location is added to the remote site.

- 6 Repeat steps 1–5 for each satellite switch location required.
- 7 When all satellite switch locations are added, click Save to save them to the Messaging Network Configuration tree view.

# Recording a spoken name

## Introduction

You can create a recording of the name of a switch location. A recorded name is heard by a local user whenever an address is played back. A recorded name for a site is played if a user does not have a personal recorded name.

### Local switch location

If your local site is not an NMS site, a spoken name is not required for the local site.

If your local site is an NMS site, you can decide if you want to record a spoken name. For example, if the NMS site uses CDP, you may decide a spoken name is not necessary.

### Remote switch location

A spoken name should be available for every remote site in your Message Delivery Configuration tree view.

The recording is played when local users compose messages to the remote site.

## Importing a spoken name

If you do not want to record your own voice using the telephone, you can import a prerecorded WAV file. See “Importing a spoken name” on page 201.

## Before you begin

A telephone serves as the microphone. Therefore, if you want to record a spoken name, a telephone must be available.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration

## To record a spoken name

- 1 In the Messaging Network Configuration tree view, select the switch location of the site for which you want to record a spoken name.
- 2 On the File menu, select Open.  
**Result:** The Switch Location Properties dialog box appears.
- 3 On the General tab, click Record.  
**Result:** The Specify Phoneset dialog box appears.



- 4 Enter the telephone number of the telephone to be used as a microphone and click Dial.  
**Result:** The telephone rings and the Voice Recorder dialog box appears.
- 5 Answer the telephone.
- 6 In the Voice Recorder dialog box, click Record.
- 7 Speak the name of the site into the telephone.
- 8 Click Stop.
- 9 To review the recording, click Play.
- 10 If you are satisfied with the recording, click Done.

# Importing a spoken name

## Introduction

You can import a prerecorded file of the name of a switch location. The recording is heard by a local user whenever an address is played back. A recording for a site is played if a user does not have a personal spoken name.

### Local switch location

If your local site is not an NMS site, a spoken name is not required for the local site.

If your local site is an NMS site, you can decide if you want to import a spoken name. For example, if the NMS site uses CDP, you may decide a spoken name is not necessary.

### Remote switch location

A spoken name should be available for every remote site in your Message Delivery Configuration tree view.

The recording is played when local users compose messages to the remote site.

## Recording a spoken name

If you do not want to import a prerecorded spoken name, you can record your own voice message using the telephone. See “Recording a spoken name” on page 199.


## Before you begin

A prerecorded WAV file must be available. Check the quality of the recording before importing the file.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration

**To import a prerecorded file**

- 1 In the Messaging Network Configuration tree view, select the switch location of the site for which you want to import a prerecorded file.
- 2 On the File menu, select Open.  
**Result:** The Switch Location Properties dialog box appears.
- 3 On the General tab, click Import.  
**Result:** The Open dialog box appears.



- 4 Select the WAV file, and click Open.  
**Result:** The file is imported.
- 5 Close the Open dialog box.

# Non-CallPilot remote sites

## Introduction

Integrated AMIS Networking can exchange messages between a CallPilot system and the following non-CallPilot remote systems:

- a Meridian Mail (Release 8 and later) system
- a Norstar Voice Mail (Release 3 and later) system

## Coordination

If a remote site is a non-CallPilot system, you must coordinate with the network administrator of that remote site to ensure that the systems are properly configured. You must share the standard information that is required between any sites in a messaging network.

## Example

The two sites must coordinate dialing plans and ensure that there are no conflicts in the configuration information.

## Terminology

A change in terminology may cause some confusion.

In Meridian Mail and Norstar Voice Mail, the name is Virtual-Node AMIS Networking, rather than Integrated AMIS Networking is used. The two are identical products.

## Adding and configuring the remote site

Adding a non-CallPilot remote site to the local network database is exactly the same as adding a CallPilot remote site.

To configure the non-CallPilot remote site, you require no special information. You must only specify the server type on the Remote Messaging Server dialog box. The rest of the configuration is the same as the configuration of a CallPilot remote site.

**Server type**

Specify the server type of a non-CallPilot system on the Messaging Network Configuration—Remote Server Properties—General tab.

**Instructions for the remote administrator**

For both Meridian Mail and Norstar Voice Mail systems, there are no special considerations that must be communicated to the remote network administrator.

You add the CallPilot site to the remote network database like any other remote site. No special configuration is required.

# Meridian Mail remote sites

## Introduction

Integrated AMIS Networking can exchange messages between a CallPilot system and a Meridian Mail (Release 8 and later) system.

## Instructions for the remote Meridian Mail administrator

You add the CallPilot site to the network database like any other site. There are no special considerations that must be communicated to the remote network administrator.

# Norstar Voice Mail remote sites

## Introduction

Integrated AMIS Networking can exchange messages between a CallPilot system and a Norstar Voice Mail (Release 3 and later) system.

## Instructions for the remote Norstar Voice Mail administrator

You add the CallPilot site to the network database like any other site. There are no special considerations that must be communicated to the network administrator.

## chapter 7

---

# Testing and backing up Integrated AMIS Networking

This chapter describes how to test the Integrated AMIS Networking configuration. The test suite determines if Integrated AMIS Networking works properly both locally and with remote sites.

This chapter also describes how to create a backup of your system to ensure that the configuration is not lost due to system failure.

### **In this chapter**

Tests and backups

209



# Tests and backups

## **In this section**

<u>Integrated AMIS Networking test suite</u>	210
<u>Call routing test</u>	212
<u>Local SDN test</u>	213
<u>Quick SDN test</u>	215
<u>Loopback test</u>	217
<u>End-to-end test</u>	219
<u>Backing up Integrated AMIS Networking</u>	222

# Integrated AMIS Networking test suite

## Introduction

After you configure CallPilot for Integrated AMIS Networking, test the system.

The Integrated AMIS Networking test suite tests every aspect of the system. If any test fails, resolve the problem and retry the test before you continue.

**Note:** These tests are not intended to validate the AMIS compliance of a third-party system. The tests assume that any system that you communicate with is AMIS-compliant.

## Test suite

The Integrated AMIS Networking test suite consists of five tests. Two tests are local site tests, which verify that your local configuration is correct. Three tests are coordinated site tests, which verify that everything works properly at your site and at every remote site.

The following table lists the local site tests and describes their purpose:

This local site test	Determines if
call routing test	<ul style="list-style-type: none"> <li>■ the local system can make outbound calls to other sites in the network.</li> <li>■ the local system cannot make outbound calls to restricted sites on the network.</li> </ul>
local or quick SDN test	ports on CallPilot are working properly, and SDNs are defined correctly.

The following table lists the coordinated site tests and describes their purpose:

This coordinated site test	Determines if
end-to-end test	a remote system can receive messages from the local system.

<b>This coordinated site test</b>	<b>Determines if</b>
loopback test	the local system can receive messages from the remote system.

## Coordination

While you can perform local site tests independently, you must work with the network administrators at each remote site to perform the coordinated site tests.

In some instances, the remote administrator must make preparations before you can conduct the test. For example, to complete the loopback test, the remote network administrator must create a loopback mailbox.

If a test is unsuccessful and you do not find the cause of the problem locally, work with the remote administrators to determine the cause of the problem.

## For quick results

When you test your implementation of Integrated AMIS Networking, there are two ways to ensure quick results:

- Change the batch threshold to 1.
- Tag a test message as an urgent priority message.

An urgent tag ensures quick results. You do not need to change the scheduling parameters to perform the tests and return them to their original settings after you complete the tests.

**Note:** An urgent test message is handled according to set scheduling parameters. For example, if the urgent message hold time is five minutes, it may take five minutes before the test message is sent.

# Call routing test

## Introduction

The call routing test determines if the local system

- can make outbound calls to other sites using Integrated AMIS Networking
- cannot make outbound calls to numbers that are configured as restricted on the system

## Before you begin

Ask the switch technician for the ACD/UCD agent and trunk printouts for the switch.

## To perform the call routing test

- 1 Use the ACD/UCD agent and trunk printouts to select an ACD/UCD agent.
  - 2 Program a telephone to use the same NCOS and TGAR as the agent.
- Note:** For instructions, consult your switch documentation.
- 3 Dial a network address.
  - 4 Repeat steps 1–3 for a number that you know should be restricted.

**Example:** Attempt to access a trunk directly.

## Evaluating test results

The call routing test is successful if an outbound call goes through to the allowed system but is blocked to a restricted system.

### If the test is not successful

If the call routing test fails or produces unexpected results, a switch technician must check the switch settings that control routing and restrictions on calls.

## What's next?

After you successfully complete the call routing test, perform the local SDN test.

# Local SDN test

## Introduction

The local SDN test verifies that the local system can receive messages from a remote system. This test confirms that the SDN for Integrated AMIS Networking in the SDN Table is correct.

The quick SDN test can be substituted for the local SDN test. See “Quick SDN test” on page 215.

**Note:** The SDN for Integrated AMIS Networking is, by default, the same default used by AMIS Networking.

If Integrated AMIS Networking and AMIS Networking share an SDN with another service, send the message to that SDN when you enter the system access number.

The SDN test consists of sending a message to a mailbox at your local site. You address the message as if it is being sent to an Open AMIS site. You enter the system access number in dialable format. For this test, the system access number consists of the following:

- the access code required to dial out of the system
- your local site’s number, including the exchange code and SDN

## To perform the SDN test

- 1 Log in to CallPilot.
- 2 Press **75** to compose a message.
- 3 Enter the following:
  - the AMIS compose prefix
  - the system access number
  - **#** to indicate the end of the system access number

- 4 Enter the local mailbox number on which you are currently logged, followed by #.  
**Result:** The system responds with the following message: Open network user <mailbox number> at <system access number>.
- 5 Press # again to indicate the end of the list of recipients.
- 6 Press 5 to record a message.
- 7 Record the message.
- 8 Press # to stop the recording.
- 9 Tag the message as urgent.
- 10 Press 79 to send the message.  
**Result:** The system responds with the following message: Message sent.
- 11 Log off.

## Evaluating test results

The message is sent according to the scheduling parameters for urgent messages.

The test is successful if you receive the message you recorded.

The test is not successful if you receive a non-delivery notification message.

### If the test is not successful

If the SDN test is not successful, check the Integrated AMIS Networking SDN in the SDN Table. Review the SDN setup requirements and make any necessary adjustments.

## See also

For an overview of setting up SDNs, consult the *Advanced Administration Guide*.

For a detailed discussion of setting up SDNs for Integrated AMIS Networking, consult “SDN Table and Integrated AMIS Networking” on page 106.

## What's next?

After you successfully complete the SDN test, perform the loopback test.

# Quick SDN test

## Introduction

The quick SDN test verifies that the local system can receive messages. This test confirms that Integrated AMIS Networking is correctly configured in the SDN Table.

The quick SDN test does not require the participation of a remote network administrator.

The local SDN test can be substituted for the local SDN test. See “Local SDN test” on page 213.

## To perform the quick SDN test

- 1 Log in to CallPilot.
- 2 From your local telephone, enter the local SDN for Integrated AMIS Networking.
- 3 Listen for the system to answer the call.
- 4 Repeat these steps for every SDN used by Integrated AMIS Networking.

## Evaluating test results

The quick SDN test is successful if the system answers and waits for a C-tone. The system times out after approximately 20 seconds.

The test is not successful if any prompts are heard.

### If the test is not successful

If the quick SDN test is not successful, check the Integrated AMIS Networking SDNs in the SDN Table. Review the SDN setup requirements and make any necessary adjustments.

**See also**

For detailed information on setting up SDNs, consult the *Advanced Administration Guide*.

**What's next?**

After you successfully complete the quick SDN test, perform the loopback test.

# Loopback test

## Introduction

A loopback test confirms that a message can be sent from a local site to a remote site, and returned to the local site.

You should perform this test after you add each remote site to the local database.

To perform the loopback test, compose and send a message to a loopback mailbox at a remote site. A loopback mailbox automatically returns a message to the originator.

## Before you begin

Before you perform the loopback test, you must ensure that a loopback mailbox exists on each remote site tested.

### Loopback mailbox

A loopback mailbox is a mailbox that is set up on every site in the messaging network. The only purpose of a loopback mailbox is to return a confirmation of receipt.

Get the loopback mailbox number from the network administrator of each remote site with which you are performing the Integrated AMIS loopback test.

## To perform the loopback test

- 1 Log in to CallPilot.
- 2 Press **75** to compose a message.
- 3 Enter the network address of the remote site.
- 4 Enter the loopback mailbox number of the remote site.
- 5 Press **5** to record a message.
- 6 Record the message, and press **#** to stop recording.
- 7 Tag the message as urgent.
- 8 Press **79** to send the message.

9 Wait for your Message Waiting Indicator light to activate.

**Note:** This light indicates that the message was successfully returned to you. Activation may take several minutes.

10 Log in and listen to the message.

11 Log out of the system.

## Evaluating test results

The test is successful if you hear the message that you recorded.

The message is not successful if you receive a non-delivery notification message.

### If the test is not successful

If the test is not successful, do the following:

- Check with the remote network administrator and confirm the loopback mailbox number.
- Perform the test again to ensure that the message was addressed correctly.
- Consult the operational measurement reports to determine the following:
  - Are the connection DNs correct?
  - Is the remote site operational?
  - Do the message transfer protocols match?

## What's next?

After you successfully complete the AMIS loopback test, perform the end-to-end test.

# End-to-end test

## Introduction

An end-to-end test verifies that users at a remote site can receive messages from users at the local site.

To perform the end-to-end test, send a message to a mailbox at a remote site. Send the test message to the mailbox of the remote network administrator and request a confirmation.

## Before you begin

You must coordinate with the remote network administrator of each site with which you wish to perform a loopback test. Each remote administrator must listen to the message you have sent before returning an acknowledgment.

## To perform the end-to-end test

- 1 Log in to a mailbox.
- 2 Press **75** to compose a message.
- 3 Enter the mailbox address for a mailbox at a remote site.
- 4 Press **#**.
- 5 Press **#** again.
- 6 Press **5** to record a message.
- 7 Record the message, and then press **#** to stop the recording.
- 8 Tag the message as urgent.
- 9 Press **79** to send the message.
- 10 Log out of the system and hang up.
- 11 Ask the remote administrator to log in to the mailbox and listen to the message.
- 12 Wait for an acknowledgment to be returned to you.
- 13 Log in to the mailbox and listen to the acknowledgment.

## Evaluating test results

The test is successful if the message is successfully delivered to the remote system.

The test is not successful if a non-delivery notification (NDN) is received, which indicates that the message was not received.

### Confirming successful delivery

Even if you do not receive an NDN, you may want to confirm that the message was successfully delivered.

To confirm the delivery, either

- log on to the remote site and read the message, or
- ask the administrator at the remote site to log on and read the message

### If the test is not successful

If the end-to-end test fails or produces unexpected results, check the following:

- Was the message correctly addressed?
- Does the mailbox on the remote system exist?
- Does the NDN provide any indication of the problem?

If you receive an NDN, listen to the message to determine why the test message was not delivered.

#### IF the NDN states

#### THEN

it took too many attempts to send the message

the cause may be

- incorrect message transfer protocol.
- incorrect site ID.
- incorrect connection DN.
- incorrect passwords.
- the remote site is disabled.

<b>IF the NDN states</b>	<b>THEN</b>
the address was incorrect	<p>the message was delivered to the remote site but could not be delivered. The cause may be</p> <ul style="list-style-type: none"><li>■ the mailbox does not exist.</li><li>■ the wrong mailbox number was used.</li><li>■ the Receive Composed Messages box on the Class of Services screen is set to No.</li><li>■ the disk at the remote site is full.</li></ul>
<ul style="list-style-type: none"><li>■ Do the Alarm and Event reports provide details of the possible causes? Since all previous tests have been successfully completed, the remote site probably caused the test to fail. Examples of remote site causes include the following:<ul style="list-style-type: none"><li>● Incorrect password pairs were assigned between sites.</li><li>● Channels were not available.</li><li>● Addresses were incorrect.</li><li>● Connection DNs do not terminate on the networking DN.</li><li>● A remote site that is not yet operational was specified.</li></ul></li></ul>	

## What's next?

The end-to-end test is the final test in the Integrated AMIS Networking test suite. When you successfully complete the end-to-end test, perform a backup of your configuration.

# Backing up Integrated AMIS Networking

## Introduction

When all tests of the system are successfully completed and Integrated AMIS Networking is working properly, perform a backup.

The backup ensures that the configuration is not lost due to system failure.

## Backup schedule

Perform a manual backup as the final step in the AMIS Networking installation.

**Note:** You must perform a manual backup even if the system is configured to perform an automatic backup.

In the unlikely event that the system experiences a disk failure before the automatic backup takes place, the networking configuration could be lost.

Whenever you modify Integrated AMIS Networking information during regular maintenance, perform a backup.

## System backup components

A system backup consists of two parts:

- switch backup
- CallPilot backup

## Switch backup

For detailed instructions on how to perform a switch backup, consult your switch documentation.

## CallPilot backup

You can perform a full or partial backup of your CallPilot server. For detailed instructions on how to perform a CallPilot backup, consult the *Advanced Administration Guide*.

## chapter 8

---

# Maintaining Integrated AMIS Networking

After you complete the Integrated AMIS Networking implementation, you only need to perform regular maintenance.

This chapter describes maintenance procedures that must be performed regularly. The chapter also describes maintenance procedures that you perform only when required.

### **In this chapter**

<u>About maintaining Integrated AMIS Networking</u>	225
<u>Regularly scheduled maintenance tasks</u>	231
<u>As-required maintenance tasks</u>	233



# About maintaining Integrated AMIS Networking

## **In this section**

<u>Overview</u>	226
<u>Maintain a network history</u>	228
<u>Printing configuration information</u>	229

# Overview

## Introduction

After you successfully install and test Integrated AMIS Networking, the system only requires maintenance. You need to perform two types of maintenance tasks:

- regularly scheduled
- as-required

## Regularly scheduled tasks

Regularly scheduled tasks include

- checking the network status
- reviewing Operational Measurement (OM) reports

Although you can perform regularly scheduled tasks at any time, perform these tasks at least once a week. Since these tasks do not interfere with the operation of Integrated AMIS Networking, you can schedule them at a convenient time during a regular workday.

If you monitor the performance of your messaging network, you avoid future problems. Careful monitoring shows bottlenecks in the system and indicates how the system can be improved.

Monitoring can also help you to plan and forecast future messaging network requirements.

## As-required tasks

Perform as-required tasks as needs arise. As-required tasks include

- modifying networking parameters
- disabling and enabling Integrated AMIS Networking
- modifications to the Integrated AMIS Networking configuration

**When to perform as-required tasks**

Since as-required tasks may affect the entire system, perform these tasks when the system is not in heavy use.

Modifications to the configuration may be necessary for the following reasons:

- New legal delivery times are announced for computer-generated calls.
- The system performance suggests that adjustments to the parameters are required.
- The system access number is changed.

**ATTENTION!**

---

Because as-required tasks may affect the performance of the entire system, schedule them for off-peak hours.

**Perform a backup following maintenance**

Perform a backup of the system whenever you modify the network parameters as part of your maintenance.

# Maintain a network history

## Introduction

Keep detailed records of your network's history. These records can

- Indicate significant performance or equipment issues that real-time monitoring may not detect.
- Provide a background for comparing the current information.
- Provide information needed during support calls.

## Information to record

A network history should contain the following types of information:

- installation dates and descriptions
- contact information for all key personnel involved in the system installation and configuration
- details of software installed on the messaging server, including versions
- installation process and results, including tests
- diagrams of the initial and subsequent network configurations
- any problems encountered and their solutions
- hardware and software changes
- changes to the messaging network layout

## Where to keep the records

Make the records of your messaging network easy to access and easy to read. Graphics, including hand-drawn sketches, can be very useful.

Keep records in a log or online. Note, however, that online records cannot be accessed if the system fails.

## See also

For a detailed description of messaging network histories, consult the *Networking Planning Guide*.

# Printing configuration information

## Introduction

Printouts of the system configuration are often included in a network history. You can print all configuration information contained in your local network database.

To print configuration information, you must open the relevant Properties dialog box. For example, to print an item in the Messaging Network Configuration tree view, you must open the Properties dialog box of the item.

If a Properties dialog box consists of more than one tab, the contents of all tabs are printed.

**Note:** You cannot print the tree view of the messaging network contained in the Messaging Network Configuration dialog box.

## When to print configuration information

Although configuration information is always available in the most recent backup of your network database, you may find it convenient to make printouts as well.

Printouts of the configuration information are especially useful in the following situations:

- You must fax information to a remote network administrator.
- You are keeping a network history.
- You are planning to change a configuration or delete an item from the Messaging Network Configuration tree view, and you want a hard copy of the original configuration.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration or Messaging Network Configuration

### To print configuration information

- 1 Open the dialog box that you want to print.
- 2 With the dialog box open, click the Print button.

**Result:** The contents of the dialog box print. The printout includes the contents of all tabs.

# Regularly scheduled maintenance tasks

## **In this section**

Reviewing OM reports and alerts

232

# Reviewing OM reports and alerts

## Introduction

Operational Measurement (OM) reports show how much of the CallPilot system is being used by AMIS Networking.

Three OM reports provide AMIS Networking information:

<b>This OM report</b>	<b>provides</b>
Open Networking Activity	information about open networking activity over a specified time interval.
Network Usage Bill-back	information to bill back the cost of users' networking activities.
Failed Networking Sessions alert	notification that the number of networking failures equals or exceeds the total number of networking attempts.

Although you can review OM reports at any time, you should review them at least weekly.

## Access to OM reports is restricted

The generation of OM reports is a restricted activity that is determined by access level. If you do not have the necessary access, you must ask your system administrator to generate the reports.

The OM report request screens let you choose the reports that you want to view and print. For many reports, you can also customize the displayed results so that you receive the information in a format that best suits your needs.

## See also

For more information on OM reports, including how to interpret them, consult the *Reporter Guide*.

# As-required maintenance tasks

## In this section

<a href="#"><u>Overview</u></a>	234
<a href="#"><u>Modifying the configuration of Integrated AMIS Networking</u></a>	236
<a href="#"><u>Disabling and enabling Integrated AMIS Networking</u></a>	238
<a href="#"><u>Modifying message delivery parameters</u></a>	241
<a href="#"><u>Modifying the channel resource allocation</u></a>	243
<a href="#"><u>Add, modify, or delete remote sites</u></a>	245
<a href="#"><u>Locating an item in the tree view</u></a>	247
<a href="#"><u>Modifying a remote site configuration</u></a>	248
<a href="#"><u>Deleting items in the tree view</u></a>	251
<a href="#"><u>Modifying dialing plan information</u></a>	254

# Overview

## Introduction

You may need to modify the Integrated AMIS Networking configuration, including

- whether the system can send or receive AMIS messages
- the time periods when outgoing messages are allowed to be sent during business and nonbusiness days
- the minimum and maximum port allocation for AMIS Networking
- how many messages to transmit in each AMIS Networking session
- the scheduling parameters

## Scheduling parameters

The scheduling parameters that may be modified are

- economy message send time
- stale times for economy, standard, and urgent messages
- batch threshold
- delivery days and times

## Identifying required modifications

Changes to the Integrated AMIS Networking configuration may be required if

- Message delivery scheduling is not performing as anticipated.
- There are changes to the long-distance charge period or to delivery days and times.
- There are changes to network traffic to and from Open AMIS sites.

**Example 1**

When you originally configured the system, you set the economy delivery start time to 8:00 p.m. and the stale time to 4 hours. Users find that many of their messages are going stale and are being returned with non-delivery notifications.

A coordination problem exists between the two scheduling parameters. If you compose an economy message in the morning, it may go stale before the delivery time begins. Therefore, you must reconfigure the stale time to 20 hours, for example. This reconfiguration ensures that messages can be composed throughout the business day and will not go stale before the delivery begins.

**Example 2**

When you originally configured Integrated AMIS Networking, the lower rates for long distance came into effect at 11:00 p.m. Therefore, you set the economy delivery start time to 11:00 p.m.

However, the telephone company has announced new periods for lower long-distance toll rates. Lower rates now begin at 8:00 p.m. Therefore, you change the economy delivery start time to 8:00 p.m.

# Modifying the configuration of Integrated AMIS Networking

## Introduction

If you need to modify the Integrated AMIS Networking configuration, follow these general guidelines.



---

### Risk of loss of functionality

Changes to the networking configuration should be done during hours when users are not logged on. Making changes to the configuration while users are logged on may result in loss of messaging functionality.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration > AMIS 1 or AMIS 2 tab

## To modify the Integrated AMIS Networking configuration

- 1 Review Chapter 5, “Configuring CallPilot for Integrated AMIS Networking”, to ensure that you understand the impact of the changes.
- 2 Enter all required modifications on the AMIS 1 and AMIS 2 tabs.
- 3 Click Save.

**Result:** The system validates the modifications and, if they are valid, puts the modifications into operation immediately.

## **Announce some modifications**

Most of the modifications that you make to the Integrated AMIS Networking configurations are transparent to your users. Although modifications may affect the performance of the system, they do not require any new input from users.

However, if you modify the AMIS compose prefix, you must announce this change to all local users.

If you modify the SAN, you must notify remote callers about this change. Also remind your local users to tell users at the open sites about the changes.

## **Perform a backup**

After you modify the configuration of Integrated AMIS Networking, perform a backup to ensure that these changes are not lost.

Also record the changes in your network history.

# Disabling and enabling Integrated AMIS Networking

## Introduction

You may need to disable Integrated AMIS Networking occasionally. When you disable Integrated AMIS Networking, users cannot compose, send, or receive AMIS messages.

You might disable Integrated AMIS Networking to

- Prevent system abuse.
- Temporarily suspend outgoing or incoming messages, or both.

## Messages sent while system is disabled

When you disable outbound Integrated AMIS Networking, your local users can continue to compose and send messages. The messages composed by your local users are held in queue until the option is enabled or the message becomes stale.

When you disable inbound Integrated AMIS networking, messages from remote systems are rejected. The remote system that sends the message is informed of the status, and messages are not accepted. The way the remote system handles this information depends on the system. For example, if the remote system is CallPilot, the sender receives a non-delivery notification that states that the system of the intended recipient is not accepting messages. AMIS-compliant systems from other vendors may handle this scenario differently.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration > AMIS 1 tab

## To disable and enable Integrated AMIS Networking

1 Do the following:

IF you want to	THEN
disable your system from receiving AMIS messages	clear the Incoming AMIS Networking check box.
disable your system from sending AMIS messages	clear the Outgoing AMIS Networking check box.
enable your system to receive AMIS messages	select the Incoming AMIS Networking check box.
enable your system to send AMIS messages	select the Outgoing AMIS Networking check box.

2 To save your settings, click Save.

## Other ways to disable and enable Integrated AMIS Networking

There are several ways to disable and enable Integrated AMIS Networking. Use the most appropriate method, depending on the circumstances.

In addition to the Message Delivery Configuration method described above, the following methods are available:

IF you want to	THEN
disable the sending and receiving of Integrated AMIS Networking messages by user class of service	set this option in Basic Administration.
disable or restrict the sending of Integrated AMIS Networking messages to specific or all SANs by a user	change the AMIS Restriction/Permission List for the user.

---

<b>IF you want to</b>	<b>THEN</b>
disable the sending of messages to any remote site, using any protocol, by the local server	clear the Send Messages to all other Servers option in the Messaging Network Configuration dialog box for the local server.  <b>Note:</b> This option is available only if additional networking solutions are installed on your local system.
disable the sending of messages, using the defined protocol, to a specific remote site	clear the Send Messages to all other Servers option in the Messaging Network Configuration dialog box for the remote server.  <b>Note:</b> This option is available only if additional networking solutions are installed on your local system.

---

# Modifying message delivery parameters

## Introduction

Message delivery parameters control when and how Integrated AMIS Networking sends messages. You can modify the following message delivery parameters as required:

- batch threshold
- stale times
- AMIS compose prefix
- economy delivery start and stop times
- AMIS delivery times

## Impact of modifications

The message delivery parameters are closely interrelated. Modifications to one parameter may necessitate changes to others. Therefore, carefully plan modifications in advance.

You must test and monitor the performance of the system after you make any modifications to ensure that the modifications have the desired effect and no unplanned side effects.

**Note:** Before you modify the message delivery parameters, review the previous discussion of how these parameters are set. Review Chapter 5, “Configuring CallPilot for Integrated AMIS Networking”.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration > AMIS 1 and AMIS 2 tabs

### **To modify message delivery parameters**

- 1 Modify the delivery parameters on both tabs as required.
- 2 Review the changes to ensure that there are no conflicts among the parameters.
- 3 Click Save.

### **Perform a backup**

After any modification to the configuration, perform a backup to ensure that the modification is not lost.

# Modifying the channel resource allocation

## Introduction

When you implemented Integrated AMIS Networking, you set the minimum and maximum channel resource allocation for both the inbound and the outbound Integrated AMIS Networking SDNs. The channel resources determine how efficiently services are accessed.

## Balance channel resources

You must carefully balance channels for each service when you allocate channel resources. You must allocate enough channels to ensure that users can access the service. However, you must not overallocate channels so that users are unable to access other services.

## Determine if modifications are necessary

To determine if modifications to the channel resource allocation are necessary, monitor service usage. After Integrated AMIS Networking is in service for a period of time, use the Reporter feature to determine how services are being used.

Reporter provides the following statistics:

- the number of calls queued for a service
- the average wait time for queued calls
- the maximum wait time for queued calls
- the number of callers who abandoned the queue

If you are dissatisfied with the performance of Integrated AMIS Networking after analyzing these statistics, modify the resource allocation. However, remember that modifications to the resource allocation for one service may affect the performance of other services.

**Getting there** Nortel SMI > Meridian Application Server > System Configuration > Service Administration > Service Directory Number > Service Directory Number Table

### To modify an SDN

- 1 In the SDN Table, select the SDN you want to modify.
- 2 On the File menu, select Properties.  
**Result:** The Edit Service Directory Number Properties dialog box appears.
- 3 Make the necessary modifications.
- 4 Click Save.

# Add, modify, or delete remote sites

## Introduction

As your messaging network grows and changes, you may need to add, modify, or delete a remote site.

**Note:** It is very important that all network administrators keep the information in their network database up-to-date.

## Before you begin

Before you add, modify, or delete a remote site, print all configuration information that will be affected.

## Add a remote site

When you add a site to the messaging network, all sites add the new site to their Messaging Network Configuration tree view. The remote administrator must provide the information necessary to add and configure a remote site.

## Modify a remote site

You can modify the configurations of both the messaging server and the switch locations as needs change. For example, if a remote site upgrades its system, you must modify its configuration information in your network database.

It is important that the information in your network database reflect the actual configuration of the remote site. The remote network administrator must inform you of all necessary changes.

## **Delete a remote site**

When you remove a site from the messaging network, all sites must delete it from their Messaging Network Configuration tree view.

## **Impact on network database**

Your network database reflects any additions, modifications, or deletions to remote sites. For this reason, you should perform the Integrated AMIS Networking test suite again, as well as a backup.

# Locating an item in the tree view

## Introduction

It can be difficult to locate a particular remote site, messaging server, or switch location in the Messaging Network Configuration tree view in a large messaging network.

There are two ways to locate an item in a large messaging network:

- Scroll through the alphabetized list.
- Use the Find feature.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration

## To locate an item using Find

- 1 On the File menu, select Find.

**Result:** The Find dialog box appears.

- 2 Enter the name of the item to be located, and press the Find button.

**Result:** The located item is highlighted in the Messaging Network Configuration tree view.

# Modifying a remote site configuration

## Introduction

Modify the configuration of a remote site as required.

To modify a remote site, you must open the Messaging Network Configuration tree view and select the remote messaging server or switch location that you wish to modify.

## Further information

Make modifications to the configuration on the Properties dialog box where the initial configuration was made. To review the settings, consult the instructions for the initial configuration.

<b>To review the settings on this Properties dialog box</b>	<b>Consult the instructions found here</b>
Remote Messaging Server	“Configuring a remote messaging server” on page 175.
Remote Prime Switch location	“Configuring a remote prime switch location” on page 184.
Remote Satellite Switch Location	“Configuring a remote satellite switch location” on page 195.

## Impact of modifications

When you modify the configuration of a remote system, networking service between the remote site and your local site may be affected. Modifications to the following settings are especially important:

- site IDs
- connection DN
- dialing plans
- message transfer protocol

## Enterprise Site IDs

Do not change the remote Enterprise Site ID unless the administrator at the remote site notifies you of a change in that ID, or if the ID is incorrect.

If you change the site ID to an invalid number by mistake, the system is unable to send or receive messages from the site.

## Connection DN

Do not change the connection DN to a remote site unless

- the administrator at the remote site notifies you that the DN in the SDN Table is changed, or
- you are changing the message transfer protocol

## Dialing plans

Do not change the dialing plan unless the dialing plan on the switch is changed.

## Network protocol

Do not change the network protocol configured for a remote site unless the network administrator of the remote site advises you to do so. Changing the network protocol used between two sites requires considerable reconfiguration.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration

### To modify the configuration of a remote site

- 1 In the Messaging Network Configuration tree view, select the remote messaging server or servers that you want to modify.
- 2 On the File Menu, select Open.  
**Result:** The Properties dialog box for the selected item opens.
- 3 Make all required modifications.
- 4 Click Save.  
**Result:** The modifications are validated and saved to the network database.
- 5 Repeat steps 1–4 for all items in the tree view that must be modified.

### After modifications are complete

You must test modifications to the configuration of a remote site. Complete the test suite to ensure that the modifications work properly.

When you are satisfied that your system is working properly, perform a backup.

# Deleting items in the tree view

## Introduction

The Messaging Network Configuration tree view contains all sites in your messaging network with which the local site exchanges messages.

A site always consists of a messaging server and a prime switch location. A site may also include satellite switch locations.

Sites and satellite switch locations are deleted from the Messaging Network Configuration tree view.

**Note:** You cannot delete the local site. You can delete local satellite switch locations.

### **ATTENTION!**

---

When an item is deleted from the Messaging Network Configuration tree view, it is permanently removed from the local network database. The information cannot be recovered. For this reason, it is strongly recommended that you print out the complete configuration of all items to be deleted. If an item is accidentally deleted, you can use the printed information to add the item again.

## Multi-administrator environments

If several administrators maintain your local network database, ensure that your view of the Messaging Network Configuration tree view is up-to-date. The Messaging Network Configuration tree view is updated when it is initially opened. An open tree view is not updated when another administrator makes changes.

## To check the status of the view

To see if another administrator has made changes to the Messaging Network Configuration tree view, on the View menu, click Refresh.

## Getting there Nortel SMI > Meridian Application Server > CallPilot > Networking > Messaging Network Configuration

### To delete a remote site

- 1 Print the configuration details of the site that you want to delete.
- 2 Open the folder of the remote site to see the messaging server, prime switch location, and any satellite switch locations.
- 3 In a multi-administrator environment, on the View menu, click Refresh.
- 4 Highlight the messaging server of the site that you want to delete.
- 5 Select File > Delete.

**Result:** A confirmation message appears asking if you really want to delete the site from your local network database.

- 6 To delete the site, click Yes.

**Tip:** You can also delete a highlighted remote site by clicking the Delete button.

### Deleting several remote sites at once

If you must delete several remote sites from the local network database, you may find it more efficient to delete all the sites at once.

### To delete several remote sites at once

- 1 Print the configuration details of all the sites that you want to delete.
- 2 In the tree view, highlight all the remote sites that you want to delete.  
**Tip:** To select more than one item in the tree view, press Ctrl and right-click the mouse.
- 3 Select File > Delete.  
**Result:** A confirmation message appears.
- 4 Click Yes to delete the sites. Click No to keep the sites.

## Deleting a satellite switch location

If there are changes to an NMS site, you can delete one or more satellite switch locations from the local site or from any remote sites.

If you remove a satellite switch location from an NMS site, you must also remove it from the local network database.

## To delete a satellite switch location

Print the configuration details of the satellite switch location.

- 1 In a multi-administrator environment, on the View menu, click Refresh.
- 2 Highlight the satellite switch location that you want to delete.
- 3 On the File menu, click Delete.

**Result:** A confirmation message appears.

- 4 Click Yes to delete the sites. Click No to keep the sites.

# Modifying dialing plan information

## Introduction

After you establish a dialing plan, you rarely modify it. Modifications to a dialing plan affect users and may require considerable relearning of the system.

However, if modifications are necessary, they are usually guided by changes made by the switch technician. These changes can be local or remote.

## Switch changes

If any changes to the dialing plan are made on a switch, the network databases of the sites in the messaging network must reflect these changes. If changes are made locally, ensure that all remote sites are notified.

## To modify the dialing plan information

If you need to modify the dialing plan, follow the general instructions to modify the local and remote sites.

### Modifying CDP steering codes

Modifications to the CDP steering codes are more complicated. For a detailed review of how to plan for and implement changes, consult Chapter 4, “Dialing plans and networking,” in the *Networking Planning Guide*.

## chapter 9

---

# Troubleshooting Integrated AMIS Networking

Although testing and regular maintenance ensure that Integrated AMIS Networking is working properly, the system may experience occasional problems.

This chapter describes how to diagnose and correct these problems.

### **In this chapter**

<u>About troubleshooting Integrated AMIS Networking</u>	257
<u>Determining if problems are switch-related</u>	263



# About troubleshooting Integrated AMIS Networking

## In this section

<u>Overview</u>	258
<u>Determine if Integrated AMIS is disabled</u>	260
<u>Reviewing Alarm and Event reports</u>	261
<u>Reviewing Operational Measurement reports</u>	262

# Overview

## Introduction

If you are experiencing problems with Integrated AMIS Networking, this chapter will help you to identify and solve these problems.

Common causes of Integrated AMIS Networking problems include the following:

- Integrated AMIS Networking is disabled.
- The status of a remote site prevents it from receiving messages from the local site.
- Networking configuration is incorrect or incomplete.
- The switch is configured incorrectly.
- There are hardware problems.

## Identify the source of the problem

To identify the source of the problem, first determine if Integrated AMIS Networking is disabled.

If Integrated AMIS Networking is properly enabled, then review the following:

- appropriate Alarm and Event reports
- network status
- Operational Measurement (OM) reports

## Configuration errors

Configuration errors may include the following:

- incorrect connection DNs
- message transfer protocols that do not match between the remote and local sites
- incorrect dialing plan information, including ESN prefixes and CDP steering codes
- scheduling parameters that need to be modified

## Site status errors

A site can be either intentionally disabled or put into error status.

A remote site may be put into error status because of unsuccessful attempts by the local site to deliver messages to the remote site. Failed message delivery can happen for the following reasons:

- The remote site is experiencing hardware or software problems.
- There are site configuration errors.

## Switch-related problems

If you are unable to identify the problem using CallPilot, the error may be switch-related. Perform the call trace test to determine if there is a problem with the switch configuration.

### Call trace

Call trace helps you to determine if network calls are being blocked for one or more of the following reasons:

- Digit manipulation is performed incorrectly. Either not enough or too many digits are inserted or deleted.
- Class of service restrictions are either too stringent or too loose.
- Dialing is incorrect. More digits are required by the trunks or trunk routes.

**Note:** On the switch, you can perform a call trace on a telephone or on a trunk and a trunk route.

## Hardware problems

If you are unable to locate the problem in the CallPilot networking configuration or in the switch, your system may be experiencing hardware problems that are not related to networking.

Perform a basic hardware check. Examine all connections.

# Determine if Integrated AMIS is disabled

## Introduction

You must enable Integrated AMIS Networking to receive incoming AMIS messages and to deliver outgoing AMIS messages.

Begin any troubleshooting session by determining if Integrated AMIS Networking is properly enabled.

There are several methods of disabling and enabling the sending and receiving of Integrated AMIS Networking messages.

If	Check this setting
the system does not receive incoming messages	Incoming AMIS Networking messages enabled.
the system does not deliver outgoing messages	Outgoing AMIS Networking messages enabled.

To determine if Integrated AMIS Networking has been disabled to receive incoming messages or to send outgoing messages, or both, check the settings on the AMIS 1 tab of the Message Delivery Configuration dialog box.

**Getting there** Nortel SMI > Meridian Application Server > CallPilot > Networking > Message Delivery Configuration

## To determine if Integrated AMIS Networking is disabled

- 1 From the Message Delivery Configuration dialog box, select the AMIS 1 tab.
- 2 Check the settings of the Outgoing AMIS Networking and Incoming AMIS Networking check boxes. Ensure that these check boxes are selected as required for your system.
- 3 Click Save to exit and save any changes that you made.

# Reviewing Alarm and Event reports

## Introduction

Alarm and Event reports track and report system errors and unusual events. These reports can be viewed on-screen or printed, or both.

## Reports related to Integrated AMIS Networking

The following reports are useful for monitoring Enterprise Networking:

- Networking Activity report
- Network Usage Bill-back report
- Failed Networking Sessions alert

## See also

For instructions on reviewing and interpreting Alarm and Event reports, consult the *Reporter Guide*.

# Reviewing Operational Measurement reports

## OM reports

Operational Measurement (OM) reports contain detailed information on how the system is functioning. When you attempt to locate problems with Integrated AMIS Networking, review these reports.

When you review the OM reports, consider the following:

This OM result	Suggests
large number of accesses	the holding time may be too low, or the batch threshold is too small.
excessive “Failed to Send” messages	the remote system may be down, or the dialing translations are incorrectly configured, or the call maximum number is too small.
high number of NDNs	users are entering incorrect addresses, or mailboxes do not exist on the remote system.
networking traffic is excessive	an unusual or cyclical event affected the system, or the number of channels used by Integrated AMIS Networking is too small, or the number of channels available to Integrated AMIS Networking is too small.
failures	the remote system does not support the AMIS protocol, or the number of channels is too small.

## See also

For detailed instructions on producing, reviewing, and interpreting Operational Measurement reports, consult the *Reporter Guide*.

# Determining if problems are switch-related

## In this section

<u>Switch-related problems</u>	264
<u>Call trace test</u>	265
<u>Link diagnostic test</u>	267

# Switch-related problems

## Integrated AMIS Networking problems and the switch

If you cannot identify the cause of the Integrated AMIS Networking errors using CallPilot, the problem may be switch-related.

The following tests identify switch-related problems:

- call trace
- link diagnostic

# Call trace test

## Purpose

If you cannot identify the Integrated AMIS Networking problem using CallPilot, calls may be blocked by the switch. The call trace test determines

- if calls are blocked
- why calls are blocked

## Why calls are blocked

A network call can be blocked for one or more of the following reasons:

- Digit manipulation is performed incorrectly. Not enough or too many digits are inserted or deleted.
- Class of service restrictions are too stringent or too loose.
- Dialing is incorrect. More digits are required by the trunks or card trunk routes.

## Where a call trace is performed

On the switch, you can perform a call trace on a phoneset or on a trunk and trunk route.

## Before you begin

To interpret the results of a call trace test, you need to understand

- how the switch processes calls
- how to interpret the results of a call trace session

**Note:** A switch technician should perform the call trace test and interpret the results.

The information that is required to perform the call trace test varies for each type of switch. However, the following information is usually required:

- your customer number
- the directory number that will be tested
- the type of telephone and key number (for multiline telephones)
- the terminal number (loop, shelf, card, unit) of the telephone or trunk that will be tested
- the route type and trunk number of the trunk and trunk route that will be tested

### **To perform the call trace test**

Follow the instructions in your switch documentation.

### **How to interpret the results**

For guidelines on how to interpret the results of the call trace test, consult your switch documentation.

# Link diagnostic test

## Purpose

If you cannot identify the cause of the networking problem on the CallPilot or by performing the call trace test, the problem may not be related to networking.

The link diagnostic test determines if the link between the switch and the Meridian Application Server is working.

## Before you begin

The link diagnostic must be performed by a switch technician.

## To perform the link diagnostic test

Follow the instructions in your switch documentation.



# Field index

## A

Add/Update Remote Users on this Server, 156

## B

Batch Threshold, 129

## C

CDP Steering Code  
  Overlap, 170  
  Prime Switch Location Properties dialog box, 170  
  Remote Prime and Satellite Switch Location Properties dialog boxes, 192  
Collect (number of) messages before sending (Batch Threshold), 129

## D

Description  
  Local Messaging Server Properties dialog box, 155  
  Prime Switch Location Properties dialog box, 161  
  Remote Messaging Server Properties dialog box, 177  
  Remote Prime and Satellite Switch Location Properties dialog boxes, 185  
Dialing plans for dialing to this location  
  Prime Switch Location Properties dialog box, 162  
  Remote Prime and Satellite Switch Location Properties dialog boxes, 187

## E

Economy Integrated AMIS stale time, 129

Economy Open AMIS stale time, 129  
Enterprise Location ID  
  Prime Switch Location Properties dialog box, 161  
  Remote Prime and Satellite Switch Location Properties dialog boxes, 186  
Enterprise Site ID  
  Local Messaging Server Properties dialog box, 156  
  Remote Messaging Server Properties dialog box, 179  
ESN Access Code used by this location  
  Prime Switch Location Properties dialog box, 166  
  Remote Prime and Satellite Switch Location Properties dialog boxes, 189  
ESN Location Code  
  Overlap, 167  
  Prime Switch Location Properties dialog box, 166  
  Remote Prime and Satellite Switch Location Properties dialog box, 189  
  Remote Prime and Satellite Switch Location Properties dialog boxes, 189

## I

Incoming AMIS Networking, 128  
Integrated AMIS economy delivery start and stop times, 133  
Integrated AMIS Networking connection DNs, 181

## L

Local Messaging Server Properties dialog box, 156  
  Add/Update Remote Users on this Server, 156  
  Description, 155  
  Name, 155  
  Receive Message Text Info, 157

Send Messages to all other Servers, 155  
 Server FQDN, 157  
 Server type, 155

## M

Mailbox addressing follows dialing plan  
 Prime Switch Location Properties dialog box, 162  
 Remote Prime and Satellite Switch Location Properties dialog boxes, 187  
 Mailbox prefixes  
 Prime Switch Location Properties dialog box, 163  
 Remote Prime and Satellite Switch Location Properties dialog boxes, 188  
 Message Delivery Configuration dialog box, 128  
 Batch Threshold, 129  
 Collect (number of) messages before sending (Batch Threshold), 129  
 Economy Integrated AMIS stale time, 129  
 Economy Open AMIS stale time, 129  
 Incoming AMIS Networking, 128  
 Integrated AMIS economy delivery start and stop times, 133  
 Open AMIS compose prefix, 133  
 Open AMIS economy delivery start and stop times, 133  
 Outgoing AMIS Networking, 128  
 Private network Local AMIS System Access Number, 129  
 Public network Local AMIS System Access Number, 128

## N

Name  
 Local Messaging Server Properties dialog box, 155  
 Prime Switch Location Properties dialog box, 161  
 Remote Messaging Server Properties dialog box, 176  
 Remote Prime and Satellite Switch Location

Properties dialog boxes, 185  
 Network protocol, 180

## O

Open AMIS compose prefix, 133  
 Open AMIS delivery times, 134  
 Open AMIS delivery times dialog box, 134  
 Open AMIS economy delivery start and stop times, 133  
 Outgoing AMIS Networking, 128  
 Overlap  
 CDP Steering Code, 170  
 ESN Location Code, 167

## P

Prime Switch Location Properties dialog box  
 CDP Steering Code, 170  
 Description, 161  
 Dialing plans for dialing to this location, 162  
 Enterprise Location ID, 161  
 ESN Access Code used by this location, 166  
 ESN Location Code, 166  
 Mailbox addressing follows dialing plan, 162  
 Mailbox prefixes, 163  
 Name, 161  
 Spoken Name Recorded, 162  
 Private network Local AMIS System Access Number, 129  
 Public network Local AMIS System Access Number, 128

## R

Receive Message Text Info, 157  
 Remote Messaging Server Properties dialog box  
 Description, 177  
 Enterprise Site ID, 179  
 Integrated AMIS Networking connection  
 DNSs, 181  
 Name, 176  
 Network protocol, 180  
 Send local user information to this Server, 178

- Send Message Text Info to this Server, 179
- Send Messages to this Server, 177
- Server FQDN, 179
- Server type, 177
- Remote Prime and Satellite Switch Location
  - Properties dialog boxes
  - CDP Steering Code, 192
  - Description, 185
  - Dialing plans for dialing to this location, 187
  - Enterprise Location ID, 186
  - ESN Access Code used by this location, 189
  - ESN Location Codes, 189
  - Mailbox addressing follows dialing plan, 187
  - Mailbox prefixes, 188
  - Name, 185
  - Spoken Name Recorded, 186
- Remote Satellite Switch Location Properties dialog box
  - See also* Remote Prime and Satellite Switch Location Properties dialog boxes
  - Spoken Name Recorded, 196

## S

- Send local user information to this Server, 178
- Send Message Text Info to this Server, 179
- Send Messages to all other Servers, 155
- Send Messages to this Server, 177
- Server FQDN
  - Local Messaging Server Properties dialog box, 157
  - Remote Messaging Server Properties dialog box, 179
- Server type
  - Local Messaging Server Properties dialog box, 155
  - Remote Messaging Server Properties dialog box, 177
- Spoken Name Recorded
  - Prime Switch Location Properties dialog box, 162
  - Remote Prime and Satellite Switch Location Properties dialog boxes, 186
  - Remote Satellite Switch Location Properties dialog box, 196

## U

- Urgent Stale Time, 130



# Index

## Numerics

120-Minute Messages, 53

## A

access code, ESN, 166  
access to OM reports, 232  
Acknowledgment Tag, 52  
adding and configuring a remote site, 174, 245  
    information required, 174  
    main steps, 174  
administration guides, 19  
Administrator-Recorded Personal Verification, 52  
AMIS 1 tab, Message Delivery Configuration dialog box, 127  
AMIS 2 tab, Message Delivery Configuration dialog box, 131, 132  
AMIS compose prefix  
    overview, 69  
    selecting, 133  
AMIS Networking  
    compared with Integrated AMIS Networking, 47  
    configuring, 137  
    enabling functionality, 137  
    implementation, 60  
    Open AMIS boxes, 123  
    parameters, 68  
    relationship to Integrated AMIS, 48  
AMIS protocol, 47  
AMIS-A Networking. *See* AMIS Networking, 47  
AMIS-A protocol, 47  
ANA (Analog Networking Agent)  
    description, 75  
    function, 79  
Analog Messaging Agent. *See* ANA  
as-required maintenance tasks, 226

Audio Messaging Interchange Specification Networking. *See* AMIS Networking, 47

## B

backing up Integrated AMIS Networking, 59, 222  
    backup schedule, 222  
    CallPilot backup, 222  
    switch backup, 222  
    types of backup, 222  
balancing channel resources, 243  
batch threshold  
    default value, 124  
    description, 65, 129  
    impact of holding time, 130

## C

call routing test  
    evaluating result, 212  
    procedure, 212  
    purpose, 210  
Call Sender, 51  
call trace test  
    evaluating result, 266  
    preliminary requirements, 265  
    purpose, 265  
CallPilot  
    and Integrated AMIS Networking, 46, 51  
    backup, 222  
    configuring, 122  
CDP dialing plan, configuration overview, 169  
CDP information  
    configuring, 171  
    remote prime switch location, 192  
CDP steering code  
    overlap, 170  
    overview, 170  
CDP tab

Prime Switch Location Properties dialog box, 161

Remote Prime Switch Location Properties dialog box, 184

Remote Satellite Switch Location Properties dialog box, 195

channel resource allocation, 243

- determining if modifications are required, 243
- minimum and maximum, 109
- modifying, 243

channel types supported, 108

checklist for gathering information, 94

complex messaging network

- implementation in, 60
- order of implementation, 60

complex network, 49

compose prefix

- description, 69
- selecting, 133

configuration errors, 258

configuration, printing information, 229

configuring

- AMIS Networking, 137
- CallPilot for Integrated AMIS Networking, 58
- CallPilot, main steps, 122
- CDP information, 171
- CDP information for a remote prime switch location, 193
- ESN information, 168
- local prime switch location, overview, 159
- local server, overview, 154
- local site, overview, 152
- message delivery parameters, 135
- non-CallPilot system as a remote site, 203
- remote messaging server, 175, 181
- remote satellite switch location, 197
- remote satellite switch location, overview, 195
- remote switch location, overview, 184

configuring Integrated AMIS Networking

- if other networking solutions are implemented, 147
- overview, 123
- preliminary requirement, 122, 125

- required information, 123
- suggested process, 125

configuring the switch, preliminary requirements, 104

confirming switch settings, 92

connection DN

- function, 72
- modifying, 249
- relationship to system access number, 71
- remote messaging server, 181

Connections tab, Remote Messaging Server Properties dialog box, 180

controlled directory number (CDN) queues, types, 116

Conventions 24, 24

coordinating information with remote sites, 72

creating a diagram of messaging network, 98

creating a loopback mailbox, 141

creating a Restriction/Permission List, 86

creating a spreadsheet of messaging network, 98

## D

default value

- batch threshold, 124
- delivery start time for economy messages, 124
- delivery stop time for economy messages, 124
- holding time for standard messages, 124
- holding time for urgent messages, 124
- parameters, 64
- reason to use, 124
- scheduling parameters, 124
- stale time for economy messages, 124
- stale time for standard messages, 124
- stale time for urgent messages, 124

definition

- integrated, 48
- Integrated AMIS Networking, 46
- network administrator, 48
- open, 48
- service directory number (SDN), 106

deleting

- in multi-administrator environment, 251

- remote messaging server, 251
- remote site, 246, 251
- satellite switch location, 251, 253
- several remote sites, 252
- delivery start and stop times, economy messages, 133
- delivery start time for economy messages, 67
  - default value, 124
- delivery stop time for economy messages, 67
  - default value, 124
- delivery times, Open AMIS, 70
  - description, 69
    - local server, 155
- diagram of how MTA and ANA handle messages, 76
- diagram of Integrated AMIS Networking, 46
- diagram of messaging network, 98
- dialing plan
  - CDP for remote prime switch location, 192
  - CDP information, 169
    - changing, 96
  - ESN for remote prime switch location, 189
  - ESN information, 165
    - information for remote prime switch location, 187
  - information required from switch, 91
  - information required to configure switch location, 162
  - local prime switch location, 162
  - mailbox addressing follows, 162
  - mailbox addressing follows for remote prime switch location, 187
  - modifying, 249, 254
  - remote satellite switch location, 196
    - requirements, 96
  - used to dial a remote switch location, 187
- directory number (DN)
  - and switch, 116
    - for Integrated AMIS Networking, 116
- disabling Integrated AMIS Networking, 128, 238
  - other methods, 239
- DN. *See* directory number
- dual-tone multifrequency tones, 47

## E

- economy delivery start and stop times, 67, 69, 133
- economy message
  - stale time, 68
- economy priority messages, 63
- Economy Tag, 53
- Electronic Switched Network. *See* ESN
- enabling Integrated AMIS Networking, 128, 155, 238
  - other methods, 239
- end-to-end test
  - evaluating results, 220
    - procedure, 219
    - purpose, 210
- Enterprise Location ID
  - local prime switch location, 161
  - remote prime switch location, 186
- Enterprise Networking
  - Enterprise Location ID, 161, 186
  - Enterprise Site ID, 156
  - Names Across the Network, 156
    - receiving message text information, 157
    - sending message text information to a remote site, 179
- Enterprise Site ID
  - description, 156
  - modifying, 249
  - remote messaging server, 179
- ESN
  - access code, 166
  - location code, 166
    - location code overlap, 167
- ESN dialing plan, configuration overview, 165
- ESN information, remote prime switch location, 189
- ESN tab
  - Prime Switch Location Properties dialog box, 160
  - Remote Prime Switch Location Properties dialog box, 184
  - Remote Satellite Switch Location Properties dialog box, 195
- evaluating gathered information, 96

**F**

Failed Networking Sessions alert, 232  
 Fax Call Answering CDN queues, 116  
 fax channel type, 108  
 features of Integrated AMIS Networking, 51  
 Find key, using to locate item, 247  
 finding a remote site, 247  
 finding problem with Integrated AMIS  
   Networking, 258  
 FQDN of local server, 157  
 FQDN of local SMTP/VPIM server, 152

**G**

gathering information  
   checklist, 94  
   evaluating, 96  
   from open sites, 90  
   from other sites, 97  
   from switch, 91  
   purpose, 90  
   remote switch location checklist, 95  
   required for network, 57  
   required from switch, 57, 93  
   to implement Integrated AMIS Networking,  
     90  
 General tab  
   Prime Switch Location Properties dialog box,  
     160  
   Remote Messaging Server Properties dialog  
     box, 176  
   Remote Prime Switch Location Properties  
     dialog box, 185, 195  
   Remote Switch Location Properties dialog  
     box, 184

**H**

hardware problems, 259  
 header contents, 62  
 holding time  
   description, 65  
   interaction with batch threshold, 130  
   relationship to stale time, 130

  standard messages, 65, 130  
   urgent messages, 65, 130  
 holding time for standard messages, default, 124  
 holding time for urgent messages, default, 124  
 how a message is transferred, 80  
 how connection DNs work, 72  
 how to  
   add and configure a new inbound service  
     directory number (SDN), 113  
   configure a local prime switch location, 163  
   configure a remote messaging server, 181  
   configure a remote prime switch location,  
     188  
   configure a remote satellite switch location,  
     197  
   configure AMIS Networking, 137  
   configure CDP information, 171  
   configure CDP information for a remote  
     prime switch location, 193  
   configure ESN information, 168  
   configure ESN information for a remote  
     prime switch location, 190  
   configure Integrated AMIS Networking  
     parameters, 135  
   configure the local messaging server, 157  
 control exchange of open networked  
   messages, 85  
 create a loopback mailbox, 141  
 delete a remote site, 252  
 delete a satellite switch location, 253  
 delete several remote sites, 252  
 determine if Integrated AMIS Networking is  
   disabled, 260  
 disable Integrated AMIS Networking, 239  
 enable Integrated AMIS Networking, 239  
 import a spoken name, 202  
 locate an item using Find, 247  
 modify a remote site configuration, 250  
 modify an SDN, 244  
 modify dialing plan information, 254  
 modify message delivery parameters, 242  
 modify the Integrated AMIS Networking,  
   236  
 print configuration information, 230  
 record a spoken name, 200  
 set the default message priority, 84

share an existing inbound service directory number (SDN), 114

## I

### implementation

- AMIS Networking, 60
- backup, 59
- configuring CallPilot, 58
- configuring the switch, 58
- creating messaging network representation, 58
- gather information for network, 57
- main steps, 57
- overview, 56
- parameters set during, 64
- preliminary requirements, 56
- recommended order in complex messaging network, 60
- testing, 59
- validation, 58

implementation order in complex messaging network, 60

importing a spoken name, 201, 202

inbound service directory number (SDN)

- how to add and configure new, 113
- how to share existing, 114
- services that can share, 112
- ways to set up, 112

indicators in OM reports, 262

information, gathering to implement Integrated AMIS Networking, 90

installation and configuration guides, 19

Integrated AMIS Networking and CallPilot, 46

- backing up information, 59
- compared with AMIS Networking, 47
- configuring a remote messaging server, 181
- configuring a remote prime switch location, 188
- configuring a remote satellite switch location, 197
- configuring CDP information, 171
- configuring CDP information for a remote prime switch location, 193

- configuring ESN information for a remote prime switch location, 190
- configuring parameters, 135
- configuring the local server, 157
- definition, 46
- determining if disabled, 260
- diagram, 46
- directory number, 116
- disabling, 128, 238
- enabling, 128, 238
- end-to-end test, 210
- features, 51
- gathering information, 90
- how it works, 71
- how to disable, 239
- how to enable, 239
- how to modify an SDN, 244
- how to modify message delivery parameters, 242
- implementation in a complex messaging network, 60
- implementation overview, 56
- in complex network, 49
- information validation, 58
- internal controls, 74
- local site configuration, 152
- maintaining, 226
- message contents, 62
- message handling, 62
- modifying channel resource allocation, 243
- modifying configuration, 234
- modifying message delivery parameters, 241
- parameters, 64
- performing backups, 222
- phantom DN, 117
- preliminary requirements for configuration, 146
- protocol used, 47
- relationship to AMIS, 48
- relevant OM reports, 232
- switch configuration required, 104
- switch requirements, 104
- switch settings required, 96, 116
- switch-related problems, 264
- testing, 59
- troubleshooting, overview, 258

Integrated AMIS Networking test suite, 210  
  call routing test, 210  
  local or quick SDN test, 210  
  loopback test, 211  
integrated, defined, 48

## L

legal delivery times for AMIS messages, 70, 134  
link diagnostic test, 267  
local AMIS system access number, 128  
local messaging server name, 152  
local prime switch location  
  configuration if NMS local site, 159  
  configuration if other networking solution implemented, 159  
  configuration overview, 159  
  configuration procedure, 163  
  description, 161  
  dialing plan information, 162  
  Enterprise Location ID, 161  
  mailbox prefix, 163  
  name, 161  
  Prime Switch Location Properties dialog box, 160  
  recording spoken name, 162  
local SDN test  
  evaluating results, 214  
  procedure, 213  
  purpose, 210  
local server  
  configuration if another networking solution implemented, 153  
  configuration overview, 154  
  configuration process, 157  
  description, 155  
  FQDN, 157  
  name, 155  
  server type, 155  
local site name, 152, 155  
local site, configuring, 152  
locating remote site, 247  
location code  
  ESN, 166

  overlap, 167  
loopback mailbox  
  creating, 141  
  description, 140  
  requirements, 140  
  using, 141  
loopback test  
  evaluating results, 218  
  procedure, 217  
  purpose, 211

## M

mailbox addressing follows dialing plan, local prime switch location, 162  
mailbox addressing, dialing plan follows for remote prime switch location, 187  
mailbox prefix  
  local prime switch location, 163  
  remote prime switch location, 188  
mailbox, loopback, 140  
main steps in implementation, 57  
maintenance  
  as-required tasks, 226  
  backups following, 227  
  overview, 226  
  regularly scheduled tasks, 226  
Meridian Mail system, remote site, 205  
message  
  body contents, 62  
  configuration for using priorities, 63  
  handling scenario, 80  
  header contents, 62  
  parts, 62  
  priorities, 63  
  transfer process, 80  
Message Delivery Configuration dialog box  
  AMIS 1 tab, 127  
  AMIS 2 tab, 131, 132  
  Standard stale time, 129  
  Urgent stale time, 129  
message delivery parameters  
  configuring, 135  
  overview, 126

- message delivery parameters, modifying
    - configuration, 241
  - message handling, 76
  - message priority, setting default, 84
  - Message Subject (Text), 53
  - Message Transfer Agent (MTA), description, 74
  - message transfer protocol, modifying, 249
  - message transfer, main steps, 75
  - messages sent while system disabled, 238
  - Messaging Administration Properties dialog box
    - Networking Loopback Mailbox, 140
  - messaging network, 146
  - Messaging Network Configuration tree view,
    - adding sites, 146
  - messaging network representation, 58
    - benefits, 99
    - coordination with other sites, 99
    - diagram, 98
    - overview, 98
    - security, 99
    - spreadsheet, 98
  - migration guides, 18
  - modifying
    - channel resource allocation, 243
    - configuration of Integrated AMIS
      - Networking, 234
    - connection DN, 249
    - dialing plan, 249, 254
    - Enterprise Site ID, 249
    - Integrated AMIS Networking, announcing, 237
    - message delivery parameters, 241
    - message transfer protocol, 249
    - remote site, 245
  - modifying remote site, 245
    - configuration, 248
    - impact, 248
    - preliminary requirement, 245
  - modifying remote site, impact on network
    - database, 246
  - MTA (Message Transfer Agent), description, 74
  - MTA Monitor, description, 75
  - multi-administrator environment, deleting items
    - from tree view, 251
  - Multiple Recipients, 52
- ## N
- name
    - local prime switch location, 161
    - remote prime switch location, 185
  - Name Addressing, 51
  - Name Dialing, 51
  - name of a remote site, 176
  - name of the local server, 155
  - name of the local site, 152
  - Names Across the Network, 51, 156
  - network administrator, defined, 48
  - network database, impact of modifying remote sites on, 246
  - network history
    - contents, 228
    - overview, 228
    - security, 228
  - network protocol used with a remote site, 180
  - network representation
    - overview, 98
    - using to add and configure a remote site, 174
  - Network Usage Bill-back report, 232
  - networking
    - documentation, 20
  - Networking Loopback Mailbox, 140
  - networking solutions
    - configuration if implemented, 147
    - order of implementation, 60
  - NMS local site, configuring local prime switch location, 159
  - NMS site
    - spoken name imported for, 201
    - spoken name recorded for, 199
  - non-CallPilot system
    - remote sites, 203
    - server type, 204
  - Norstar Voice Mail, remote site, 206
- ## O
- OM reports
    - importance of reviewing, 232
    - relevant for Integrated AMIS Networking, 232

- restricted access, 232
- online guides, 22
- online Help, accessing, 22
- Open AMIS boxes on screens, 123
- Open AMIS compose prefix, 69, 133
- Open AMIS delivery times, 70, 134
- Open AMIS parameters, 68
- Open Networking Activity report, 232
- open, defined, 48
- order of implementation, recommended, 60
- outbound service directory number (SDN), 112
- overlap
  - CDP steering code, 170
  - ESN location code, 167

## P

- parameters
  - AMIS Networking, 68
  - default values, 64
  - importance, 68
  - Integrated AMIS Networking, 64
  - overview, 68
  - set during implementation, 64
- Personal Distribution Lists, 51
- phantom DN
  - how to select, 117
  - relationship to service directory number (SDN), 108
  - required by Integrated AMIS Networking, 117
  - ways to create, 118
- planning guides, 18
- prefix
  - compose, 133
  - mailbox, 163
- Prime Switch Location Properties dialog box, 160
  - CDP tab, 161
  - ESN tab, 160
  - General tab, 160
  - SMTP/VPIM tab, 161
- printing configuration information, 229
- priorities of messages, 63
- Private Tag, 52

- protocol, AMIS Networking, 47
- protocol, used with a remote site, 180

## Q

- quick SDN test
  - evaluating results, 215
  - procedure, 215
  - purpose, 210

## R

- Received Time Announced, 53
- receiving message text information, 157
- Recipient's Name (Text), 53
- recording a spoken name, 200
- regularly scheduled maintenance tasks, 226
- remote messaging server
  - configuration if another messaging solution implemented, 175
  - configuration overview, 175
  - connection DN, 181
  - deleting, 251
  - Enterprise Site ID, 179
  - name, 176
  - network protocol used, 180
  - sending local user information to, 178
  - sending message text information, 179
  - sending messages to a remote site, 177
  - server FQDN, 179
  - server types supported, 177
- Remote Messaging Server Properties dialog box
  - Connections tab, 180
  - General tab, 176
- remote prime switch location
  - CDP information, 192
  - configuring, 188
  - configuring ESN information, 190
  - dialing plan for dialing to this location, 187
  - dialing plan information, 187
  - Enterprise Location ID, 186
  - ESN information, 189
  - mailbox addressing follows dialing plan, 187
  - mailbox prefix, 188
  - name, 185

- spoken name recorded, 186
  - Remote Prime Switch Location Properties
    - dialog box
    - CDP tab, 184
    - ESN tab, 184
    - General tab, 185
    - SMTP/VPIM tab, 184
    - tabs, 184
  - remote satellite switch location
    - configuration overview, 195
    - configuring, 197
    - dialing plan, 196
    - spoken name recorded, 196
  - Remote Satellite Switch Location Properties
    - dialog box
    - CDP tab, 195
    - ESN tab, 195
    - tabs, 195
  - remote site
    - adding, 245
    - adding and configuring, 174
    - adding, modifying, and deleting, 245
    - coordinating information, 72
    - deleting, 246, 251
    - how to delete, 252
    - how to modify configuration, 250
    - if other networking solutions implemented, 147
    - impact of modification, 248
    - information required to add and configure, 174
    - locating, 247
    - main steps to add and configure, 174
    - Meridian Mail system, 205
    - modifying, 245
    - modifying configuration, 248
    - name, 176
    - non-CallPilot, 203
    - Norstar Voice Mail system, 206
    - using network representation to add and configure, 174
  - Remote Site Spoken Names, 52
  - remote switch location
    - configuration overview, 184
    - information required, 95
    - spoken name, 199, 201
  - Remote Switch Location Properties dialog box,
    - General tab, 184
  - Reply All, 52
  - Reply To, 52
  - reports for Integrated AMIS Networking, 261
  - restricting message exchange, 156
  - restricting sending messages to a remote site, 177
  - Restriction/Permission Lists
    - assigning for AMIS Networking, 86
    - creating, 86
    - purpose, 86
  - reviewing Alarm and Event reports, 261
  - reviewing OM reports, 232
    - what to look for, 262
- ## S
- satellite switch location
    - configuring remote, 195
    - deleting, 251
  - scheduling backups, 222
  - SDN. *See* service directory number
  - Sender's Department, 53
  - Sender's Name (Text), 53
  - sending local user information to a remote site, 178
  - sending message text information to a remote site, 179
  - sending messages to other sites, 155
  - Sent Time Announced, 53
  - server FQDN, 157
    - local SMTP/VPIM server, 152
    - remote site, 179
  - server type
    - local server, 155
    - non-CallPilot remote sites, 204
    - supported for remote messaging server, 177
  - service directory number (SDN)
    - adding and configuring new, 113
    - and DN setting on switch, 107
    - definition, 106
    - examples, 109
    - how to modify, 244
    - inbound, 106, 112

- outbound, 106, 112
- relationship to other numbers, 107
- sharing existing inbound, 114
- Service Directory Number (SDN) Table
  - description, 106
  - example, 107
- Shared Distribution Lists, 52
- site status errors, 259
- SMTP/VPIM server FQDN, 152
- SMTP/VPIM tab
  - Prime Switch Location Properties dialog box, 161
  - Remote Prime Switch Location Properties dialog box, 184
- speech recognition channel type, 108
- Speech Recognition Messaging CDN queues, 116
- spoken name
  - for remote switch location, 199, 201
  - importing, 201, 202
  - importing for local NMS site, 201
  - recorded for remote satellite switch location, 196
  - recording, 200
  - recording for local NMS site, 199
  - recording for local prime switch location, 162
  - recording overview, 199
- spoken name recorded
  - remote prime switch location, 186
  - ways to record, 186
- spreadsheet of messaging network, 98
- stale time
  - description, 66, 129
  - relationship to holding time, 130
- stale time for economy messages, default, 124
- stale time for standard messages, default, 124
- stale time for urgent messages, default, 124
- standard message, holding time, 65
- standard priority messages, 63
- standard stale time, 129
- start and stop times, economy messages, 69
- steering code for CDP, 170
- switch
  - and directory numbers (DNs), 116
  - backup, 222
  - configuration changes, 254

- configuring for Integrated AMIS
  - Networking, 58
- confirming settings, 92
- dialing plan information required, 91
- gathering information, 91
- gathering information directly from, 91
- how an Integrated AMIS message is treated, 104
- information required from, 93
- information to gather, 57
- Integrated AMIS Networking requirements, 104
- mandatory requirements, 96
- setting required for Integrated AMIS
  - Networking, 116
- switch-related problems, 264
  - call trace, 259
  - call trace test, 265
  - link diagnostic test, 267
- system access number
  - coordinating information, 72
  - private network, 129
  - public network, 128
  - purpose, 128
  - relationship to connection DN, 71

## T

- technical support, 23
- terms used in this guide, 48
- test suite
  - call routing test, 210
  - end-to-end test, 210
  - local SDN test, 210
  - loopback test, 211
  - purpose, 210
  - quick SDN test, 210
  - tests included, 210
- testing Integrated AMIS Networking, 59
  - compliance of third-party systems, 210
  - coordination required, 211
  - ensuring quick results, 211
- testing with loopback mailbox, 141
- text information in messages, 157
- third-party systems, testing compliance, 210

Timed Delivery, 53  
tree view, deleting items from, 251  
troubleshooting  
    reference documentation, 22  
    technical support, 23  
troubleshooting Integrated AMIS Networking  
    configuration errors, 258  
    hardware problems, 259  
    identifying problem, 258  
    overview, 258  
    site status errors, 259  
    switch-related problems, 259

## U

urgent messages, 63  
    holding time, 65  
Urgent stale time, 129  
Urgent Tag, 52  
user guides, 21  
User's Actual Personal Verification, 52  
using a loopback mailbox, 141

## V

validation of information, 58  
Virtual Node AMIS, terminology note, 203  
virtual node, replaced by integrated, 48  
voice channel type, 108  
Voice Messaging CDN queue, 116  
VPIM Networking, server FQDN of remote site,  
    179

## W

ways to disable Integrated AMIS Networking,  
    239  
ways to enable Integrated AMIS Networking,  
    239





# CallPilot

## Integrated AMIS Networking Implementation and Administration Guide

Copyright © 2003 Nortel Networks, All Rights Reserved

Information is subject to change without notice. Nortel Networks reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant.

The process of transmitting data and call messaging between the CallPilot server and the switch or system is proprietary to Nortel Networks. Any other use of the data and the transmission process is a violation of the user license unless specifically authorized in writing by Nortel Networks prior to such use. Violations of the license by alternative usage of any portion of this process or the related hardware constitutes grounds for an immediate termination of the license and Nortel Networks reserves the right to seek all allowable remedies for such breach.

Publication number:	555-7101-305
Product release:	2.5
Document release:	Standard 1.0
Date:	October 2003

