

SLACK TAPE MECHANISM REQUIREMENT

APPARATUS AFFECTED: All 28 Typing Reperforator Units; 28H Reperforator Unit; all 28 Reperforator-Transmitter Units; 28A, 28B, 28D, 28E, 28F, 28G, 28G-1, 28H, 28J, 28J-1, 28K Perforator-Transmitter-Bases.

OBJECT: To provide lubrication requirements for the slack tape mechanism.

CHANGE: The following requirements are added to the lubrication sections on 28 perforators and reperforators for the slack tape mechanism.

1. All pivot points for the tape depressor/clamp plate shall have one or two drops of oil and a light coat of grease.
2. The drive roller shall have one or two drops of oil and a light coat of grease.
3. The clamp plate spring shall have a light coat of grease on both ends.

NOTE: This mechanism is covered in Specification 50,247S.

CLASSIFICATION FOR APPARATUS FURNISHED BY TELETYPE: These requirements are now in effect.

APPLICATION TO APPARATUS IN THE FIELD: The requirements under "CHANGE" should be used to lubricate all units equipped with the slack tape mechanism.

APPLICATION AT W.E.CO. DIST. HOUSE REPAIR SHOPS: The requirements under "CHANGE" shall be used to lubricate all units equipped with the slack tape mechanism.