

“DATASPEED*” AP25 PRINTER
ROUTINE MAINTENANCE

CONTENTS	PAGE
1. GENERAL	1
2. VISUAL CHECKS.....	1
3. LUBRICATION	1
4. CLEANING AND APPEARANCE...	1

1. GENERAL

1.01 This section provides routine maintenance procedures for the DATASPEED AP25 Printer.

1.02 Whenever this section is reissued, the reason for reissue will be listed in this paragraph.

1.03 A routine maintenance should be performed, at the convenience of the customer, at least once a year.

1.04 Routine maintenance consists of visual checks, lubrication and cleaning. When performed at routine intervals, the possibility of later troubles will be reduced.

1.05 Following the routine maintenance, a station installation checkout should be performed. See Section 582-300-500, DATA-SPEED 4540 Remote Clustered Station Arrangements — Testing and Troubleshooting.

2. VISUAL CHECKS

2.01 The following areas should be checked for mechanical condition:

- (a) Frayed belts on spacing motor.
- (b) Worn or frayed ribbon.
- (c) All cable connectors fully seated.

3. LUBRICATION

3.01 Lubrication of the printer is required during routine maintenance. Refer to Section 582-310-700 for type, location and amounts of lubrication.

4. CLEANING AND APPEARANCE

4.01 Examine exterior areas for smudges, dust, etc.

4.02 Exterior cleaning should normally be limited to wiping with a soft cloth (such as KS-2423) moistened with a mild detergent. However, in case of ink stained plastic surfaces, a waterless (nonabrasive) hand cleaner or a lather from abrasive bar soap applied with a cloth should be used.

4.03 Interior areas should be examined with the cover opened and accumulations of paper dust or ribbon fragments cleaned by carefully brushing loose material onto a cloth. Ink stains or deposits on interior surfaces, ribbon rollers, platen, etc, can be wiped with a cloth dampened in KS-19578 trichloroethane.

Warning: Do not allow trichloroethane to contact exterior plastic surfaces.

*Registered Trademark of AT&TCo.