

47A1 DATA UNIT IDENTIFICATION

1. GENERAL

1.01 This section provides an identification and a general description of the 47A1 data unit. The 47A1 data unit, shown in Fig. 1, is intended for use with the 46A1 data unit in the 407-type multiple data station.

1.02 This section is reissued to change "data set 407A" to "data set 407-type" and to add reference to the 41A2 data mounting.

1.03 The 47A1 data unit is normally supplied with the 41A1 and 41A2 data mountings and enables local testing of data set (DS) 407-type mounted in a data mounting. The local test may be performed by a telephone company (telco) employee or the customer, as required.

2. PHYSICAL DESCRIPTION

2.01 The 47A1 data unit is approximately 4.5 inches wide, 2.5 inches high, 4.5 inches deep, and weighs 1.5 pounds. The data unit is a modified 16-button Touch-Tone® dial containing four light emitting diodes (LEDs) across the top and four LEDs down the right side of the dial.

3. FUNCTIONAL DESCRIPTION

3.01 Local testing of data set 407-type is provided by operating the LOCAL-REMOTE test switch on the 46A1 data unit to LOCAL TEST. During a local test, if a Touch-Tone button on the 47A1 data unit is depressed and held, the two LEDs representing the horizontal and vertical coordinates of the depressed button will flash at a steady rate.




Fig. 1—47A1 Data Unit

NOTICE

Not for use or disclosure outside the
Bell System except under written agreement

SECTION 590-100-133

The local test verifies that data set 407-type can receive and detect Touch-Tone signals.

4. REFERENCES

4.01 The following documents pertain to the 47A1 data unit:

SD- & CD-1D240-01 Data Systems Station— 407-Type Data Station

| SECTION | TITLE |
|----------------|---|
| 476-270-201 | 2B Automatic Call Distributing System—Identification and Installation |
| 590-100-132 | 46A1 Data Unit—Identification |
| 590-102-132 | 41-Type Data Mounting—Identification |
| 594-030-100 | Data Set 407-Type—Identification |

| SECTION | TITLE |
|----------------|--|
| 594-800-100 | 407-Type Multiple Data Station—Description |
| 594-800-101 | 407-Type Multiple Data Station Using 2B Automatic Call Distributor—Description |
| 594-800-200 | 407-Type Multiple Data Station—Installation and Connections |
| 594-800-300 | 407-Type Multiple Data Station—Maintenance |
| 594-800-500 | 407-Type Multiple Data Station—Test |
| 594-800-501 | 407-Type Multiple Data Station Using 2B Automatic Call Distributor—System Test |