

DATA AUXILIARY SET 801C LIST-TYPE INSTALLATION AND CONNECTIONS

1. GENERAL

1.001 This addendum supplements Section 598-012-202, Issue 2. Place this pink sheet ahead of page 1 of the section.

1.002 This addendum is reissued to delete information pertaining to lists 3 and 4 and to add information for connecting data sets 103E, G, or H to DAS 801C-L1/2.

2. CHANGES TO SECTION

2.001 On page 1, paragraph 1.02, delete reference to lists 3 and 4.

2.002 On page 1, revise paragraph 1.03 as follows: DASs 801C-L1/2 and 801C-L1/2A are used to provide automatic calling capabilities for a data station. These sets are referred to in this section as ACUs (automatic calling units). DAS 801C-L1/2A is the same as DAS 801C-L1/2 except the 52A1 data mounting furnished with a shipped-loose M13G cord is replaced with a 52A2 data mounting which includes a shipped-loose M15H cord.

2.003 On page 1, delete the note following paragraph 1.03.

2.004 On page 2, revise paragraph 2.02 as follows, but retain the listing following paragraph 2.02: Special items which may be required to install a DAS 801C-L1/2 are listed as follows:

2.005 On page 10, Table D, add a note after Table D as follows: At installations involving data sets 103E, G, or H, tape and store the S-W lead of the M13G cord and connect the O-R lead of the M13G cord to the terminal where the S-W lead of the replaced ACU was connected.

2.006 On page 19, Fig. 11, change Note 1 to read as follows:

1. DAS OPTIONS

REQUIRED	NOT USED	CHOOSE
ZG	Q	V OR Y
G	Z	W OR X
B	E	S OR T
		R OR H
		ZQ, ZR, ZS, OR ZT

2.007 On page 20, Fig. 12, add tip and ring connections to 565HK or 2565HK tel set block on screw terminals RR and RT. Change the designation of DAS 801C-L1/2 to DAS 801C-L1/2A.

NOTICE

Not for use or disclosure outside the
Bell System except under written agreement