

**QWEST Communications
International Inc.
Reference Publication**

**Voice Grade Special Service
Basic Voice
Transmission Parameters, Limits
And Interface Combinations**

NOTICE

This publication has been prepared to provide InterLATA Carriers with a description of Voice Grade Basic (VGB); a service offered by QWEST.

QWEST assumes no responsibility for any costs incurred by an InterLATA Carrier in conforming to the contents of this publication. Further, conformance to this publication does not constitute a guarantee of acceptance of a given carrier's equipment and/or its associated documentation.

QWEST reserves the right, without prior notice, to revise this publication for any reason.

If further information is required, please contact:

QWEST Communications International Inc.
Manager – New Services Planning
700 W. Mineral Ave. MN-F15.15
Littleton, CO 80120
(303) 707-7107
(303) 707-9497 Fax #
E-mail: jhsmit2@qwest.com

COMMENTS on PUB 77PUB

PLEASE TEAR OUT AND SEND YOUR COMMENTS/SUGGESTIONS TO:

QWEST Corporation
Manager – New Services Planning
700 W. Mineral Ave. MN-F15.15
Littleton, CO 80120
(303) 707-7107
(303) 707-9497 Fax #
E-mail: jhsmit2@qwest.com

Information from you helps us to improve our Publications. Please take a few moments to answer the following questions and return to the above address.

Was this Publication valuable to you in understanding The technical parameters of our service?	YES _____ NO _____
Was the information accurate and up-to-date?	YES _____ NO _____
Was the information easily understood?	YES _____ NO _____
Were the contents logically sequenced?	YES _____ NO _____
Were the tables and figures understandable and helpful	YES _____ NO _____
Were the pages legible?	YES _____ NO _____

If you answered NO to any of the questions and/or if you have any other comments or suggestions, please explain:

(Attach additional sheet, if necessary)

Name _____ Date _____

Company _____

Address _____

Telephone Number _____

E-Mail _____

CONTENTS

Chapter and Section	Page
1. General	1-1
2. Purpose.....	2-1
3. Service Description.....	3-1
4. Interface Codes and Combinations	4-1
5. Technical Specifications	5-1
6. Interface Illustrations	6-3
6.1 Interface Type 02NO2	6-3
6.2 Interface Type 04NO2	6-4
7. Definitions	7-1
7.1 Acronyms.....	7-1
8. References.....	8-1
8.1 Miscellaneous Publications	8-1
8.2 Ordering Information.....	8-1
8.3 Trademarks.....	8-2
Figure	
4-1 Valid Code Combinations for VGB.....	4-1

CONTENTS

Chapter and Section	Page
1. General	1-1

1. General

This document describes Basic Voice. Voice Grade Basic (VGB) is a service offered by QWEST to InterLATA Carriers (IC) and End Users (EUs). The description herein covers service features, technical specifications, and valid interfaces.

An IC desiring to serve a Local Access Transport Area (LATA), by interconnecting with Local Exchange Carrier (LEC) facilities, must establish one or more Points Of Termination (POTs) within the LATA for connection of its facilities with those of the LEC. The LEC will provide special access from an End-User Point Of Termination (EU-POT) to an IC Point Of Termination (IC-POT) within a LATA. A POT is the physical point where the access service terminates and the customer's facility begins.

CONTENTS

Chapter and Section	Page
2. Purpose.....	2-1

2. Purpose

The purpose of this document is to describe VGB service by defining the interface combinations and technical specifications and to provide a quantitative and qualitative description of the service and its interfaces so compatible operation can be achieved.

It is not the intent of this document to provide specific ordering information. Refer to applicable filed tariffs.

CONTENTS

Chapter and Section	Page
3. Service Description.....	3-1

3. Service Description

VGB Special Access service is a nonswitched service used for voice grade (300 to 3000Hz) applications without signaling or supervision. The facility may be metallic or carrier derived at the option of the Local Exchange Carrier (LEC). DC continuity is not inherent in this service. Two-wire circuits, end-to-end, will be limited to one central office while four-wire circuits may be ordered within or between central offices. Voice band signaling may be used for supervision by the IC but will not be supported by the LEC. The nominal bandwidth available with VGB is 300 to 3000Hz. Energy outside this band is permissive only and must comply with accepted limits shown in Technical Publications (see References, Chapter 8).

VGB is a nondesigned service. No special equipment is added to compensate for attenuation distortion, delay distortion, loss, noise or longitudinal balance. Circuit loss is not fixed and will vary based on the type and length of facilities connecting the two locations. It is assumed that the IC can evaluate the performance of a VGB circuit and can provide the needed equipment to compensate for facility effects. Typical circuit loss will be in the range of 0-16 dB. Higher circuit losses are possible but their occurrence would be rare. When carrier facilities are provided their loss contribution will be set to 0 dB measured at 1004Hz. Therefore, circuit losses will be the accumulation of losses associated with loaded or nonloaded metallic facilities.

CONTENTS

Chapter and Section	Page
4. Interface Codes and Combinations	4-1
Figure	
4-1 Valid Code Combinations for VGB.....	4-1

4. Interface Codes and Combinations

The electrical interface with the LEC for VGB is described by an interface code at each end of the service. Interface codes for VGB are made up of three components: (1) the number of wires, (2) protocol code, and (3) the nominal impedance code. For example, for the interface code 04NO2, the 04 represents the number of wires (2 pair), the “NO” protocol code means no signaling provided by the LEC, and the “2” means a nominal AC impedance of 600 ohms.

	A Loc	Z Loc
Intra Wire Center	02NO2 to 02NO2 -or- 04NO2 to 04NO2	
Inter Wire Center		04NO2 to 04NO2

Figure 4-1 Valid Code Combinations for VGB

Only the code combinations shown above will be provided. Note that 2-Wire to 4-Wire conversion is not available with this nondesigned service. In addition, the LEC will assume that the impedance provided to the network will always be 600 ohms.

CONTENTS

Chapter and Section	Page
5. Technical Specifications	5-1

5. Technical Specifications

A Basic Voice ordered between two central offices will generally encounter carrier facilities in the LEC. The loss contribution of all carrier facilities will be set to OdB. This leaves only the loss of the local channels serving each POT. At no time will the transmit level exceed 0 dB into the cable facility.

The circuit loss and frequency response is a function of the facility length, gauge of the wire, and loading schemes. Substantial description of local service loops has been published by the Institute of Electrical and Electronics Engineers (IEEE). This IEEE document can be used effectively to predict expected circuit loss.

Because this is a nondesigned service, the Design Layout Record (DLR) will not be produced. Service turnup tests will be limited to “continuity” tests only. When carrier facilities are involved, continuity will be checked using a test tone. Typically 1004 Hz will be used. On metallic facilities, DC tests may be used to determine circuit continuity.

CONTENTS

Chapter and Section	Page
6. Interface Illustrations	6-3
6.1 Interface Type 02NO2	6-3
6.2 Interface Type 04NO2	6-4

6. Interface Illustrations

6.1 Interface Type 02NO2

DESCRIPTION: Connects customer to an access service suitable for voice transmission with no signaling provided by the LEC. End-user and/or IC may apply inband type signaling to the channel.


2-Wire (T,R)

IMPEDANCE: 600 ohms nominal

TRANSMISSION LEVELS (dB):

at POT	RCV (out of LEC) *	XMT (into LEC) 0
--------	--------------------------	------------------------

* Determined by cable loss, see Chapter 5.



6.2 Interface Type 04NO2

DESCRIPTION: Connects customers to an access service suitable for voice transmission with no signaling provided by the LEC. End-user and/or IC may apply inband type signaling to the channel.

4-Wire (T,R,T1,R1)


IMPEDANCE: 600 ohms nominal

TRANSMISSION LEVELS (dB):

	RCV (Out of LEC)	XMT (into LEC)
at POT	*	0
at POT %	*	-16 to +7

* Determined by cable loss, see Chapter 5.

% Where LEC Carrier is terminated at the POT



Arrows denote direction of voice transmission

CONTENTS

Chapter and Section	Page
7. Definitions	7-1
7.1 Acronyms	7-1

7. Definitions

7.1 Acronyms

DLR	Design Layout Record
EEE	Institute of Electrical and Electronics Engineers
EU's	End Users
EU-POT	End User Point Of Termination
IC	InterLATA Carriers
IC-POT	IC Point Of Termination
LATA	Local Access Transport Area
LEC	Local Exchange Carrier
VGB	Voice Grade Basic

CONTENTS

Chapter and Section	Page
8. References	8-1
8.1 Miscellaneous Publications	8-1
8.2 Ordering Information	8-1
8.3 Trademarks	8-2

8. References

8.1 Miscellaneous Publications

PUB 43401 Transmission Specifications for Private Line Metallic Circuits

IEEE 820 Telephone Loop Performance Characteristics - 1985

8.2 Ordering Information

All documents are subject to change and their citation in this document reflects the most current information available at the time of printing. Readers are advised to check status and availability of all documents.

Ordering Information for Employees of QWEST Communications International Inc.

Employees of QWEST Communications International Inc. may order publications by submitting form RG 31-0033 to:

Central Distribution Center (CDC)
1005 17th St., S-30
Denver, CO 80202
Phone: (303) 896-9446
Fax: (303) 965-8652

Most QWEST publications are available to QWEST employees on the company network (E*MEDIA). Call (303) 624-4796 or email: emedial@qwest.com for further information.

Those who are not QWEST employees may order:

- Telcordia documents from:

Telcordia Customer Relations
8 Corporate Place, PYA 3A-184
Piscataway, NJ 08854-4156
Fax: (908) 336-2559
Phone: (800) 521-CORE (2673) (U.S. and Canada)
Phone: (908) 699-5800 (Others)
Web: www.telcordia.com

- Institute of Electrical and Electronic Engineers (IEEE) Publications from:

Institute of Electrical and Electronics Engineers, Inc.
345 East 47th Street
New York, NY 10017-2394

- QWEST Technical Publications from:

<http://www.qwest.com/techpub>

8.3 Trademarks

QWEST®

Registered Trademark of QWEST Communications International
Inc.