

| CODE DIGIT 5 FEATURE | | CODE | CODE DIGIT 6 FEATURE | | CODE | CODE DIGIT 7 FEATURE | | CODE |
|-------------------------|--------|-------|-------------------------|-----|------|---|-----|------|
| GROUND OR LOOP START | | | ARRANGED FOR SMAS | YES | 1 | DRY LOOP - TST JK | | |
| TOLL DIVERSION | | | | NO | 0 | | | 2 |
| LOOP SIGNALING EXTENDER | X //1/ | | | | | CSS-201 COMPATIBLE | X | 3 |
| | X //2/ | | | | | NON-SMAS W/ TOLL DIV, MOD FOR IMPROVED VOLTAGE PROTECTION | YES | 1 |
| | X X 3 | | | | | | NO | //0/ |
| | | | | | | >LOW INSERTION LOSS IN IDLE STATE | | 4 |
| | | | | | | OTHER | | //0/ |
| CODE DIGIT 8 | | | | | | | | |
| REFERENCE | | 5 | 6 | 7 | CODE | | | |
| SD-1C359-01 | 1 | 10, 1 | 10 | A** | | | | |
| | 2 | 10 | 10, 1 | | | | | |
| > | 3 | 11 | 10, 2, 3, 4 | | | | | |

NOTES: SEE MTM2 FOR MOUNTING

DESCRIPTION: METALLIC FACILITY TERMINAL- LOOP SIGNALING EXTENDER

