

CODE DIGIT 5 FEATURE			CODE	CODE DIGIT 6 FEATURE			CODE	CODE DIGIT 7 FEATURE			CODE
EXTERNAL SIGNALING LEAD				SMAS RETROFIT				PBX TIE TRUNK LEAD			
2 WIRE				SUPERIMPOSED RINGING REQD FOR TRMSN POS							0
2 WIRE OR 4 WIRE								NO			X 2
			X 1				0				
STANDARD (1)			X 2	-48V TLK			X 4	YES			X 3
			X 3	(3)			X 2				
			X A	BAT SUPPLY TO MTG			X X 6				
			X B				1				
WITH TYPE 3 SMAS MAINTENANCE CAPABILITY CONNECTOR			X X D	-72V TLK			X 5				
			X 4	(3)			X 3				
			X 5				X X 7				
			X 6								
CONNECTORIZED CABLE WITHOUT SMAS CAPABILITY (2)			X E								
			X F								
			X H								
CODE DIGIT 8											
REFERENCE		5	6	7	CODE						
SD-1C359-01	11 TO 3	10 TO 7	10 TO 3	*A//							
SD-7C010-01	H	12,3	10,2	D							
SD-7C018-01	14 TO 6,	10 TO 7	10 TO 3	B*							
	A,B,D,										
	E,F,H										
>SD-7C018-02	M TO W	12,3	10 TO 3	E*							

NOTES: (1) ORDER IN MULTIPLES OF 12 (2) ORDER IN MULTIPLES OF 24 (3) -72V IS PROVIDED BY PLUG-IN  
DESCRIPTION: METALLIC FACILITY TERMINAL - MOUNTING - SINGLE MODULE  
CONVERTER/FILTER IN BAY. W/O CONVERTER -48V IS PROVIDED

CODE DIGIT 5 FEATURE				ICODE	CODE DIGIT 6 FEATURE				ICODE	CODE DIGIT 7 FEATURE				ICODE		
EXTERNAL SIGNALING LEAD					SUPERIMPOSED RINGING REQD FOR TRMSN POS					PBX TIE TRUNK LEAD						
2 WIRE														0		
2 WIRE OR 4 WIRE									0	MFT REPEATER DISABLING OPTION				NO		
				X	J	CONNECTORIZED CABLE				X	2					X
CONNECTORIZED CABLE WITHOUT BACKPLANE (4) W/O SMAS CAPABILITY				X	K	BAT SUP TO MTG					1					
				X	L	-48V TLK				X	2					
						-72V TLK (3)				X	3					X
MAINTENANCE						CONNECTOR CONTROLLER										
P RELAY																
A																
N																
E PATCH																
L THROUGH																
				X	X	X	X	M								
				X	X	X		N								
				X	X	X	X	P								
WITH SMAS CAPABILITY							X	R								
TYPE 4 MAINTENANCE CONNECTOR							X	S								
						X	X	T								
				X	X	X		U								
				X	X	X		V								
				X	X	X	X	W								
													CODE DIGIT 8			
REFERENCE					5	6	7	CODE								
SD-7C018-01					IJ TO L	10 TO 3	10 TO 3	B*								
NOTES: (4) FOR USE WHEN ORDERING MTB0 UNEQUIPPED										DESCRIPTION: METALLIC FACILITY TERMINAL - MOUNTING - SINGLE MODULE						

MTM1 MTM1 MTM1 MTM1 MTM1 MTM1 MTM1 795-201-165





CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE		CODE	CODE DIGIT 7 FEATURE		CODE		
TELLABS		T	MFT ADAPTER FOR USE WITH TELLABS TYPE 10 MODULE	4 WIRE TO 4 WIRE WIRED 2 WIRE TO 2 WIRE UNWIRED	A B C	NO CHOICE		0		
						CODE DIGIT 8				
						REFERENCE	5	6	7	CODE
						TSLs	T	A TO C	10	9%
NOTES:			DESCRIPTION: METALLIC FACILITY TERMINAL - MOUNTING - SINGLE MODULE							

CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE		CODE	CODE DIGIT 7 FEATURE				CODE
WESCOM		W	2 WIRE			CONNECTORIZED			NO	0
	WECO MFT MTG	M	4 WIRE						YES	1
			ARR FOR	SIGNALING						
				REPEATER DISABLING						
				CONTROL A						
				CONTROL B						
					4					
					5					
					6					
					7					
					8					
					9					
			LTS 77 SYSTEM							
				UNIVERSAL	3					
				SHELF PROGRAM PLUG	A					
				AC, EC, AD, CD	C					
				SA, SB, BD, WC	D					
				DA, DB	E					
			WIRED MFT ADAPTER FOR USE WITH WSCM MODULE 4151-( )		PB, PD, PG, PH, PJ, PK	F				
					RA, RF, RE, RH, WL	G				
					RC, RG	H				
					WB	J				
		WA	K							
		WD	L							
						CODE DIGIT 8				
						REFERENCE	5	6	7	CODE
						WSCM	IW	IA	IO	5%
							IM	IC TO L	IO	
						WSCM MTG	IW	13	TO 9	1
								14	TO 9	1

NOTES:

DESCRIPTION: METALLIC FACILITY TERMINAL - MOUNTING - SINGLE MODULE