

CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE				CODE	CODE DIGIT 7 FEATURE		CODE
KENTROX	HARDWIRED	K	A&B FACILITY & SWITCH					AMPLITUDE & CURRENT LIMITING		YES 1
	PLUG-IN	A	E/W CCB CONNECTORS							
LEAR SIEGLER		L	SX FACILITY AND A&B SWITCH					SURGE PROTECTION		3
PROCTOR		P	SX FACILITY					SIMPLEX		4
RIXON (LORAIN)		N	D.C. BYPASS					DUPLEX		5
TELLABS		T	2 WIRE					OTHER		0
TRANSCOM		R	4 WIRE							
WESCOM	HIGH DENSITY	Z								
	STANDARD	W								
			600/900:	X	X		X		7	
			600/900					X	8	
								X	1	
			FACILITY TO SWITCH IMPEDANCE				X		2	
			600:600/900				X		3	
			600:600, 900:900, 900:600					X	4	
				X	X				6	
			600: 150/600/ 1200				X	X	5	
				X	X				9	
							CODE DIGIT 8			
			REFERENCE	5	6	7	CODE			
>KNTX CL		K		15,6,9	12		3			
		A		16	12		3%			
LEAR		L		14,7	12		2%			
PRTR		P		11	12		2%			
RIXN		N		11,2	12		6%			
				11	11					
TSLs		T		17	10,3		4%			
				18	10					
TSCM		R		12	14,5		5%			
WSCM		Z		13	11		1%			
WSCM		W		11,2	11,2		1%			

NOTES:

DESCRIPTION: REPEAT COILS - DUAL 2W OR 4W

CODE DIGIT 5 FEATURE		ICODE	CODE DIGIT 6 FEATURE		ICODE	CODE DIGIT 7 FEATURE		ICODE
PULSECOM		M	SX LEAD			E/W ADJ PADS		1
			SX/AB LEAD			OTHER		0
			600:600/900		X	A		
			FACILITY TO SWITCH IMPEDANCE 2W/4W	600/900:600/900	X	B		
			150/600/1200:	150/600/1200	X	C		
			600:75		X	D		
CODE DIGIT 8								
REFERENCE		5	6	7	CODE			
PLSE	M	A, B, C, D	0	1	4%			
		A						
NOTES:			DESCRIPTION: REPEAT COILS - DUAL 2W OR 4W					

RC00

RC00

RC00

RC00

RC00

RC00

RC00

795-201-437