

| CODE DIGIT 5 FEATURE | | | CODE | CODE DIGIT 6 FEATURE | | | CODE | CODE DIGIT 7 FEATURE | | | CODE |
|-------------------------|-------------------------|--------|---------|-------------------------|----------------|---|------|-------------------------|-----------------------|--------|--------|
| E OR X TYPE UNIT | 2W - TRANSMIT 2400HZ | | //2/ | TYPE PLUG-IN | E & M OR LOOP | | | 2W BLOCKING NET CONTROL | | | |
| | W/FX 20HZ SUPPLY | | //1/ | | E & M | | | | | | |
| | 2W/4W - TRANSMIT 2600HZ | | 4 | A & B LEADS | YES | | X | 0 | DROP SIDE | 2 WIRE | //1/ |
| | W/FX 20HZ SUPPLY | | 3 | | NO | | X | //1/ | W/REG LEAD | | X //3/ |
| | | | | | | X | 2 | | 2 WIRE/4 WIRE | 0 | |
| | | | | | | X | 3 | | | X 2 | |
| | | | | | | | | | N CARRIER PACKAGE BAY | N2 | Y |
| | | | | | | | | | | N3 | Z |
| CODE DIGIT 8 | | | | | | | | | | | |
| REFERENCE | | 5 | 6 | 7 | CODE | | | | | | |
| SD-56292-01 | | 2,4 | 11 | 0,2 | /B// | | | | | | |
| SD-96499-01 | | 4 | 10,2 | 1 | /J// | | | | | | |
| SD-97186-02+ | | 3,4 | 10 | Y,Z | S _a | | | | | | |
| SD-98086-01 | | 4 | 2 | 3 | *G// | | | | | | |
| SD-98087-01 | | 4 | 2 | 1,3 | *F// | | | | | | |
| SD-98138-01 | | 3 | 12 | 3 | *H// | | | | | | |
| SD-98151-01 | | 1 TO 4 | 10 TO 3 | 0,1 | /A// | | | | | | |

NOTES: USE SD-56292-01 FOR X TYPE UNITS

DESCRIPTION: SF SIGNALING - MOUNTING FOR OTHER THAN REVERTIVE
TERMINATING UNITS

| CODE DIGIT 5 FEATURE | | CODE | CODE DIGIT 6 FEATURE | | CODE | CODE DIGIT 7 FEATURE | | | | CODE |
|-------------------------|--|------|------------------------------------|--|-------|--------------------------------|------|----------|-------|------|
| COLLINS | | C | 2600 HZ EXTERNAL OSCILLATOR | | | ARRANGED FOR PLUG-INS E/W PADS | | | | |
| DIGITAL (FARINON) | | D | RINGING GEN | | | | | | | 1 |
| LEAR SIEGLER | | S | E/W PULSE CORRECTOR | | | 2 WIRE | | | | X 3 |
| LENKURT | | L | FILTER UNIT | | D | INTERFACE | | | | 2 |
| LYNCH | | H | RIXN SF80 SERIES | | X J | 4 WIRE | | | | X 4 |
| RIXON (LORAIN) | | R | UNIVERSAL | | X 1 | OTHER (1) | | | | 0 |
| WESCOM | | W | STANDARD | | | | | | | |
| | | Z | HI DENSITY | | | | | | | |
| | | | TYPE PLUG-IN | | X 6 | | | | | |
| | | | E & M | | | | | | | |
| | | | OFC END | | | | | | | |
| | | | FX SVC | | X 4 | | | | | |
| | | | SUB END | | X X 5 | | | | | |
| | | | OUT OF BAND | | | | | | | |
| | | | SINGLE SLOT PLUG-IN FOR ONE PIU | | A | | | | | |
| | | | WECO ADAPTER | | | DGTL MTG | D | 12, 3, 9 | 10 | 3 |
| | | | E SIG BAY | | | LNKT MTG | L | 12, 6, D | 12 | 5 |
| | | | SHELF ADAPTER - 10 F-TYPE UNITS | | C | LNCH MTG | H | B | 10 | 2 |
| | | | 4 OR 8 PARTY SUBSCRIBER SERVICE | | B | RIXN MTG | R | J | 10 | 4 |
| | | | STRAPPING FOR 6630 TY SF SIG EQUIP | | K | SFT-7160AD | S | 13, 6 | 13 | 2a |
| | | | W/SF BUS AND A&B BAT | | L | SFU-7160AD | S | 13, 6 | 12, 4 | 1a |
| | | | OTHER (1) | | 0 | SFU-7161AD+ | S | 14, 5 | 11, 3 | 3a |
| | | | | | | FXU-7161AD | | | | |
| | | | | | | SFU-7162AD+ | S | 17, 8 | 11, 3 | 4a |
| | | | | | | FXU-7162AD | | | | |
| | | | | | | WSCM | Z | A | 10 | 1% |
| | | | | | | WSCM MTG | W, Z | 10 | 10 | 6 |
| | | | | | | | W | 12 | 11, 2 | |
| | | | | | | | Z | K, L | 10 | |
| | | | | | | WSCM 66MA | Z | C | 10 | 6 |
| | | | | | | 518-891216 | C | 12 | 12 | 8 |
| | | | | | | 518-891217 | C | 11 | 12 | 7 |

NOTES: (1) CABLE PER LOCAL DWG
(2) SEE SFCT & SFS6

DESCRIPTION: SF SIGNALING - MOUNTING FOR OTHER THAN REVERTIVE
TERMINATING UNITS

| CODE DIGIT 5 FEATURE | | ICODE | CODE DIGIT 6 FEATURE | | | | ICODE | CODE DIGIT 7 FEATURE | | | | ICODE |
|-------------------------|-----|---------------|--------------------------------------|---|------|--|-------|-------------------------|--|--|--|-------|
| SEE PAGE 5 | | | DOUBLE MOD CKTS | | | | | SEE PAGE 5 | | | | |
| | | | NON-SF APPLICATIONS | | | | | | | | | |
| | | | DUAL SINGLE MOD CKTS | | | | | | | | | |
| | | | -24V | | | | | | | | | |
| | | | -24/48V | | | | | | | | | |
| | | | +/-14V CONV & 2600 HZ TONE BUFFER | | | | | | | | | |
| | | | E/W 4W EXT & EQL | | | | X X | | | | | U |
| | | | 600 OHM | | | | X X | | | | | V |
| FOR | FOR | | E/W | | | | | | | | | |
| >WECO | ONE | | 4W | | | | X X | | | | | W |
| FW | PIU | | TERM | | | | | | | | | |
| BAY | | | 900 OHM & LPF | | | | X X | | | | | X |
| CODE DIGIT 8 | | | | | | | | | | | | |
| REFERENCE | | 5 | 6 | 7 | CODE | | | | | | | |
| | | SEE PAGE 5 | | | | | | | | | | |

NOTES: DESCRIPTION: SF SIGNALING - SINGLE SLOT PLUG-IN ADAPTER
MOUNTING FOR OTHER THAN REVERTIVE
TERMINATING UNITS