

CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE				CODE	CODE DIGIT 7 FEATURE		CODE
	UNMODIFIED	//1/	COMPATIBLE WITH TUBE UNITS AT DISTANT END	YES				HARDENED UNIT	NO 0	
PLUG-IN UNIT 2 OR 4 WIRE	TALK-OFF IMPROVED	//2/		NO	ARRANGED FOR SS1 SIGNALING	YES //1/			YES H	
	TALK-OFF IMPROVED COMPATIBLE WITH AUTOVON AND PULSING IMPROVED	//3/				NO //2/				
PLUG-IN "X" TYPE		//X/	COMPATIBLE WITH DP ORIGINATING OFFICE			YES 0				
PLUG-IN UNIT 4 WIRE ONLY (1)		//4/				NO //4/				
WIRED UNIT		//Z/								
E1B UNIT ARRANGED FOR CUT CONTROL		//Y/								
CODE DIGIT 8										
	REFERENCE	5	6	7	CODE					
	SD-56202-02	Z	10	10	//D//					
	SD-56292-01	X	10	10	R%					
	SD-98085-01	1,2,Y	1,2	10	L%					
	SD-98090-01	1,2,3	10	10	M%					
	SD-98124-01	1,2,3	10,4	10	N%					
	SD-98124-02	2,3	10,4	10,H	P%					
	SD-98124-03	4	10	10,H	//S%/					
NOTES: (1) USE OLDER UNITS FOR 2 WIRE OPERATION			DESCRIPTION: SF SIGNALING - E1B TO E4B & X UNITS - 4 WIRE E&M							

SF60

SF60

SF60

SF60

SF60

SF60

SF60

795-201-548

CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE				CODE	CODE DIGIT 7 FEATURE			CODE
"F" TYPE		F	CGA RELAY ISOLATED FROM ALARM CKT					HARDENED UNIT			H
			NO				//1/				
			FU AUX UNIT	W/CGA	DELAY		//2/				
					MAKE 10 SEC		-				
			YES		BUSY		X//5/				
					SIGNAL		-				
					2.5 SEC		X 6				
			FWA UNIT		MODIFIED TO		NO	//0/			
					REDUCE		-				
					CROSSTALK		YES	3			
			FWC - NONCOMPANDORED CARRIER - MF								4
CODE DIGIT 8											
			REFERENCE		5	6	7	CODE			
			SD-1C225-01		F	10,3	H	E**			
			SD-1C227-01		F	1,2,5,6	H	A**			
			SD-1C583-01		F	4	H	F**			
			WSCM		F	3	H	6%			
NOTES: WSCM UNIT BUILT TO WECO SPEC					DESCRIPTION: SF SIGNALING - 4 WIRE E&M - MF OR DP						

CODE DIGIT 5 FEATURE	CODE	CODE DIGIT 6 FEATURE	CODE	CODE DIGIT 7 FEATURE	CODE
LYNCH	L	CARRIER GROUP ALARM	EXTERNAL	REQUIRES EXTERNAL 2600HZ SUPPLY	NO 1
			INTERNAL		YES H
		E/W ADJ TRANSMISSION PADS			
		OUT-OF-BAND			
		BAT SUP 48V			

CODE DIGIT 8				
REFERENCE	5	6	7	CODE
LNCH	L	5 E, P	1, H 1	1%

NOTES:

DESCRIPTION: SF SIGNALING - 4 WIRE E&M - DP

SF60

SF60

SF60

SF60

SF60

SF60

SF60

795-201-548

