

CODE DIGITS 5 & 6 FEATURE			CODE	CODE DIGITS 5 & 6 FEATURE			CODE	CODE DIGIT 7 FEATURE			CODE
TRANSMIT - RECEIVE	TRU		10		RINGING GENERATOR	A2		IMPROVED NOISE IMMUNITY FOR THE SLC-96 PROTECTION LINE		1	
ALARM CONTROL	ACU		20	REMOTE TERMINAL	BATTERY CHARGER FOR 7A OR 8A POWER PANEL	B1		WHEN RT IS 48 CHAN MINIBANK		2	
	MAINTENANCE	AMU	24		POWER CONTROL	B2		VISUAL PWR ALM LAMP		3	
ALARM, DATA, SWITCH SPECIAL SERVICE (SLC-48)	ADSU		21		LSU	C0		FOR USE WITH NO. 5 ESS		4	
SPECIAL SERVICE	SSU		30	ALARM SUPPRESSOR UNIT USED IN PLACE OF:	TRU	D0		D4 COMPATIBILITY		5	
LINE SWITCH	ELECL INTFC	LSU	40		SSU	G0		W/PRECISE GAIN TOLERANCE (APPROVED FOR D4 SPECIAL SERVICE)		6	
	OPTICAL INTFC		41	ALARM FOR COT		E1		IMPROVED LOOP BACK FEATURE		7	
DATA LINK	DLU		50		DATA/ALARM PROCESSING UNIT	A3		IMPROVED OPERATION OF OVER-CURRENT >SHUTDOWN CIRCUIT AT ELEVATED TEMPERATURES		8	
CHANNEL TEST	CTU-COT		61	SLIM	ALARM UNIT	B3		OTHER		0	
	CTU-RT		62		LINE SIGNAL GENERATOR	C3					
TIME ASSIGNMENT	TAU-COT		71		ALARM/STATUS INTFC UNIT	D3					
	TAU-RT		72								
MULTIPLEX	MXU		90								
LINE FEED CONVERTER FOR 6A POWER PANEL	LFC		F3								
POWER CONVERTER	PU		80								
CHANNEL TERMINAL TEST UNIT (FIBER-SLC)	COT		H0								
	RT		J0								
CODE DIGIT 8											
REFERENCE 5 6 7 CODE											
SEE PAGE 2											

NOTES:

DESCRIPTION: SUBSCRIBER LOOP CARRIER - SLC-96 TYPE COMMON PLUG-IN
UNITS

CODE DIGITS 5 & 6 FEATURE		CODE	CODE DIGITS 5 & 6 FEATURE		CODE	CODE DIGIT 7 FEATURE			CODE	
SEE PAGE 1						SEE PAGE 1				
CODE DIGIT 8										
						REFERENCE	5	6	7	CODE
						SD-3C420-01	E	11	10	F**
						SD-3C420-02	E	11	10,7	H**
						ED-3C864-30	IC,D	10	10	E**
						ED-3C866-30	ID	13	10	J**
						WM1 CP	I	10	10	/A%/
							I	10	16	A**
						WM1B CP	I	10	15	A**
						WM11 CP	A	13	10	A**
						WM20	IH	10	10	A**
						WM21	IJ	10	10	A**
						WN- CP	I	14	10,4	/A%/
							I	14	11,2	A**
							I	15	12	A**
							I	15	10	A**
							I	16	10,2	A**
							I	16	10	A**
							I	17	11,2	A**
							I	17	10	A**
							I	18	10	A**
							I	14	10	A**
						WN14	I	19	10	/A%/
						WN14B	I	19	15	A**
						WP- CP	I	12	11,4	A**
							I	13	10	A**
							I	13	10	A**
						WP1	I	12	10	/A%/
						WP1B	I	12	15	A**
						YL- CP	I	12	10,3	D**
						1A RNGEN	I	12	10	C**
						4A BAT CHG	I	11	10	G**
						>295A PWR U	I	18	10,8	B**

NOTES: DESCRIPTION: SUBSCRIBER LOOP CARRIER - SLC-96 TYPE COMMON PLUG-IN UNITS