

CODE DIGIT 5 FEATURE			ICODE	CODE DIGIT 6 FEATURE			ICODE	CODE DIGIT 7 FEATURE			ICODE
PROTECTED				D ENCAPSULANT				HOT DIPPED GALVANIZED			
DUAL FAULT LOCATE WIRING								FLAMED ON ZINC			
REPEATER CAPACITY AND TYPE	COVER PIECES			10	//0/		WHITE ENAMEL				
	1		//1/	15	//1/						
25- T1	2		//2/	20	2		X	X	0		
	1	X	//3/	25	3		OUTER TREATMENT			X	
	2	X	//4/	30	4	X	F	WEATHERPROOF ALUMINUM CASE			3
5- T1	1	X	//5/	35	//5/						
			6	40	6						
25- T1	3	X	7								
		X	8								
		X	9								
5- T1	1	X	A								
25- T1C (1)			//B/								
	3	X	//C/								
			F								
		X	G								
2- T1 SLM & SLC-40		X	//D/								
	1	X	H								
4- T1 SLM & SLC-40		X	//E/								
		X	J								

  

CODE DIGIT 8				
REFERENCE	5	6	7	CODE
466- APPCS	1,2	10 TO 6	1,2	//L%/
468- APPCS	3 TO 5,	10 TO 6	10,1,2	//L%/
	A			
475- APPCS	A	10 TO 6	10	L*%
	6 TO 9	10,1,3,5	10	//L%/
	6 TO 9	2,4,6	10	L*%
	9	F	10	L*%
478- APPCS	D,E	3	3	//L%/
	H,J	3	3	L*%
479- APPCS	B,C	2,4,6	2	//L%/
	F,G	4,6	2	L*%

NOTES: SEE T1FI T1LC T1OW T1RO T1R1  
(1) MAY BE T1 WHEN CONVERSION TO T1C IS PLANNED

DESCRIPTION: T1 CARRIER - REPEATER APPARATUS CASE

CODE DIGIT 5 FEATURE				CODE	CODE DIGIT 6 FEATURE			CODE	CODE DIGIT 7 FEATURE			CODE
PROTECTED					PLASTIC CABLE STUB				PLASTIC CASE WITH PLASTIC COVERS			4
DUAL FAULT LOCATE WIRING					1- 30 FT 108 PAIR			81A1-1H	A			
25 RPTR CAPACITY FOR		HOUSING			2- 30 FT UNIDIRECTIONAL			81A1-2H	B			
T1	238	88A1		8	> 54 PAIR			BIDIRECTIONAL	81A2-2H	D		
	239	89A1	X	9	1- 30 FT 108 PAIR, FILLED			81B1-1H	C			
		(2)	89B1	X	M	HOUSING W/O BASE			0			
T1C/ T1D	218/248		88A1C		F							
	219/249		89A1C	X	G							
	218/248 (3)		88A2C	X	H							
	219/249 (3)		89A2C	X	J							
		(2)	89B1C	X	L							
BASE W/O HOUSING					0							
CODE DIGIT 8												
REFERENCE			5	6	7	CODE						
>818- RPTCS			8	A	14	A**						
			H	A, D	14							
			F	A, B	14							
>819- RPTCS			9	A	14	A**						
			J	A, D	14							
			G	A, B, C	14							
			L, M	C	14							
>81- RPTCSB			10	A, B, C, D	14	A**						
88- RPTCSH			8, F, H	10	14	A**						
89- RPTCSH			9, G, J,	10	14	A**						
			L, M									
NOTES: (2) PRESSURE TESTED HOUSING				DESCRIPTION: T1 CARRIER - REPEATER APPARATUS CASE								
(3) 218 OR 219 A THRU G MUST NOT BE USED												

T1RC

T1RC

T1RC

T1RC

T1RC

T1RC

T1RC

795-209-142

CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE		CODE	CODE DIGIT 7 FEATURE		CODE		
RPTR CAPACITY	TYPE		25 FOOT 52 PAIR 25 GAUGE SCREEN FILED PLASTIC CABLE STUB ARRANGED FOR MTG	POLE PEDESTAL	A B	PLASTIC CASE WITH METAL COVER		5		
12	239 PROTECTED	K								
						CODE DIGIT 8				
						REFERENCE	5	6	7	CODE
						809- RPTCS	K	A, B	5	A*
NOTES:			DESCRIPTION: T1 CARRIER - REPEATER APPARATUS CASE							

T1RC

T1RC

T1RC

T1RC

T1RC

T1RC

T1RC

795-209-142

CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE			CODE	CODE DIGIT 7 FEATURE				CODE		
INTERNATIONAL TEL & TEL		T	REPEATER CAPACITY			8	MOUNTING HARDWARE		POLE				
LENKURT		N	24				MANHOLE						
LYNCH		L	1 CABLE			X	PRESSURIZED						
			REPEATER HOUSING W/10FT STUB(S) FOR OPER W/						10		X	X	
			2 CABLES			X			12		X	X	
			1 OR 2 CABLES			X			24		X	X	
			ARRANGED FOR GAS TUBE ARRESTORS				CAPACITY		3				
			W/RPTR BY-PASS						6				
			TWO PIECE CASE COVER			20	X	D	25		X	X	
								8					
								X	A				
						25	X	X	E				
									4				
			STUB LENGTH IN FEET					X	F				
								X	5				
			ONE PIECE CASE COVER			40	X	X	6				
									7				
						25	X	G	CODE DIGIT 8				
						10	X	H	REFERENCE	5	6	7	CODE
						30	X	J	>ITTN	T	D, H, J	5, 6, 7	2%
						50	X	0			I, J	2, 3, 8	
									LNKT	N	10	2, 8	
											4, 5, 6, 11, 2		1%
											E, F		
									LNCH	L	17	2	
											18, A	3	
											16, G	4	
											11 TO 3	0	1%

NOTES:

DESCRIPTION: T1 CARRIER - REPEATER HOUSING

T1RC

T1RC

T1RC

T1RC

T1RC

T1RC

T1RC

795-209-142