

CODE DIGIT 5 FEATURE				CODE	CODE DIGIT 6 FEATURE				CODE	CODE DIGIT 7 FEATURE				CODE		
INDIVIDUAL COMM PLUG-IN UNITS FOR ONE 24 CHAN BANK				T	WITH LOOP CLOSURE REQUIRED FOR ESS					WITH E2 ALARM PWB ASSEMBLY				NO YES	0 1	
RECEIVE UNIT				R	TRK PROCESSOR ARRANGED FOR MORE THAN ONE NO.1 ESS REM MASTER SCANNER				X 1	WITH STATUS AND CONTROL PWB				NO YES	0 2	
ALARM CONTROL				A	APPLIQUE CKT FOR USE IN OFFICE:					RECEIVE UNIT IMPROVED FOR NO.4 ESS DIGROUP TERMINAL					3	
TRUNK PROC-ESSOR CONTACT PROTECT-ION				NO YES	//P/ S	ALL EXCEPT SXS				X 3						
INTER-FACE UNIT				FOR USE WITH T1WB-4	NO YES	I E	INTERFACE - OPTIONAL UNIT									
TRANSMISSION MON					M	2 SECOND TIMING & HIT INTEGRATION										
POWER CONVERTER					C	FOR USE WITH SPL STATUS CONT BAY										
HOT SPARE PANEL				CHANNEL ACCESS UNIT		V	LESS SENSITIVE TO NOISE TRANS									
24 CHAN BANK ADAPTER				D3 TO D2 OPERATION		2	IMPROVED ALARM CONTROL				X X //5/ X //6/					
COMMON (1) PLUG-IN UNITS FOR				24 CHAN BANK		X	OTHER				0	CODE DIGIT 8				
HOT-SPARE & MAINT SHELF						Y						REFERENCE	5	6	7	CODE
												SD-3C104-01	2, D, X, Y	10	10	K**
												SD-3C105-01	T	10	10	A**
												SD-3C106-01	R	10	10	/B*/
												SD-3C107-01	R	10	13	B**
												SD-3C108-01	A	10, 5, 6, 7	10	C**
												SD-3C109-01	IM	10	10	F**
												SD-3C109-01	I	10	10, 1, 2	E**
												SD-3C110-01	G	10	10, 1, 2	J**
												SD-3C111-01	P, S	10	10	/D*/
												SD-3C111-02	S	11	10	
												SD-3C111-02	S	11, 3, 4, 8	10	/M*/
												SD-3C111-03	IS	11, 3, 4	10	S**
												SD-3C112-01	IV	10	10	H**
												SD-3C114-01	E	10	10, 1, 2	L**
												SD-3C120-01	I	12	10, 1, 2	P**
												SD-82099-01	IC	10	10	/G*/
												SD-82099-02	IC	10	10	/N*/
												SD-82099-03	IC	10	10	R**
												SD-82370-01	IC	10	10	T**

NOTES: (1) INTFC, TRK PROCR & CD GENR UNITS ARE NOT INCLUDED

DESCRIPTION: D3 CHANNEL BANK - GROUP UNITS

CODE DIGIT 5 FEATURE	CODE	CODE DIGITS 6 & 7 FEATURE	CODE	CODE DIGITS 6 & 7 FEATURE	CODE
INTERNATIONAL TEL & TEL CORP	T	WECCO D-TYPE CHANNEL BANK COMPATABILITY	D1D D2 D3	WECCO D-TYPE CHANNEL BANK COMPATABILITY	D1D D2 D3
		TRANSMIT LOGIC	X A0 X B0 X C0	DECODER UNIT DISC ALM LOW NOISE	X X X H0 X X X H1 X X X H2
		(1) ENHANCED LOOP TIMING FOR NO. 4 ESS	X A1 X B1	POWER SUPPLY & ALARM WITHOUT CGA HOLD WITH CGA HOLD	X X X J0 X X X J1
		> NO SIGNALING, 8 BIT VF ENCODING	X C1 X B2	POWER SUPPLY AC-DC ALARM & BALLAST (T324)	X X X0 X V0
		RECEIVE LOGIC	X D0 X E0 X F0	ALARMS ONLY LOOP SUB VERIF W/LINE TEST & ALM & ALARMS C.O.	Y0 T0 U0
		VF MUTING	X E1 X F1	ALARM BOARD (T148)	Z0
		RECEIVE LOGIC FRAME TIMING	X D2 X E2	CODE DIGIT 8	
		RECEIVE LOGIC W/SIG STATE STORAGE	X W0 X W1	REFERENCE	5 6 7 CODE
		VF MUTING	X G0 X G1	ISD-23006 IT IG 10,1 3%	
		ENCODER		ISD-23009 IT IH 10,1,2 4%	
		UNIT DISC ALM		ISD-23107 IT IA TO C 10,1 1%	
				ISD-23108 IT IB 12 2%	
				ISD-23110 IT ID TO F 10,1,2 5%	
				ITTN IT IC,F,J, 10 7%	
				IT TO Z 11	

NOTES: (1) REQUIRES A D3EC

DESCRIPTION: DIGITAL CARRIER - COMMON EQUIPMENT PLUG-IN UNITS

