

CODE DIGIT 5 FEATURE		ICODE	CODE DIGITS 6 & 7 FEATURE		ICODE	CODE DIGITS 6 & 7 FEATURE		ICODE
SEE PAGE 2			600 OHM			600 OHM		
			150, 600 OR 1200 OHM			150, 600 OR 1200 OHM		
			SCREW DOWN OPTION D2, D3/D1D			SCREW DOWN OPTION D2, D3/D1D		
			VF RESPONSE EQUALIZER			VF RESPONSE EQUALIZER		
			RING LDGND THRU 400 OHM RES			RING LDGND THRU 400 OHM RES		
			RING DETECTOR ON RING LEAD			RING DETECTOR ON RING LEAD		
			-19 TO -13 DBM IN +7 TO +10 DBM OUT		X 34	4W STA -20 TO +12 DBM IN END -21 TO +11 DBM OUT		X 48
					X 30			
			-19 TO +5 DBM IN -14 TO +10 DBM OUT		X 35			
4W OFF END					X 31			
					X 36			
					X 32			
			-20 TO +12 DBM IN -21 TO +11 DBM OUT (EXTENDED VF RANGE)		X 37 X 33			
					X 38			
			-19 TO -13 DBM IN +7 TO +10 DBM OUT		X 44			
					X 40			
			-19 TO +5 DBM IN -14 TO +10 DBM OUT		X 45			
4W STA END					X 41			
					X 46			
					X 42	CODE DIGIT 8		
			-20 TO +12 DBM IN -21 TO +11 DBM OUT		X 47 X 43	REFERENCE 5 6 7 CODE		
						SEE PAGE 2		

NOTES:

DESCRIPTION: T324 PCM MULTIPLEX - FOREIGN EXCHANGE CHANNEL UNIT

