

CODE DIGIT 5 FEATURE			CODE DIGIT 6 FEATURE			CODE DIGIT 7 FEATURE		
		CODE			CODE			CODE
ORIGINATING	(DPO)	1	IMPEDANCE	600 OHM	1	W/CIRCUIT OPT FOR DP OR MF		1
TERMINATING	(DPT)	2		900 OHM	0	OTHER		0
ORIGINATING - SLEEVE GROUND (SDPO)								
ORIGINATING - MULTIFREQUENCY (DPMO)								

CODE DIGIT 8				
REFERENCE	5	6	7	CODE
SD-3C322-01	11	10	10	/A%/
SD-3C322-02	11	10	10	/G%/
SD-3C322-03	11	10	11	M*%
SD-3C323-01	12	10	10	/B%/
SD-3C323-02	12	10	10	/E%/
SD-3C323-03	12	10, 1	10	K*%
SD-3C330-01	13	10	10	/C%/
SD-3C330-02	13	10	10	/H%/
SD-3C330-03	13	10	10	L*%
SD-3C333-01	14	10	10	/D%/
SD-3C333-02	14	10	10	/F%/
SD-3C333-03	14	10	10	/J%/

NOTES: DESCRIPTION: D4 CHANNEL BANK - DIAL PULSE CHANNEL UNITS

CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE		CODE	CODE DIGIT 7 FEATURE		CODE		
INTERNATIONAL TEL & TEL		T	IMPEDANCE	900 OHM		BUSY SWITCH, SCREW DOWN & STRAP OPTIONS		1		
LENKURT		L		600 OHM		GROUND S LEAD		2		
WESCOM		W				INTEGRITY CHECK		3		
					X X	A				
					X	G				
					X	L				
			ORIGINATING		X X	C				
					X X	D				
			SLEEVE GROUND (3W)	WITH PEG COUNT	X	J				
					X	K				
			W/LEAD COND		X X	B				
					X X	E				
					X	H				
			TERMINATING		X	M				
					X	N				
				SLEEVE GROUND (3W)	X	P				
				WINK START GEN	X X	F				
CODE DIGIT 8										
						REFERENCE	5	6	7	CODE
						ITTN	T	G TO M	11	3%
						LNKT	L	H, M, N, P	13	2%
						WSCM	W	A, B, E, F	11	1%
								C, D	12	

NOTES:

DESCRIPTION: D4 CHANNEL BANK - DIAL PULSE CHANNEL UNITS

D4CD

D4CD

D4CD

D4CD

D4CD

D4CD

D4CD

795-209-360