	CODE DIGITS 5,6 & 7 FEATURE		CODE
LOW SPEED PROTN SWG	4 DS1 LINES WITH CABLE LENGTH (FT)	0 TO 220	100
		221 TO 440	110
		441 TO 655	120
	2 DS1C LINES (REQUIRES 2 T1C EQL PER D4EC)		B00
	1 DS2 LINE (REQUIRES 2 T2 EQL PER D4EC)		C00
	STANDBY BUS STRAP FOR UNASSIGNED LINES (4 DS1, 2 DS1C OR 1 DS2)		330
DSX3 NETWORK & SWITCH	LSTA		270
	LTMA		280
>	LTMA AND FRAME		28B

	CODE DIGITS 5,6 & 7 FEATURE	CODE
W/O LOW SPEED PROTN SWG	4 DS1 LINES (REQUIRES 4 T1 EQL PER DMED)	150
	2 DS1C LINES (REQUIRES 2 T1C EQL PER DMED)	
	1 DS2 LINE (REQUIRES 2 T2 EQL PER D4EC)	A00

CODE DIGITS 5,6 & 7 FEATURE | CODE

	CODE DIGIT 8			
REFERENCE	5	6	7	CODE
ED-2C572-30	A			A*%
ED-2C581-30	B			B*%
ED-2C582-30	C			C*%
>TG- CP	1,2,3			D*%

NOTES:

DESCRIPTION: MX3 DIGITAL MULTIPLEX TERMINALS - NETWORK AND SWITCH CIRCUIT PACKS

M3LP   M3LP   M3LP   M3LP   M3LP   M3LP   M3LP   795-209-511

BELL SYSTEM PRACTICES
AT&T CO STANDARD

COMMON LANGUAGE ENCODER
TRANSMISSION EQUIPMENT

SECTION 795-209-511
ISSUE 4, APRIL 1982

CODE DIGIT 5 FEATURE	CODE	CODE DIGIT 6 FEATURE	CODE	CODE DIGIT 7 FEATURE	CODE
HARRIS	H	RECEIVE PROTECTION SWITCH	A	NO CHOICE	0

CODE DIGIT 8				
REFERENCE	5	6	7	CODE
HARS	H	A	0	1%

NOTES:

DESCRIPTION: MX3 DIGITAL MULTIPLEX TERMINALS - LINE
PROTECTION SWITCH