CODE DIGIT 5 FEATURE

Feature			CODE
LINE SWITCH CONTROL - B1 ALARM			
CABLE TYPE	POLYETHYLENE	.270	
		.375	
	RUBBER	.270	
SUPL EQUALIZATION			
SWITCHING MAIN >OR TERMINAL			A
			B
			C
			D
			E
			F
			G
			H
			J
			K
			L
			M
NON-SWITCHING MAIN			N
	REVERSE DIRECTION OF ONE LINE		P
			R
			S
			T
			U
>TRANSMITTING PILOT INDICATOR			V

CODE DIGIT 6 FEATURE

Feature		CODE
POWER LOADING		
TERMINAL OR BRANCH POINT		
CABLE	1 MILE OF .27 OR 1.4 MILES OF .375 COAXIAL CABLE	A
		B
		C
		D
	2 MILES OF .27 OR 2.8 MILES OF .375 COAXIAL CABLE	E
		F
		G
		H
	3 MILES OF .27 OR 4.2 MILES OF .375 COAXIAL CABLE	J
		K
		L
		M
	4 MILES OF .27 OR 5.6 MILES OF .375 COAXIAL CABLE	N
		P
		R
		S
	NONE	T
		U
		V
		W
>OTHER		0

CODE DIGIT 7 FEATURE

Feature	CODE
40 DB PAD	A
PILOT INSERTION	C
OTHER	0

CODE DIGIT 8

REFERENCE	5	6	7	CODE
J68770J	N TO U	A TO W	A	
J68770K	A TO M	A TO W	A,C	
J68770G	V	0	0	

NOTES: REFERENCE 804-627-152

DESCRIPTION: L1 CARRIER-REPEATER AND TRANSMITTING PILOT INDICATOR BAYS

L1BR L1BR L1BR L1BR L1BR L1BR L1BR L1BR L1BR L1BR

COPYRIGHT AMERICAN TELEPHONE AND TELEGRAPH COMPANY, 1976 PRINTED IN U.S.A.