

| CODE DIGIT 5 FEATURE | CODE | CODE DIGIT 6 FEATURE | CODE | CODE DIGIT 7 FEATURE | CODE |
|------------------------------------|------|------------------------------------------------------------------------------------------|------|-------------------------|------|
| >PRI CESIUM BEAM TST SET | A | INTERNAL BATTERY & CHARGER | | >1 PPS DELAY/ADVANCE | 1 |
| >CESIUM FREQUENCY STANDARD TST SET | B | | 1 | OTHER | 0 |
| >STRATUM ONE REFERENCE SOURCE | C | 1,5 & 10 MHZ SINUSODIAL OUTPUT WITH 1 PPS CLOCK | X 2 | | |
| | | ONE RF OUTPUT EACH AT 5 MHZ AND 10 MHZ | X 3 | | |
| | | W/10MHZ OUTPUT SIGNAL OPTIMIZED FOR LOW PHASE NOISE FLOOR & FAST WARM-UP | X 3 | | |
| | | W/5MHZ OUTPUT SIGNAL OPTIMIZED FOR EXCELLENT CLOSE-IN PHASE NOISE & SHORT-TERM STABILITY | X 4 | | |
| | | >STRIP CHART RECORDER | 5 | | |
| | | W/PUSHBUTTON - SELECTABLE RANGES | 6 | | |

| CODE DIGIT 8 | | | | |
|--------------|---|-----|---|------|
| REFERENCE | 5 | 6 | 7 | CODE |
| FTSM | A | 1 | 0 | 1*% |
| > | | 2 | 1 | |
| > | B | 3,4 | 1 | |
| >SLTC | C | 5,6 | 0 | 2*% |

NOTES:

DESCRIPTION: BASIC SYSTEM REFERENCE TRANSMISSION