

**TRUNK AND CONVERTER FINDERS  
AND 10-CAPACITY FINDER SHELVES  
NO. 1, 350A, 355A, AND INTERTOLL DIALING OFFICES  
EQUIPMENT DESIGN REQUIREMENTS  
STEP-BY-STEP SYSTEMS**

**1. GENERAL**

**1.001** This addendum supplements Section 814-414-150, Issue 10.

**1.002** This addendum is issued:

(a) To add office 35E97 in the title of SD-33028-01. This change is in accordance with SD-33028-01, Issue 7B.

(b) To correct an error in lists 5 and 6, and to add list 7 to J32004BA. This change is in accordance with SD-31953-01, Issue 25B.

(c) To add list 10 to J32004AY, to correct an error in list 2, add list 8 to J32004BA, and add list 9 to J32004BD. This change is in accordance with SD-31514-01, Issue 31B.

**3. DRAWINGS**

The following changes apply to Part 3 of the section:

*Under Circuits*

*Change:*

SD-33028-01—Step-by-Step System No. 1, 350A, or 355A

*To Read:*

SD-33028-01—Step-by-Step Systems No. 1, 350A, 355A, or 35E97

**4. EQUIPMENT**

The following changes apply to Part 4 of the section:

*Under J32004AY*

*Change:* J3200AY

*To Read:* J32004AY

*Add:*

*List 10*—Wiring and apparatus required in addition to list 7 or 9 to provide an alarm indication to CSACS per SD-31514-01, option N.

*Under J32004BA*

*Change:* Lists 1, 2, 5, and 6

*To Read:*

*List 1*—Framework, assembly, wiring, and equipment for one unit of ten 100-point 8-wire trunk finders, less finders and banks for the first unit of a group.

	WIRE	EQUIP	NOTES
Bat. Tst Jk Ckt, SD-31333-01: Fig. 1	1	1	<i>List 5</i> —Wiring and equipment per SD-31953-01, Fig. 2, 3, and 4, B apparatus only; Fig. 6, F wiring and apparatus only; Fig. 17 with F wiring and apparatus; and SD-31514-01, Fig. 1 with P wiring only, required in addition to list 1 for TOUCH-TONE® calling in No. 1 and 350A offices (omit A wiring).
Sw Tbl Alm Ckt, SD-31514-01: Rls Alm Ckt, Fig. 1	1	1	
Call-Blocked Alm Ckt, Fig. 1	1	1	<i>List 6</i> —Wiring and equipment per SD-31953-01, Fig. 2, 3, and 4, with B apparatus only; Fig. 6 with E wiring and apparatus only; Fig. 17 with E wiring and apparatus, required in addition to list 1 for TOUCH-TONE calling in No. 355A office (omit A wiring).
Fuse Alm Ckt, Fig. 5, X App	1	1	
Trk Fdr Ckt, SD-31953-01: Start Ckt			<i>Add:</i>
Fig. 2, Q Wrg, First	1	1	
Fig. 3, Intermediate	8	8	<i>List 7</i> —Wiring and equipment per SD-31953-01, Fig. 6 with ZA wiring and apparatus only, and Fig. 17 with ZA wiring and apparatus, required in addition to list 1 to provide timed release of D relays in idle finders in CAMA or No. 1 step-by-step AMA (omit A wiring).
Fig. 4, Last	1	1	
Trk Fdr Ckt, Fig. 5, W Wrg			<i>List 8</i> —Wiring and apparatus required in addition to list 1 to provide alarm indication to CSACS per SD-31514-01, option N.
Jk Wiring Only	10	10	
Grp Ckt, Fig. 6, A Wrg	1	1	
Tst Line Jk, Fig. 7	1	0	
Tst and Make-Busy Jk Fig. 13 and 15	1	1	
Fig. 14	8	8	

*List 2*—Framework, assembly, wiring, and equipment for one unit of ten 100-point 8-wire trunk finders, less finders and banks for additional units of a group.

	WIRE	EQUIP	NOTES
Sw Tbl Alm Ckt, SD-31514-01: Rls Alm Ckt, Fig. 3	1	1	<i>Under J32004BD-( )</i>
Fuse Alm Ckt, Fig. 5, X App	1	1	
Trk Fdr Ckt, SD-31953-01: Trk Fdr Ckt, Fig. 5, Jk Wiring Only	10	10	<i>Add:</i>
Tst Line Jk, Fig. 7	1	0	
Tst and Make-Busy Jk: Fig. 13 and 15	1	1	<i>List 9</i> —Wiring and apparatus required in addition to list 1 to provide alarm indication to CSACS per SD-31514-01, option N.¶
Fig. 14	8	8	

Bell Telephone Laboratories, Incorporated

Dept 5245