

**OUTGOING SENDER CONNECTOR FRAME
AND ASSOCIATED EQUIPMENT UNITS
EQUIPMENT DESIGN REQUIREMENTS
NO. 1 CROSSBAR SYSTEM**

1. GENERAL

1.001 This addendum supplements Section 816-305-150, Issue 1.

1.002 This addendum is issued to bring the J specification into agreement with manufacturing drawings.

These changes are in accordance with SD-27759-01, Issue 2D.

4. EQUIPMENT

The following changes apply to Part 4 of the section:

Under J28158C

Change: List 1 *To Read:*

List 1 — Assembly, wiring and equipment for one sender subgroup relay unit arranged for five markers and one sender group and equipped for one marker and one sender group per SD-27759-01, Fig. 1.

Add:

List 2 — Equipment per SD-27759-01, Fig. 1 required in addition to list 1 for each additional marker equipped.

Under J28158D

Change: List 1 *To Read:*

List 1 — Assembly, wiring and equipment for one preference chain transfer unit arranged for ten markers and six connectors and equipped for six markers (TR0 relay) and two connectors per SD-27760-01, Fig. 1 and 3.

Change: List 2 *To Read:*

List 2 — Equipment per SD-27760-01, Fig. 1 and 3 (TR0 relay) required in addition to list 1 for each additional pair of connectors.

Change: List 3 *To Read:*

List 3 — Equipment per SD-27760-01, Fig. 3 (TR1 relay) required in addition to lists 1 and 2 for each pair of connectors when over six markers are provided.

Remove: Lists 4 and 5.

Add:

J28158K (AT&TCo Std) — Preference Chain Unit

Equipment — J28158K-()

List 1 — Assembly, wiring and equipment for one preference chain unit arranged for one marker and six connectors and equipped for two connectors per SD-27760-01, Fig. 2.

List 2 — Equipment per SD-27760-01, Fig. 2 required in addition to list 1 for each additional pair of connectors.

Bell Telephone Laboratories, Incorporated

Dept 5615