

**KEYPULSING SENDER LINK FRAME  
OR COIN SUPERVISORY LINK FRAME  
EQUIPMENT DESIGN REQUIREMENTS  
NO. 1 CROSSBAR SYSTEM**

**1. GENERAL**

**1.001** This addendum supplements Section 816-428-150, Issue 6.

**1.002** The addendum is reissued:

- (a) To provide information for the coin service improvements (dial-tone-first) features.
- (b) To provide equipment and wiring information to eliminate the coin present test when collecting for charge calls.
- (c) To provide for recycle of coin disposal function with a count of first and second trial failures.
- (d) To provide equipment and wiring information for Centralized Status, Alarm and Control System (CSACS) feature.

**1.003** The above changes are in accordance with SD-25061-01, Issues 25D and 26D, SD-25061-02, Issues 27D and 28D, SD-25444-01, Issues 14D and 16D, and SD-25029-01, Issue 41B.

The following changes apply to Part 1 of the section:

- (b) Under Subdivisions of Equipment, J21551K—added.

***Under Subdivisions of Equipment***

**Add:** J21551K

J21551K—AT&TCo Std—Coin Supervisory Improvement Unit

**4. EQUIPMENT**

The following changes apply to Part 4 of the section:

- (a) J21551C, Lists 1, 2, and 3—revised
- (b) J21551C, Lists 5, 6, 7, and 8—added
- (c) J21551F, List 6—added
- (d) J21551G, Lists 1 and 2—revised
- (e) J21551G, Lists 6, 7, and 8—added
- (f) J21551K—added

***Under J21551C***

**Change:** Lists 1, 2, and 3

***To Read:***

**List 1**—Framework, assembly, wiring, and common equipment for a coin supervisory unit wired for two coin supervisory circuits.

	WIRE	EQUIP	NOTES
Framework, ED-25028-01: Item 10		1	
Cable Bracket, ED-25020-01: Item 12		1	B
Coin Supervisory Ckt, SD-25061-01: Fig. 1, E, F, H, J, K, and SD-25061-02: Fig. 1, D, F, J, K, L, M, O, P, Q, S	2	0	D,G,H

**List 2**—Equipment per SD-25061-01, Fig. 1, H, and J, required in addition to list 1 for one coin supervisory circuit not arranged for overtime coin collection. (See Note E.)

**List 3**—Equipment per SD-25061-02, Fig. 1, D, F, O, P, and S, required in addition to list 1 for one coin supervisory circuit arranged for overtime collection. (See Notes F and J.)

**Add:**

**List 5**—Equipment per SD-25061-01, Fig. K (omit Fig. J), required in addition to list 2 when coin service improvements (dial-tone-first) feature is provided.

**List 6**—Equipment per SD-25061-02, Fig. Q (omit Fig. P), required in addition to list 3 when coin service improvements (dial-tone-first) feature is provided.

**List 7**—Equipment per SD-25061-02, ZT option, required in addition to list 6 when Fig. A, B, J, or K is provided.

**List 8**—Equipment per SD-25061-02, ZU option, required in addition to list 6 when Fig. G or L is provided.

**Under J21551F**

**Add:**

**List 6**—Wiring and equipment per SD-25029-01, YT option, required in addition to list 1 when office is to operate with the Centralized Status, Alarm and Control System (CSACS).

**Under J21551G**

**Change:** Lists 1 and 2

**To Read:**

**List 1**—Framework, assembly, wiring, and common equipment for a coin supervisory unit wired for two coin supervisory circuits.

WIRE EQUIP NOTES

Framework, ED-25028-01: Item 15		1	
Terminal Strip Mtg Detail, ED-25020-01: Item 1		1	
Cable Bracket, ED-25020-01: Item 12		1	B
Coin Supervisory Ckt, SD-25444-01: Fig. 1, A, B, D, E, and F	2	0	E,F

**List 2**—Equipment per SD-25444-01, Fig. 1, D, and E, less W or X apparatus, required in addition to list 1 for one coin supervisory circuit not arranged for ringback.

**Add:**

**List 6**—Equipment per SD-25444-01, Fig. F (omit Fig. E), required in addition to list 2 when office is arranged for coin service improvements (dial-tone-first) feature.

**List 7**—Apparatus and wiring per SD-25444-01, option ZN required in addition to list 2 to eliminate the coin present test when collecting for a charge call.

**List 8**—Apparatus and wiring per SD-25444-01, option ZQ required in addition to list 2 to recycle the coin disposal function and count the first and second trial failures.

**Add:**

**J21551K—AT&T Co Std—Coin Supervisory Improvement Unit**

Equipment—J21551K-( )

**List 1**—Assembly, wiring, and equipment for one coin supervisory improvement unit required for the recycle of the coin disposal function with a count of the first and second trial failures per SD-25061-01, Fig. L and option ZE, or SD-25061-02, Fig. T and option ZX, or SD-25444-01, Fig. G and option ZQ.

**List 2**—Wiring and equipment required in addition to list 1 for one additional circuit per SD-25061-01, Fig. L and option ZE, or

SD-25061-02, Fig. T and option ZX, or  
SD-25444-01, Fig. G and option ZQ.

**List 3**—Wiring and equipment per SD-25061-01,  
ZH option, or SD-25061-02, ZZ option, or  
SD-25444-01, ZS option, to provide for the  
identification of coin lines by the use of  
ANI tones.

**Notes:**

- A. This is a surface-wired unit intended to mount  
on a miscellaneous frame.

Bell Telephone Laboratories, Incorporated

Dept 5245