

**INCOMING TRUNK TEST FRAME
AND INCOMING TRUNK TEST CONNECTOR FRAME
EQUIPMENT DESIGN REQUIREMENTS
NO. 1 CROSSBAR AND CROSSBAR TANDEM SYSTEMS**

1. GENERAL

◆ *Under J27753D,L2*

1.001 This addendum supplements Section 816-601-150 and 817-701-150, Issue 12.

Remove:

1.002 This addendum is issued:

2-Digit Code, Fig. 54

WIRE EQUIP NOTES

1 0

(a) To change J27753V,L1, to add reference to option U for including MDT busy in PF alarm and to provide a visual cancel ATA indication per SD-28101-01, Issue 2B.

Rate: List 31 A&M Only

(b) To add J27753X—Trap Unit for Stuck Sender Trunk Identification, per SD-28120-01, Issue 1.

Add:

◆ (c) To add lists 49 through 53 under J27753D, per SD-25191-01, Issue 68B.

List 49—Apparatus and wiring per SD-25161-01, Fig. 71 required in addition to list 2 when “High-Five” codes are required.

(d) To add lists 48 through 51 under J27753E, per SD-25191-01, Issue 68B. ◆

List 50—Apparatus and wiring per SD-25161-01, Fig. 78 required in addition to list 2 and 3 when two selections using incoming advance, seven selections, or nonstandard test line codes are required.

List 51—Apparatus and wiring per SD-25161-01, option PX required in addition to list 3 when 6-digit codes are required.

4. EQUIPMENT

The following changes apply to Part 4 of the section:

List 52—Apparatus and wiring per SD-25161-01, option OC required in addition to list 43 when a second ANI code is required.

List 53—Apparatus and wiring per SD-25161-01, option OD required in addition to list 43 when a third ANI code is required.

◆ (a) J27753D,L2—revised

Under J27753E

(b) J27753D,L31—rerated

Add:

(c) J27753D,L49-53—added

List 48—Apparatus and wiring per SD-25161-01, Fig. 41, option OQ required in addition to lists 1, 10, and 19 when 2-way EAS and satellite trunks are to be tested.

(d) J27753E,L48-51—added ◆

List 49—Apparatus and wiring per SD-25161-01, Fig. 71 required in addition to list 2 when “High-Five” codes are required.

(e) J27753V,L1—revised

(f) J27753X—added

NOTICE

Not for use or disclosure outside the
Bell System except under written agreement

List 50—Apparatus and wiring per SD-25161-01, Fig. 78 required in addition to lists 2, 14, and 45 when two selections using incoming advance, seven selections, or nonstandard test line codes are required.

List 51—Apparatus and wiring per SD-25161-01, option PX required in addition to list 45 when 6-digit codes are required. ◀

Under J27753V

Change: List 1

To Read:

List 1—Assembly, wiring, and equipment for one trunk select control unit required for stuck sender trunk identification per SD-28101-01, Fig. 2, with option U for including MDT busy in PF alarm and to provide a visual cancel indication. [See J27753U-() unit.]

Add:

J27753X—AT&T Co Std—Crossbar Systems No. 1—Trap Unit for Stuck Sender Trunk Identification.

Bell Telephone Laboratories, Incorporated

Dept 5251

List 1—Assembly, wiring, and equipment for one trap unit for stuck sender trunk identification per SD-28120-01, Fig. 1. (See Note A.)

Note

A. This unit is to be mounted on relay rack. To facilitate switchboard cabling, it is desirable, but not essential, that this unit be located near the Printer Control Unit, J27753W.

5. GENERAL NOTES AND INDEXES

The following change applies to Part 5 of the section:

▶ **Under: List of A&M only and Mfr Disc Equipment**

Add:

EQUIPMENT	RATING	DETAILS LAST SHOWN IN ISSUE	REPLACING EQUIPMENT
J27753D,L31	A&M Only	12	— ◀