

**INCOMING TRUNK TEST FRAME  
AND INCOMING TRUNK TEST CONNECTOR FRAME  
EQUIPMENT DESIGN REQUIREMENTS  
NO. 1 CROSSBAR AND CROSSBAR TANDEM SYSTEMS**

**1. GENERAL**

◆ *Under J27753D,L2*

**1.001** This addendum supplements Section 816-601-150 and 817-701-150, Issue 12.

*Remove:*

**1.002** This addendum is issued:

2-Digit Code, Fig. 54

WIRE      EQUIP      NOTES

1            0

(a) To change J27753V,L1, to add reference to option U for including MDT busy in PF alarm and to provide a visual cancel ATA indication per SD-28101-01, Issue 2B.

*Rate: List 31 A&M Only*

(b) To add J27753X—Trap Unit for Stuck Sender Trunk Identification, per SD-28120-01, Issue 1.

*Add:*

◆ (c) To add lists 49 through 53 under J27753D, per SD-25191-01, Issue 68B.

*List 49*—Apparatus and wiring per SD-25161-01, Fig. 71 required in addition to list 2 when "High-Five" codes are required.

(d) To add lists 48 through 51 under J27753E, per SD-25191-01, Issue 68B. ◆

*List 50*—Apparatus and wiring per SD-25161-01, Fig. 78 required in addition to list 2 and 3 when two selections using incoming advance, seven selections, or nonstandard test line codes are required.

*List 51*—Apparatus and wiring per SD-25161-01, option PX required in addition to list 3 when 6-digit codes are required.

**4. EQUIPMENT**

The following changes apply to Part 4 of the section:

*List 52*—Apparatus and wiring per SD-25161-01, option OC required in addition to list 43 when a second ANI code is required.

*List 53*—Apparatus and wiring per SD-25161-01, option OD required in addition to list 43 when a third ANI code is required.

◆ (a) J27753D,L2—revised

*Under J27753E*

(b) J27753D,L31—rerated

*Add:*

(c) J27753D,L49-53—added

*List 48*—Apparatus and wiring per SD-25161-01, Fig. 41, option OQ required in addition to lists 1, 10, and 19 when 2-way EAS and satellite trunks are to be tested.

(d) J27753E,L48-51—added ◆

*List 49*—Apparatus and wiring per SD-25161-01, Fig. 71 required in addition to list 2 when "High-Five" codes are required.

(e) J27753V,L1—revised

(f) J27753X—added

**NOTICE**

Not for use or disclosure outside the  
Bell System except under written agreement

**List 50**—Apparatus and wiring per SD-25161-01, Fig. 78 required in addition to lists 2, 14, and 45 when two selections using incoming advance, seven selections, or nonstandard test line codes are required.

**List 51**—Apparatus and wiring per SD-25161-01, option PX required in addition to list 45 when 6-digit codes are required. ◀

**Under J27753V**

**Change: List 1**

**To Read:**

**List 1**—Assembly, wiring, and equipment for one trunk select control unit required for stuck sender trunk identification per SD-28101-01, Fig. 2, with option U for including MDT busy in PF alarm and to provide a visual cancel indication. [See J27753U-( ) unit.]

**Add:**

**J27753X—AT&T Co Std—Crossbar Systems No. 1—Trap Unit for Stuck Sender Trunk Identification.**

Bell Telephone Laboratories, Incorporated

Dept 5251

**List 1**—Assembly, wiring, and equipment for one trap unit for stuck sender trunk identification per SD-28120-01, Fig. 1. (See Note A.)

**Note**

A. This unit is to be mounted on relay rack. To facilitate switchboard cabling, it is desirable, but not essential, that this unit be located near the Printer Control Unit, J27753W.

## 5. GENERAL NOTES AND INDEXES

The following change applies to Part 5 of the section:

▶ **Under: List of A&M only and Mfr Disc Equipment**

**Add:**

EQUIPMENT	RATING	DETAILS LAST SHOWN IN ISSUE	REPLACING EQUIPMENT
J27753D,L31	A&M Only	12	— ◀