

NEGATIVE IMPEDANCE PROVIDED BY SERIES E-TYPE REPEATERS

CONTENTS	PAGE
1. GENERAL	1
2. SUMMARY OF DATA	1

2. SUMMARY OF DATA

1. GENERAL

1.01 This practice gives, in tabular form, the negative impedances provided by Series E-type negative impedance repeaters for all of the strapping combinations given in Section 332-200-107. Information on the values of the various network elements is given in Section 852-305-105.

1.02 A knowledge of the actual negative impedance required in the repeater to give a desired transmission gain is not required for many of the circuit design problems ordinarily encountered. For certain specific problems, however, such as the use of these repeaters to improve the impedance characteristics of a line, or to determine the effect of the repeater on return loss, and in certain of the more complex special service line applications, data of this kind are useful.

2.01 Table 1 gives the negative impedance characteristic of the series element E-type repeater for the half-section termination of the 17 types of loaded line facilities listed in the strapping charts of Section 332-200-107. A separate impedance-frequency characteristic is tabulated for each nominal gain step which covers a range of nominal gain from 1.5 db to 8.0 db in 0.5-db steps. The frequency range is from 200 cps to about 1.1 times the cutoff frequency of the facility involved.

2.02 Table 2 lists the negative impedance of the repeater at 1000 cps with its network adjusted for various end sections of loaded cable ranging from 0.3 to 1.2 sections.

2.03 Table 3 lists similar data for certain sample conditions of facility and gain for various end sections and various frequencies.

2.04 Since these data represent values obtained from measurements on a single representative repeater, some variation is to be expected. It is not expected, however, that the values obtained with particular repeaters will vary more than ± 5 percent from the information given herein.

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 1X
 19 CNB)
 22 BSA)B88
 24 DSM)

Gain	F	R	X	Gain	F	R	X
1.5db	200	- 409	- 133	3.5db	200	- 844	- 339
	500	- 429	- 24		500	- 898	- 89
	1000	- 441	+ 20		1000	- 911	+ 24
	1500	-	-		1500	-	-
	2000	- 481	105		2000	- 963	165
	2800	- 545	185		2800	-1068	277
	3000	- 564	214		3000	-1108	310
	3500	- 638	335		3500	-1243	457
	.8 fc → 3900	- 672	512		.8 fc → 3900	-1396	701
	4000	- 641	609		4000	-1425	822
	fc → 4900	- 154	889		fc → 4900	-1727	614
	5000	- 69	866		5000	- 384	1787
	5200	- 8	803		5200	- 129	1606
	1.1 fc → 5400	+ 26	723		1.1 fc → 5400	- 5	1423
2.0db	200	- 544	- 193	4.0db	200	- 976	- 407
	500	- 572	- 44		500	-1035	- 102
	1000	- 585	+ 33		1000	-1036	+ 52
	1500	-	-		2000	-1048	213
	2000	- 626	136		2800	-1104	290
	2800	- 699	231		3000	-1135	303
	3000	- 723	263		3500	-1301	350
	3500	- 806	397		.8 fc → 3900	-1599	446
	.8 fc → 3900	- 874	590		4000	-1737	521
	4000	- 879	673		fc → 4900	- 432	2558
	fc → 4900	- 212	1146		5000	- 136	2222
	5000	- 149	1112		5200	+ 66	1860
	5200	- 39	985		1.1 fc → 5400	+ 90	1547
	1.1 fc → 5400	+ 19	906				
2.5db	200	- 641	- 232	4.5db	200	- 994	- 440
	500	- 679	- 63		500	-1082	- 136
	1000	- 690	+ 7		1000	-1110	+ 7
	1500	-	-		1500	-	-
	2000	- 739	115		2000	-1187	127
	2800	- 819	205		2800	-1342	239
	3000	- 846	234		3000	-1386	273
	3500	- 947	329		3500	-1572	428
	.8 fc → 3900	-1053	464		.8 fc → 3900	-1780	634
	4000	-1081	514		4000	-1838	739
	fc → 4900	- 884	1419		fc → 4900	-1176	2466
	5000	- 709	1553		5000	- 855	2604
	5200	- 351	1584		5200	- 309	2415
	1.1 fc → 5400	- 103	1416		1.1 fc → 5400	- 7	2101
3.0db	200	- 788	- 314	5.0db	200	-1040	- 460
	500	- 838	- 83		500	-1129	- 150
	1000	- 850	+ 25		1000	-1150	- 9
	1500	-	-		2000	-1233	+ 113
	2000	- 894	148		2400	-1293	158
	2800	- 976	244		2800	-1381	214
	3000	-1011	273		3000	-1431	242
	3500	-1125	375		3500	-1646	367
	.8 fc → 3900	-1260	526		.8 fc → 3900	-1891	549
	4000	-1295	586		4000	-1976	630
	fc → 4900	- 944	1817		fc → 4900	-1835	2781
	5000	- 687	1915		5000	-1236	2922
	5200	- 328	1862		5200	- 486	2793
	1.1 fc → 5400	- 28	1635		1.1 fc → 5400	- 49	2413

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 1X (Cont'd)
 19 CMB)
 22 BSA)B88
 24 DSM)

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.5db	200	-1200	- 563	7.5db	200	-1358	- 713		
	500	-1314	- 145		300	-1495	- 451		
	1000	-1324	+ 56		500	-1569	- 234		
	1500				1000	-1613	- 25		
	2000	-1360	258		1500	-1659	+ 79		
	2800	-1492	386		2000	-1732	171		
	3000	-1560	440		2400	-1817	252		
	3500	-1793	658		2800	-1949	344		
	.8 fc →	3900	-2065		1174	3000	-2031	431	
	fc →	4000	-2087		1410	3500	-2334	719	
		4900	- 291		2230	.8 fc →	3900		
		5000	- 141		2063	fc →	4000	-2534	1478
	1.1 fc →	5200	+ 37		1812	fc →	4900	- 585	3037
		5400	+ 86		1646	5000	- 365	2875	
				5200	+ 64	2571			
				1.1 fc →	5400				
6.0db	200	-1246	- 598	8.0db	200	-1490	- 812		
	500	-1357	- 156		500	-1665	- 245		
	1000	-1378	+ 49		1000	-1700	- 7		
	2000	-1450	277		2000	-1782	+ 223		
	2400	-1528	371		2400	-1847	300		
	2800	-1634	484		2800	-1955	381		
	3000	-1710	580		3000	-2026	430		
	3500	-1939	1025		3500	-2311	607		
	.8 fc →	3900	-1911		1677	.8 fc →	3900	-2688	950
	fc →	4000	-1747		1929	4000	-2799	1142	
		4900	- 122		1956	fc →	4900	-1135	3741
		5000	- 17		1792	5000	- 623	3523	
	1.1 fc →	5200	+ 87		1607	5200	- 136	3072	
		5400	+ 76		1448	1.1 fc →	5400	+ 63	2588
6.5db	200	-1275	- 630	7.0db	200	-1415	- 736		
	500	-1425	- 159		500	-1546	- 232		
	1000	-1439	+ 70		1000	-1580	- 19		
	1500				2000	-1698	+ 200		
	2000	-1451	287		2400	-1780	292		
	2800	-1606	426		2800	-1902	393		
	3000	-1676	471		3000	-1985	463		
	3500	-1984	693		3500	-2209	775		
	.8 fc →	3900	-2227		1286	.8 fc →	3900	-2378	1261
	fc →	4000	-2214		1597	4000	-2383	1403	
		4900	- 202		2266	fc →	4900	-1145	2760
		5000	- 88		2116	5000	- 904	2714	
	1.1 fc →	5200	+ 63		1892	5200	- 538	2640	
		5400	+ 152		1697	1.1 fc →	5400	- 238	2446

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 2X
 19 DMB)^{B88}
 24 GSM)

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
1.5db	200	- 4.53	- 152	3.5db	200	- 965	- 407		
	500	- 4.73	- 26		500	-1035	- 109		
	1000	- 4.83	+ 36		1000	-1052	+ 23		
	1500	- 4.89	79		1500	-1062	101		
	2000	- 5.02	117		2000	-1083	170		
	2400	- 5.23	14.8		2400	-1116	220		
	2800	- 54.8	184		2800	-1166	271		
	3000	- 570	201		3000	-1196	295		
	4000	- 733	424		4000	-14.81	599		
	.8 fc →	4300	- 775		586	.8 fc →	4300	-1598	810
		5000	- 34.7		1054		5000	-14.21	1862
		5400	- 82		934		5400	- 6.50	2163
	fc →	5500	- 30		880	fc →	5500	- 4.75	2120
		5600	- 11		844		5600	- 282	2074
1.1 fc →	6100	+ 69	721	1.1 fc →	6100	+ 135	1567		
2.0db	200	- 598	- 203	4.0db	200	-1051	- 460		
	500	- 629	- 32		500	-1137	- 117		
	1000	- 633	+ 4.5		1000	-1138	+ 38		
	1500	- 637	111		1500	-114.5	136		
	2000	- 64.6	164		2000	-1162	214		
	2400	- 659	197		2400	-1188	272		
	2800	- 688	242		2800	-1219	326		
	3000	- 706	264		3000	-124.3	357		
	4000	- 926	544		4000	-1583	613		
	.8 fc →	4300	- 950		786	.8 fc →	4300	-1782	819
		5000	- 156		1228		5000	-14.38	2575
		5400	+ 9		985		5400	- 1.25	2306
	fc →	5500	+ 31		962	fc →	5500	+ 18	2129
		5600	+ 72		900		5600	+ 109	1909
1.1 fc →	6100	+ 78	727	1.1 fc →	6100	+ 142	1411		
2.5db	200	- 724	- 276	4.5db	200	-1124	- 518		
	500	- 769	- 81		500	-1218	- 163		
	1000	- 780	0		1000	-1250	+ 15		
	1500	- 796	+ 52		1500	-1289	69		
	2000	- 821	93		2000	-1346	144		
	2400	- 842	123		2400	-1400	215		
	2800	- 877	150		2800	-1489	298		
	3000	- 907	167		3000	-1532	352		
	4000	-1118	285		4000	-1764	833		
	.8 fc →	4300	-1236		364	.8 fc →	4300	-1822	1075
		5000	-1703		887		5000	-1542	1921
		5400	-1637		1865		5400	-1001	2356
	fc →	5500	-1365		2075	fc →	5500	- 832	2384
		5600	-1078		2281		5600	- 624	2380
1.1 fc →	6100	+ 55	1734	1.1 fc →	6100	+ 114	1994		
3.0db	200	- 883	- 358	5.0db	200	-1190	- 571		
	500	- 934	- 81		500	-1310	- 177		
	1000	- 935	+ 55		1000	-1330	- 10		
	1500	- 933	134		1500	-1356	+ 83		
	2000	- 935	196		2000	-1396	159		
	2400	- 947	242		2400	-1438	215		
	2800	- 973	280		2800	-1505	282		
	3000	- 992	299		3000	-1542	317		
	3500	-1084	399		4000	-1859	619		
	4000	-1264	486		.8 fc →	4300	-2002	796	
	.8 fc →	4300	-1529		699		5000	-2288	1732
		4500	-1489		832		5400	-1925	2707
		5000	-1318		1682	fc →	5500	-1585	2866
		5400	- 591		1957		5600	-1258	3015
fc →	5500	- 396	1897		6000	- 30	2662		
	5600	- 24.5	1828	1.1 fc →	6100	+ 56	2460		
1.1 fc →	6100	+ 65	1380						

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 2X (Cont'd)
 19 DNB) B88
 24 CSM)

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>
5.5db	200	-1317	- 665	7.5db	200	-1569	- 903
	500	-1454	- 200		500	-1799	- 250
	1000	-1479	+ 8		1000	-1803	+ 35
	1500	-1509	110		1500	-1803	200
	2000	-1551	201		2000	-1794	307
	2400	-1600	275		2400	-1811	366
	2800	-1672	362		2800	-1858	417
	3000	-1720	412		3000	-1896	442
	4000	-2106	892		4000	-2458	746
	.8 fc → 4300	-2155	1222		.8 fc → 4300	-2771	1076
	5000	-1795	2481		5000	-2304	3277
	5400	- 849	2837		5400	- 858	3496
	fc → 5500	- 608	2831		fc → 5500	- 555	3365
	5600	- 423	2737		5600	- 289	3208
1.1 fc → 6100	+ 167	2114	1.1 fc → 6100	+ 236	2351		
6.0db	200	-1387	- 717	8.0db	200	-1652	- 998
	500	-1540	- 212		500	-1887	- 302
	1000	-1559	+ 10		1000	-1910	+ 14
	1500	-1575	136		1500	-1921	142
	2000	-1602	230		2000	-1937	249
	2400	-1648	296		2400	-1976	313
	2800	-1720	365		2800	-2039	376
	3000	-1771	410		3000	-2085	404
	4000	-2259	845		4000	-2624	706
	.8 fc → 4300	-2413	1204		.8 fc → 4300	-2941	946
	5000	-1854	2837		5000	-3240	2799
	5400	- 806	2829		5400	-1944	3867
	fc → 5500	- 507	2868		fc → 5500	-1502	3922
	5600	- 360	2733		5600	-1081	3873
6000	+ 113	2180	6000	- 75	3178		
1.1 fc → 6100	+ 163	2070	1.1 fc → 6100	+ 65	2997		
6.5db	200	-1444	- 765	7.0db	200	-1527	- 839
	500	-1618	- 212		300	-1650	- 512
	1000	-1628	+ 42		500	-1711	- 233
	1500	-	-		1000	-1726	+ 35
	2000	-1631	293		1500	-1732	188
	2400	-1652	360		2000	-1753	302
	2800	-1696	422		2400	-1789	369
	3000	-1745	454		2800	-1856	451
	4000	-2194	826		3000	-1908	494
	.8 fc → 4300	-2410	1158		3500	-2589	670
	5000	-1906	2826		4000	-2400	1039*
	5400	- 598	2968		.8 fc → 4300	-2519	1526
	fc → 5500	- 535	2949		5000	-1510	3056
	5600	- 286	2758		5400	- 513	2912
1.1 fc → 6100	+ 161	2119	fc → 5500	- 305	2791		
			5600	- 148	2660		
			6000	+ 161	2108		
			1.1 fc → 6100	+ 223	2014		

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 3X
 19 CNB)
 22 BSA)D88
 24 DSM)

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
1.5db	200	- 342	- 116	3.5db	200	- 723	- 278		
	300	- 354	- 70		300	- 750	- 168		
	500	- 360	- 25		500	- 766	- 68		
	1000	- 372	+ 24		1000	- 792	+ 35		
	1500	- 393	64		1500	- 819	108		
	2000	- 429	109		2000	- 871	182		
	2500	- 473	165		2500	- 961	277		
	3000	- 530	262		3000	-1099	441		
	.8 fc →	3200	- 560		330	.8 fc →	3200	-1180	563
	fc →	3500	- 583		468	fc →	3500	-1284	945
1.1 fc →	4000	- 382	788	1.1 fc →	4000	- 502	1636		
	4400	- 83	735		4400	+ 16	1228		
	5000	+ 33	523		5000	+ 57	848		
2.0db	200	- 454	- 154	4.0db	200	- 805	- 312		
	300	- 470	- 93		300	- 836	- 182		
	500	- 475	- 32		500	- 850	- 73		
	1000	- 483	+ 36		1000	- 868	+ 46		
	1500	- 497	83		1500	- 891	122		
	2000	- 527	123		2000	- 932	190		
	2500	- 575	169		2500	-1021	266		
	3000	- 673	242		3000	-1204	407		
	.8 fc →	3200	- 732		308	.8 fc →	3200	-1318	529
	fc →	3500	- 829		470	fc →	3500	-1498	945
1.1 fc →	4000	- 597	1023	1.1 fc →	4000	- 556	1816		
	4400	- 147	981		4400	+ 13	1307		
	5000	+ 36	699		5000	+ 55	915		
2.5db	200	- 547	- 193	4.5db	200	- 895	- 364		
	300	- 562	- 112		300	- 924	- 223		
	500	- 571	- 37		500	- 939	- 100		
	1000	- 590	+ 47		1000	- 962	+ 77		
	1500	- 614	110		1500	- 992	156		
	2000	- 660	176		2000	-1059	230		
	2500	- 735	286		2500	-1204	365		
	3000	- 823	503		3000	-1462	709		
	.8 fc →	3200	- 813		654	.8 fc →	3200	-1501	980
	fc →	3500	- 673		912	fc →	3500	-1211	1618
1.1 fc →	4000	- 195	971	1.1 fc →	4000	- 189	1575		
	4400	- 11	806		4400	+ 51	1208		
	5000	+ 15	629		5000	+ 66	964		
3.0db	200	- 644	- 231	5.0db	200	- 928	- 381		
	300	- 664	- 132		300	- 976	- 228		
	500	- 674	- 40		500	- 994	- 84		
	1000	- 687	+ 59		1000	-1019	+ 47		
	1500	- 701	129		1500	-1053	142		
	2000	- 739	192		2000	-1113	227		
	2500	- 815	270		2500	-1243	354		
	3000	- 981	442		3000	-1478	645		
	.8 fc →	3200	-1057		603	.8 fc →	3200	-1551	882
	fc →	3500	-1025		1065	fc →	3500	-1441	1456
1.1 fc →	4000	- 166	1246	1.1 fc →	4000	- 333	1726		
	4400	+ 24	955		4400	- 6	1335		
	5000	- 28	686		5000	+ 53	992		

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 3X (Cont'd)
 19 CNB)
 22 BSA)D88
 24 DSM)

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.5db	200	- 971	- 413	7.5db	200	-1175	- 551		
	300	-1016	- 253		300	-1236	- 350		
	500	-1046	- 111		500	-1275	- 175		
	1000	-1076	+ 38		1000	-1320	- 6		
	1500	-1134	135		1500	-1396	+ 108		
	2000	-1237	243		2000	-1515	237		
	2500	-1413	434		2500	-1677	420		
	3000	-1625	927		3000	-1865	753		
	.8 fc →	3200	-1561		1306	.8 fc →	3200	-1951	958
	fc →	3500	-1117		1795	fc →	3500	-1949	1462
1.1 fc →	4000	- 216	1606	1.1 fc →	4000	-1055	2335		
	4400	+ 35	1272		4400	- 103	2013		
	5000	+ 85	972		5000	+ 49	1408		
6.0db	200	-1055	- 460	8.0db	200	-1249	- 599		
	300	-1110	- 283		300	-1319	- 368		
	500	-1138	- 135		500	-1361	- 173		
	1000	-1170	+ 6		1000	-1410	+ 10		
	1500	-1226	111		1500	-1469	139		
	2000	-1303	202		2000	-1574	261		
	2500	-1440	310		2500	-1754	431		
	3000	-1712	520		3000	-2036	777		
	.8 fc →	3200	-1901		705	.8 fc →	3200	-2180	1038
	fc →	3500	-2172		1333	fc →	3500	-2205	1858
1.1 fc →	4000	- 578	2480	1.1 fc →	4000	- 577	2543		
	4400	+ 40	1663		4400	+ 5	1893		
	5000	+ 49	1180		4500	+ 67	1792		
					5000	+ 96	1315		
6.5db	200	-1090	- 489	7.0db	200	-1136	- 502		
	300	-1145	- 305		300	-1200	- 311		
	500	-1179	- 140		500	-1229	- 141		
	1000	-1204	+ 31		1000	-1261	+ 17		
	1500	-1234	135		1500	-1296	123		
	2000	-1295	219		2000	-1358	215		
	2500	-1417	310		2500	-1472	305		
	3000	-1668	426		3000	-1693	444		
	.8 fc →	3200	-1872		528	.8 fc →	3200	-1833	552
	fc →	3500	-2344		1029	fc →	3500	-1873	906
1.1 fc →	4000	- 856	2833	1.1 fc →	4000	-1216	2771		
	4400	+ 31	1888		4400	+ 187	2225		
	5000	+ 84	1268		5000	+ 379	1379		

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 4X
 19 DNB) D88
 24 GSM)

Gain	F	R	X	Gain	F	R	X		
1.5db	200	- 396	- 126	3.5db	200	- 798	- 297		
	300	- 413	- 80		300	- 828	- 173		
	500	- 421	- 24		500	- 837	- 58		
	1000	- 430	+ 36		1000	- 845	+ 69		
	1500	- 440	83		1500	- 850	152		
	2000	- 459	121		2000	- 875	215		
	2500	- 487	166		2500	- 934	285		
	3000	- 536	226		3000	-1064	397		
	3200	- 571	260		3200	-1147	485		
	3500	- 616	333		3500	-1280	743		
	.8 fc →	3600	- 635		364	.8 fc →	3600	-1290	883
	fc →	4000	- 669		586	fc →	4000	- 914	1510
	1.1 fc →	4500	- 421		901	1.1 fc →	4500	- 105	1405
	5000	- 44	827			5000	+ 76	1043	
5700	+ 12	615		5700	+ 88	827			
2.0db	200	- 496	- 177	4.0db	200	- 883	- 358		
	300	- 511	- 109		300	- 926	- 221		
	500	- 517	- 44		500	- 939	- 96		
	1000	- 526	+ 31		1000	- 960	+ 25		
	1500	- 544	73		1500	- 982	106		
	2000	- 571	120		2000	-1020	174		
	2500	- 617	151		2500	-1077	252		
	3000	- 698	200		3000	-1176	351		
	3200	- 755	236		3200	-1230	400		
	3500	- 852	317		3500	-1333	514		
	.8 fc →	3600	- 883		361	.8 fc →	3600	-1379	567
	fc →	4000	-1020		728	fc →	4000	-1578	961
	1.1 fc →	4500	- 489		1277	1.1 fc →	4500	-1164	1980
	5000	- 27	1007			5000	- 50	1672	
5700	+ 61	751		5700	+ 96	1117			
2.5db	200	- 573	- 215	4.5db	200	- 951	- 399		
	300	- 592	- 133		300	- 994	- 245		
	500	- 604	- 60		500	-1017	- 117		
	1000	- 619	+ 8		1000	-1040	0		
	1500	- 642	55		1500	-1070	+ 75		
	2000	- 678	97		2000	-1112	131		
	2500	- 728	140		2500	-1205	195		
	3000	- 805	201		3000	-1328	253		
	3200	- 848	235		3200	-1429	310		
	3500	- 925	301		3500	-1600	413		
	.8 fc →	3600	- 966		323	.8 fc →	3600	-1621	473
	fc →	4000	-1130		523	fc →	4000	-1181	695
	1.1 fc →	4500	-1175		1193	1.1 fc →	4500	-1382	2548
	5000	- 243	1567			5000	- 22	1912	
5700	+ 75	999		5700	+ 135	1272			
3.0db	200	- 682	- 255	5.0db	200	-1055	- 454		
	300	- 703	- 154		300	-1105	- 270		
	500	- 717	- 67		500	-1133	- 113		
	1000	- 724	+ 19		1000	-1152	+ 49		
	1500	- 731	82		1500	-1171	149		
	2000	- 761	126		2000	-1215	232		
	2500	- 825	153		2500	-1297	317		
	3000	- 932	187		3000	-1499	472		
	3200	- 996	199		3200	-1620	589		
	3500	-1166	274		3500	-1802	944		
	.8 fc →	3600	-1217		298	.8 fc →	3600	-1859	1094
	fc →	4000	-1665		768	fc →	4000	-1348	2067
	1.1 fc →	4500	- 720		2031	1.1 fc →	4500	- 191	1909
	5000	+ 132	1286			5000	+ 100	1348	
5700	+ 93	933		5700	+ 84	1042			

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 4X (Cont'd)
 19 DNB) D88
 24 CSM)

Gain	F	R	X	Gain	F	R	X		
5.5db	200	-1090	- 496	7.5db	200	-1320	- 658		
	300	-1148	- 311		300	-1406	- 405		
	500	-1259	- 95		500	-1438	- 184		
	1000	-1210	0		1000	-1461	+ 17		
	1500	-1254	+ 88		1500	-1482	122		
	2000	-1327	173		2000	-1516	184		
	2500	-1459	276		2500	-1601	239		
	3000	-1625	476		3000	-1799	289		
	3200	-1730	590		3200	-1924	329		
	3500	-1854	850		3500	-2180	442		
	.8 fc →	3600	-1859		1000	.8 fc →	3600	-2314	516
	fc →	4000	-1756		1674	fc →	4000	-2853	1201
	1.1 fc →	4500	- 826		2207	1.1 fc →	4500	-2118	3076
		5000	- 91		1909		5000	- 359	2817
		5700	+ 120		1325		5700	+ 118	1800
6.0db	200	-1132	- 515	8.0db	200	-1384	- 711		
	300	-1189	- 322		300	-1489	- 433		
	500	-1225	- 156		500	-1548	- 193		
	1000	-1250	+ 10		1000	-1561	+ 40		
	1500	-1286	102		1500	-1571	165		
	2000	-1349	180		2000	-1607	243		
	2500	-1459	270		2500	-1727	306		
	3000	-1643	418		3000	-1972	409		
	3200	-1743	502		3200	-2144	508		
	3500	-1900	722		3500	-2444	759		
	.8 fc →	3600	-1963		834	.8 fc →	3600	-2524	1018
	fc →	4000	-2058		1561	fc →	4000	-2578	2281
	1.1 fc →	4500	-1138		2437	1.1 fc →	4500	- 726	2923
		5000	- 189		2017		5000	+ 47	2056
		5700	+ 93		1415		5700	+ 162	1480
6.5db	200	-1251	- 601	7.0db	200	-1283	- 618		
	300	-1320	- 369		300	-1365	- 385		
	500	-1355	- 170		500	-1406	- 171		
	1000	-1380	+ 21		1000	-1424	+ 10		
	1500	-1418	126		1500	-1441	124		
	2000	-1479	232		2000	-1487	197		
	2500	-1587	317		2500	-1583	263		
	3000	-1774	468		3000	-1793	356		
	3200	-1889	566		3200	-1923	407		
	3500	-2094	837		3500	-2191	607		
	.8 fc →	3600	-2157		956	.8 fc →	3600	-2283	713
	fc →	4000	-2173		1816	fc →	4000	-2598	1611
	1.1 fc →	4500	-1006		2595	1.1 fc →	4500	-1300	2945
		5000	- 128		2098		5000	- 45	2309
		5700	+ 100		1442		5700	+ 146	1534

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 5X
 19 GNB)
 22 BSA)H88
 24 DSM)

Gain	F	R	X	Gain	F	R	X		
1.5db	200	- 307	- 103	3.5db	200	- 650	- 236		
	500	- 323	- 16		500	- 676	- 63		
	1000	- 333	+ 30		1000	- 700	+ 28		
	1500	- 348	71		1500	- 738	98		
	2000	- 376	105		2000	- 803	159		
	2400	- 414	137		2400	- 891	231		
	.8 fc →	2800	- 503		197	.8 fc →	2500	- 929	258
	3000	- 579	255		2800	-1063	380		
	3200	- 655	411		3000	-1196	547		
	3400	- 604	672		3200	-1262	879		
	fc →	3500	- 463		796	3400	-1035	1364	
	1.1 fc →	3600	- 306		827	fc →	3500	- 740	1499
	3800	- 84	728		3600	- 471	1496		
	3900	- 42	671		3800	- 114	1327		
4000	- 21	603	3900	- 63	1195				
			4000	+ 12	1081				
2.0db	200	- 385	- 127	4.0db	200	- 692	- 256		
	500	- 401	- 21		500	- 727	- 63		
	1000	- 411	+ 25		1000	- 754	+ 26		
	1500	- 437	66		1500	- 793	94		
	2000	- 477	100		2000	- 868	157		
	2400	- 538	135		2400	- 977	227		
	.8 fc →	2800	- 657		206	2500	-1023	256	
	3000	- 753	291		.8 fc →	2800	-1204	403	
	3200	- 836	464		3000	-1354	613		
	3400	- 793	773		3200	-1400	1039		
	fc →	3500	- 658		940	3400	-1097	1534	
	1.1 fc →	3600	- 446		1019	fc →	3500	- 781	1648
	3800	- 158	951		3600	- 514	1622		
	3900	- 79	889		3800	- 144	1358		
4000	- 35	795	3900	- 54	1226				
			4000	+ 12	1115				
2.5db	200	- 443	- 155	4.5db	200	- 767	- 288		
	500	- 472	- 33		500	- 818	- 70		
	1000	- 493	+ 33		1000	- 832	+ 58		
	1500	- 523	94		1500	- 855	130		
	2000	- 565	161		2000	- 897	194		
	2400	- 603	241		2400	-1006	264		
	.8 fc →	2500	- 626		267	2500	-1035	278	
	2800	- 662	369		.8 fc →	2800	-1168	375	
	3000	- 671	453		3000	-1282	509		
	3200	- 670	572		3200	-1402	796		
	3400	- 606	696		3400	-1323	1300		
	fc →	3500	- 557		766	fc →	3500	-1119	1526
	1.1 fc →	3600	- 460		816	3600	- 833	1683	
	3800	- 323	867		3800	- 310	1593		
3900	- 226	891	3900	-	-				
4000	- 144	841	4000	- 30	1318				
3.0db	200	- 566	- 191	5.0db	200	- 845	- 339		
	300	- 585	- 118		500	- 902	- 91		
	500	- 592	- 39		1000	- 931	+ 29		
	1000	- 618	+ 41		1500	- 981	108		
	1500	- 650	110		2000	-1080	189		
	2000	- 713	181		2400	-1215	295		
	2400	- 797	280		2500	-1265	336		
	.8 fc →	2500	- 823		317	2800	-1433	548	
	2800	- 923	497		3000	-1544	792		
	3000	- 929	703		3200	-1535	1195		
	3200	- 787	973		3400	-1241	1632		
	3400	- 520	1114		fc →	3500	- 986	1756	
	fc →	3500	- 362		1118	3600	- 730	1768	
	1.1 fc →	3600	- 239		1061	3800	- 308	1660	
3800	- 88	900	3900	- 191	1539				
3900	- 64	850	4000	- 88	1416				
4000	- 25	790							

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 5X (Cont'd)
 19 CNB)
 22 BSA)H88
 24 DSM)

Gain	F	R	X	Gain	F	R	X		
5.5db	200	- 864	- 342	7.5db	200	-1051	- 451		
	500	- 919	- 89		500	-1133	- 130		
	1000	- 944	+ 43		1000	-1171	+ 24		
	1500	- 983	120		1500	-1220	112		
	2000	-1087	217		2000	-1317	188		
	2400	-1206	289		2400	-1512	265		
	2500	-1253	324		2500	-1569	285		
	.8 fc →	2800	-1428		512	.8 fc →	2800	-1903	458
	3000	-1540	764		3000	-2218	776		
	3200	-1554	1191		3200	-2434	1581		
	3400	-1261	1663		3400	-1766	2568		
	fc →	3500	- 970		1808	fc →	3500	-1097	2711
	1.1 fc →	3600	- 688		1840	1.1 fc →	3600	- 628	2570
3800		- 271	1673	3800	- 93		2118		
3900		- 144	1556	3900	- 12		1900		
4000		- 40	1443	4000	+ 38		1741		
6.0db	200	- 941	- 383	8.0db	200	-1066	- 482		
	500	-1006	- 100		300	-1138	- 303		
	1000	-1032	+ 15		500	-1184	- 154		
	1500	-1088	97		1000	-1240	- 14		
	2000	-1202	181		1500	-1323	+ 75		
	2400	-1379	284		2000	-1433	178		
	2500	-1444	329		2400	-1609	264		
	.8 fc →	2800	-1692		592	.8 fc →	2500	-1665	291
	3000	-1833	945		2800	-1915	436		
	3200	-1736	1426		3000	-2255	655		
	3400	-1252	1839		3200	-2600	1390		
	fc →	3500	- 944		2004	fc →	3500	-1272	3130
	1.1 fc →	3600	- 649		2001	1.1 fc →	3800	+ 27	2212
3800		- 263	1755	4000	+ 114		1696		
3900		- 148	1640						
4000		- 66	1485						
6.5db	200	- 964	- 408						
	500	-1039	- 153						
	1000	-1075	+ 9						
	1500	-1157	120						
	2000	-1277	221						
	2400	-1426	344						
	2500	-1485	394						
	.8 fc →	2800	-1673	629					
	3000	-1837	948						
	3200	-1792	1546						
	3400	-1223	2188						
	fc →	3500	- 887	2275					
	1.1 fc →	3600	- 503	2193					
3800		- 69	1831						
3900		- 13	1640						
4000		+ 20	1473						
7.0db	200	-1022	- 438						
	500	-1100	- 128						
	1000	-1140	+ 13						
	1500	-1201	114						
	2000	-1314	210						
	2400	-1479	317						
	2500	-1549	363						
	.8 fc →	2800	-1801	574					
	3000	-2009	896						
	3200	-2086	1525						
	3400	-1593	2241						
	fc →	3500	-1074	2406					
	1.1 fc →	3600	- 706	2363					
3800		- 172	1970						
3900		- 63	1766						
4000		+ 8	1586						

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 6X
 19 DNB)^{H88}
 24 GSM)

Gain	F	R	X	Gain	F	R	X
1.5db	200	- 346	- 115	3.5db	200	- 671	- 261
	500	- 360	- 12		500	- 718	- 76
	1000	- 371	+ 23		1000	- 750	+ 13
	1500	- 387	67		1500	- 798	86
	2000	- 413	104		2000	- 876	168
	2400	- 453	131		2400	= 953	268
	2800	- 491	183		2800	-1058	437
	.8 fc → 3000	- 528	221		.8 fc → 3000	-1092	537
	3100	- 550	250		3100	-1102	629
	3500	- 604	450		3500	-1015	1063
	3800	- 534	690		3800	- 678	1365
	fc → 3900	- 448	754		fc → 3900	- 500	1386
	4000	- 335	801		4000	- 354	1376
4100	- 252	815	4100	- 253	1340		
1.1 fc → 4300	- 96	759	1.1 fc → 4300	- 98	1202		
4400	- 54	713	4400	-	-		
2.0db	200	- 399	- 134	4.0db	200	- 818	- 308
	500	- 422	- 32		500	- 865	- 71
	1000	- 441	+ 9		1000	- 866	+ 43
	1500	- 473	48		1500	- 886	123
	2000	- 519	90		2000	- 938	192
	2400	- 573	141		2400	-1001	251
	2800	- 645	225		2800	-1119	340
	.8 fc → 3000	- 688	291		.8 fc → 3000	-1207	430
	3100	- 706	332		3100	-1276	471
	3500	- 717	617		3500	-1518	989
	3800	- 589	682		3800	-1161	1705
	fc → 3900	- 436	931		fc → 3900	- 839	1822
	4000	- 317	933		4000	- 496	1805
4100	- 211	958	4100	- 303	1697		
1.1 fc → 4300	- 66	863	1.1 fc → 4300	+ 23	1469		
4400	-	-	4400	-	-		
2.5db	200	- 496	- 180	4.5db	200	- 847	- 329
	500	- 524	- 41		500	- 899	- 87
	1000	- 550	+ 15		1000	- 921	+ 20
	1500	- 589	80		1500	- 968	95
	2000	- 653	152		2000	-1029	170
	2400	- 718	250		2400	-1108	240
	2800	- 773	431		2800	-1227	354
	.8 fc → 3000	- 763	573		.8 fc → 3000	-1304	439
	3100	- 739	654		3100	-1338	490
	3500	- 449	917		3500	-1504	915
	3800	- 190	899		3800	-1391	1485
	fc → 3900	- 130	870		fc → 3900	-1247	1663
	4000	- 82	818		4000	- 936	1823
4100	- 44	774	4100	- 756	1879		
1.1 fc → 4300	- 9	694	1.1 fc → 4300	- 307	1780		
4400	-	-	4400	-	-		
3.0db	200	- 628	- 228	5.0db	200	- 937	- 390
	500	- 666	- 46		500	- 995	- 109
	1000	- 680	+ 40		1000	-1019	+ 16
	1500	- 695	104		1500	-1057	96
	2000	- 730	153		2000	-1133	164
	2400	- 788	198		2400	-1230	226
	2800	- 915	270		2800	-1397	335
	.8 fc → 3000	-1004	339		.8 fc → 3000	-1519	433
	3100	-1052	399		3100	-1593	506
	3500	-1144	988		3500	-1850	1113
	3800	- 599	1438		3800	-1536	1863
	fc → 3900	- 387	1434		fc → 3900	-1255	2070
	4000	- 192	1368		4000	- 910	2138
4100	- 85	1259	4100	- 668	2115		
1.1 fc → 4300	+ 30	1058	1.1 fc → 4300	- 243	1917		
4400	-	-	4400	- 107	1753		

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 6X (Cont'd)
 19 DNB)
 24 CSM) H88

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.5db	200	- 956	- 414	7.5db	200	-1162	- 541		
	500	-1027	- 109		500	-1263	- 148		
	1000	-1043	+ 25		1000	-1284	+ 28		
	1500	-1071	99		1500	-1313	134		
	2000	-1124	155		2000	-1372	202		
	2400	-1217	184		2400	-1482	242		
	2800	-1401	237		2800	-1699	287		
	.8 fc →	3000	-1548		295	.8 fc →	3000	-1902	346
		3100	-1652		341		3100	-2036	401
		3500	-2027		677		3500	-2834	1350
		3800	-1862		2073		3800	-1871	3101
	fc →	3900	-1522		2366	fc →	3900	-1153	3100
		4000	-1021		2432		4000	- 564	2903
		4100	- 644		2373		4100	- 274	2633
1.1 fc →	4300	- 195	2018	1.1 fc →	4300	+ 8	2067		
	4400	-	-		4400	-	-		
6.0db	200	-1071	- 447	8.0db	200	-1238	- 593		
	500	-1150	- 104		500	-1360	- 160		
	1000	-1153	+ 79		1000	-1386	+ 37		
	1500	-1172	182		1500	-1421	149		
	2000	-1228	263		2000	-1496	220		
	2400	-1325	332		2400	-1619	275		
	2800	-1552	498		2800	-1893	375		
	.8 fc →	3000	-1687		671	.8 fc →	3000	-2157	500
		3100	-1755		801		3100	-2317	607
		3500	-1637		1727		3500	-2740	2065
		3800	- 855		2064		3800	-1153	3115
	fc →	3900	- 579		2015	fc →	3900	- 652	2949
		4000	- 391		1909		4000	- 246	2543
		4100	- 247		1754		4100	- 76	2309
1.1 fc →	4300	- 75	1529	1.1 fc →	4300	+ 109	1903		
	4400	-	-		4400	+ 107	1728		
6.5db	200	-1085	- 494	7.0db	200	-1135	- 509		
	500	-1178	- 137		500	-1229	- 137		
	1000	-1209	+ 25		1000	-1257	+ 27		
	1500	-1253	131		1500	-1296	147		
	2000	-1335	227		2000	-1371	237		
	2400	-1441	323		2400	-1477	314		
	2800	-1609	500		2800	-1702	450		
	.8 fc →	3000	-1700		643	.8 fc →	3000	-1852	567
		3100	-1746		738		3100	-1986	679
		3500	-1778		1396		3500	-2254	1868
		3800	-1421		1929		3800	-1015	2706
	fc →	3900	-1141		2090	fc →	3900	- 616	2549
		4000	- 900		2094		4000	- 316	2361
		4100	- 698		2111		4100	- 124	2158
1.1 fc →	4300	- 334	1966	1.1 fc →	4300	+ 6	1807		
	4400	-	-		4400	- 30	1539		

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 7X
 19 DNB M88

Gain	F	R	X	Gain	F	R	X		
1.5db	200	- 266	- 87	3.5db	200	- 596	- 193		
	300	- 275	- 48		300	- 622	- 112		
	500	- 280	- 12		500	- 629	- 28		
	1000	- 296	+ 22		1000	- 639	+ 70		
	1500	- 320	59		1500	- 653	132		
	2000	- 360	96		2000	- 702	183		
	2400	- 424	143		2400	- 831	248		
	.8 fc →	2600	- 488		205	.8 fc →	2600	- 979	341
		2800	- 554		327		2800	-1134	607
		3000	- 491		573		3000	- 949	1122
fc →	3200	- 232	694	fc →	3200	- 380	1253		
1.1 fc →	3500	- 24	532	1.1 fc →	3500	+ 59	966		
2.0db	200	- 349	- 116	4.0db	200	- 650	- 232		
	300	- 357	- 68		300	- 670	- 137		
	500	- 366	- 21		500	- 683	- 46		
	1000	- 379	+ 32		1000	- 702	+ 37		
	1500	- 399	69		1500	- 737	96		
	2000	- 446	107		2000	- 818	141		
	2400	- 524	137		2400	- 982	189		
	.8 fc →	2600	- 605		172	.8 fc →	2600	-1136	263
		2800	- 727		273		2800	-1382	494
		3000	- 807		544		3000	-1466	1092
fc →	3200	- 563	918	fc →	3200	-1001	1644		
1.1 fc →	3500	- 91	815	1.1 fc →	3500	- 152	1350		
2.5db	200	- 452	- 146	4.5db	200	- 729	- 252		
	300	- 466	- 83		300	- 746	- 141		
	500	- 473	- 12		500	- 758	- 40		
	1000	- 484	+ 62		1000	- 774	+ 82		
	1500	- 503	119		1500	- 820	174		
	2000	- 560	178		2000	- 936	284		
	2400	- 685	274		2400	-1141	567		
	.8 fc →	2600	- 782		428	.8 fc →	2600	-1148	867
		2800	- 765		733		2800	- 942	1213
		3000	- 462		971		3000	- 553	1340
fc →	3200	- 132	899	fc →	3200	- 267	1209		
1.1 fc →	3500	- 5	671	1.1 fc →	3500	- 65	959		
3.0db	200	- 514	- 168	5.0db	200	- 810	- 304		
	300	- 526	- 93		300	- 838	- 177		
	500	- 534	- 13		500	- 848	- 64		
	1000	- 548	+ 56		1000	- 859	+ 56		
	1500	- 574	117		1500	- 887	135		
	2000	- 646	168		2000	- 973	181		
	2400	- 790	274		2400	-1156	249		
	.8 fc →	2600	- 934		437	.8 fc →	2600	-1347	348
		2800	- 948		791		2800	-1582	575
		3000	- 627		1112		3000	-1714	1149
fc →	3200	- 221	1042	fc →	3200	-1306	1793		
1.1 fc →	3500			1.1 fc →	3500	- 338	1706		

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 7X (Cont'd)
 19 DNB MSB

Gain	F	R	X	Gain	F	R	X		
5.5db	200	- 790	- 305	7.5db	200	- 990	- 400		
	300	- 829	- 183		300	-1006	- 248		
	500	- 849	- 78		500	-1034	- 112		
	1000	- 876	+ 31		1000	-1074	+ 31		
	1500	- 927	95		1500	-1131	120		
	2000	-1062	164		2000	-1264	198		
	2400	-1260	281		2400	-1511	299		
	.8 fc →	2600	-1405		445	.8 fc →	2600	-1724	433
		2800	-1538		763		2800	-2069	788
		3000	-1442		1325		3000	-2080	1702
	fc →	3200	- 927		1736	fc →	3200	-1129	2419
		3400	- 380		1659		3400	- 309	2130
	1.1 fc →	3500	- 188		1509	1.1 fc →	3500	- 61	1865
	4000	+ 32	1000						
6.0db	200	- 901	- 350	8.0db	200	-1020	- 425		
	300	- 934	- 207		300	-1070	- 258		
	500	- 954	- 83		500	-1098	- 107		
	1000	- 975	+ 58		1000	-1139	+ 75		
	1500	-1023	146		1500	-1200	193		
	2000	-1144	230		2000	-1350	331		
	2400	-1349	373		2400	-1593	560		
	.8 fc →	2600	-1516		556	.8 fc →	2600	-1764	832
		2800	-1625		862		2800	-1762	1400
		3000	-1593		1418		3000	-1309	1987
	fc →	3200	-1171		1820	fc →	3200	- 944	2312
	1.1 fc →	3500	- 390		1726	1.1 fc →	3400	- 164	1668
							3500	- 62	1510
6.5db	200	- 898	- 360	7.0db	200	- 943	- 381		
	300	- 938	- 216		300	- 986	- 238		
	500	- 967	- 92		500	-1004	- 114		
	1000	-1005	+ 42		1000	-1044	+ 22		
	1500	-1054	137		1500	-1116	108		
	2000	-1168	223		2000	-1251	185		
	2400	-1395	328		2400	-1506	302		
	.8 fc →	2600	-1599		486	.8 fc →	2600	-1734	444
		2800	-1805		919		2800	-2019	773
		3000	-1610		1757		3000	-2145	1586
	fc →	3200	- 620		2085	fc →	3200	-1430	2400
	1.1 fc →	3400	- 135		1680	1.1 fc →	3500	- 265	2008
		3500							

TABLE 1
 NETTIVE IMPEDANCE OF NETWORK SX
 19 CNB)
 22 BSA) BL35

Gain	F	R	X	Gain	F	R	X		
1.0db	200	- 353	- 130	3.0db	200	- 926	- 359		
	500	- 377	- 26		300	- 972	- 214		
	1000	- 389	+ 25		500	- 995	- 71		
	1500	- 406	61		1000	-1005	+ 54		
	2000	- 436	100		1500	-1039	168		
	2400	- 466	132		2000	-1097	257		
	2800	- 518	182		2400	-1211	370		
	3000	- 555	216		2600	-1289	456		
	.8 fc →	3200	- 587		264	2800	-1383	596	
	fc →	3500	- 636		380	3000	-1476	792	
	1.1 fc →	4000	- 568		748	.8 fc →	3200	-1477	1147
		4400	- 220		866	fc →	3500	-1114	1681
				1.1 fc →	4000	- 180	1565		
					4400	- 10	1172		
1.5db	200	- 502	- 179	3.5db	200	-1068	- 472		
	500	- 527	- 50		500	-1149	- 145		
	1000	- 544	+ 16		1000	-1181	+ 28		
	1500	- 576	60		1500	-1241	121		
	2000	- 628	110		2000	-1336	217		
	2400	- 681	161		2400	-1462	336		
	2800	- 746	241		2800	-1631	547		
	3000	- 791	299		3000	-1702	719		
	.8 fc →	3200	- 830		373	.8 fc →	3200	-1756	980
	fc →	3500	- 876		542	fc →	3500	-1673	1474
	1.1 fc →	4000	- 267		561	1.1 fc →	4000	- 807	2025
		4400	- 240		1127		4400	- 202	1737
2.0db	200	- 643	- 240	4.0db	200	-1176	- 540		
	500	- 683	- 77		300	-1245	- 334		
	1000	- 710	+ 7		500	-1279	- 156		
	1500	- 757	49		1000	-1310	0		
	2000	- 832	105		1500	-1364	+ 110		
	2400	- 924	175		2000	-1472	199		
	2800	-1006	260		2400	-1625	303		
	3000	-1101	390		2800	-1877	519		
	.8 fc →	3200	-1159		516	3000	-2009	721	
	fc →	3500	-1187		822	.8 fc →	3200	-2120	1045
	1.1 fc →	4000	- 738		1391	fc →	3500	-2049	1782
		4400	- 230		1321	1.1 fc →	4000	- 775	2348
					4400	- 128	1922		
2.5db	200	- 799	- 316	4.5db	200	-1233	- 590		
	500	- 843	- 87		500	-1355	- 161		
	1000	- 863	+ 22		1000	-1383	+ 32		
	1500	- 890	86		1500	-1424	155		
	2000	- 939	136		2000	-1506	241		
	2400	-1020	175		2400	-1640	325		
	2800	-1153	226		2800	-1896	493		
	3000	-1270	272		3000	-2065	661		
	.8 fc →	3200	-1421		352	.8 fc →	3200	-2243	955
	fc →	3500	-1777		706	fc →	3500	-2201	1878
	1.1 fc →	4000	- 836		2190	1.1 fc →	4000	- 555	2526
		4400	- 9		1591		4400	+ 5	1858

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 8X (Cont'd)
 19 CNB)
 22 BSA) B135

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.0db	200	-1371	- 678	7.0db	200	-1674	- 953		
	300	-1461	- 424		500	-1894	- 317		
	500	-1511	- 205		1000	-1962	- 36		
	1000	-1550	0		1500	-2043	+ 128		
	1500	-1608	+ 130		2000	-2154	274		
	2000	-1701	237		2400	-2301	411		
	2400	-1848	351		2800	-2508	578		
	2600	-1950	424		3000	-2691	694		
	2800	-2066	520		.8 fc →	3200	-2931	883	
	3000	-2215	666		fc →	3500	-3383	1400	
	.8 fc →	3200	-2383		89C	1.1 fc →	4000	-2787	4230
	fc →	3500	-2667		1565		4400	- 323	3677
	1.1 fc →	4000	-1648		3065				
		4400	- 281		2626				
5.5db	200	-1364	- 711						
	500	-1533	- 220						
	1000	-1591	+ 27						
	1500	-1651	101						
	2000	-1771	198						
	2400	-1940	302						
	2800	-2203	460						
	3000	-2400	644						
	.8 fc →	3200	-2593	914					
	fc →	3500	-2718	1778					
	1.1 fc →	4000	-1136	3103					
	4400	- 89	2443						
6.0db	200	-1542	- 809						
	300	-1664	- 497						
	500	-1724	- 223						
	1000	-1767	- 12						
	1500	-1838	+ 118						
	2000	-1954	229						
	2400	-2113	331						
	2600	-2231	394						
	2800	-2384	473						
	3000	-2597	597						
	.8 fc →	3200	-2886	812					
	fc →	3500	-3434	1645					
	1.1 fc →	4000	-1830	4169					
		4400	- 139	3017					
6.5db	200	-1538	- 875						
	500	-1760	- 277						
	1000	-1815	+ 10						
	1500	-1854	68						
	2000	-2030	256						
	2400	-2201	398						
	2800	-2508	653						
	3000	-2674	870						
	.8 fc →	3200	-2843	1236					
	fc →	3500	-2808	2194					
	1.1 fc →	4000	-1121	3215					
		4400	- 112	2647					

TABLE 1
NEGATIVE IMPEDANCE OF NETWORK 9X
19DNB-BL35

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
1.0db	200	- 409	- 134	3.0db	200	-1044	- 455		
	500	- 429	- 24		500	-1127	- 124		
	1000	- 432	+ 19		1000	-1149	+ 26		
	1500	- 448	62		1500	-1171	113		
	2000	- 466	94		2000	-1227	176		
	2400	- 492	120		2400	-1319	235		
	2800	- 531	153		2800	-1465	309		
	3000	- 559	170		3000	-1570	387		
	.8 fc→	3600	- 695		274	.8 fc→	3600	-1952	1022
	fc→	4000	- 806		480	fc→	4000	-1585	1964
1.1 fc→	4500	- 644	999	1.1 fc→	4500	- 426	2081		
	4600	-	-		4600	- 271	1959		
	4900	- 164	996		4900	- 35	1646		
	5000	- 90	942		5000	+ 35	1545		
5600	+ 36	699							
1.5db	200	- 590	- 202	3.5db	200	-1161	- 522		
	500	- 621	- 24		500	-1270	- 125		
	1000	- 626	+ 58		1000	-1276	+ 73		
	1500	- 629	124		1500	-1284	181		
	2000	- 654	172		2000	-1313	260		
	2400	- 697	221		2400	-1404	321		
	2800	- 781	295		2800	-1555	405		
	3000	- 855	354		3000	-1691	484		
	.8 fc→	3600	- 915		931	.8 fc→	3600	-2064	1293
	fc→	4000	- 346		1191	fc→	4000	-1291	2287
1.1 fc→	4500	+ 9	915	1.1 fc→	4500	- 221	2022		
	4600	- 11	834		4600	- 78	1864		
	4900	+ 19	739		4900	+ 40	1537		
	5000	+ 38	701		5000	+ 87	1463		
2.0db	200	- 724	- 276	4.0db	200	-1332	- 642		
	500	- 769	- 66		300	-1423	- 382		
	1000	- 792	+ 29		500	-1451	- 138		
	1500	- 823	107		1000	-1446	+ 111		
	2000	- 871	178		1500	-1441	250		
	2400	- 936	247		2000	-1471	334		
	2800	-1029	342		2400	-1553	393		
	3000	-1109	423		2800	-1782	500		
	.8 fc→	3600	-1265		1074	3000	-1962	636	
	fc→	4000	- 519		1639	.8 fc→	3500	-2349	1782
1.1 fc→	4500	+ 61	1154	1.1 fc→	3600	-2186	2171		
	4600	+ 40	1054		4000	- 559	2593		
	4900	+ 78	916		4600	+ 60	1630		
	5000	+ 76	875		4900	+ 80	1413		
5000	+ 96	1315							
2.5db	200	- 872	- 364	4.5db	200	-1359	- 687		
	500	- 935	- 113		300	-1448	- 431		
	1000	- 970	+ 8		500	-1501	- 207		
	1500	-1004	69		1000	-1530	0		
	2000	-1073	134		1500	-1576	+ 118		
	2400	-1140	196		2000	-1661	212		
	2800	-1241	285		2400	-1778	295		
	3000	-1305	346		2800	-1970	425		
	.8 fc→	3600	-1547		672	3000	-2102	538	
	fc→	4000	-1598		1236	.8 fc→	3500	-2563	1040
1.1 fc→	4500	- 815	2052	1.1 fc→	3600	-2552	1314		
	4600	- 573	2053		4000	-2072	2524		
	4900	- 53	1753		4600	- 247	2496		
	5000	+ 49	1601		4900	+ 51	2050		
5000	+ 127	1912							

TABLE 1

 NEGATIVE IMPEDANCE OF NETWORK 9X (Cont'd)
 19DNB-BL35

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	
5.0db	200	-1430	- 785	
	300	-1552	- 498	
	500	-1619	- 257	
	1000	-1684	+ 50	
	1500	-1772	70	
	2000	-1902	201	
	2400	-2066	334	
	2800	-2244	570	
	3000	-2344	717	
	.8 fc →	3600	-2493	1611
		4000	-1985	2473
	1.1 fc →	4600	- 527	2677
		4900	- 101	2293
	5000	-	-	
5.5db	200	-1504	- 836	
	500	-1744	- 298	
	1000	-1804	- 73	
	1500	-1878	+ 22	
	2000	-2002	120	
	2400	-2146	207	
	2500	-2197	237	
	2800	-2355	360	
	3000	-2517	450	
	.8 fc →	3600	-2979	1169
		4000	-	-
	1.1 fc →	4600	-1091	3440
		4900	- 282	3001
	5000	- 43	2850	
6.0 db	200	-1597	- 935	
	500	-1876	- 295	
	1000	-1921	+ 40	
	1500	-1970	103	
	2000	-2049	215	
	2400	-2164	304	
	2800	-2333	404	
	3000	-2455	482	
	.8 fc →	3600	-3125	962
		4000	-3395	2426
	1.1 fc →	4600	- 288	3712
		4900	+ 277	2778
		5000	+ 313	2490

TABLE 1

 NEGATIVE IMPEDANCE OF NETWORK 10X
 19CNE)
 22BSA)D135

Gain	F	R	X	Gain	F	R	X		
1.0db	200	- 286	- 97	3.0db	200	- 734	- 285		
	300	- 296	- 58		300	- 759	- 178		
	500	- 303	- 17		500	- 780	- 90		
	1000	- 320	+ 16		1000	- 830	+ 6		
	1500	- 346	56		1500	- 917	83		
	2000	- 385	96		2000	-1063	199		
	2500	- 454	163		2500	-1289	475		
	.8 fc →	2600	- 478		186	.8 fc →	2600	-1332	586
		2800	- 519		244		2800	-1389	903
	fc →	3000	- 561		345	fc →	3000	-1254	1327
	1.1 fc →	3200	- 557		502	1.1 fc →	3200	- 768	1622
	3600	- 196	733		3600	- 73	1285		
	4000	- 7	545		4000	+ 30	949		
1.5db	200	- 406	- 140	3.5db	200	- 848	- 340		
	300	- 418	- 86		300	- 883	- 206		
	500	- 429	- 24		500	- 905	- 95		
	1000	- 450	+ 9		1000	- 954	+ 46		
	1500	- 485	60		1500	-1029	153		
	2000	- 546	111		2000	-1163	283		
	2500	- 644	179		2500	-1500	621		
	.8 fc →	2600	- 681		219	.8 fc →	2600	-1585	802
		2800	- 758		290		2800	-1555	1389
	fc →	3000	- 853		448	fc →	3000	- 863	1879
	1.1 fc →	3200	- 861		739	1.1 fc →	3200	- 217	1668
	3600	- 209	1007		3600	- 10	1097		
	4000	+ 7	707		4000	- 2	877		
2.0db	200	- 545	- 184	4.0db	200	- 970	- 398		
	300	- 567	- 108		300	-1016	- 237		
	500	- 579	- 28		500	-1039	- 101		
	1000	- 598	+ 41		1000	-1077	+ 43		
	1500	- 642	102		1500	-1145	147		
	2000	- 733	174		2000	-1263	244		
	2500	- 923	390		2500	-1565	541		
	.8 fc →	2600	- 947		485	.8 fc →	2600	-1744	570
		2800	- 922		776		2800	-1968	961
	fc →	3000	- 671		1068	fc →	3000	-1919	1774
	1.1 fc →	3200	- 313		1116	1.1 fc →	3200	-1127	2358
	3600	- 11	805		3300	- 593	2229		
	4000	+ 39	653		3600	- 113	1678		
2.5db	200	- 688	- 251	4.5db	200	-1047	- 453		
	300	- 713	- 153		300	-1105	- 287		
	500	- 728	- 65		500	-1139	- 139		
	1000	- 757	+ 30		1000	-1195	+ 16		
	1500	- 808	102		1500	-1284	126		
	2000	- 900	188		2000	-1432	270		
	2500	-1063	342		2500	-1705	535		
	.8 fc →	2600	-1111		403	.8 fc →	2600	-1772	634
		2800	-1195		574		2800	-1903	945
	fc →	3000	-1222		856	fc →	3000	-1894	1465
	1.1 fc →	3200	-1039		1247	1.1 fc →	3200	-1413	2090
	3600	- 237	1393		3600	- 252	1910		
	4000	+ 18	967		4000	+ 38	1350		

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 10X (Cont'd)
 19CNB)^{D135}
 22BSA)

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.0db	200	-1261	- 335	7.0db	200	-1427	- 707		
	300	-1207	- 314		300	-1373	- 569		
	500	-1238	- 152		500	-1567	- 211		
	1000	-1291	+ 15		1000	-1629	+ 19		
	1500	-1383	123		1500	-1743	162		
	2000	-1576	236		2000	-1964	311		
	2500	-1999	554		2500	-2508	730		
	.8 fc →	2600	-2127		715	.8 fc →	2600	-2673	934
	2800	-2346	1193		2800	-2894	1596		
	3000	-2197	1979		3000	-2635	2665		
fc →	3200	-1487	2536	fc →	3200	-1679	3220		
3300	-1032	2558	3300	-1160	3187				
1.1 fc →	3600	- 311	2135	1.1 fc →	3600	- 258	2469		
4000	- 64	1584	4000	- 115	1874				
5.5db	200	-1188	- 566	7.5db	200	-1467	- 762		
	300	-1275	- 358		300	-1585	- 461		
	500	-1320	- 189		500	-1641	- 199		
	1000	-1336	+ 25		1000	-1690	+ 70		
	1500	-1510	108		1500	-1782	238		
	2000	-1659	263		2000	-1983	411		
	2500	-2043	567		2500	-2489	910		
	.8 fc →	2600	-2112		671	.8 fc →	2600	-2620	1190
	2800	-2302	1038		2800	-2621	1973		
	3000	-2363	1683		3000	-1934	2791		
fc →	3200	-1845	2550	fc →	3200	- 865	2875		
1.1 fc →	3600	- 226	2304	1.1 fc →	3600	- 36	2000		
4000	+ 90	1552	4000	+ 29	1462				
6.0db	200	-1271	- 597	8.0db	200	-1517	- 773		
	300	-1333	- 375		300	-1637	- 490		
	500	-1375	- 199		500	-1683	- 230		
	1000	-1457	- 17		1000	-1721	+ 20		
	1500	-1584	+ 110		1500	-1805	139		
	2000	-1785	257		2000	-2018	207		
	2500	-2176	569		2500	-2683	406		
	.8 fc →	2600	-2306		710	.8 fc →	2600	-2942	549
	2800	-2548	1090		2800	-3504	1180		
	3000	-2695	1784		3000	-3621	2694		
fc →	3200	-2225	2701	fc →	3200	-2473	3837		
3300	-1741	2958	3300	-1759	3914				
1.1 fc →	3600	- 415	2605	1.1 fc →	3600	- 323	2973		
4000	- 116	1872	4000	- 109	2179				
6.5db	200	-1409	- 692						
	300	-1481	- 391						
	500	-1529	- 153						
	1000	-1563	+ 124						
	1500	-1644	322						
	2000	-1821	571						
	2500	-2094	1252						
	.8 fc →	2600	-2092		1517				
	2800	-1739	2186						
	3000	- 978	2404						
fc →	3200	- 385	2169						
1.1 fc →	3600	- 7	1509						
4000	+ 10	1217							

TABLE 1
NEGATIVE IMPEDANCE OF NETWORK 11X
19DNB-D135

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
1.0db	200	- 317	- 108	3.0db	200	- 882	- 352		
	300	- 325	- 67		300	- 923	- 212		
	500	- 332	- 25		500	- 939	- 81		
	1000	- 348	+ 11		1000	- 961	+ 24		
	1500	- 372	48		1500	- 992	102		
	2000	- 410	83		2000	-1064	163		
	2500	- 472	130		2500	-1227	237		
	2800	- 525	178		2800	-1429	334		
	2900	- 548	207		2900	-1521	407		
	.8 fc→	3000	- 566		232	.8 fc→	3000	-1629	505
		3200	- 622		302		3200	-1842	880
		3500	- 682		512		3500	-1523	1841
	fc→	3600	- 657		618	fc→	3600	-1187	2057
1.1 fc→	4000	- 252	849	1.1 fc→	4000	- 97	1719		
	4600	+ 20	604		4600	+ 94	1130		
1.5db	200	- 499	- 170	3.5db	200	- 975	- 407		
	300	- 515	- 99		300	-1020	- 243		
	500	- 522	- 28		500	-1036	- 96		
	1000	- 534	+ 45		1000	-1060	+ 53		
	1500	- 557	100		1500	-1091	139		
	2000	- 606	153		2000	-1183	206		
	2500	- 719	252		2500	-1413	331		
	2800	- 822	400		2800	-1666	546		
	2900	- 850	477		2900	-1756	688		
	.8 fc→	3000	- 856		576	.8 fc→	3000	-1817	900
		3200	- 792		834		3200	-1794	1466
		3500	- 400		1039		3500	- 999	2071
	fc→	3600	- 263		1034	fc→	3600	- 695	2026
1.1 fc→	4000	- 6	791	1.1 fc→	4000	- 30	1539		
	4600	+ 39	600		4600	+ 49	1044		
2.0db	200	- 640	- 234	4.0db	200	-1065	- 461		
	300	- 660	- 139		300	-1117	- 293		
	500	- 675	- 56		500	-1145	- 148		
	1000	- 700	+ 28		1000	-1192	+ 11		
	1500	- 735	94		1500	-1275	89		
	2000	- 799	161		2000	-1399	194		
	2500	- 927	255		2500	-1613	376		
	2800	-1056	376		2800	-1791	569		
	2900	-1113	451		2900	-1855	672		
	.8 fc→	3000	-1184		548	.8 fc→	3000	-1938	798
		3200	-1262		871		3200	-2062	1128
		3500	- 792		1517		3500	-1882	1973
	fc→	3600	- 501		1535	fc→	3600	-1630	2251
1.1 fc→	4000	+ 2	1093	1.1 fc→	4000	- 415	2236		
	4600	+ 16	760		4600	- 21	1511		
2.5db	200	- 735	- 275	4.5db	200	-1166	- 534		
	300	- 762	- 166		300	-1241	- 343		
	500	- 779	- 63		500	-1273	- 165		
	1000	- 799	+ 43		1000	-1315	+ 13		
	1500	- 839	115		1500	-1395	108		
	2000	- 922	193		2000	-1523	227		
	2500	-1097	348		2500	-1746	407		
	2800	-1236	592		2800	-1936	586		
	2900	-1243	705		2900	-2019	695		
	.8 fc→	3000	-1255		856	.8 fc→	3000	-2144	822
		3200	-1126		1177		3200	-2308	1267
		3500					3500	-2019	2329
	fc→	3600	- 598		1436	fc→	3600	-1551	2596
1.1 fc→	4000	+ 5	1045	1.1 fc→	4000	- 264	2216		
	4600	+ 15	818		4600	+ 49	1408		

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 11X (Cont'd)
19DNB-D135

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.0db	200	-1276	- 584	7.0db	200	-1540	- 810		
	300	-1347	- 365		300	-1662	- 520		
	500	-1375	- 173		500	-1726	- 265		
	1000	-1407	+ 31		1000	-1793	- 15		
	1500	-1459	136		1500	-1912	+ 151		
	2000	-1561	209		2000	-2114	316		
	2500	-1816	319		2500	-2465	633		
	2800	-2104	462		2800	-2805	1083		
	2900	-2246	566		2900	-2929	1289		
	.8 fc→	3000	-2391		705	.8 fc→	3000	-2997	1624
		3200	-2700		1203		3200	-2918	2370
	fc→	3500	-2508		2655	fc→	3500	-1949	3403
	1.1 fc→	3600	-2084		2925	1.1 fc→	3600	-1431	3395
		4000	- 415		2605		4000	- 313	2687
	4600	- 76	1800		4600	- 81	1932		
5.5db	200	-1308	- 653	7.5db	200	-1595	- 875		
	300	-1396	- 419		300	-1723	- 560		
	500	-1459	- 225		500	-1807	- 273		
	1000	-1537	- 50		1000	-1872	+ 9		
	1500	-1651	+ 73		1500	-1959	169		
	2000	-1831	224		2000	-2144	325		
	2500	-2115	477		2500	-2505	601		
	2800	-2293	760		2800	-2826	1005		
	2900	-2389	916		2900	-3011	1257		
	.8 fc→	3000	-2471		1076	.8 fc→	3000	-3086	1551
		3200	-2522		1559		3200	-2910	2470
	fc→	3500	-2106		2577	fc→	3500	-1520	3451
	1.1 fc→	3600	-1708		2831	1.1 fc→	3600	- 989	3344
		4000	- 211		2489		4000	+ 7	2360
	4600	+ 80	1598		4600	+ 88	1627		
6.0db	200	-1402	- 712	8.0db	200	-1701	- 923		
	300	-1502	- 448		300	-1844	- 583		
	500	-1553	- 234		500	-1906	- 274		
	1000	-1606	- 21		1000	-1949	+ 32		
	1500	-1694	+ 100		1500	-2000	196		
	2000	-1824	204		2000	-2133	304		
	2500	-2079	347		2500	-2488	451		
	2800	-2345	486		2800	-2936	701		
	2900	-2473	567		2900	-3121	851		
	.8 fc→	3000	-2600		668	.8 fc→	3000	-3365	1102
		3200	-3052		995		3200	-3730	1972
	fc→	3500	-3348		2397	fc→	3500	-2897	3845
	1.1 fc→	3600	-3172		2969	1.1 fc→	3600	-2171	4090
		4000	- 811		3506		4000	- 445	3276
	4600	- 153	2238		4600	- 105	2299		
6.5db	200	-1447	- 760						
	300	-1569	- 470						
	500	-1638	- 217						
	1000	-1704	+ 38						
	1500	-1807	214						
	2000	-1983	411						
	2500	-2328	845						
	2800	-2504	1445						
	2900	-2506	1749						
	.8 fc→	3000	-2338		2128				
		3200	-1750		2681				
	fc→	3500	- 503		2587				
	1.1 fc→	3600	- 277		2345				
		4000	+ 64		1742				
	4600	+ 72	1339						

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 12X
 19CNB) HL35
 22BSA)

Gain	F	R	X	Gain	F	R	X		
1.5db	200	- 369	- 114	3.5db	300	- 823	- 165		
	300	- 379	- 58		500	- 827	- 50		
	500	- 390	- 5		1000	- 841	+ 85		
	1000	- 398	+ 51		1500	- 882	149		
	1500	- 458	115		2000	-1064	213		
	2000	- 569	254		.8 fc→	2200	-1239	301	
	.8 fc→	2200	- 593		407	2400	-1441	558	
	2400	- 497	596		2600	-1456	1171		
	2600	- 280	679		fc→	2800	- 868	1644	
	fc→	2800	- 105		604	3000	- 314	1532	
	3000	- 36	519		1.1 fc→	3100	- 161	1389	
	1.1 fc→	3100	- 23		494	3200	- 72	1259	
3200	- 21	456							
2.0db	200	- 461	- 155	4.0db	300	- 887	- 202		
	300	- 477	- 90		500	- 910	- 90		
	500	- 490	- 26		1000	- 961	+ 27		
	1000	- 526	+ 55		1500	-1056	120		
	1500	- 585	138		2000	-1260	227		
	2000	- 710	301		.8 fc→	2200	-1439	331	
	.8 fc→	2200	- 774		459	2400	-1728	595	
	2400	- 710	735		2600	-1907	1319		
	2600	- 385	912		fc→	2800	-1278	2099	
	fc→	2800	- 108		803	3000	- 445	1940	
	3000	- 5	671		1.1 fc→	3100	- 245	1692	
	1.1 fc→	3100	+ 3		622	3200	- 135	1528	
3200	- 30	560							
2.5db	300	- 579	- 121	4.5db	300	- 984	- 230		
	500	- 594	- 56		500	-1013	- 104		
	1000	- 641	+ 25		1000	-1067	+ 43		
	1500	- 724	112		1500	-1184	168		
	2000	- 868	269		2000	-1401	367		
	.8 fc→	2200	- 940		400	.8 fc→	2200	-1521	551
	2400	- 984	605		2400	-1585	910		
	2600	- 862	913		2600	-1382	1530		
	fc→	2800	- 577		1133	fc→	2800	- 830	1768
	3000	- 226	1057		1.1 fc→	3000	- 317	1683	
	1.1 fc→	3100	- 136		981	3100	- 156	1536	
	3200	- 82	889			3200	- 50	1365	
3.0db	300	- 717	- 139	5.0db	200	- 975	- 410		
	500	- 725	- 44		300	-1022	- 252		
	1000	- 747	+ 73		500	-1054	- 113		
	1500	- 812	146		1000	-1117	+ 27		
	2000	-1011	277		1500	-1241	147		
	.8 fc→	2200	-1143		432	2000	-1523	358	
	2400	-1237	785		.8 fc→	2200	-1687	555	
	2600	- 980	1256		2400	-1848	992		
	fc→	2800	- 453		1340	2600	-1640	1675	
	3000	- 169	1137		fc→	2800	- 930	2031	
	1.1 fc→	3100	- 108		1011	3000	- 319	1834	
	3200	- 82	938			3100	- 172	1662	
				3200	- 48	1490			

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 12X (Cont'd)
 19CNB)
 22BSA)H135

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.5db	300	-1105	- 276	7.5db	200	-1301	- 629		
	500	-1147	- 135		300	-1389	- 382		
	1000	-1211	+ 20		500	-1439	- 166		
	1500	-1334	136		1000	-1514	+ 60		
	2000	-1590	256		1500	-1662	246		
	.8 fc→	2200	-1789		365	2000	-1969	573	
		2400	-2127		651	.8 fc→	2200	-2145	856
		2600	-2267		1565		2400	-2225	1401
	fc→	2800	-1199		2531	fc→	2600	-1874	2109
	1.1 fc→	3000	- 224		2165		2800	-1063	2459
	3100	- 78	1864	1.1 fc→	3000	- 408	2192		
	3200	- 10	1646		3100	- 225	1993		
					3200	- 76	1800		
6.0db	200	-1134	- 513	8.0db	200	-1336	- 656		
	300	-1195	- 318		300	-1426	- 406		
	500	-1232	- 139		500	-1470	- 177		
	1000	-1273	+ 32		1000	-1533	+ 48		
	1500	-1360	121		1500	-1661	188		
	2000	-1620	175		2000	-1988	378		
	.8 fc→	2200	-1869		222	.8 fc→	2200	-2322	557
		2400	-2345		424		2400	-2579	1016
		2600	-2946		1399	fc→	2600	-2587	1977
	fc→	2800	-1949		3010		2800	-1628	2813
1.1 fc→	3000	- 470	2650	1.1 fc→	3000	- 581	2639		
	3100	- 192	2285		3100	- 325	2409		
	3200	- 64	1967		3200	- 106	2141		
6.5db	300	-1268	- 320	7.0db	200	-1261	- 604		
	500	-1321	- 121		300	-1332	- 368		
	1000	-1376	+ 84		500	-1381	- 166		
	1500	-1467	238		1000	-1462	+ 46		
	2000	-1832	468		1500	-1600	218		
	.8 fc→	2200	-2021		787	2000	-1885	497	
		2400	-2079		1513	.8 fc→	2200	-2061	737
		2600	-1339		2274		2400	-2212	1230
	fc→	2800	- 443		2157	fc→	2600	-2049	1923
	1.1 fc→	3000	- 77		1714		2800	-1285	2472
	3100	- 25	1578	1.1 fc→	3000	- 506	2286		
	3200	+ 49	1408		3100	- 325	2106		
					3200	- 141	1887		

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 13X
 19DNB-H135

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
1.0db	200	- 261	- 97	3.0db	200	- 737	- 288		
	300	- 268	- 58		300	- 762	- 179		
	500	- 275	- 29		500	- 778	- 90		
	1000	- 300	0		1000	- 815	+ 3		
	1500	- 333	+ 21		1500	- 886	51		
	2000	- 400	51		2000	-1030	105		
	2400	- 490	94		2400	-1264	213		
	.8 fc→	2500	- 525		109	.8 fc→	2500	-1353	273
	2800	- 684	229		2800	-1657	672		
	3000	- 790	477		3000	-1674	1280		
fc→	3200	- 581	877	fc→	3200	-1119	1841		
1.1 fc→	3500	- 70	751	1.1 fc→	3500	- 274	1626		
3600	- 5	665	3600	- 133	1472				
1.5db	200	- 420	- 134	3.5db	200	- 845	- 337		
	300	- 428	- 73		300	- 878	- 201		
	500	- 438	- 16		500	- 895	- 89		
	1000	- 452	+ 39		1000	- 922	+ 15		
	1500	- 502	98		1500	- 983	75		
	2000	- 592	171		2000	-1130	116		
	2400	- 723	368		2400	-1438	216		
	.8 fc→	2500	- 749		466	.8 fc→	2500	-1561	291
	2800	- 571	824		2800	-1967	890		
	3000	- 304	851		3000	-1744	1712		
fc→	3200	- 133	773	fc→	3200	- 902	2073		
1.1 fc→	3500	- 47	625	1.1 fc→	3500	- 144	1625		
3600	- 40	609	3600	- 48	1490				
2.0db	200	- 547	- 188	4.0db	200	- 943	- 381		
	300	- 592	- 171		300	- 982	- 241		
	500	- 580	- 34		500	-1006	- 119		
	1000	- 610	+ 15		1000	-1066	+ 5		
	1500	- 663	87		1500	-1177	109		
	2000	- 754	162		2000	-1368	270		
	2400	- 913	271		2400	-1581	591		
	.8 fc→	2500	- 974		336	.8 fc→	2500	-1618	715
	2800	-1150	747		2800	-1606	1224		
	3000	- 918	1214		3000	-1366	1633		
fc→	3200	- 362	1272	fc→	3200	- 926	1741		
1.1 fc→	3500	- 34	939	1.1 fc→	3500	- 425	1705		
3600	+ 13	845	3600	- 311	1600				
.5db	200	- 701	- 234	4.5db	200	-1026	- 446		
	300	- 724	- 123		300	-1071	- 276		
	500	- 728	- 9		500	-1101	- 139		
	1000	- 723	+ 114		1000	-1150	+ 4		
	1500	- 740	182		1500	-1237	76		
	2000	- 899	249		2000	-1429	141		
	2400	-1229	698		2400	-1798	269		
	.8 fc→	2500	-1178		1025	.8 fc→	2500	-1946	354
	2800	- 345	1274		2800	-2477	1174		
	3000	- 69	1059		3000	-2161	2258		
fc→	3200	- 25	845	fc→	3200	- 934	2615		
1.1 fc→	3500	+ 29	697	1.1 fc→	3500	- 78	1864		
3600	+ 7	671	3600	+ 35	1635				

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 13X (Cont'd)
19DNB-H135

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.0db	200	-1123	- 474	7.0db	200	-	-		
	300	-1158	- 293		300	-1395	- 413		
	500	-1196	- 134		500	-1463	- 234		
	1000	-1230	+ 42		1000	-1566	- 80		
	1500	-1305	134		1500	-1741	+ 23		
	2000	-1505	201		2000	-2040	168		
	2400	-1938	390		2400	-2475	456		
	.8 fc→	2500	-2124		541	.8 fc→	2500	-2613	619
		2800	-2216		1598	2600	-2734	860	
		3000	-1766		2568	2800	-2815	1620	
	3200	- 800	2524	3000	-2316	2705			
	3500	- 199	1945	3200	-1220	3129			
	3600	- 167	1755	3500	- 178	2526			
				3600	-	-			
5.5db	200	-1173	- 543	7.5db	200	-1402	- 738		
	300	-1236	- 337		300	-1501	- 464		
	500	-1270	- 155		500	-1558	- 239		
	1000	-1321	+ 19		1000	-1646	- 31		
	1500	-1402	116		1500	-1796	+ 111		
	2000	-1590	191		2000	-2071	295		
	2400	-1983	276		2400	-2501	638		
	.8 fc→	2500	-2186		352	.8 fc→	2500	-2656	831
		2800	-3021		1316	2800	-2865	1897	
		3000	-2391		2993	3000	-2289	2854	
	3200	- 693	2994	3200	-1153	3115			
	3500	+ 2	1997	3500	- 250	2476			
	3600	+ 36	1778	3600	- 45	2227			
6.0db	200	-	-	8.0db	200	-1504	- 777		
	300	-1311	- 363		300	-1615	- 493		
	500	-1364	- 178		500	-1674	- 242		
	1000	-1421	- 27		1000	-1740	0		
	1500	-1515	+ 43		1500	-1863	+ 122		
	2000	-1755	87		2000	-2170	236		
	2400	-2214	194		2400	-2740	535		
	.8 fc→	2500	-2382		281	.8 fc→	2500	-2956	758
		2600	-2594		421	2800	-3487	2057	
		2800	-3002		1092	3000	-2874	3367	
	3000	-2758	2283	3200	-1604	3690			
	3200	-1512	3121	3500	- 495	2994			
	3500	- 183	2503	3600	- 368	2807			
	3600	- 78	2222						
6.5db	200	-1330	- 641						
	300	-1416	- 387						
	500	-1465	- 156						
	1000	-1499	+ 85						
	1500	-1576	217						
	2000	-1834	344						
	2400	-2413	747						
	.8 fc→	2500	-2580	1049					
		2800	-1984	2716					
		3000	- 808	2805					
	3200	- 166	2249						
	3500	+ 30	1693						
	3600	+ 35	1545						

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 14X
 19DNB-EL75

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
1.0db	200	- 454	- 154	3.0db	200	-1200	- 563		
	500	- 473	- 40		500	-1312	- 146		
	1000	- 482	+ 13		1000	-1336	+ 44		
	1500	- 506	54		1500	-1368	150		
	2000	- 537	82		2000	-1451	243		
	2500	-	-		2500	-1638	369		
	3000	- 705	145		3000	-1973	701		
	.8 fc →	3100	- 741		156	.8 fc →	3100	-2034	824
	fc →	3900	-1192		917	fc →	3500	-2007	1721
	1.1 fc →	4000	-1043		1167	fc →	3900	- 969	2373
1.5db	4300	- 317	1334	1.1 fc →	4000	- 704	2325		
	4600	- 11	1041	4300	- 225	1993			
	200	- 631	- 240	4600	+ 29	1643			
	500	- 671	- 76	3.5db	200	-1341	- 647		
	1000	- 702	0		500	-1458	- 210		
	1500	- 755	52		1000	-1504	0		
	2000	- 822	111		1500	-1579	+ 117		
	2500	- 906	161		2000	-1705	234		
	3000	-1086	396		2500	-1925	416		
	.8 fc →	3100	-1134		470	3000	-2250	804	
fc →	3900	- 973	1290		.8 fc →	3100	-2350	912	
1.1 fc →	4000	- 774	1438		fc →	3500	-2482	1807	
4300	- 375	1429	1.1 fc →		3900	-1719	2878		
4600	- 139	1264	4000	-1295	2953				
2.0db	200	- 840	- 330	4300	- 384	2616			
	500	- 891	- 76	4600	- 96	2228			
	1000	- 922	+ 49	4.0db	200	-1404	- 696		
	1500	- 968	142		500	-1546	- 207		
	2000	-1056	250		1000	-1591	+ 22		
	2500	-1205	438		1500	-1652	168		
	3000	-1347	908		2000	-1769	304		
	.8 fc →	3100	-1293		1088	2500	-1972	490	
	fc →	3900	- 106		1324	3000	-2326	894	
	1.1 fc →	4000	- 35		1227	.8 fc →	3100	-2366	1019
4300	+ 37	1018	fc →		3500	-2504	1989		
4600	+ 50	883	1.1 fc →		3900	-1582	2947		
2.5db	200	- 998	- 431	4300	- 458	2633			
	500	-1082	- 135	4600	- 171	2194			
	1000	-1120	+ 10	4.5db	200	-1472	- 814		
	1500	-1182	94		500	-1697	- 245		
	2000	-1262	187		1000	-1790	+ 7		
	2500	-1413	325		1500	-1873	148		
	3000	-1581	601		2000	-2094	314		
	.8 fc →	3100	-1627		695	2500	-2423	634	
	fc →	3900	-1282		1824	3000	-2705	1704	
	1.1 fc →	4000	-1067		1942	.8 fc →	3100	-2612	2013
4300	- 544	1957	fc →		3500	-1273	2955		
4600	- 103	1697	1.1 fc →		3900	- 183	2410		
				4000	- 23	2173			
				4300	+ 107	1798			
				4600	+ 85	1536			

TABLE 1

 NEGATIVE IMPEDANCE OF NETWORK 14X (Cont'd)
 19DNB-BL75

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	
5.0db	200	-1581	- 919	
	500	-1881	- 282	
	1000	-1940	+ 20	
	1500	-2000	172	
	2000	-2120	297	
	2500	-2381	458	
	3000	-2893	917	
	.8 fc →	3100	-3039	1125
		3500	-2814	2864
	fc →	3900	- 671	3388
		4000	- 350	3117
	1.1 fc →	4300	+ 88	2360
		4600	-	
5.5db	200	-1385	-1004	
	500	-1591	- 367	
	1000	-2043	- 110	
	1500	-2184	+ 50	
	2000	-2390	225	
	2500	-2684	516	
	3000	-3040	1151	
	.8 fc →	3100	-3072	1333
		3500	-2577	2537
	fc →	3900	-1388	3514
		4000	- 914	3560
	1.1 fc →	4300	- 318	3182
		4600	+ 359	2682
6.0db	200	-1764	-1071	
	500	-2111	- 382	
	1000	-2221	- 77	
	1500	-2330	+ 98	
	2000	-2510	255	
	2500	-2817	490	
	3000	-3209	1031	
	.8 fc →	3100	-3300	1212
		3500	-3175	2466
	fc →	3900	-1927	3710
		4000	-1395	3791
	1.1 fc →	4300	- 269	3359
		4600	+ 175	2660

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 15X
 19DNB-D175

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
1.0db	200	- 366	- 120	3.0db	200	- 955	- 394		
	300	- 377	- 67		300	-1010	- 237		
	500	- 387	- 20		500	-1039	- 100		
	1000	- 405	+ 37		1000	-1076	+ 38		
	1500	- 433	87		1500	-1134	131		
	2000	- 497	146		2000	-1257	229		
	2200	- 534	187		2200	-1340	276		
	2500	- 618	299		2500	-1579	415		
	.8 fc →	2600	- 645		374	.8 fc →	2600	-1681	516
	fc →	2800	- 629		582	fc →	2800	-1932	935
1.1 fc →	3000	- 408	791	fc →	3000	-1787	1773		
	3200	- 168	749	1.1 fc →	3200	- 843	2310		
1.5db	3500	- 6	597	1.1 fc →	3500	- 32	1768		
	4000	+ 5	447	4000	+ 101	1107			
	1.5db	200	- 452	- 189	3.5db	200	-1116	- 483	
		300	- 525	- 128		300	-1188	- 275	
		500	- 570	- 39		500	-1219	- 81	
		1000	- 590	+ 42		1000	-1223	+ 124	
		1500	- 582	101		1500	-1245	247	
		2000	- 682	176		2000	-1386	347	
		2200	- 792	230		2200	-1512	434	
		2500	- 923	391		2500	-1806	776	
.8 fc →		2600	- 963	490		.8 fc →	2600	-1888	1020
fc →		2800	- 929	767		fc →	2800	-1650	1785
1.1 fc →	3000	- 675	1083	fc →	3000	- 914	2176		
	3200	- 310	1127	1.1 fc →	3200	- 242	1899		
2.0db	3500	- 27	885	1.1 fc →	3500	+ 14	1391		
	4000	+ 32	644	4000	+ 84	1037			
	2.0db	200	- 721	- 255	4.0db	200	-1181	- 531	
		300	- 756	- 138		300	-1241	- 341	
		500	- 769	- 24		500	-1279	- 172	
		1000	- 767	+ 102		1000	-1366	+ 12	
		1500	- 784	178		1500	-1518	186	
		2000	- 883	242		2000	-1689	420	
		2200	- 983	306		2200	-1800	586	
		2500	-1209	580		2500	-1922	926	
.8fc →		2600	-1221	805		.8 fc →	2600	-1966	1079
fc →		2800	- 942	1292		fc →	2800	-1950	1459
1.1 fc →	3000	- 452	1321	fc →	3000	-1743	1942		
	3200	- 93	1157	1.1 fc →	3200	-1231	2293		
2.5db	3500	+ 4	860	1.1 fc →	3500	- 344	2120		
	4000	+ 45	681	4000	- 67	1456			
	2.5db	200	- 874	- 338	4.5db	200	-1313	- 615	
		300	- 918	- 190		300	-1387	- 361	
		500	- 938	- 56		500	-1433	- 163	
		1000	- 943	+ 83		1000	-1479	+ 99	
		1500	- 960	160		1500	-1543	272	
		2000	-1075	210		2000	-1831	521	
		2200	-1175	250		2200	-1931	721	
		2500	-1425	417		2500	-2232	1415	
.8 fc →		2600	-1530	555		.8 fc →	2600	-2053	1874
fc →		2800	-1609	1083		fc →	2800	-1207	2468
1.1 fc →	3000	-1205	1699	fc →	3000	- 419	2244		
	3200	- 538	1802	1.1 fc →	3200	- 16	1829		
1.1 fc →	3500	- 43	1373	1.1 fc →	3500	- 9	1395		
	4000	+ 68	960	4000	+ 82	1122			

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 15X (Cont'd)
 19DNB-D175

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>		
5.0db	200	-1419	- 695	7.0db	200	-1736	-1052		
	300	-1506	- 437		300	-1913	- 652		
	500	-1553	- 210		500	-1995	- 299		
	1000	-1616	+ 37		1000	-2072	+ 37		
	1500	-1735	200		1500	-2202	252		
	2000	-1959	379		2000	-2489	493		
	2200	-2102	490		2200	-2682	646		
	2500	-2404	925		2500	-3121	1209		
	.8 fc →	2600	-2562		1096	.8 fc →	2600	-3255	1528
		2800	-2706		1756		2800	-3245	2550
	3000	-2342	2639		3000	-2290	3505		
fc →	3200	-1366	3073	fc →	3200	-1043	3524		
1.1 fc →	3500	- 374	2536	1.1 fc →	3500	- 158	2690		
	4000	- 117	1802		4000	+ 31	1862		
5.5db	200	-1508	- 792	7.5db	200	-1746	-1064		
	300	-1622	- 493		300	-1944	- 669		
	500	-1690	- 232		500	-2032	- 308		
	1000	-1752	+ 55		1000	-2100	+ 43		
	1500	-1859	240		1500	-2212	237		
	2000	-2056	448		2000	-2481	419		
	2200	-2167	575		2200	-2683	537		
	2500	-2409	928		2500	-3188	951		
	.8 fc →	2600	-2494		1074	.8 fc →	2600	-3386	1258
		2800	-2877		1833		2800	-3584	2326
	3000	-2345	2320		3000	-2810	3625		
fc →	3200	-1520	2853	fc →	3200	-	-		
1.1 fc →	3500	- 418	2555	1.1 fc →	3500	- 139	2941		
	4000	+ 50	1719		4000	+ 120	1914		
6.0db	200	-1575	- 853	8.0db	200	-1821	-1108		
	300	-1703	- 547		300	-2026	- 702		
	500	-1769	- 277		500	-2125	- 338		
	1000	-1850	- 16		1000	-2218	+ 27		
	1500	-1983	+ 157		1500	-2371	248		
	2000	-2217	320		2000	-2766	514		
	2200	-2379	417		2200	-3085	746		
	2500	-2793	707		2500	-3614	1567		
	.8 fc →	2600	-2972		861	.8 fc →	2600	-3702	2136
		2800	-3349		1432		2800	-3310	3270
	3000	-3439	2641		3000	-2131	3943		
fc →	3200	-2544	3698	fc →	3200	-1121	3753		
1.1 fc →	3500	- 672	3371	1.1 fc →	3500	- 363	2897		
	4000	- 118	2281		4000	- 154	2263		
6.5db	200	-1370	- 893						
	300	-1697	- 628						
	500	-1840	- 307						
	1000	-1940	+ 23						
	1500	-2101	202						
	2000	-2381	470						
	2200	-2563	632						
	2500	-2880	1142						
	.8 fc →	2600	-2959		1410				
		2800	-2944		2232				
	3000	-2256	3110						
fc →	3200	-1194	3293						
1.1 fc →	3500	- 199	2597						
	4000	+ 68	1763						

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 16X
 19DNB-H175

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>
1.0db	200	- 307	- 105	3.5db	200	- 967	- 383
	500	- 325	- 31		500	-1044	- 74
	1000	- 350	+ 10		1000	-1075	+ 91
	1500	- 389	45		1500	-1153	190
	2000	- 467	88		2000	-1458	358
.8 fc→	2200	- 514	115	.8 fc→	2200	-1682	599
	2400	- 582	162		2400	-1804	1235
fc→	2800	- 718	508	fc→	2800	- 410	1798
1.1 fc→	3000	- 521	813	1.1 fc→	3000	- 96	1461
	3200	- 176	807		3200	- 30	1207
1.5db	200	- 457	- 158	4.0db	200	-1103	- 475
	500	- 487	- 45		500	-1192	- 113
	1000	- 520	+ 13		1000	-1249	+ 94
	1500	- 580	62		1500	-1350	265
	2000	- 694	136		2000	-1578	507
.8 fc→	2200	- 768	190	.8 fc→	2200	-1737	703
	2400	- 857	298		2400	-1896	1185
fc→	2800	- 873	857	fc→	2800	- 846	2218
1.1 fc→	3000	- 524	1068	1.1 fc→	3000	- 275	1850
	3200	- 182	1010		3200	- 85	1496
2.0db	200	- 606	- 214	4.5db	200	-1185	- 545
	500	- 645	- 50		300	-1282	- 323
	1000	- 692	+ 64		500	-1326	- 113
	1500	- 795	182		1000	-1371	+ 116
	2000	- 926	408		1500	-1457	287
.8 fc→	2200	- 956	621	.8 fc→	2000	-1791	565
	2400	- 845	902		2200	-1960	919
fc→	2800	- 293	1099	fc→	2400	-1903	1653
1.1 fc→	3000	- 79	871	1.1 fc→	2800	- 408	2064
	3200	- 30	739		3000	- 80	1673
					3200	+ 14	1391
2.5db	200	- 736	- 273	5.0db	200	-1294	- 607
	500	- 784	- 62		500	-1411	- 160
	1000	- 830	+ 59		1000	-1458	+ 61
	1500	- 912	146		1500	-1559	184
	2000	-1127	344		2000	-1870	316
.8 fc→	2200	-1235	541	.8 fc→	2200	-2151	459
	2400	-1236	878		2400	-2574	894
fc→	2800	- 486	1376	fc→	2800	-1878	2922
1.1 fc→	3000	- 179	1201	1.1 fc→	3000	- 722	2813
	3200	- 83	1023		3200	- 183	2201
3.0db	200	- 842	- 334	5.5db	200	-1347	- 671
	500	- 907	- 101		300	-1456	- 407
	1000	- 952	+ 33		500	-1506	- 171
	1500	-1042	106		1000	-1548	+ 76
	2000	-1253	200		1500	-1634	211
.8 fc→	2200	-1453	291		2000	-1921	353
	2400	-1738	526	.8 fc→	2200	-2158	490
fc→	2800	-1090	2025		2400	-2193	873
1.1 fc→	3000	- 327	1858	fc→	2800	-1598	2814
	3200	- 50	1417	1.1 fc→	3000	- 397	2769
					3200	- 206	2272

TABLE 1

NEGATIVE IMPEDANCE OF NETWORK 16X (Cont'd)
19DNB-H175

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	
6.0db	200	-1411	- 707	
	300	-1511	- 440	
	500	-1554	- 203	
	1000	-1602	+ 35	
	1500	-1733	142	
	2000	-2132	242	
	.8 fc →	2200	-2493	400
		2400	-3024	902
	fc →	2800	-2133	3384
	1.1 fc →	3000	- 818	3140
		3200	- 269	2524
	6.5db	200	-1470	- 751
		300	-1575	- 448
500		-1641	- 185	
1000		-1684	+ 100	
1500		-1813	249	
2000		-2266	537	
.8 fc →		2200	-2581	919
		2400	-2689	1740
fc →		2800	- 870	2743
1.1 fc →		3000	- 304	2322
		3200	- 89	1891
7.0db		200	-1733	- 943
		300	-1719	- 505
	500	-1778	- 190	
	1000	-1821	+ 126	
	1500	-1936	303	
	2000	-2393	593	
	.8 fc →	2200	-2722	978
		2400	-2891	1874
	fc →	2800	- 823	2973
	1.1 fc →	3000	- 220	2392
		3200	- 8	1951
	7.5db	200	-1591	- 918
		300	-1728	- 552
500		-1813	- 249	
1000		-1877	+ 47	
1500		-2001	194	
2000		-2414	325	
.8 fc →		2200	-2780	493
		2400	-3318	1034
fc →		2800	-1964	3801
1.1 fc →		3000	-567	3280
		3200	- 148	2660
8.0db		200	-1640	- 942
		300	-1818	- 575
	500	-1916	- 235	
	1000	-1989	+ 110	
	1500	-2137	321	
	2000	-2645	692	
	.8 fc →	2200	-2900	1153
		2400	-2852	2186
	fc →	2800	- 704	2999
	1.1 fc →	3000	- 226	2467
		3200	- 19	2010

SECTION 852-305-104

TABLE 1
NEGATIVE IMPEDANCE OF NETWORK 17X
19CNB-H44

Gain	F	R	X	Gain	F	R	X		
2.5db	200	- 345	- 115	4.0db	200	- 496	- 176		
	300	- 355	- 61		300	- 509	- 106		
	500	- 358	- 6		500	- 514	- 40		
	1000	- 362	+ 12		1000	- 523	+ 14		
	1500	- 369	+ 70		1500	- 539	+ 65		
	2000	- 381	+ 117		2000	- 563	+ 105		
	2500	- 392	+ 150		2500	- 593	+ 140		
	2800	- 401	+ 173		2800	- 622	+ 166		
	3000	- 411	+ 188		3000	- 644	+ 185		
	3200	- 422	+ 202		3200	- 671	+ 206		
	3400	- 437	+ 219		3400	- 702	+ 230		
	3600	- 456	+ 232		3600	- 744	+ 262		
	3800	- 486	+ 246		3800	- 783	+ 299		
	0.8 fc	4000	- 530		+ 262	0.8 fc	4000	- 842	+ 354
		4200	- 602		+ 292		4200	- 922	+ 443
4500		- 781	+ 415	4500	-1019		+ 639		
4800		- 936	+ 910	4800	-1089		+ 901		
fc	5000	- 378	+1276	fc	5000	- 819	+1280		
	5200	+ 34	+1017		5200	- 483	+1400		
1.1 fc	5500	+ 86	+ 818	1.1 fc	5500	- 95	+1265		
3.0db	200	- 406	- 137	4.5db	200	- 555	- 202		
	300	- 418	- 76		300	- 565	- 115		
	500	- 421	- 15		500	- 572	- 44		
	1000	- 428	+ 38		1000	- 582	+ 29		
	1500	- 436	+ 91		1500	- 602	+ 76		
	2000	- 453	+ 137		2000	- 631	+ 123		
	2500	- 472	+ 178		2500	- 672	+ 169		
	2800	- 497	+ 210		2800	- 704	+ 206		
	3000	- 521	+ 238		3000	- 737	+ 236		
	3200	- 543	+ 261		3200	- 772	+ 270		
	3400	- 578	+ 302		3400	- 811	+ 315		
	3600	- 629	+ 363		3600	- 856	+ 374		
	3800	- 681	+ 447		3800	- 919	+ 458		
	0.8 fc	4000	- 700		+ 565	0.8 fc	4000	- 979	+ 588
		4200	- 664		+ 793		4200	- 993	+ 781
4500		- 392	+1011	4500	- 974		+ 989		
4800		- 122	+ 958	4800	- 661		+1244		
fc	5000	- 6	+ 827	fc	5000	- 411	+1253		
	5200	+ 2	+ 727		5200	- 214	+1158		
1.1 fc	5500	+ 21	+ 649	1.1 fc	5500	- 91	+ 987		
3.5db	200	- 460	- 162	5.0db	200	- 587	- 211		
	300	- 476	- 93		300	- 602	- 129		
	500	- 481	- 27		500	- 612	- 41		
	1000	- 486	+ 30		1000	- 624	+ 20		
	1500	- 494	+ 77		1500	- 643	+ 63		
	2000	- 504	+ 116		2000	- 671	+ 113		
	2500	- 523	+ 148		2500	- 710	+ 161		
	2800	- 542	+ 170		2800	- 742	+ 194		
	3000	- 557	+ 183		3000	- 771	+ 222		
	3200	- 581	+ 199		3200	- 802	+ 253		
	3400	- 605	+ 214		3400	- 832	+ 290		
	3600	- 646	+ 235		3600	- 876	+ 340		
	3800	- 681	+ 249		3800	- 929	+ 404		
	0.8 fc	4000	- 725		+ 265	0.8 fc	4000	- 968	+ 462
		4200	- 844		+ 359		4200	-1020	+ 615
4500		- 977	+ 567	4500	-1059		+ 830		
4800		-1014	+1021	4800	-1004		+1115		
fc	5000	- 604	+1446	fc	5000	- 772	+1369		
	5200	- 163	+1384		5200	- 468	+1474		
1.1 fc	5500	+ 80	+1177	1.1 fc	5500	- 197	+1397		

TABLE 1
 NEGATIVE IMPEDANCE OF NETWORK 17X (Cont'd)
 19CNB-H44

<u>Gain</u>	<u>F</u>	<u>R</u>	<u>X</u>	
5.5db	200	- 627	- 233	
	300	- 656	- 139	
	500	- 664	- 53	
	1000	- 686	0	
	1500	- 700	+ 53	
	2000	- 733	+ 108	
	2500	- 772	+ 154	
	2800	- 809	+ 191	
	3000	- 831	+ 217	
	3200	- 863	+ 247	
	3400	- 902	+ 284	
	3600	- 943	+ 325	
	3800	-1000	+ 342	
	0.8 fc	4000	-1055	+ 445
		4200	-1130	+ 548
4500		-1236	+ 766	
fc	4800	-1297	+1152	
	5000	-1136	+1578	
1.1 fc	5200	- 646	+1831	
	5500	- 86	+1685	

TABLE 2
 NEGATIVE IMPEDANCE AT 1 KC FOR OTHER SECTIONS (1X AND 2X)
 (USING STRAPPING CHARTS)

Net No.	Sec.	1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
1X 19 CMB-888	.3			-440	0	-583	-12	-700	-28	-881	-43	
	.4			-440	0	-588	+12	-688	-4	-852	+3	
	.6			-442	45	-585	61	-686	+39	-855	68	
	.7			-438	66	-583	80	-687	67	-852	87	
	.8			-434	87	-577	109	-681	93	-843	127	
	.9			-429	99	-566	134	-673	119	-833	167	
	1.0			-422	112	-562	151	-666	141	-832	187	
	1.1			-413	131	-548	172	-656	164	-807	217	
	1.2			-403	145	-537	184	-641	188	-799	236	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	-920	-19	-1187	-278	-1121	-59	-1202	-115	-1360	-23
	.4	-915	+7	-1039	+18	-1108	-45	-1153	-43	-1320	0	
	.6	-908	69	-1035	90	-1111	+27	-1150	+18	-1314	117	
	.7	-909	97	-1026	147	-1109	83	-1150	77	-1310	159	
	.8	-898	146	-1016	178	-1102	122	-1148	113	-1285	239	
	.9	-883	190	-998	232	-1094	164	-1142	154	-1268	286	
	1.0	-872	209	-981	254	-1085	198	-1124	208	-1241	331	
	1.1	-854	247	-969	280	-1073	245	-1106	246	-1212	382	
	1.2	-841	265	-940	333	-1059	276	-1085	280	-1181	411	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1384	-64	-1491	-79	-1599	-132	-1705	-152	-1855	-150	
	.4	-1377	-13	-1465	-6	-1580	-72	-1615	-93	-1695	-80	
	.6	-1369	+124	-1459	+127	-1584	+58	-1621	+39	-1699	+60	
	.7	-1357	190	-1445	199	-1578	118	-1612	114	-1692	135	
	.8	-1339	241	-1429	266	-1565	193	-1609	161	-1680	189	
	.9	-1298	330	-1402	320	-1545	245	-1587	246	-1667	255	
	1.0	-1287	369	-1372	377	-1524	302	-1572	296	-1646	322	
	1.1	-1237	421	-1339	423	-1495	355	-1543	364	-1619	383	
	1.2	-1206	470	-1301	475	-1460	416	-1506	423	-1581	438	
		1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
2X 19 DMB-888	.3			-490	0	-645	0	-800	-21	-990	-28	
	.4			-487	11	-633	19	-778	-8	-933	+26	
	.6			-484	53	-630	67	-779	+32	-928	103	
	.7			-482	72	-624	102	-777	52	-922	126	
	.8			-477	90	-620	124	-779	72	-913	149	
	.9			-473	106	-608	154	-772	102	-897	194	
	1.0			-464	121	-595	172	-768	119	-888	212	
	1.1			-457	139	-583	190	-758	150	-864	256	
	1.2			-446	150	-566	210	-751	167	-853	277	
			3.5db GAIN		4.0db GAIN		4.5 db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	-1050	-25	-1140	0	-1223	-89	-1352	-92	-1494	-111
	.4	-1045	+22	-1138	38	-1246	-63	-1329	-55	-1475	-69	
	.6	-1042	86	-1129	115	-1251	+23	-1330	+36	-1475	+43	
	.7	-1042	86	-1129	115	-1248	63	-1328	80	-1474	97	
	.8	-1034	149	-1114	184	-1241	116	-1321	133	-1467	148	
	.9	-1011	206	-1114	184	-1234	153	-1314	172	-1455	195	
	1.0	-1011	206	-1086	247	-1223	202	-1301	211	-1434	261	
	1.1	-988	257	-1050	313	-1211	235	-1285	257	-1409	311	
	1.2	-988	257	-1050	313	-1193	276	-1265	299	-1388	371	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1552	-68	-1632	-67	-1724	-57	-1805	-18	-1904	-106	
	.4	-1558	-49	-1630	-13	-1731	-44	-1820	-17	-1918	0	
	.6	-1557	+68	-1625	+107	-1727	+115	-1815	+121	-1912	97	
	.7	-1552	131	-1620	165	-1721	160	-1804	192	-1912	97	
	.8	-1541	177	-1610	208	-1705	228	-1790	231	-1893	207	
	.9	-1529	232	-1588	286	-1687	288	-1767	310	-1893	207	
	1.0	-1509	281	-1564	335	-1666	349	-1736	380	-1865	302	
	1.1	-1485	337	-1540	386	-1622	428	-1722	412	-1825	399	
	1.2	-1458	391	-1501	447	-1606	444	-1666	495	-1825	399	

TABLE 2
 NEGATIVE IMPEDANCE AT 1 KC FOR OTHER SECTIONS (5X AND 6X)
 (USING STRAPPING CHARTS)

Net No.	Sec.	1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
5X 19 GNB-H88	.3			- 361	- 39	- 420	- 21	- 608	- 21	- 632	- 61	
	.4			- 338	- 11	- 415	0	- 505	+ 3	- 616	+ 20	
	.6			- 337	+ 48	- 415	43	- 502	64	- 614	92	
	.7			- 333	68	- 417	73	- 492	94	- 605	128	
	.8			- 328	83	- 409	86	- 486	115	- 590	163	
	.9			- 318	101	- 401	109	- 471	143	- 571	190	
	1.0			- 311	113	- 393	124	- 458	164	- 557	212	
	1.1			- 299	126	- 386	136	- 440	183	- 539	234	
	1.2			- 290	136	- 368	158	- 423	201	- 509	254	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	- 710	- 33	- 750	- 14	- 851	- 60	- 941	- 52	- 951	- 58
	.4	- 702	- 3	- 754	- 9	- 837	0	- 931	- 16	- 941	- 10	
	.6	- 702	+ 72	- 752	+ 78	- 828	102	- 931	+ 77	- 937	+ 97	
	.7	- 692	112	- 743	123	- 818	156	- 919	126	- 925	147	
	.8	- 677	150	- 732	154	- 801	192	- 898	196	- 902	205	
	.9	- 664	185	- 709	195	- 783	224	- 877	236	- 880	250	
	1.0	- 640	219	- 685	230	- 744	284	- 848	280	- 855	289	
	1.1	- 618	245	- 664	262	- 724	306	- 822	312	- 831	323	
	1.2	- 593	272	- 631	288	- 697	332	- 795	340	- 797	348	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1022	- 86	-1103	-142	-1155	-129	-1203	-150	-1304	-219	
	.4	-1031	- 33	-1073	- 61	-1138	- 79	-1181	- 37	-1253	- 82	
	.6	-1027	+ 83	-1076	+ 76	-1142	+ 99	-1167	+ 93	-1247	+ 61	
	.7	-1021	154	-1066	139	-1126	168	-1149	157	-1227	142	
	.8	-1001	207	-1047	203	-1120	202	-1133	216	-1216	199	
	.9	- 974	256	-1019	264	-1082	271	-1097	291	-1194	257	
	1.0	- 948	304	- 990	314	-1051	321	-1062	350	-1166	322	
	1.1	- 914	345	- 957	361	-1017	377	-1018	396	-1122	389	
	1.2	- 873	377	- 915	399	- 966	421	- 969	446	-1097	417	
6X 19 DNB-H88		1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
		.3			- 371	- 2	- 454	- 4	- 551	- 31	- 700	- 21
		.4			- 379	0	- 454	- 2	- 557	0	- 695	0
		.6			- 380	45	- 456	+ 33	- 555	60	- 687	86
		.7			- 376	64	- 454	55	- 549	93	- 680	122
		.8			- 370	82	- 452	79	- 539	126	- 670	147
		.9			- 362	91	- 446	99	- 529	154	- 651	182
		1.0			- 354	110	- 435	117	- 507	176	- 631	210
		1.1			- 341	125	- 428	133	- 486	199	- 610	239
		1.2			- 335	137	- 416	150	- 468	211	- 586	264
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
		R	X	R	X	R	X	R	X	R	X	
	.3	- 762	- 59	- 901	- 65	- 955	-143	-1053	-128	-1105	-162	
	.4	- 752	- 33	- 870	+ 8	- 922	- 33	-1017	- 29	-1052	- 52	
	.6	- 759	+ 68	- 869	88	- 925	+ 63	-1016	+ 78	-1050	+ 83	
	.7	- 757	98	- 860	133	- 917	110	-1011	126	-1045	119	
	.8	- 743	145	- 838	191	- 916	151	- 998	170	-1032	171	
	.9	- 730	171	- 820	224	- 891	210	- 977	223	-1019	211	
	1.0	- 709	212	- 797	257	- 867	250	- 953	276	-1000	251	
	1.1	- 689	236	- 766	290	- 867	250	- 923	316	- 960	313	
	1.2	- 663	267	- 752	310	- 845	290	- 889	358	- 960	313	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1182	- 95	-1206	- 45	-1282	- 95	-1471	-458	-1418	-236	
	.4	-1160	+ 18	-1210	+ 10	-1261	- 23	-1306	-142	-1385	- 45	
	.6	-1147	148	-1216	98	-1249	+131	-1287	+ 87	-1375	+136	
	.7	-1132	204	-1202	164	-1241	176	-1273	168	-1360	189	
	.8	-1106	256	-1181	225	-1224	248	-1262	214	-1338	246	
	.9	-1069	325	-1162	282	-1197	302	-1243	266	-1309	317	
	1.0	-1034	378	-1137	336	-1164	359	-1220	313	-1274	383	
	1.1	- 987	423	-1118	356	-1155	389	-1186	362	-1236	439	
	1.2	- 937	464	-1068	417	-1095	443	-1163	402	-1199	472	

TABLE 2

NEGATIVE IMPEDANCE AT 1 KC FOR OTHER SECTIONS (7X AND 8X)
(USING STRAPPING CHARTS)

Est. No.	Sec.	1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
7X 19 DMB-M88	.3			- 301	- 35	- 400	- 28	- 500	0	- 580	- 20	
	.4			- 295	+ 7	- 380	+ 8	- 495	22	- 551	+ 24	
	.6			- 294	42	- 380	51	- 483	100	- 538	107	
	.7			- 291	60	- 375	72	- 466	135	- 530	139	
	.8			- 285	77	- 369	92	- 448	163	- 507	178	
	.9			- 279	91	- 359	112	- 434	179	- 488	199	
	1.0			- 273	106	- 350	127	- 409	204	- 472	218	
	1.1			- 262	116	- 336	142	- 384	221	- 440	243	
	1.2					- 323	159	- 363	236	- 407	262	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	- 701	- 50	- 700	- 12	- 780	- 3	- 890	- 18	- 901	- 59
	.4	- 641	+ 27	- 719	+ 24	- 776	+ 20	- 865	+ 12	- 872	- 23	
	.6	- 631	119	- 698	78	- 752	146	- 851	125	- 874	+ 85	
	.7	- 616	158	- 687	120	- 733	194	- 839	164	- 861	139	
	.8	- 595	198	- 667	168	- 701	247	- 813	219	- 843	201	
	.9	- 570	227	- 652	201	- 671	276	- 790	255	- 810	252	
	1.0	- 537	249	- 633	228	- 628	312	- 759	298	- 791	283	
	1.1	- 513	271	- 606	256	- 582	341	- 718	336	- 752	327	
	1.2	- 481	294	- 580	281	- 551	364	- 695	357	- 724	356	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1001	- 56	-1102	-129	-1102	-119	-1185	-189	-1192	- 89	
	.4	- 977	- 8	-1005	- 14	-1053	- 39	-1075	- 37	-1136	- 23	
	.6	- 968	+123	- 998	+105	-1033	+122	-1074	+ 99	-1124	+148	
	.7	- 957	167	- 977	193	-1016	184	-1058	175	-1105	210	
	.8	- 916	260	- 954	242	- 996	243	-1034	238	-1065	290	
	.9	- 893	301	- 913	313	- 965	291	-1004	296	-1027	349	
	1.0	- 856	338	- 880	355	- 932	336	- 970	342	- 982	394	
	1.1	- 826	374	- 846	386	- 901	375	- 910	407	- 922	463	
	1.2	- 788	405	- 788	427	- 864	411	- 868	441	- 870	489	
		1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
8X 19 CMB-B135	.3	- 390	- 2	- 552	- 26	- 711	- 46	- 912	-108	-1012	- 23	
	.4	- 390	+ 6	- 545	- 11	- 709	- 27	- 864	- 21	-1013	0	
	.6	- 388	42	- 547	+ 40	- 713	+ 40	- 865	+ 66	-1004	126	
	.7	- 385	61	- 545	66	- 711	71	- 857	110	- 985	164	
	.8	- 383	76	- 539	95	- 700	113	- 850	150	- 962	242	
	.9	- 378	95	- 533	119	- 693	140	- 836	189	- 940	288	
	1.0	- 371	109	- 520	140	- 683	164	- 818	226	- 907	329	
	1.1	- 366	120	- 514	159	- 663	199	- 799	262	- 925	308	
	1.2	- 356	138	- 500	190	- 650	223	- 783	299	- 898	398	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	-1175	- 90	-1303	- 61	-1400	- 37	-1561	- 77	-1601	- 84
	.4	-1180	- 14	-1307	- 31	-1390	- 18	-1544	- 50	-1592	- 65	
	.6	-1174	+ 97	-1298	+114	-1376	+131	-1544	+ 79	-1591	+ 63	
	.7	-1167	138	-1288	166	-1364	200	-1535	163	-1583	141	
	.8	-1149	211	-1257	252	-1336	281	-1496	277	-1563	230	
	.9	-1133	252	-1241	298	-1304	347	-1474	335	-1533	308	
	1.0	-1095	318	-1192	375	-1264	397	-1450	384	-1486	407	
	1.1	-1055	379	-1163	416	-1228	453	-1411	443	-1458	449	
	1.2	-1028	402	-1129	451	-1171	501	-1370	502	-1412	505	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1803	-163	-1803	-132	-2003	-175					
	.4	-1768	-114	-1806	-119	-1952	-127					
	.6	-1766	+ 72	-1813	+ 72	-1962	+ 71					
	.7	-1755	164	-1802	166	-1948	167					
	.8	-1730	260	-1775	268	-1919	281					
	.9	-1697	343	-1743	354	-1893	367					
	1.0	-1666	424	-1706	435	-1854	454					
	1.1	-1622	502	-1663	509	-1816	534					
	1.2	-1568	563	-1609	580	-1746	615					

TABLE 2
 NEGATIVE IMPEDANCE AT 1 KC FOR OTHER SECTIONS (9X AND 10X)
 (USING STRAPPING CHARTS)

Net No.	Sec.	1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
9X 19 DNB-B135	.3	-450	-10	-640	0	-810	-31	-991	-46	-1156	-29	
	.4	-438	+7	-630	10	-795	0	-971	-24	-1150	-9	
	.6	-434	37	-623	85	-792	72	-973	+54	-1142	+107	
	.7	-433	48	-616	126	-782	123	-970	84	-1136	142	
	.8	-430	75	-603	145	-770	157	-956	135	-1114	215	
	.9	-426	94	-586	181	-753	204	-951	159	-1103	249	
	1.0	-420	108	-562	213	-734	230	-932	209	-1088	281	
	1.1	-415	121	-549	228	-714	258	-911	256	-1054	346	
	1.2	-401	136	-544	254	-664	314	-898	277	-1021	367	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	-1302	-84	-1542	-114	-1511	-78	-1703	-173	-1809	-178
	.4	-1294	-42	-1455	+52	-1534	-70	-1691	-116	-1807	-147	
	.6	-1279	+117	-1422	241	-1532	+51	-1699	+26	-1830	+6	
	.7	-1254	209	-1403	297	-1528	144	-1696	100	-1826	85	
	.8	-1241	253	-1384	351	-1511	218	-1680	177	-1816	149	
	.9	-1220	293	-1320	448	-1486	279	-1654	280	-1803	230	
	1.0	-1179	370	-1288	487	-1457	339	-1626	355	-1782	309	
	1.1	-1151	408	-1207	563	-1422	412	-1590	424	-1752	381	
	1.2	-1124	444	-1165	595	-1381	458	-1553	471	-1710	452	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-2002	-119									
	.4	-1940	-119									
	.6	-1945	+58									
	.7	-1938	142									
	.8	-1919	241									
	.9	-1898	321									
	1.0	-1864	397									
	1.1	-1827	467									
	1.2	-1774	563									
10X 19 CNB-D135		1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
		.3	-322	-13	-570	-6	-610	-9	-780	-5	-831	-30
		.4	-320	+6	-453	0	-604	0	-759	-8	-823	-31
		.6	-324	38	-454	35	-598	81	-756	+79	-829	+83
		.7	-322	57	-450	67	-588	118	-745	124	-821	123
		.8	-319	74	-446	92	-566	162	-728	168	-798	195
		.9	-317	81	-438	110	-546	193	-707	209	-779	229
		1.0	-305	104	-422	135	-525	219	-681	245	-734	285
		1.1	-295	117	-410	154	-499	242	-648	277	-708	305
		1.2	-284	127	-398	177	-473	264	-617	302	-688	335
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
		R	X	R	X	R	X	R	X	R	X	
	.3	-950	-28	-1100	-8	-1211	-80	-1302	-94	-1404	-150	
	.4	-952	0	-1077	-22	-1199	-50	-1285	-66	-1393	-100	
	.6	-931	145	-1071	+110	-1195	+112	-1282	+101	-1399	+86	
	.7	-914	193	-1043	208	-1180	185	-1264	193	-1380	186	
	.8	-869	278	-1013	272	-1145	277	-1241	264	-1353	267	
	.9	-840	318	-983	322	-1109	343	-1199	335	-1326	335	
	1.0	-779	379	-945	368	-1065	403	-1157	409	-1277	408	
	1.1	-745	403	-904	408	-1016	448	-1098	471	-1214	478	
	1.2	-698	429	-838	455	-964	496	-1035	520	-1144	547	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1504	-157	-1602	-113	-1686	-201	-1706	-160	-1700	-6	
	.4	-1446	-116	-1572	-24	-1623	-91	-1700	+10	-1720	-2	
	.6	-1455	+113	-1552	+199	-1627	+143	-1682	189	-1711	+118	
	.7	-1441	171	-1507	333	-1602	230	-1640	333	-1680	232	
	.8	-1415	266	-1445	450	-1563	342	-1599	419	-1632	368	
	.9	-1380	343	-1396	496	-1510	442	-1538	513	-1593	424	
	1.0	-1331	425	-1351	548	-1459	519	-1465	598	-1524	524	
	1.1	-1278	494	-1261	627	-1381	597	-1357	702	-1476	578	
	1.2	-1202	563	-1179	697	-1293	678	-1298	727	-1411	654	

TABLE 2
NEGATIVE IMPEDANCE AT 1 KC FOR OTHER SECTIONS (11X AND 12X)
(USING STRAPPING CHARTS)

Net No.	Sec.	1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
11X 19 DMB-M35	.3	-370	0	-552	-13	-700	-23	-800	-13	-1012	-87	
	.4	-355	2	-541	+14	-705	-3	-802	-3	-971	-23	
	.6	-356	30	-537	79	-701	+95	-797	+82	-962	+92	
	.7	-353	44	-526	109	-690	124	-786	134	-958	149	
	.8	-353	61	-511	145	-678	165	-768	182	-938	192	
	.9	-348	76	-495	169	-658	196	-747	212	-916	235	
	1.0	-343	92	-479	188	-634	227	-722	255	-895	278	
	1.1	-335	105	-461	213	-612	255	-693	286	-865	316	
	1.2	-329	121	-440	231	-588	279	-673	314	-831	353	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	-1102	-83	-1203	-104	-1324	-125	-1422	-90	-1516	-174
	.4	-1060	-12	-1188	-53	-1318	-73	-1402	-52	-1530	-137	
	.6	-1051	+118	-1191	+77	-1314	+110	-1394	+133	-1541	+32	
	.7	-1038	177	-1187	115	-1303	167	-1380	185	-1531	131	
	.8	-1015	236	-1167	194	-1286	238	-1361	246	-1513	207	
	.9	-987	291	-1140	269	-1254	309	-1337	327	-1477	307	
	1.0	-953	340	-1122	308	-1218	374	-1297	389	-1449	371	
	1.1	-918	382	-1079	370	-1175	428	-1260	448	-1410	430	
	1.2	-874	418	-1054	398	-1118	489	-1190	519	-1358	504	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1683	-151	-	-	-1807	-193	-1907	-202	-2000	-24	
	.4	-1601	-92	-1703	-127	-1788	-110	-1873	-82	-1945	-58	
	.6	-1604	+59	-1699	+134	-1792	+120	-1877	+134	-1938	+165	
	.7	-1598	153	-1682	215	-1777	194	-1846	246	-1910	280	
	.8	-1565	273	-1628	372	-1732	349	-1791	410	-1855	402	
	.9	-1540	339	-1593	445	-1695	423	-1750	490	-1814	504	
	1.0	-1515	399	-1549	509	-1643	519	-1704	556	-1764	582	
	1.1	-1476	464	-1503	562	-1581	598	-1635	632	-1711	654	
	1.2	-1430	517	-1453	618	-1516	654	-1571	701	-1628	715	
12X 19 CMB-M35		1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
		.3			-416	-3	-531	-34	-635	-60	-790	-34
		.4			-416	+10	-530	0	-637	-25	-755	+9
		.6			-403	94	-517	97	-639	+90	-741	136
		.7			-389	124	-498	143	-627	129	-716	192
		.8			-371	146	-477	177	-604	177	-682	240
		.9			-349	170	-446	211	-580	212	-646	281
		1.0			-324	187	-420	231	-565	229	-611	315
		1.1			-298	202	-389	248	-508	267	-567	339
		1.2			-	-	-369	259	-485	292	-525	358
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
		R	X	R	X	R	X	R	X	R	X	
	.3	-901	-59	-1003	-122	-1093	-91	-1100	-27	-1280	-20	
	.4	-873	+30	-966	-38	-1076	-30	-1113	-48	-1221	-41	
	.6	-840	145	-944	+112	-1063	+132	-1110	+134	-1204	+122	
	.7	-820	203	-926	181	-1017	252	-1081	221	-1182	208	
	.8	-790	255	-902	227	-989	307	-1049	280	-1135	304	
	.9	-755	297	-863	289	-953	352	-972	384	-1092	369	
	1.0	-717	337	-828	345	-915	431	-924	422	-1049	425	
	1.1	-681	367	-773	386	-877	465	-894	470	-996	478	
	1.2	-637	389	-737	413	-839	485	-804	528	-936	510	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1303	-181	-1402	-91	-1507	-188	-1526	-173	-1605	-183	
	.4	-1301	-53	-1395	-12	-1460	-105	-1518	-76	-1544	-64	
	.6	-1275	+130	-1350	+211	-1461	+122	-1512	+192	-1536	+186	
	.7	-1246	225	-1303	355	-1434	227	-1471	303	-1496	291	
	.8	-1211	305	-1244	435	-1346	408	-1385	451	-1447	396	
	.9	-1162	382	-1146	535	-1282	498	-1313	537	-1370	489	
	1.0	-1109	442	-1076	592	-1208	566	-1228	615	-1305	578	
	1.1	-1058	500	-1009	631	-1126	627	-1148	670	-1210	639	
	1.2	-997	543	-932	659	-1048	675	-1062	704	-1109	705	

TABLE 2
 NEGATIVE IMPEDANCE AT 1 KC FOR OTHER SECTIONS (13X AND 14X)
 (USING STRAPPING CHARTS)

Net No.	Sec.	1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
13X 19 DNB-H135	.3	-341	-54	-462	-15	-626	-58	-790	26	-813	-83	
	.4	-321	-34	-458	+8	-612	-10	-736	56	-822	-40	
	.6	-309	+13	-448	72	-612	+72	-706	170	-822	+61	
	.7	-309	32	-443	109	-604	115	-677	220	-818	96	
	.8	-310	47	-427	136	-587	153	-648	261	-804	152	
	.9	-308	62	-412	161	-572	182	-613	300	-791	187	
	1.0	-303	78	-393	185	-551	215	-579	323	-767	233	
	1.1	-294	92	-375	201	-524	240	-538	348	-737	275	
	1.2	-290	103	-350	213	-497	260	-497	359	-714	296	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	-1002	-105	-1102	-98	-1215	-177	-1308	-216	-1462	-352
	.4	-953	-73	-1063	-55	-1170	-81	-1254	-65	-1313	-83	
	.6	-925	+84	-1072	+74	-1154	+88	-1219	+137	-1322	+120	
	.7	-915	133	-1057	140	-1142	152	-1202	213	-1305	202	
	.8	-900	176	-1029	236	-1122	216	-1165	300	-1279	278	
	.9	-875	236	-998	287	-1086	296	-1119	367	-1233	365	
	1.0	-848	278	-967	339	-1046	354	-1076	424	-1182	438	
	1.1	-823	310	-925	382	-1005	409	-1030	478	-1118	497	
	1.2	-779	353	-882	420	-963	450	-973	512	-1053	548	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1487	-220	-1628	-243	-1590	-253	-1652	-110	-1793	-142	
	.4	-1456	-135	-1509	+37	-1569	-176	-1651	-150	-1725	-112	
	.6	-1428	+68	-1488	205	-1576	+47	-1647	+101	-1735	+121	
	.7	-1416	168	-1457	323	-1570	144	-1626	201	-1703	271	
	.8	-1396	240	-1403	409	-1537	249	-1585	315	-1674	342	
	.9	-1359	335	-1341	494	-1515	319	-1553	388	-1625	437	
	1.0	-1323	394	-1261	572	-1476	410	-1494	493	-1564	539	
	1.1	-1299	446	-1261	572	-1412	488	-1429	561	-1511	600	
	1.2	-1232	520	-1186	639	-1403	514	-1411	582	-1424	680	
14X 19 DNB-B175	.3	-510	-6	-701	-49	-921	-47	-1129	-126	-1412	-220	
	.4	-490	0	-693	-42	-920	0	-1114	-74	-1332	-18	
	.6	-485	37	-703	+22	-915	107	-1123	+90	-1323	+154	
	.7	-486	56	-695	54	-903	156	-1117	126	-1315	208	
	.8	-483	82	-696	99	-873	221	-1100	193	-1303	252	
	.9	-477	100	-689	125	-849	265	-1091	225	-1266	342	
	1.0	-469	117	-681	152	-827	302	-1060	290	-1237	390	
	1.1	-463	131	-663	187	-783	350	-1045	320	-1191	458	
	1.2	-448	154	-646	206	-750	378	-1012	375	-1160	494	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	-1502	-79	-1603	-98	-1807	-188	-2009	-244	-2088	-296
	.4	-1504	0	-1591	+22	-1781	-116	-1944	-102	-2065	-208	
	.6	-1496	126	-1573	174	-1784	+116	-1945	+136	-2080	+15	
	.7	-1496	126	-1573	174	-1750	259	-1923	245	-2075	140	
	.8	-1464	258	-1532	309	-1723	342	-1890	354	-2052	243	
	.9	-1411	370	-1532	309	-1686	433	-1850	455	-2020	368	
	1.0	-1411	370	-1480	435	-1624	518	-1805	550	-1985	455	
	1.1	-1344	473	-1480	435	-1566	609	-1738	624	-1928	556	
	1.2	-1344	473	-1390	547	-1504	668	-1675	699	-1868	655	
		6.0db GAIN		6.5db GAIN		7.0db GAIN		7.5db GAIN		8.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-2218	-257									
	.4	-2209	-177									
	.6	-2226	+58									
	.7	-2216	192									
	.8	-2196	290									
	.9	-2167	408									
	1.0	-2115	511									
	1.1	-2059	607									
	1.2	-1991	706									

TABLE 2
 NEGATIVE IMPEDANCE AT 1 KC FOR OTHER SECTIONS (15X AND 16X)
 (USING STRAPPING CHARTS)

Het No.	Sec.	1.Odb GAIN		1.5db GAIN		2.Odb GAIN		2.5db GAIN		3.Odb GAIN		
		R	X	R	X	R	X	R	X	R	X	
15X 19 DNB-11.75	.3	-420	-31	-611	-35	-821	-52	-993	-105	-1101	-84	
	.4	-403	+7	-590	+4	-771	+57	-945	+37	-1071	-27	
	.6	-401	68	-593	83	-752	172	-926	165	-1068	+107	
	.7	-395	94	-581	122	-728	213	-905	210	-1052	173	
	.8	-375	129	-562	165	-693	265	-871	276	-1030	235	
	.9	-368	144	-546	197	-651	307	-829	331	-1004	290	
	1.0	-354	162	-525	224	-615	336	-799	361	-971	340	
	1.1	-336	176	-499	246	-572	364	-753	403	-930	385	
	1.2	-314	191	-475	268	-540	373	-714	419	-887	424	
			3.5db GAIN		4.Odb GAIN		4.5db GAIN		5.Odb GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
		.3	-1271	-50	-1386	-183	-1505	-166	-1626	-166	-1745	-129
	.4	-1235	+41	-1358	-102	-1483	-38	-1612	-78	-1743	-41	
	.6	-1205	217	-1365	+65	-1460	+212	-1605	+146	-1740	+150	
	.7	-1171	295	-1349	173	-1429	301	-1564	279	-1697	330	
	.8	-1131	371	-1317	272	-1375	416	-1537	365	-1661	404	
	.9	-1084	432	-1268	371	-1343	457	-1486	459	-1624	481	
	1.0	-1033	487	-1243	411	-1270	540	-1412	547	-1532	599	
	1.1	-973	527	-1179	484	-1192	605	-1324	638	-1476	659	
	1.2	-911	558	-1144	518	-1107	663	-1265	669	-1406	708	
		6.Odb GAIN		6.5db GAIN		7.Odb GAIN		7.5db GAIN		8.Odb GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1911	-321	-1922	-320	-2055	-136	-2118	-236	-2286	-296	
	.4	-1864	-143	-1933	-168	-2060	-106	-2089	-74	-2213	-104	
	.6	-1845	+110	-1922	+129	-1959	+235	-2081	+198	-2198	+196	
	.7	-1816	262	-1897	261	-1990	370	-2041	337	-2161	357	
	.8	-1783	350	-1859	377	-1938	485	-1955	530	-2062	571	
	.9	-1740	450	-1790	519	-1866	608	-1891	635	-1970	683	
	1.0	-1681	541	-1732	603	-1787	701	-1832	704	-1922	767	
	1.1	-1602	642	-1657	703	-1678	805	-1781	765	-1817	862	
	1.2	-1554	700	-1571	774	-1594	875	-1653	878	-1714	920	
16X 19 DNB-11.75		1.Odb GAIN		1.5db GAIN		2.Odb GAIN		2.5db GAIN		3.Odb GAIN		
		R	X	R	X	R	X	R	X	R	X	
		.3	-363	-82	-521	-38	-688	-64	-824	-89	-983	-132
		.4	-343	-15	-511	-23	-689	-7	-825	-6	-977	-87
		.6	-352	+34	-517	+52	-673	+126	-809	+129	-941	+107
		.7	-348	57	-511	91	-651	184	-791	187	-920	178
		.8	-342	75	-501	116	-624	228	-753	247	-904	229
		.9	-339	91	-483	156	-588	266	-709	300	-865	286
		1.0	-326	113	-471	178	-535	309	-676	336	-822	342
		1.1	-313	126	-451	201	-496	325	-621	369	-773	385
		1.2	-303	138	-424	218	-451	348	-588	391	-722	416
			3.5db GAIN		4.Odb GAIN		4.5db GAIN		5.Odb GAIN		5.5db GAIN	
		R	X	R	X	R	X	R	X	R	X	
	.3	-1101	-66	-1303	-118	-1398	-110	-1502	-92	-1604	-156	
	.4	-1080	-15	-1253	0	-1390	+21	-1492	+79	-1570	-52	
	.6	-1049	+189	-1231	184	-1337	260	-1440	187	-1528	+216	
	.7	-1009	280	-1180	315	-1262	399	-1401	306	-1499	298	
	.8	-972	328	-1140	386	-1202	477	-1371	363	-1447	408	
	.9	-918	395	-1053	477	-1137	539	-1313	461	-1389	497	
	1.0	-850	440	-994	520	-1028	608	-1244	544	-1273	606	
	1.1	-792	486	-939	556	-954	639	-1146	615	-1175	667	
	1.2	-727	516	-841	600	-896	671	-1076	648	-1175	667	
		6.Odb GAIN		6.5db GAIN		7.Odb GAIN		7.5db GAIN		8.Odb GAIN		
		R	X	R	X	R	X	R	X	R	X	
	.3	-1664	-168	-1705	-171	-1908	-298	-1903	-178	-2010	-218	
	.4	-1625	-102	-1701	+42	-1813	-79	-1891	-48	-2002	-31	
	.6	-1586	+188	-1657	259	-1805	220	-1856	+226	-1943	+357	
	.7	-1559	297	-1619	365	-1774	311	-1831	325	-1889	464	
	.8	-1515	400	-1541	467	-1695	479	-1750	480	-1780	631	
	.9	-1441	503	-1465	574	-1645	547	-1690	560	-1701	714	
	1.0	-1400	559	-1332	692	-1536	676	-1619	660	-1617	758	
	1.1	-1305	636	-1332	692	-1390	767	-1522	751	-1546	828	
	1.2	-1185	709	-1216	757	-1365	798	-1409	807	-1365	903	

TABLE 2

NEGATIVE IMPEDANCE AT 1 KC FOR OTHER SECTIONS
(USING STRAPPING CHART 17X)

Net No. 17X	End Sec.	1.0db GAIN		1.5db GAIN		2.0db GAIN		2.5db GAIN		3.0db GAIN		
		R	X	R	X	R	X	R	X	R	X	
19 CNB-H14	.3							-320	+ 29	-429	+ 9	
	.4							-363	+ 12	-428	+ 38	
	.5							-362	+ 12	-428	+ 38	
	.6							-374	+ 52	-427	+ 68	
	.7							-371	+ 58	-421	+ 85	
	.8							-365	+ 71	-414	+104	
	.9							-361	+ 91	-404	+122	
	1.0							-354	+106	-392	+137	
	1.1							-347	+121	-383	+155	
	1.2							-340	+131	-370	+168	
			3.5db GAIN		4.0db GAIN		4.5db GAIN		5.0db GAIN		5.5db GAIN	
			R	X	R	X	R	X	R	X	R	X
	.3	-420	0	-530	0	-550	0	-971	+ 36	-650	0	
	.4	-492	+ 11	-522	0	-582	0	-755	+ 39	-678	- 11	
	.5	-486	+ 30	-523	+ 14	-582	+ 29	-624	+ 20	-686	0	
	.6	-474	+ 8	-524	+ 34	-580	+ 51	-620	+ 40	-680	+ 34	
	.7	-472	+ 74	-518	+ 63	-580	+ 76	-626	+ 73	-675	+ 69	
	.8	-469	+ 84	-519	+ 75	-572	+102	-614	+ 75	-668	+ 95	
	.9	-469	+120	-520	+ 91	-565	+120	-614	+111	-652	+127	
	1.0	-453	+115	-506	+119	-551	+144	-595	+151	-653	+155	
	1.1	-445	+136	-500	+133	-546	+159	-586	+176	-644	+182	
	1.2	-450	+172	-494	+149	-529	+190	-574	+194	-631	+196	

TABLE 3
 REPEATER IMPEDANCE WITH NETWORK 1X
 FOR 3 db GAIN AND VARIOUS END SECTIONS
 19CNB)
 22BSA) B88
 24DSM)

F	.3 END SECTION		.4 END SECTION		.5 END SECTION		.6 END SECTION		.7 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-799	-j361	-793	-j332	-793	-j331	-799	-j332	-797	-j319
300	-820	-j226	-822	-j205	-819	-j201	-819	-j187	-826	-j180
500	-831	-j98	-831	-j98	-832	-j89	-834	-j70	-838	-j59
1000	-849	+j0	-849	+j0	-844	+j16	-842	+j62	-840	+j82
1500	-850	+j22	-854	+j59	-863	+j85	-851	+j149	-839	+j178
2000	-890	+j32	-888	+j101	-888	+j141	-861	+j231	-844	+j269
2500	-902	+j63	-935	+j146	-926	+j197	-882	+j318	-862	+j369
2800	-990	+j21	-982	+j159	-965	+j234	-907	+j378	-861	+j433
3000	-1000	+j31	-1020	+j174	-1000	+j261	-923	+j416	-873	+j485
3500	-1111	+j42	-1151	+j233	-1117	+j358	-970	+j570	-884	+j647
3800	-1253	+j73	-1278	+j288	-1219	+j461	-1005	+j703	-872	+j773
*3900	-1300	+j78	-1328	+j316	-1263	+j496	-1007	+j764	-865	+j830
4000	-1356	+j108	-1401	+j352	-1300	+j555	-1014	+j840	-843	+j891
4500	-1862	+j219	-1836	+j773	-1509	+j1083	-855	+j1243	-640	+j1173
4900	-3020	+j125	-1876	+j1826	-1176	+j1826	-461	+j1419	-328	+j1245
5000	-3619	+j172	-1572	+j2157	-907	+j1944	-309	+j1436	-211	+j1257
5200	-4634	+j1679	-863	+j2459	-481	+j1951	-153	+j1340	-89	+j1151
5400	-3180	+j4481	-306	+j2286	-123	+j1783	-23	+j1227	-11	+j1071
F	.8 END SECTION		.9 END SECTION		FULL SECTION		1.1 END SECTION		1.2 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-796	-j309	-807	-j304	-805	-j296	-808	-j291	-817	-j289
300	-830	-j170	-832	-j157	-832	-j151	-832	-j141	-866	-j201
500	-835	-j38	-835	-j12	-836	-j3	-832	+j12	-832	+j25
1000	-830	+j123	-820	+j180	-813	+j181	-793	+j214	-791	+j231
1500	-819	+j240	-788	+j291	-771	+j316	-726	+j357	-716	+j371
2000	-801	+j341	-739	+j403	-715	+j423	-655	+j466	-628	+j480
2500	-777	+j453	-691	+j509	-653	+j528	-571	+j557	-530	+j562
2800	-763	+j521	-654	+j571	-606	+j594	-512	+j598	-475	+j598
3000	-754	+j571	-633	+j619	-571	+j629	-471	+j625	-438	+j617
3500	-701	+j713	-543	+j730	-493	+j707	-376	+j682	-339	+j685
3800	-646	+j821	-477	+j803	-422	+j778				
*3900	-648	+j834	-450	+j804	-409	+j764	-270	+j726	-237	+j699
4000	-590	+j904	-436	+j819	-349	+j802	-251	+j734	-229	+j705
4500	-382	+j1010	-234	+j870	-197	+j827	-122	+j727	-104	+j698
4900	-166	+j1016	-94	+j852	-68	+j807	-69	+j680	-60	+j645
5000	-105	+j1010	-67	+j823	-39	+j783	-31	+j675	-40	+j630
5200	-43	+j954	-26	+j780						
5400	+14	+j882	0	+j741	+12	+j700	+24	+j637	+17	+j607

* .8 of cut-off frequency of facility

TABLE 3
 REPEATER IMPEDANCE WITH NETWORK 2X
 FOR 3 db GAIN AND VARIOUS END SECTIONS
 19DNB) B88
 24GSM)

F	.3 END SECTION		.4 END SECTION		.5 END SECTION		.6 END SECTION		.7 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-869	-j416	-880	-j381	-887	-j369	-897	-j362	-891	-j368
300	-921	-j266	-910	-j230	-923	-j219	-921	-j203	-918	-j202
500	-909	-j118	-923	-j101	-931	-j88	-928	-j57	-927	-j48
1000	-951	-j58	-929	+j19	-932	+j50	-927	+j105	-914	+j124
1500	-950	+j0	-929	+j96	-931	+j132	-911	+j206	-891	+j237
2000	-950	+j29	-935	+j141	-930	+j195	-898	+j292	-868	+j332
2400	-990	+j28	-953	+j170	-941	+j236	-889	+j352	-852	+j400
2800	-991	+j56	-984	+j195	-966	+j274	-900	+j413	-848	+j467
3000	-1002	+j84	-1005	+j206	-988	+j291	-915	+j447	-846	+j497
3500	-1092	+j79	-1098	+j228	-1077	+j350	-951	+j546	-861	+j612
4000	-1214	+j104	-1288	+j270	-1237	+j460	-1019	+j728	-867	+j804
4200	-1308	+j157	-1404	+j313	-1333	+j544	-1032	+j834	-864	+j899
*4300	-1404	+j196	-1477	+j341	-1393	+j606	-1038	+j913	-844	+j957
4500	-1527	+j272	-1667	+j442	-1506	+j776	-1006	+j1060	-793	+j1088
5000	-2330	+j492	-2140	+j1343	-1463	+j1632	-670	+j1383	-495	+j1289
5400	-4101	+j38	-1505	+j2402	-690	+j2014	-309	+j1405	-222	+j1262
5500	-4705	+j495	-1157	+j2525	-512	+j1982	-241	+j1355	-189	+j1234
5600	-5229	+j1507	-910	+j2544	-327	+j1943	-183	+j1308	-105	+j1195
6000	-1722	+j4979	-345	+j2352	+13	+j1594	-39	+j1155	-5	+j1086
6100	-960	+j4528	-49	+j2057	+54	+j1527	-17	+j1115	+23	+j1052

F	.8 END SECTION		.9 END SECTION		FULL SECTION		1.1 END SECTION		1.2 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-898	-j354	-901	-j343	-905	-j340	-914	-j335	-910	-j328
300	-924	-j190	-930	-j175	-929	-j170	-932	-j155	-932	-j146
500	-932	-j83	-930	-j9	-930	+j5	-929	+j28	-923	+j39
1000	-914	+j149	-896	+j193	-887	+j215	-869	+j259	-846	+j278
1500	-878	+j270	-839	+j331	-823	+j358	-779	+j406	-754	+j431
2000	-844	+j368	-782	+j433	-748	+j468	-691	+j509	-652	+j520
2400	-822	+j443	-737	+j505	-696	+j531	-616	+j563	-573	+j574
2800	-803	+j508	-701	+j574	-653	+j597	-554	+j619	-509	+j622
3000	-796	+j547	-680	+j608	-626	+j627	-529	+j644	-477	+j639
3500	-787	+j661	-627	+j707	-563	+j707	-478	+j692	-402	+j682
4000	-755	+j837	-567	+j825	-485	+j823	-374	+j757	-319	+j739
4200	-724	+j902	-526	+j869	-451	+j832				
*4300	-684	+j971	-465	+j923	-400	+j888	-308	+j803	-260	+j761
4500	-618	+j1050	-416	+j935	-367	+j878	-252	+j815	-207	+j776
5000	-365	+j1149	-210	+j990	-192	+j898	-146	+j794	-120	+j742
5400	-158	+j1079								
5500	-132	+j1068	-96	+j894	-75	+j833	-54	+j750	-57	+j700
5600										
6000	-18	+j923	-23	+j794						
6100	-10	+j913	-23	+j794	-15	+j746	-5	+j690	-15	+j646

* .8 of cut-off frequency of facility

TABLE 3
 REPEATER IMPEDANCE WITH NETWORK 5X
 FOR 2 db GAIN AND VARIOUS END SECTIONS
 19CNB)
 22BSA) H88
 24DSM)

F	.3 END SECTION		.4 END SECTION		.5 END SECTION		.6 END SECTION		.7 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-390	-j136	-380	-j138	-385	-j127	-383	-j128	-383	-j128
300	-403	-j77	-387	-j86	-386	-j80	-387	-j66	-387	-j66
500	-400	-j0	-394	-j40	-401	-j21	-400	-j3	-400	-j3
1000	-400	-j0	-410	+j0	-411	+j25	-406	+j63	-406	+j63
1500	-410	-j0	-431	+j21	-437	+j66	-414	+j136	-414	+j136
2000	-460	-j0	-473	+j39	-477	+j100	-431	+j209	-431	+j209
2400	-500	+j17	-527	+j43	-538	+j135	-443	+j286	-443	+j286
2600	-550	+j25	-573	+j41			-447	+j335	-447	+j335
*2800	-582	+j64	-641	+j38	-657	+j206	-445	+j410	-445	+j410
3000	-655	+j116	-749	+j41	-753	+j291	-418	+j494	-418	+j494
3200	-785	+j203	-938	+j66	-836	+j464	-341	+j579	-341	+j579
3400	-1055	+j301	-1250	+j237	-793	+j773	-230	+j631	-230	+j631
3500	-1288	+j346	-1430	+j495	-658	+j940	-162	+j630	-162	+j630
3600	-1655	+j354	-1470	+j922	-446	+j1019	-120	+j610	-120	+j610
3700	-2321	+j80	-1122	+j1362			-76	+j566	-76	+j566
3800	-2880	+j755	-773	+j1543	-158	+j951	-61	+j545	-61	+j545
3900	-2396	+j2208	-375	+j1471	-79	+j889	-43	+j515	-43	+j515
4000	-958	+j2490	-168	+j1286	-35	+j795	-25	+j485	-25	+j485

F	.8 END SECTION		.9 END SECTION		FULL SECTION		1.1 END SECTION		1.2 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-384	-j126	-384	-j125	-381	-j117	-381	-j117	-385	-j111
300	-394	-j61	-390	-j55	-392	-j49	-391	-j46	-390	-j33
500	-398	+j0	-395	+j0	-392	+j5	-389	+j16	-387	+j33
1000	-399	+j82	-395	+j102	-381	+j119	-375	+j131	-353	+j155
1500	-399	+j159	-380	+j185	-354	+j205	-340	+j216	-304	+j233
2000	-397	+j238	-360	+j266	-313	+j283	-295	+j294	-238	+j289
2400	-393	+j318	-336	+j338	-261	+j331	-245	+j343	-193	+j330
2600	-380	+j371	-308	+j379	-229	+j355	-216	+j371	-165	+j347
*2800	-360	+j432	-276	+j424	-193	+j382	-186	+j394	-137	+j359
3000	-318	+j489	-231	+j453	-168	+j423	-145	+j403	-105	+j365
3200	-246	+j541	-169	+j478	-125	+j433	-105	+j409	-75	+j361
3400	-160	+j549	-109	+j478	-75	+j429	-65	+j400	-47	+j347
3500	-120	+j551	-77	+j469						
3600	-80	+j529	-57	+j459	-40	+j412	-33	+j385	-27	+j343
3700	-52	+j506	-38	+j446						
3800	-29	+j488	-24	+j424	-14	+j380	-13	+j365	-17	+j333
3900	-12	+j464	-14	+j412						
4000	-6	+j451	-7	+j400	-10	+j367	-7	+j353	-6	+j309

* .8 of cut-off frequency of facility.

TABLE 3
 REPEATER IMPEDANCE WITH NETWORK 6X
 FOR 2 db GAIN AND VARIOUS END SECTIONS
 19DNB) H88
 24CSM)

F	.3 END SECTION		.4 END SECTION		.5 END SECTION		.6 END SECTION		.7 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-406	-j169	-409	-j155	-413	-j151	-411	-j148	-415	-j145
300	-418	-j110	-418	-j103	-423	-j92	-420	-j88	-423	-j81
500	-422	-j54	-426	-j68	-432	-j42	-429	-j30	-431	-j19
1000	-440	-j13	-448	-j7	-449	+j11	-446	+j33	-444	+j57
1500	-465	+j13	-470	+j12	-477	+j48	-475	+j87	-463	+j124
2000	-500	+j18	-523	+j34	-526	+j95	-509	+j155	-483	+j204
2400	-550	+j23	-580	+j55	-583	+j147	-548	+j225	-494	+j292
2800	-626	+j45	-677	+j89	-657	+j229	-576	+j340	-483	+j408
*3000	-684	+j63	-740	+j114	-698	+j233	-585	+j416	-468	+j476
3100	-717	+j72	-780	+j134	-722	+j336	-584	+j465	-448	+j511
3500	-957	+j123	-1017	+j298	-771	+j606	-478	+j664	-319	+j622
3800	-1348	+j114	-1183	+j690	-616	+j875	-328	+j781		
3900	-1595	+j102	-1173	+j912	-553	+j917	-271	+j791	-159	+j656
4000	-1894	+j108	-1049	+j1148	-420	+j946	-193	+j795	-118	+j647
4100	-2209	+j451	-853	+j1289	-303	+j977	-143	+j767		
4300	-2105	+j1897	-383	+j1350	-137	+j863	-63	+j707	-33	+j590
4400	-1455	+j2316	-251	+j1253	-86	+j853	-28	+j672	-18	+j572

F	.8 END SECTION		.9 END SECTION		FULL SECTION		1.1 END SECTION		1.2 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-418	-j140	-415	-j136	-414	-j135	-417	-j131	-418	-j124
300	-425	-j74	-424	-j71	-421	-j65	-425	-j59	-427	-j51
500	-430	-j6	-430	+j0	-428	-j6	-426	+j18	-425	+j31
1000	-438	+j79	-434	+j96	-425	+j116	-413	+j134	-404	+j150
1500	-447	+j158	-433	+j186	-409	+j208	-385	+j234	-361	+j249
2000	-451	+j249	-410	+j282	-371	+j303	-331	+j320	-304	+j328
2400	-433	+j342	-372	+j365	-322	+j376	-280	+j374	-243	+j364
2800	-391	+j439	-315	+j439						
*3000	-358	+j485	-278	+j477	-221	+j452	-176	+j424	-146	+j395
3100	-333	+j513								
3500	-219	+j565	-157	+j509	-118	+j465	-94	+j424	-81	+j391
3800										
3900	-98	+j557	-68	+j488	-54	+j450	-42	+j406	-43	+j376
4000	-78	+j550			-41	+j437				
4100										
4300	-32	+j511	-21	+j453	-14	+j410	-13	+j381	-21	+j358
4400	-15	+j491								

* .8 of cut-off frequency of facility.

TABLE 3
 REPEATER IMPEDANCE WITH NETWORK 8X
 FOR 3.5 db GAIN AND VARIOUS END SECTIONS
 19CNB)
 22BSA) B135

F	.3 END SECTION		.4 END SECTION		.5 END SECTION		.6 END SECTION		.7 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-1047	-j528	-1053	-j496	-1063	-j490	-1076	-j481	-1075	-j473
300	-1104	-j344	-1101	-j309	-1119	-j307	-1120	-j280	-1119	-j271
500	-1123	-j202	-1131	-j157	-1141	-j144	-1148	-j102	-1143	-j83
1000	-1158	-j118	-1171	-j24	-1171	+j8	-1170	+j98	-1162	+j132
1500	-1213	+j93	-1235	+j47	-1229	+j107	-1200	+j240	-1172	+j303
2000	-1312	+j104	-1341	+j116	-1320	+j214	-1249	+j405	-1191	+j487
2400	-1444	+j120	-1485	+j189	-1439	+j333	-1290	+j583	-1194	+j675
2800	-1660	+j160	-1702	+j330	-1599	+j539	-1301	+j854	-1153	+j917
3000	-1829	+j185	-1859	+j457	-1677	+j709	-1284	+j1018	-1074	+j1079
3100	-1936	+j187	-1934	+j543	-1737	+j808	-1247	+j1111	-1006	+j1156
*3200	-2071	+j191	-2017	+j667	-1765	+j941	-1192	+j1197	-947	+j1227
3500	-2633	+j89	-2192	+j1197	-1712	+j1418	-939	+j1430	-729	+j1342
3800	-3513	+j430	-1912	+j2054	-1321	+j1929	-583	+j1537		
4000	-4137	+j1455	-1361	+j2367	-873	+j2083	-362	+j1486	-233	+j1320
4200	-3845	+j3081	-841	+j2380	-529	+j1992	-171	+j1425		
4400	-2100	+j4157	-398	+j2223	-225	+j1841	-50	+j1299	-55	+j1123

F	.8 END SECTION		.9 END SECTION		FULL SECTION		1.1 END SECTION		1.2 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-1079	-j459	-1088	-j453	-1100	-j437	-1107	-j418	-1110	-j414
300	-1125	-j248	-1134	-j240	-1136	-j214	-1142	-j189	-1144	-j179
500	-1143	-j41	-1146	-j18	-1142	+j9	-1138	+j56	-1139	+j75
1000	-1133	+j210	-1125	+j248	-1088	+j312	-1051	+j374	-1026	+j404
1500	-1105	+j406	-1077	+j458	-986	+j530	-908	+j586	-861	+j609
2000	-1058	+j611	-998	+j657	-856	+j717	-738	+j736	-696	+j727
2400	-985	+j788	-894	+j816	-733	+j824	-629	+j798	-527	+j809
2800	-858	+j956	-740	+j978	-583	+j892	-429	+j865	-390	+j818
3000	-769	+j1064	-642	+j1044	-474	+j926	-392	+j837	-322	+j812
3100										
*3200	-626	+j1141	-529	+j1083	-363	+j940	-292	+j856	-253	+j803
3500	-454	+j1146	-358	+j1079	-218	+j923	-173	+j828	-162	+j774
3800										
4000	-144	+j1058	-131	+j974	-77	+j827	-79	+j732	-69	+j693
4200										
4400	-32	+j905	-35	+j853	-5	+j742	-38	+j664	-36	+j636

* .8 of cut-off frequency of facility.

SECTION 852-305-104

TABLE 3
 REPEATER IMPEDANCE WITH NETWORK 9X
 FOR 3.5 db GAIN AND VARIOUS END SECTIONS
 19DNB B135

F	.3 END SECTION		.4 END SECTION		.5 END SECTION		.6 END SECTION		.7 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-1177	-j629	-1173	-j579	-1185	-j560	-1174	-j545	-1200	-j534
300	-1224	-j348	-1233	-j366	-1241	-j334	-1244	-j319	-1255	-j297
500	-1253	-j128	-1264	-j190	-1267	-j136	-1270	-j109	-1273	-j62
1000	-1290	+j0	-1270	-j25	-1273	+j64	-1263	+j111	-1246	+j204
1500	-1300	+j21	-1290	+j6	-1277	+j179	-1254	+j247	-1200	+j375
2000	-1300	+j21	-1341	+j29	-1309	+j259	-1268	+j356	-1151	+j511
2400	-1400	+j40	-1411	+j30	-1381	+j325	-1325	+j438	-1168	+j636
2800	-1503	+j120	-1565	+j14	-1521	+j404	-1439	+j555	-1159	+j806
3000	-1600	+j212	-1680	+j18	-1630	+j479	-1521	+j662	-1202	+j903
3500	-2093	+j601	-2282	+j64	-2024	+j961	-1632	+j1230	-1039	j1352
*3600	-2221	+j684	-2521	+j36	-2099	+j1164	-1595	+j1394	-967	j1456
3800	-2721	+j822			-2084	+j1691				
3920			-3629	+j553						
4000	-3646	+j911	-3925	+j927	-1711	+j2296	-963	+j1982	-514	+j1725
4200	-5016	+j638	-4208	+j2382	-1181	+j2529	-592	+j2036	-337	+j1586
4350	-6638	+j773								
4500	-6884	+j4075	-1850	+j4240	-442	+j2338	-218	+j1895	-182	+j1502
4600	-5256	+j5938	-1145	+j3999	-402	+j2298	-114	+j1725		
4900	-826	+j5234	-185	+j3078	-111	+j1881	-2	+j1485	-47	+j1402
5000	-318	+j1466	-5	+j2809	-79	+j1801	-2	+j1485	-1	+j1267

F	.8 END SECTION		.9 END SECTION		FULL SECTION		1.1 END SECTION		1.2 END SECTION	
	Measured		Measured		Measured		Measured		Measured	
	R	X	R	X	R	X	R	X	R	X
200	-1201	-j524	-1210	-j516	-1218	-j501	-1220	-j493	-1225	-j481
300	-1259	-j282	-1264	-j267	-1271	-j237	-1270	-j225	-1273	-j402
500	-1271	-j39	-1271	-j14	-1263	+j29	-1262	+j59	-1258	+j82
1000	-1224	+j243	-1207	+j286	-1172	+j365	-1134	+j394	-1109	+j431
1500	-1161	+j430	-1121	+j483	-1045	+j568	-984	+j595	-931	+j623
2000	-1105	+j579	-1046	+j633	-907	+j704	-834	+j725	-776	+j743
2400	-1083	+j736	-986	+j754	-832	+j811	-739	+j816	-664	+j817
2800	-1073	+j951	-928	+j887	-742	+j906	-629	+j919	-544	+j856
3000	-1081	+j1050	-889	+j974	-672	+j966	-557	+j936	-481	+j919
3500	-803	+j1362								
*3600	-719	+j1416	-583	+j1258	-377	+j1097	-268	+j984	-251	+j964
3800										
3920										
4000	-389	+j1450	-254	+j1229	-174	+j1028	-114	+j935	-130	+j889
4200	-251	+j1408								
4350										
4500	-109	+j1302	-79	+j1070	-74	+j895	-29	+j824	-23	+j795
4600										
4900	-44	+j1154	-32	+j958	-29	+j824	13	+j751	-1	+j713
5000	-25	+j1104	-16	+j934	-14	+j800				

* .8 of cut-off frequency of facility.