

9 PLY POLYESTER TWINE
REPLACING 8 AND 10 POLYESTER TWINE

1. GENERAL

1.1 The purpose of this UIS is to provide information on a new 9 ply polyester twine which will replace present 8 and 10 ply when stock depletes.

2. INSTRUCTIONS

2.1 Effective 6-20-79, any purchases of R-2916 L-8 and L-10 have been replaced with R-2916 L-9, 9 Ply Polyester Twine (White), Ordering No. 23291609.

2.2 During the interim period stockkeeping will deplete stock and may substitute 8 and 10 ply for Installers request of 9 ply. The following requirements in Paragraph 2.21, 2.22, and 2.23 shall be observed as in the past.

2.21 The R-2916 L8, 8 Ply Polyester Twine (White), Ordering No. 23291608, shall be used for all sewing, banding, and securing applications, at all types of framework and equipment, unless otherwise specified on a Standard Drawing or in the Job Specification. L-8 (8 Ply) Twine shall not be used on horizontal and vertical cable racks.

2.22 The R-2916 L-10, 10 Ply Polyester Twine (Red), Ordering No. 23291610, shall be used for banding and securing applications on both horizontal and vertical cable racks unless otherwise specified on a Standard Drawing or in the Job Specification. L-10 (10 Ply) Twine shall not be used for banding, sewing, and securing applications described in Paragraph 2.21.

2.23 The R-4265 Nylon Cable Ties may be used as a replacement for L-8 (8 Ply) Twine providing the requirements of Handbook 9, Section 205, can be met.

2.3 The new R-2916 L9, 9 Ply Polyester Twine (White), Ordering No. 23291609, will become a universal twine to be used for all sewing, banding, and sewing applications at all types of framework, equipment, or horizontal and vertical cable racks unless otherwise specified on a Standard Drawing or in the Job Specification.

Engineering Planning Manager
(Installation)

NOTICE - NOT FOR USE OR DISCLOSURE OUTSIDE THE BELL
SYSTEM EXCEPT UNDER WRITTEN AGREEMENT

Printed in U.S.A.