



NOTES:
 1. WHITE LEADS FROM DIAL MAY BE INTERCHANGED AT TERMINALS C & R. WHITE LEADS FROM HANDSET MAY BE INTERCHANGED AT TERMINALS GN & R. YELLOW LEADS FROM DIAL MAY BE INTERCHANGED AT KEY TERMINAL STRIP, TERMINALS 29 AND 30.

COLORS OF MOUNTING CORD CONDUCTORS TO TERMINALS ON KEY, LAMP TERMINAL STRIP AND TERMINAL STRIP

| MTG CORD | CORD END | BL-W | W-BL | O-W | W-O | G-W | W-G | BR-W | W-BR | S-W | W-S | BL-R | R-BL | O-R | R-O | G-R | R-G | BR-R | R-BR | S-R | R-S | BL-BK | BK-BL | O-BK | BK-O | G-BK | BK-G | BR-BK | BK-BR | S-BK | BK-S | BL-Y | Y-BL | O-Y | Y-O | G-Y | Y-G | BR-Y | Y-BR | S-Y | Y-S | BL-V | V-BL | O-V | V-O | G-V | V-G | BR-V | V-BR | S-V | V-S | BK-G |
|----------|----------|------|------|-----|-----|-----|-----|------|------|-----|-----|------|------|-----|-----|-----|-----|------|------|-----|-----|-------|-------|------|------|------|------|-------|-------|------|------|------|------|-----|-----|-----|-----|------|------|-----|-----|------|------|-----|-----|-----|-----|------|------|-----|-----|------|
| | | DSOH | SET | 1 | 2 | 4 | 15 | 5 | 16 | 18 | 7 | 8 | 9 | 19 | 10 | 12 | 21 | 11 | 20 | G* | R* | 13 | 26 | 3 | 14 | 27 | 28 | 23 | F* | RR* | 29 | 30 | G* | GN* | 22 | L1* | L2* | 25 | 1LG | 1L | 2L | 3L | 4LG | 4L | 5LG | 5L | L2* | DD | 17 | 6 | 6L | R* |
| | CONN | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | |

DD CONDUCTORS ARE TAPED AND STORED
 * TERMINALS ON NETWORK

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES. UNLIMITED DIMENSIONS OTHER THAN SIZE OF RAW MATERIAL SHALL BE HELD AS FOLLOWS WHEN EXPRESSED:
 TO 2 DECIMAL PLACES ± AS ANGLES ±
 TO 3 DECIMAL PLACES ±
 FOR GENERAL INFORMATION ON SYMBOLS AND NOTES REFER TO MANUFACTURING STANDARD 16.002, PART 2, SECTION 227. (THIS NOTE IS NOT APPLICABLE TO CENTRAL OFFICE EQUIPMENT.)