



Insulation Color Coding:

<u>Pair</u>	<u>Tip</u>	<u>Ring</u>
1	WH-BL	BL-WH
2	WH-OR	OR-WH
3	WH-GR	GR-WH
4	WH-BR	BR-WH
5	WH-SL	SL-WH
6	RD-BL	BL-RD
7	RD-OR	OR-RD
8	RD-GR	GR-RD
9	RD-BR	BR-RD
10	RD-SL	SL-RD
11	BK-BL	BL-BK
12	BK-OR	OR-BK
13	BK-GR	GR-BK
14	BK-BR	BR-BK
15	BK-SL	SL-BK
16	YL-BL	BL-YL
17	YL-OR	OR-YL
18	YL-GR	GR-YL
19	YL-BR	BR-YL
20	YL-SL	SL-YL
21	VI-BL	BL-VI
22	VI-OR	OR-VI
23	VI-GR	GR-VI
24	VI-BR	BR-VI
25	VI-SL	SL-VI

Unit Binder Colors:

<u>Cable</u>	<u>Outer Unit</u> <u>WH Binder</u>	<u>Center Unit</u> <u>BL Binder</u>	
28 Pair	Pairs 1 – 25	Pairs 1 – 3	
32 Pair	1 through 25	1 through 7	
30 Pair	<u>BL/WH-1 Unit</u> 1 through 10	<u>BL/WH-2 Unit</u> 11 through 20	<u>OR/WH</u> 1 through 10
56 Pair	<u>BL/WH Unit</u> 1 through 20	<u>OR/WH Unit</u> 1 through 20	<u>GR/WH Unit</u> 1 through 16

Outer Jacket Diameter:

<u>Pairs</u>	<u>Typical Diameter(in)</u>
6	0.37
12	0.45
16	0.50
25	0.61
32	0.65
56	0.86