

STOCKLIST								
ITEM NBR	LIST GROUP CODE	QTY PER CODE	PRODUCT IDENTIFIER	CODE	DESCRIPTION	REFERENCE POSITION	NOTE	
							SYM	NBR
1010	1,2,3,4,5,6	2	103125365	982AD	CONNECTOR, BACKPLANE (2 X 8)			
1050	3,4,5,6	1	401785183	KS21238L1	WIRE, SHIELDED 28GA TIGHT TWIST BL/W ORANGE INSULATING JACKET A DIMENSION = 2 FEET 0 INCH			
1055	1,2	1	401785183	KS21238L1	WIRE, SHIELDED 28GA TIGHT TWIST BL/W ORANGE INSULATING JACKET A DIMENSION = 5 FEET 0 INCH			
1060	3,4,5,6	1	401215272	KS21238L2	WIRE, SHIELDED 28GA TIGHT TWIST G/W A DIMENSION = 2 FEET 0 INCH			
1065	1,2	1	401215272	KS21238L2	WIRE, SHIELDED 28GA TIGHT TWIST G/W A DIMENSION = 5 FEET 0 INCH			
1070	3,4,5,6	1	401216809	KS21238L3	WIRE, SHIELDED 28GA TIGHT TWISTED PR BR/W A DIMENSION = 2 FEET 0 INCH			
1075	1,2	1	401216809	KS21238L3	WIRE, SHIELDED 28GA TIGHT TWISTED PR BR/W A DIMENSION = 5 FEET 0 INCH			
1080	3,4,5,6	1	401216817	KS21238L4	WIRE, SHIELDED 28GA TIGHT TWISTED PR R/W A DIMENSION = 2 FEET 0 INCH			
1085	1,2	1	401216817	KS21238L4	WIRE, SHIELDED 28GA TIGHT TWISTED PR R/W A DIMENSION = 5 FEET 0 INCH			
1090	3,4,5,6	1	401216825	KS21238L5	WIRE, SHIELDED 28GA TIGHT TWISTED PR BK/W A DIMENSION = 2 FEET 0 INCH			
1095	1,2	1	401216825	KS21238L5	WIRE, SHIELDED 28GA TIGHT TWISTED PR BK/W A DIMENSION = 5 FEET 0 INCH			
1120	1,2,3,4,5,6	10	900225194		SLEEVE, SOLDER #D146-40-3 ORANGE INSULATING JACKET RAYCHEM CORP.			

***** END OF STOCKLIST *****

S H O P	I N S T	MANUFACTURING NOTES																							
		<p>1. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN METRICS (CM). EQUIVALENT INCH DIMENSIONS ARE ENCLOSED IN BRACKETS.</p> <p>2. DIMENSIONS 12 INCHES AND OVER ARE EXPRESSED IN FEET AND INCHES. ALL OTHER DIMENSIONS ARE IN INCHES.</p> <p>3. RESERVED.</p> <p>4. OVERALL CABLE LENGTH (DESIGNATED "A" DIM IN TBL S) IS THE LENGTH OF FINISHED CABLE MEASURED FROM THE FARTHEST TIP OF CONN AT ONE END OF THAT CABLE TO THE FARTHEST TIP OF CONN AT THE OTHER END.</p> <p>5. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS WILL HOLD A LENGTH TOLERANCE AS FOLLOWS:</p> <table border="0" style="margin-left: 40px;"> <tr> <td>METRIC LENGTH</td> <td>TOLERANCE</td> <td>ENGLISH LENGTH</td> <td>TOLERANCE</td> </tr> <tr> <td>-----</td> <td>-----</td> <td>-----</td> <td>-----</td> </tr> <tr> <td>0-1 M</td> <td>+/-1.5 CM</td> <td>(ZERO TO 3' 4"</td> <td>+/-0.5")</td> </tr> <tr> <td>1 M AND UP</td> <td>+/-1.5%</td> <td>(3' 4" & UP</td> <td>+/-1.5%)</td> </tr> <tr> <td></td> <td></td> <td>ROUNDED UP TO 1 CM OR 0.5"</td> <td></td> </tr> </table> <p>6. A/R=AS REQUIRED.</p> <p>7. BL-W/W-BL ETC., INDICATES PAIRED LEADS. COLOR AT LEFT OF SLASH INDICATES COLOR OF LEAD TO BE CONNECTED. COLOR AT RIGHT OF SLASH IS THE COLOR OF THE OTHER LEAD IN THE PAIR.</p> <p>8. () INDICATES DESIGNATIONS TO BE STAMPED IN ACCORDANCE WITH JOB INFORMATION.</p> <p>9. EQL (EQUIPMENT LOCATION) SHOWN IN THE STAMPING TABLE IS IDENTIFIED AS FOLLOWS:</p> <p style="text-align: center;">(VERT) (HOR) 119 - 042</p> <p>10. REFER TO LOCAL MANUFACTURING DOCUMENTATION FOR SPECIFICS.</p> <p>11. AA,AB,BA,BB ETC., ARE FOR TERMINAL REFERENCE ONLY. DO NOT STAMP THESE ON BACKPLANE CONNECTORS.</p> <p>12. < > INDICATES DESIGNATIONS PROVIDED IN ACCORDANCE WITH OTHER INFORMATION.</p> <p>13. { } INDICATES DESIGNATIONS SHOWN FOR INFORMATION ONLY AND ARE NOT TO BE STAMPED.</p> <p>14. UNLESS OTHERWISE SPECIFIED, THE SHINER LENGTH IS TO BE DETERMINED BY THE INDIVIDUAL MANUFACTURING LOCATIONS AND IS IN ADDITION TO THE SPECIFIED DIMENSIONS.</p>				METRIC LENGTH	TOLERANCE	ENGLISH LENGTH	TOLERANCE	-----	-----	-----	-----	0-1 M	+/-1.5 CM	(ZERO TO 3' 4"	+/-0.5")	1 M AND UP	+/-1.5%	(3' 4" & UP	+/-1.5%)			ROUNDED UP TO 1 CM OR 0.5"	
METRIC LENGTH	TOLERANCE	ENGLISH LENGTH	TOLERANCE																						
-----	-----	-----	-----																						
0-1 M	+/-1.5 CM	(ZERO TO 3' 4"	+/-0.5")																						
1 M AND UP	+/-1.5%	(3' 4" & UP	+/-1.5%)																						
		ROUNDED UP TO 1 CM OR 0.5"																							

ED5D585-19

SEE PROPRIETARY NOTICE ON SHEET ONE			
XT13			
5ESS SWITCHING EQUIPMENT SPECIFICATION FOR CABLE ASSEMBLIES FOR DTIC COMMUNICATION MODULE CM2			
DWG SIZE C2	ISSUE 8		
LUCENT TECHNOLOGIES INC		ED5D585-19	SHEET D1 OF 4