



Note 1: If filter is not provided connect brown-yellow lead from switch contacts to "Y" of dial instead of to filter terminal bracket. Terminals Y-BK, SR and W-BB are on the manual set apparatus blank.

Note 2: On six conductor mounting cord, insulate the cord tip of the unused conductor with WLP Perma Grip Adhesive Dull Litho Coated Paper, or approved equivalent, and store conductor so as not to interfere with moving parts of the set.

ISSUE 1 7-7-41
THE RED-GREEN LEAD BETWEEN THE RG TERMINAL AND THE 2 MF CONDENSER WAS GREEN. THE RED-GREEN LEAD BETWEEN THE RG TERMINAL AND THE SWITCH WAS RED.

R.B.R. Y

ISSUE 2 7-25-47 NK

"B.S.P. C63.915" WAS SPEC. IN THE TITLE.

RHD JIC

ISSUE 3 3-21-55 NK

ADDED-NOTE 2 AND ASSOCIATED REFERENCE

JIC C.M.

ISSUE 4 10/5/59

B.S.P. C 63.915	
USED ON	DWG.
●-DENOTES	MANUFACTURE DISCONTINUED
307A, B, C & D TEL. SET CONNECTIONS	
DRAWN	SCALE <input checked="" type="checkbox"/> APPROVED
CHECKED	
WESTERN ELECTRIC CO. INC. ENGINEER OF MANUFACTURE	

LA-
L

APPL'S			
DR.	M.C.M.	CH.	W.L.B.
BELL TELEPHONE LABORATORIES, INC. NEW YORK			
ESL-780524			
LA-			

LA-