

B RURAL WIRE
SPlicing AND TERMINATING

NOTES CONCERNING THIS ADDENDUM

This addendum supplements Section G34.101.3 with additional instructions for splicing B Rural Wire.

The cross-reference "See Addendum" should be marked in G34.101.3 to indicate the following:

Paragraph 1.03 - Replaced
Paragraph 1.04 - Added

1. GENERAL

1.03 For all trunk or toll usage, and for exchange loop plant usage in excess of five miles or where it is expected that carrier will operate over it, make splices in accordance with the following:

(a) Designate the end of the B Rural Wire toward the central office as the reference end. The other end shall be referred to as the random end.

(b) At each noncolor coded splice, on the reference end, number the pairs 1 to 6 in a counter clockwise direction with the tracer as pair number 1. On the random end of the splice, number the pairs from 1 to 6 in a clockwise direction with the tracer as pair number 1.

(c) Splice the pairs as follows:

Reference End		Random End	
Non-Color	Color Code Ring Wire	Non-Color	Color Code Ring Wire
1 (Tracer)	Blue	3	Green
2	Red	6	Yellow
3	Green	2	Red
4	Brown	5	Slate
5	Slate	1 (Tracer)	Blue
6	Yellow	4	Brown

In color-coded wire, all tip wires are black.

1.04 A wire terminal shall be used for splicing B Rural Wire at reel ends.