

BELL SYSTEM PRACTICES
Outside Plant Construction
and Maintenance

SECTION G59.010.2
Issue 3, January, 1957
AT&TCo Standard

LOADING COIL CASES

WELDED STEEL CASE DATA

AERIAL

1. GENERAL

1.01 This section replaces Issue 2. It covers the various types of welded steel cases used specifically in loading aerial cables. ↗

1.02 The cylindrical welded steel cases now being manufactured are intended for loading either underground or aerial cables and are covered in Section G59.010.3.

1.03 The 133A and 133B cases (which are rectangular in cross section) are the only current standard cases intended specifically for loading aerial cables. ↙

2. WELDED STEEL LOADING COIL CASE DATA

2.01 The following table lists the two standard welded steel aerial loading coil cases as well as all types of superseded welded steel aerial cases. The table gives the dimensions and weights of the cases, diameter and gauge of the stubs and the types of supports required to mount the cases on poles. The current standard cases (133A and 133B) are indicated by asterisks (*).

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
53A	30	17-3/4	12-1/2	1,000	14	1-1/2	19	M	H4 or H6
53B	35	17-3/4	12-1/2	1,200	24	1-29/32	19	M	H4 or H6
53C	40-1/4	17-3/4	12-1/2	1,450	28	2	19	M	H4 or H6
53D	45-1/4	17-3/4	12-1/2	1,650	36	2-3/16	19	M	H4 or H6
53E	22-3/4	17	11-3/4	475	10	1-7/16	19	M	H4 or H6
53F	27-1/4	17	11-3/4	550	14	1-1/2	19	M	H4 or H6
53G	32-3/4	17	11-3/4	625	24	1-29/32	19	M	H4 or H6
53H	37-1/2	17	11-3/4	725	28	2	19	M	H4 or H6
53J	42-1/8	17	11-3/4	825	36	2-3/16	19	M	H4 or H6
54A	45-1/4	23	12-1/2	1,750	46	2-5/16	19	M	H4 or H6
54B	50-1/4	23	12-1/2	2,150	56	2-1/2	19	M	H4 or H6
54C	42-1/8	22-1/4	11-3/4	1,035	46	2-5/16	19	M	H4 or H6
54D	47-5/8	22-1/4	11-3/4	1,175	56	2-1/2	19	M	H4 or H6
55A	45-1/4	23	17-3/4	2,400	72	2-11/32	22	M	H4 or H6
55B	50-1/4	23	17-3/4	2,700	84	2-1/2	22	M	H4 or H6
55C	42-1/8	22-1/4	17	1,495	72	2-11/32	22	M	H4 or H6
55D	47-5/8	22-1/4	17	1,675	84	2-1/2	22	M	H4 or H6
56A	9-1/2	5-1/2 Diam.		65	1	9/16	19	(2) 1/2" x 4-1/2" Drive Screws	
56B	14-1/4	5-1/2 Diam.		90	2	21/32	19	(2) 1/2" x 4-1/2" Drive Screws	
56C	19	5-1/2 Diam.		115	3	3/4	19	(4) 1/2" x 4-1/2" Drive Screws	
56D	43	5-1/2 Diam.		200	7	1-1/8	19	(4) 1/2" x 4-1/2" Drive Screws	
57A	38-1/2	5-1/2 Diam.		195	25	57/64	22	(4) 1/2" x 4-1/2" Drive Screws	

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
72A	22-3/4	10-1/4	10-1/4	325	50	1-5/32	22	M	H4 or H6
72B	38	10-1/4	10-1/4	525	100	1-5/8	22	M	H4 or H6
73A	48-1/4	15	10-1/4	810	200	2-1/8	22	M	H4 or H6
74A	49-1/2	15	15	1,125	300	2-17/32	22	M	H4 or H6
75A	14-3/4	6-1/2 Diam.		150	25	29/32	22	(4) 1/2" x 4-1/2" Drive Screws	
75B	22-1/4	6-1/2 Diam.		200	50	1-5/32	22	(4) 1/2" x 4-1/2" Drive Screws	
75C	38-1/4	6-1/2 Diam.		290	100	1-5/8	22	(4) 1/2" x 4-1/2" Drive Screws	
76A	32	21-3/4	8-1/2	455	200	2-1/8	22	M	H4 or H6
76B	44-1/2	21-3/4	8-1/2	610	300	2-17/32	22	M	H4 or H6
79A	30-5/8	20-1/2	27	1,170	8	2-5/16	16	M	H4 or H6
79AG	30-5/8	20-1/2	27	1,000	8	2-5/16	16	Same as 79A case	
79B	37-1/2	20-1/2	27	1,360	8	2-5/16	16	M	H4 or H6
79BG	37-1/2	20-1/2	27	1,200	8	2-5/16	16	Same as 79B case	
80A	5-1/8	11-1/2	13	120	1	23/32	16	(2) 1/2" x 4-1/2" Drive Screws	
80AG	5-1/8	11-1/2	13	107	1	23/32	16	(2) 1/2" x 4-1/2" Drive Screws	
80B	9-3/8	11-1/2	13	160	2	29/32	16	(2) 1/2" x 4-1/2" Drive Screws	
80BG	9-3/8	11-1/2	13	143	2	29/32	16	(2) 1/2" x 4-1/2" Drive Screws	
80C	13	11-1/2	13	190	1	29/32	16	(2) 1/2" x 4-1/2" Drive Screws	
80CG	13	11-1/2	13	170	1	29/32	16	(2) 1/2" x 4-1/2" Drive Screws	
80D	16-1/4	11-1/2	13	235	1	29/32	16	(4) 1/2" x 4-1/2" Drive Screws	

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
80DG	16-1/4	11-1/2	13	210	1	29/32	16	(4) 1/2" x 4-1/2" Drive Screws	
80E	22-1/2	11-1/2	13	285	1	29/32	16	(4) 1/2" x 4-1/2" Drive Screws	
80EG	22-1/2	11-1/2	13	254	1	29/32	16	(4) 1/2" x 4-1/2" Drive Screws	
80F	19	11-1/2	13	245	4	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80FG	19	11-1/2	13	219	4	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80G	23-1/4	11-1/2	13	320	6	1-11/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80GG	23-1/4	11-1/2	13	285	6	1-11/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80H	23-1/4	11-1/2	13	330	2	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80HG	23-1/4	11-1/2	13	295	2	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80J	30-1/8	11-1/2	13	380	8	1-13/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80JG	30-1/8	11-1/2	13	340	8	1-13/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80K	30-1/8	11-1/2	13	365	2	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80KG	30-1/8	11-1/2	13	325	2	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80L	33-5/8	11-1/2	13	415	3	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80LG	33-5/8	11-1/2	13	375	3	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80M	37	11-1/2	13	460	10	1-15/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80MG	37	11-1/2	13	410	10	1-15/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80N	37	11-1/2	13	445	2	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80NG	37	11-1/2	13	397	2	1-9/16	16	(4) 1/2" x 4-1/2" Drive Screws	
80P	44	11-1/2	13	550	12	2-1/16	16	(4) 1/2" x 4-1/2" Drive Screws	

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
80PG	44	11-1/2	13	480	12	2-1/16	16	(4) 1/2" x 4-1/2"	Drive Screws
80R	44	11-1/2	13	540	4	1-13/16	16	(4) 1/2" x 4-1/2"	Drive Screws
80RG	44	11-1/2	13	472	4	1-13/16	16	(4) 1/2" x 4-1/2"	Drive Screws
80S	44	11-1/2	13	530	3	1-11/16	16	(4) 1/2" x 4-1/2"	Drive Screws
80SG	44	11-1/2	13	475	3	1-11/16	16	(4) 1/2" x 4-1/2"	Drive Screws
80T	54-1/4	11-1/2	13	650	3	1-11/16	16	(4) 1/2" x 4-1/2"	Drive Screws
80TG	54-1/4	11-1/2	13	580	3	1-11/16	16	(4) 1/2" x 4-1/2"	Drive Screws
80U	54-1/4	11-1/2	13	660	5	1-15/16	16	(4) 1/2" x 4-1/2"	Drive Screws
80UG	54-1/4	11-1/2	13	590	5	1-15/16	16	(4) 1/2" x 4-1/2"	Drive Screws
81A	30-1/8	11-1/8	27	735	16	2-5/16	16	M	H4 or H6
81AG	30-1/8	11-1/8	27	655	16	2-5/16	16	Same as 81A	
81B	30-1/8	11-1/8	27	705	4	1-13/16	16	M	H4 or H6
81BG	30-1/8	11-1/8	27	630	4	1-13/16	16	Same as 81B	
81C	33-1/2	11-1/8	27	800	6	2-1/16	16	M	H4 or H6
81CG	33-1/2	11-1/8	27	715	6	2-1/16	16	Same as 81C	
81D	37	11-1/8	27	880	5	1-15/16	16	M	H4 or H6
81DG	37	11-1/8	27	785	5	1-15/16	16	Same as 81D	
81E	37	11-1/8	27	850	4	1-13/16	16	M	H4 or H6
81EG	37	11-1/8	27	760	4	1-13/16	16	Same as 81E	
81F	44	11-1/8	27	1,055	6	2-1/16	16	M	H4 or H6

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
81FG	44	11-1/8	27	940	6	2-1/16	16		
81G	44	11-1/8	27	1,085	8	2-5/16	16	M	H4 or H6
81GG	44	11-1/8	27	970	8	2-5/16	16		Same as 81G
81H	47-1/8	11-1/8	27	1,085	5	1-15/16	16	M	H4 or H6
81HG	47-1/8	11-1/8	27	970	5	1-15/16	16		Same as 81H
81J	54-1/4	11-1/8	27	1,275	6	2-1/16	16	M	H4 or H6
81JG	54-1/4	11-1/8	27	1,140	6	2-1/16	16		Same as 81J
85A	22	6-3/4	7	180	6	1-9/32	16	(4)	1/2" x 4-1/2" Drive Screws
85B	11	6-3/4	7	135	2	5/764	16	(4)	1/2" x 4-1/2" Drive Screws
85C	16-1/2	6-3/4	7	160	4	1-5/64	16	(4)	1/2" x 4-1/2" Drive Screws
87A	30-1/2	7-1/2	9	350	12	1-3/8	16	(4)	1/2" x 4-1/2" Drive Screws
88A	5-1/2	3-1/4	6	20	1	35/64	16	(4)	1/2" x 4-1/2" Drive Screws
91A	7-3/4	4-3/4 Diam.		28	5	9/16	22	(2)	3/8" x 4" Drive Screws
91B	12-1/2	4-3/4 Diam.		39	10	21/32	22	(2)	3/8" x 4" Drive Screws
91C	17	4-3/4 Diam.		52	15	21/32	22	(2)	3/8" x 4" Drive Screws
100A	9-1/2	7-5/8 Diam.		115	1	47/64	19	(2)	1/2" x 4-1/2" Drive Screws
100B	13-1/2	8-1/2	7-1/4	170	2	9/16	19	(2)	1/2" x 4-1/2" Drive Screws
100C	18	8-1/2	7-1/4	225	3	21/32	19	(4)	1/2" x 4-1/2" Drive Screws
100D	39-1/2	8-1/2	7-1/4	385	4-8	1-11/64	19	(4)	1/2" x 4-1/2" Drive Screws
100E	48-1/8	8-1/2	7-1/4	430	9-10	1-7/16	19	(4)	1/2" x 4-1/2" Drive Screws

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
101A	34-1/2	21-3/4	11	585	11-14	1-1/2	19	M	H4 or H6
101B	43	21-3/4	11	690	15-18	1-5/8	19	M	H4 or H6
102A	25-3/4	25-3/8	21-3/4	800	19-24	1-29/32	19	M	H4 or H6
102B	34-1/2	25-3/8	21-3/4	985	25-34	2-5/32	19	M	H4 or H6
102C	43	25-3/8	21-3/4	1,165	35-44	2-5/16	19	M	H4 or H6
102D	51-3/4	25-3/8	21-3/4	1,350	45-54	2-1/2	19	M	H4 or H6
103A	34-1/2	25-3/8	21-3/4	1,420	55-68	2-5/16	22	M	H4 or H6
103B	38-3/4	25-3/8	21-3/4	1,565	69-78	2-7/16	22	M	H4 or H6
103C	43-1/4	25-3/8	21-3/4	1,695	79-88	2-17/32	22	M	H4 or H6
103D	47-1/2	29	14-1/2	1,870	89-98	(2)2-1/4 each	19	Same as 103A case	
103E	51-3/4	29	14-1/2	2,000	99-108	(2)2-11/32 each	19	Same as 103A case	
104A	17-1/2	8-1/4	11-1/8	240	4-8	1-11/64	19	(2) 1/2" x 4-1/2" Drive Screws	
104AG	17-1/2	8-1/4	11-1/8	214	4-8	1-11/64	19	(2) 1/2" x 4-1/2" Drive Screws	
104B	21	8-1/4	11-1/8	280	9-10	1-7/16	19	(4) 1/2" x 4-1/2" Drive Screws	
104BG	21	8-1/4	11-1/8	250	9-10	1-7/16	19	(4) 1/2" x 4-1/2" Drive Screws	
104C	28	8-1/4	11-1/8	350	11-14	1-1/2	19	(4) 1/2" x 4-1/2" Drive Screws	
104CG	28	8-1/4	11-1/8	310	11-14	1-1/2	19	(4) 1/2" x 4-1/2" Drive Screws	
104D	35	8-1/4	11-1/8	430	15-18	1-5/8	19	(4) 1/2" x 4-1/2" Drive Screws	

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
104DG	35	8-1/4	11-1/8	385	15-18	1-5/8	19	(4) 1/2" x 4-1/2" Drive Screws	
105A	19-1/2	14	22	540	19-24	1-29/32	19	M	H4 or H6
105AG	19-1/2	14	22	480	19-24	1-29/32	19		Same as 105A case
105B	24	14	22	630	25-30	2-3/32	19	M	H4 or H6
105BG	24	14	22	560	25-30	2-3/32	19		Same as 105B case
105C	28	14	22	720	31-36	2-3/16	19	M	H4 or H6
105CG	28	14	22	640	31-36	2-3/16	19		Same as 105C case
105D	31-1/2	14	22	810	37-42	2-9/32	19	M	H4 or H6
105DG	31-1/2	14	22	730	37-42	2-9/32	19		Same as 105D case
106A	23-3/4	24-1/2	22	900	43-50	2-13/32	19	M	H4 or H6
106AG	23-3/4	24-1/2	22	815	43-50	2-13/32	19		Same as 106A case
106B	28	24-1/2	22	1,000	51-60	2-3/16	22	M	H4 or H6
106BG	28	24-1/2	22	890	51-60	2-3/16	22		Same as 106B case
106C	31-1/2	24-1/2	22	1,100	61-70	2-11/32	22	M	H4 or H6
106CG	31-1/2	24-1/2	22	980	61-70	2-11/32	22		Same as 106C case
106D	35	24-1/2	22	1,200	71-80	2-15/32	22	M	H4 or H6
106DG	35	24-1/2	22	1,070	71-80	2-15/32	22		Same as 106D case
108A	10-1/2	8-3/8 Diam.		90	7-12	1-19/32	19	(4) 1/2" x 4-1/2" Drive Screws	
108B	14-1/2	8-3/8 Diam.		105	13-18	1-3/4	19	(4) 1/2" x 4-1/2" Drive Screws	
108C	18-1/2	8-3/8 Diam.		130	19-24	1-29/32	19	(4) 1/2" x 4-1/2" Drive Screws	

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
108E	26-1/2	8-3/8 Diam.		180	31-36	2-3/16	19	(4) 1/2" x 4-1/2" Drive Screws	
108F	30-1/2	8-3/8 Diam.		205	37-42	2-9/32	19	(4) 1/2" x 4-1/2" Drive Screws	
108G	34-1/2	8-3/8 Diam.		230	43-48	2-7/16	19	(4) 1/2" x 4-1/2" Drive Screws	
109A	6-5/8	8 Diam.		40	1-4	51/64	22	Pole Mounting Brackets	
109B	10-5/8	8 Diam.		50	5-8	1	22	Pole Mounting Brackets	
110A	10-5/8	11-3/4 Diam.		110	9-16	1-1/4	22	Pole Mounting Brackets	
110B	14-3/4	11-3/4 Diam.		135	17-24	1-7/16	22	Pole Mounting Brackets	
110C	18-3/4	11-3/4 Diam.		165	25-32	1-41/64	22	Pole Mounting Brackets	
110D	22-3/4	11-3/4 Diam.		195	33-40	1-3/4	22	Pole Mounting Brackets	
110E	26-3/4	11-3/4 Diam.		230	41-48	1-59/64	22	Pole Mounting Brackets	
120A	12-1/2	7-1/2	22	260	100	1-5/8	22	Same as 120B case	
120B	16-1/4	7-1/2	22	300	150	1-29/32	22	M H4 or H6	
120C	20	7-1/2	22	360	200	2-1/8	22	M H4 or H6	
120D	27-1/2	7-1/2	22	450	300	2-17/32	22	M H4 or H6	
121A	21	11	8-1/4	280	50	1-5/32	22	(4) 1/2" x 4-1/2" Drive Screws	
121AG	21	11	8-1/4	250	50	1-5/32	22	(4) 1/2" x 4-1/2" Drive Screws	
122A	19-1/2	21-3/4	14	500	100	1-5/8	22	M H4 or H6	
122AG	19-1/2	21-3/4	14	460	100	1-5/8	22	M H4 or H6	
122B	23-3/4	21-3/4	14	630	150	1-29/32	22	M H4 or H6	

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
122BG	23-3/4	21-3/4	14	580	150	1-29/32	22	M	H4 or H6
122C	31-1/2	21-3/4	14	800	200	2-1/8	22	M	H4 or H6
122CG	31-1/2	21-3/4	14	750	200	2-1/8	22	M	H4 or H6
123A	28	21-3/4	24-1/2	1,000	300	2-17/32	22	M	H4 or H6
123AG	28	21-3/4	24-1/2	940	300	2-17/32	22	M	H4 or H6
125A	16-1/4	5-3/8 Diam.		85	75-101	1-3/8	24	(2) 1/2" x 4-1/2" Drive Screws	
125B	23-1/4	5-3/8 Diam.		100	152	1-29/32	22	(4) 1/2" x 4-1/2" Drive Screws	
125C	30-1/2	5-3/8 Diam.		120	202	2-1/8	22	(4) 1/2" x 4-1/2" Drive Screws	
126A	25	7-1/4 Diam.		145	303	2-17/32	22	(4) 1/2" x 4-1/2" Drive Screws	
128A	15-1/4	6-1/4 Diam.		67	16-51	1-1/8	24	Pole Mounting Brackets	
128B	23-3/4	6-1/4 Diam.		92	60-101	1-7/16	24	Pole Mounting Brackets	
129A	16-3/4	12 Diam.		171	152	1-11/16	24	Pole Mounting Brackets	
129B	20-3/4	12 Diam.		204	202	1-15/16	24	Pole Mounting Brackets	
129C	26-3/4	12 Diam.		263	303	2-5/16	24	Pole Mounting Brackets	
130A	10-3/4	12 Diam.		50	1	21/32	19	Pole Mounting Brackets	
130B	15	12 Diam.		70	2	23/32	19	Pole Mounting Brackets	
130C	19	12 Diam.		90	1	23/32	19	Pole Mounting Brackets	
130D	21	12 Diam.		110	4	1-1/8	19	Pole Mounting Brackets	
130E	29	12 Diam.		150	6	1-1/4	19	Pole Mounting Brackets	
130F	29	12 Diam.		150	2	1-1/8	19	Pole Mounting Brackets	
130G	35	12 Diam.		190	8	1-9/32	19	Pole Mounting Brackets	

2.02 WELDED STEEL LOADING CASE DATA. Cases listed below are of superseded design.
(Continued)

Code Number (Case)	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	Number of Coils	Stub Cable		Type of Aerial Support	
						Diam. (Inches)	Gauge	Single	Multiple
130H	39	12 Diam.		210	3	1-7/32	19	Pole Mounting Brackets	
130J	41-3/4	12 Diam.		240	10	1-13/32	19	Pole Mounting Brackets	
131A	14-3/4	21-1/8	19-3/4	300	12	1-17/32	19	Pole Mounting Brackets	
131B	14-3/4	21-1/8	19-3/4	300	4	1-9/32	19	Pole Mounting Brackets	
131C	18-1/4	21-1/8	19-3/4	410	5	1-13/32	19	Pole Mounting Brackets	
131D	18-1/4	21-1/8	19-3/4	410	16	1-57/64	19	Pole Mounting Brackets	
131E	21-3/4	21-1/8	19-3/4	500	6	1-9/16	19	Pole Mounting Brackets	
131F	25-1/4	21-1/8	19-3/4	600	8	1-7/8	19	Pole Mounting Brackets	
*133A	25-1/4	21-1/8	19-3/4	275	2-5	2-9/32	19	Pole Mounting Brackets	
*133B	25-1/4	21-1/8	19-3/4	350	6-10	2-9/32	19	Pole Mounting Brackets	
135A	21	6-3/8 Diam.		75	60-101	1-7/16	24	Pole Mounting Brackets	
135B	27-5/16	6-3/8 Diam.		100	152	1-23/32	24	Pole Mounting Brackets	
136A	18-3/16	11-3/4 Diam.		125	202	1-15/16	24	Pole Mounting Brackets	
136B	22-3/16	11-3/4 Diam.		165	303	2-5/16	24	Pole Mounting Brackets	
136C	27	11-3/4 Diam.		225	455	2-3/4	24	Pole Mounting Brackets	
139A	11-3/4	5-3/4 Diam.		25	2-4	15/16	19	Same as Lead Sleeve Case	
139B	16-3/4	5-3/4 Diam.		35	5 or 6	1-1/16	19	Same as Lead Sleeve Case	
139C	20-1/2	5-3/4 Diam.		50	7-10	1-5/32	19	Same as Lead Sleeve Case	
152A	29-1/2	20-1/4	21-3/4	325	6-8	2-3/32	19	M	H4 or H6
152B	27-1/2	23-3/4	21-3/4	420	9-10	2-11/32	19	Same as 152A case	
152C	27-1/4	13-1/4	21-3/4	160	2-4	2-1/8	19	Same as 152A case	