

BELL SYSTEM PRACTICES
Outside Plant Construction
and Maintenance

SECTION G59.010.3
Issue 4, May, 1959
AT&T Co Standard

COIL CASES

WELDED STEEL CASE DATA

AERIAL, UNDERGROUND AND BURIED

1. GENERAL

1.01 This section covers the welded steel cases potting load-
ing coils or inductors now being manufactured for use
on (1) underground cables only, (2) those intended for use on
either aerial or underground plant and (3) those used in buried
plant. Information relative to the superseded welded steel under-
ground and buried cases is also included.

1.02 The section has been reissued to cover new cases in
the 500 series; namely the 500B, 500C, 550B, 550C, and
501D cases.

2. WELDED STEEL CASE DATA

2.01 The following table lists the current standard welded
steel cases. These cases, except the 231 and 233 types,
are of cylindrical cross section and are used on either aerial
or underground cables and are supplied with pole mounting
brackets and a base plate. The pole mounting brackets may be
discarded when the case is installed in a manhole and the base
plate may be discarded when the case is attached to a pole.
The 231 and 233 types are of rectangular cross section and are
intended for use only in manholes. The table gives the dimen-
sions and weights of the cases and the diameter and gauge of
the stubs. Welded steel cases are generally installed in an
upright position but, if necessary, they may be installed in a
horizontal position.

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
124A	7-7/8	4-1/8 diam.	-	15	5-15	11/16	24
124B	13-3/8	4-1/8 diam.	-	25	16-26	17/32	24
124C	20	4-1/8 diam.	-	40	35-51	1-1/16	24
195A	9-3/8	4-1/8 diam.	-	20	2-5	3/4	24
195B	13-3/8	4-1/8 diam.	-	25	6-10	3/4	24
195C	17-7/8	4-1/8 diam.	-	30	11-15	3/4	24
209A	8-5/8	9-1/2	9-1/2	45	1-4	13/16	22
209B	12-5/8	9-1/2	9-1/2	50	5-8	1	22
210A	12-5/8	12-3/4	12-3/4	115	9-16	1-1/4	22
210B	16-3/4	12-3/4	12-3/4	140	17-24	1-7/16	22
210C	20-3/4	12-3/4	12-3/4	175	25-32	1-21/32	22
210D	24-3/4	12-3/4	12-3/4	205	33-40	1-25/32	22
210E	28-3/4	12-3/4	12-3/4	240	41-48	1-15/16	22
228A	17-1/8	6-5/8	6-5/8	67	16-51	1-1/8	24
228B	25-3/4	6-5/8	6-5/8	92	60-101	1-7/16	24
229A	18-3/4	12-3/4	12-3/4	171	152	1-11/16	24
229B	22-3/4	12-3/4	12-3/4	204	202	1-15/16	24
229C	28-3/4	12-3/4	12-3/4	263	303	2-5/16	24
230A	13	12-3/4	12-3/4	60	1	21/32	19
230B	17	12-3/4	12-3/4	80	2	23/32	19
230C	21	12-3/4	12-3/4	100	1	23/32	19
230D	23	12-3/4	12-3/4	125	4	1-1/8	19
230E	31	12-3/4	12-3/4	165	6	1-1/4	19
230F	31	12-3/4	12-3/4	165	2	1-1/8	19
230G	37	12-3/4	12-3/4	210	8	1-9/32	19

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
230H	41	12-3/4	12-3/4	230	3	1-7/32	19
230J	44	12-3/4	12-3/4	260	10	1-13/32	19
†231A	17	20-1/2	20-1/2	325	12	1-17/32	19
†231B	17	20-1/2	20-1/2	325	4	1-9/32	19
†231C	20-1/2	20-1/2	20-1/2	440	5	1-13/32	19
†231D	20-1/2	20-1/2	20-1/2	440	16	1-29/32	19
†231E	24	20-1/2	20-1/2	525	6	1-17/32	19
†231F	27-1/2	20-1/2	20-1/2	640	8	1-29/32	19
†233A	27-1/2	20-1/2	20-1/2	285	2-5	2-9/32	19
†233B	27-1/2	20-1/2	20-1/2	360	6-10	2-9/32	19
235A	22	6-5/8	6-5/8	80	60-101	1-7/16	24
235B	29-1/2	6-5/8	6-5/8	105	152	1-23/32	24
236A	16-1/2	12-3/4	12-3/4	130	202	1-15/16	24
236B	20	12-3/4	12-3/4	175	303	2-5/16	24
236C	28-3/4	12-3/4	12-3/4	235	455	2-3/4	24
239A	12	6 Diam.		27	2-4	15/16	19
239B	17	6 Diam.		38	5 or 6	1-1/16	19
239C	20-1/2	6 Diam.		53	7-10	1-5/32	19
500A	21	8-1/2	8-1/2	125	27-51	1-11/32	24
500B	17	8-1/2	8-1/2	100	16-26	1-3/32	24
500C	27-1/2	8-1/2	8-1/2	150	52-76	1-9/16	24
501A	21-1/4	12-3/4	12-3/4	200	77-101	1-11/16	24
501B	23-1/4	12-3/4	12-3/4	240	152	1-31/32	24
501C	27-1/4	12-3/4	12-3/4	300	160-202	2-7/32	24
501D	37-1/4	12	12-3/4	400	303	2-11/16	24

† These cases are intended for loading only underground cables

2.02 The following table lists the superseded welded steel cases that are suitable only for loading underground cables in manholes.

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
59A	23	13-3/4	18-7/8	550	10	1-7/16	19
59B	27-5/8	13-3/4	18-7/8	625	14	1-1/2	19
59C	33-1/8	13-3/4	18-7/8	705	24	1-29/32	19
59D	37-3/4	13-3/4	18-7/8	815	28	2	19
59E	42-7/16	13-3/4	18-7/8	915	36	2-3/16	19
60A	42-7/16	13-3/4	24-1/8	1,140	46	2-5/16	19
60B	47-15/16	13-3/4	24-1/8	1,300	56	2-1/2	19
61A	42-7/16	18-7/8	24-1/8	1,625	72	2-11/32	22
61B	47-15/16	18-7/8	24-1/8	1,810	84	2-1/2	22
62A	10-11/16	7-9/16 diam.		115	1	9/16	19
62B	14-11/16	7-9/16 diam.		140	2	21/32	19
62C	19-15/16	7-9/16 diam.		170	3	3/4	19
62D	41-11/16	7-9/16 diam.		245	7	1-1/8	19
63A	37-1/4	7-9/16 diam.		235	25	29/32	22
64A	22-7/8	12-3/16	12-1/16	325	50	1-5/32	22
64B	38-1/8	12-3/16	12-1/16	550	100	1-5/8	22
65A	48-1/2	16-3/4	12-1/16	820	200	2-1/8	22
66A	49-1/2	16-3/4	16-7/8	1,160	300	2-17/32	22
67A	15-3/4	8-3/4 diam.		160	25	29/32	22
67B	23-3/16	8-3/4 diam.		210	50	1-5/32	22
67C	39	8-3/4 diam.		300	100	1-5/8	22
68A	32-1/2	9-11/16	16-1/8	485	200	2-1/8	22

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
68B	45	9-11/16	16-1/8	645	300	2-17/32	22
69A	36-3/8	16-1/4	16-1/8	850	450	2-21/32	24
69B	44	16-1/4	16-1/8	1,115	600	(2) 2-1/4	24
70A	33-1/2	21-1/4	21-1/4	1,205	8	2-5/16	16
70B	40-1/2	21-1/4	21-1/4	1,400	8	2-5/16	16
70C	33-1/2	21-1/4	21-1/4	1,240	6	2-1/16	16
71A	9	14-1/2	13-3/4	130	1	23/32	16
71AG	9	14-1/2	13-3/4	117	1	23/32	16
71B	12-3/4	14-1/2	13-3/4	170	2	29/32	16
71BG	12-3/4	14-1/2	13-3/4	153	2	29/32	16
71C	16	14-1/2	13-3/4	200	1	29/32	16
71CG	16	14-1/2	13-3/4	180	1	29/32	16
71D	19-1/2	14-1/2	13-3/4	250	1	29/32	16
71DG	19-1/2	14-1/2	13-3/4	225	1	29/32	16
71E	23	14-1/2	13-3/4	300	1	29/32	16
71EG	23	14-1/2	13-3/4	270	1	29/32	16
71F	20	14-1/2	13-3/4	265	4	1-9/16	16
71FG	20	14-1/2	13-3/4	240	4	1-9/16	16
71G	26-1/2	14-1/2	13-3/4	340	6	1-11/16	16
71GG	26-1/2	14-1/2	13-3/4	305	6	1-11/16	16
71H	26-1/2	14-1/2	13-3/4	350	2	1-9/16	16
71HG	26-1/2	14-1/2	13-3/4	315	2	1-9/16	16
71J	33-1/2	14-1/2	13-3/4	400	8	1-13/16	16

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
71JG	33-1/2	14-1/2	13-3/4	360	8	1-13/16	16
71K	33-1/2	14-1/2	13-3/4	390	2	1-9/16	16
71KG	33-1/2	14-1/2	13-3/4	350	2	1-9/16	16
71L	37	14-1/2	13-3/4	440	3	1-11/16	16
71LG	37	14-1/2	13-3/4	400	3	1-11/16	16
71M	40-1/2	14-1/2	13-3/4	490	10	1-15/16	16
71MG	40-1/2	14-1/2	13-3/4	450	10	1-15/16	16
71N	40-1/2	14-1/2	13-3/4	475	2	1-9/16	16
71NG	40-1/2	14-1/2	13-3/4	430	2	1-9/16	16
71P	47-1/2	14-1/2	13-3/4	585	12	2-1/16	16
71PG	47-1/2	14-1/2	13-3/4	515	12	2-1/16	16
71R	47-1/2	14-1/2	13-3/4	575	4	1-13/16	16
71RG	47-1/2	14-1/2	13-3/4	505	4	1-13/16	16
71S	47-1/2	14-1/2	13-3/4	565	3	1-11/16	16
71SG	47-1/2	14-1/2	13-3/4	500	3	1-11/16	16
71T	54-1/4	14-1/2	13-3/4	690	3	1-11/16	16
71U	54-1/4	14-1/2	13-3/4	620	5	1-15/16	16
77A	34	13-1/4	23-3/4	750	16	2-5/16	16
77AG	34	13-1/4	23-3/4	690	16	2-5/16	16
77B	34	13-1/4	23-3/4	720	4	1-13/16	16
77BG	34	13-1/4	23-3/4	650	4	1-13/16	16
77C	37-1/2	13-1/4	23-3/4	820	6	2-1/16	16
77CG	37-1/2	13-1/4	23-3/4	735	6	2-1/16	16

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
77D	41	13-1/4	23-3/4	895	5	1-15/16	16
77DG	41	13-1/4	23-3/4	800	5	1-15/16	16
77E	41	13-1/4	23-3/4	865	4	1-13/16	16
77EG	41	13-1/4	23-3/4	775	4	1-13/16	16
77F	48	13-1/4	23-3/4	1,085	6	2-1/16	16
77FG	48	13-1/4	23-3/4	970	6	2-1/16	16
77G	48	13-1/4	23-3/4	1,085	8	2-5/16	16
77GG	48	13-1/4	23-3/4	970	8	2-5/16	16
77H	51	13-1/4	23-3/4	1,115	5	1-15/16	16
77HG	51	13-1/4	23-3/4	1,000	5	1-15/16	16
77J	54-1/2	13-1/4	23-3/4	1,300	6	2-1/16	16
77K	34	13-1/4	23-3/4	735	3	1-11/16	16
77KG	34	13-1/4	23-3/4	645	3	1-11/16	16
77L	34	13-1/4	23-3/4	740	5	1-15/16	16
77LG	34	13-1/4	23-3/4	650	5	1-15/16	16
84A	23	7-9/16	8-3/16	190	6	1-7/32	16
84B	12-1/4	7-9/16	8-3/16	140	2	7/8	16
84C	17-5/8	7-9/16	8-3/16	165	4	1-1/16	16
86A	31-1/2	8-11/16	10	375	12	1-3/4	16
88A	5-11/16	3-9/16	5-5/8	25	1	9/16	16
90A	52-1/4	16-1/4	19-3/8	1,700	900	(2) 2-21/32	24
92A	8-5/8	5-7/8 diam.		32	5	9/16	22
92B	13-1/4	5-7/8 diam.		44	10	21/32	22
92C	17-7/8	5-7/8 diam.		59	15	3/4	22

COIL CASES
WELDED STEEL CASE DATA
AERIAL, UNDERGROUND AND BURIED

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable		
						Diam. (Inches)	Gauge	
200A	10-5/8	8-3/4 diam.	9-5/8	130	1	9/16	19	
200B	14-11/16			8-1/8	190	2	21/32	19
200C	19			8-1/8	245	3	3/4	19
200D	40-5/8			8-1/8	410	4-8	1-3/16	19
200E	49-1/4			8-1/8	460	9-10	1-7/16	19
201A	34-7/8	11-7/8	11-3/8	600	11-14	1-1/2	19	
201B	43-1/2	11-7/8	11-3/8	710	15-18	1-5/8	19	
202A	26-1/4	11-1/8	25-1/4	805	19-24	1-29/32	19	
202B	34-7/8	11-1/8	25-1/4	1,000	25-34	2-5/32	19	
202C	43-1/2	11-1/8	25-1/4	1,190	35-44	2-5/16	19	
202D	52-1/8	11-1/8	25-1/4	1,385	45-54	2-1/2	19	
203A	35	15-5/8	26-3/8	1,475	55-68	2-5/16	22	
203B	39-1/4	15-5/8	26-3/8	1,615	69-78	2-7/16	22	
203C	43-1/2	15-5/8	26-3/8	1,765	79-88	2-17/32	22	
203D	47-7/8	15-5/8	26-3/8	1,930	89-98	(2) 2-1/4	19	
203E	52-1/4	15-5/8	26-3/8	2,075	99-108	(2) 2-11/32	19	
204A	18-1/2	9-1/2	12	250	4-8	1-3/16	19	
204AG	18-1/2	9-1/2	12	225	4-8	1-3/16	19	
204B	22	9-1/2	12	290	9-10	1-7/16	19	
204BG	22	9-1/2	12	260	9-10	1-7/16	19	
204C	29	9-1/2	12	370	11-14	1-1/2	19	
204CG	29	9-1/2	12	330	11-14	1-1/2	19	
204D	36	9-1/2	12	450	15-18	1-5/8	19	
204DG	36	9-1/2	12	405	15-18	1-5/8	19	

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
205A	20	15	20-1/4	560	19-24	1-29/32	19
205AG	20	15	20-1/4	500	19-24	1-29/32	19
205B	24	15	20-1/4	650	25-30	2-3/32	19
205BG	24	15	20-1/4	580	25-30	2-3/32	19
205C	28-1/2	15	20-1/4	750	31-36	2-3/16	19
205CG	28-1/2	15	20-1/4	690	31-36	2-3/16	19
205D	32	15	20-1/4	840	37-42	2-9/32	19
205DG	32	15	20-1/4	760	37-42	2-9/32	19
206A	24	15	26	940	43-50	2-13/32	19
206AG	24	15	26	855	43-50	2-13/32	19
206B	28-1/2	15	26	1,040	51-60	2-3/16	22
206BG	28-1/2	15	26	930	51-60	2-3/16	22
206C	32	15	26	1,150	61-70	2-11/32	22
206CG	32	15	26	1,030	61-70	2-11/32	22
206D	35-1/2	15	26	1,250	71-80	2-15/32	22
206DG	35-1/2	15	26	1,120	71-80	2-15/32	22
208A	12-1/4	9-1/4	9-1/4	95	7-12	1-19/32	19
208B	16-3/8	9-1/4	9-1/4	110	13-18	1-3/4	19
208C	20-3/8	9-1/4	9-1/4	135	19-24	1-29/32	19
208D	24-1/4	9-1/4	9-1/4	165	25-30	2-3/32	19
208E	28-1/4	9-1/4	9-1/4	190	31-36	2-3/16	19
208F	32-1/4	9-1/4	9-1/4	215	37-42	2-9/32	19
208G	36-1/4	9-1/4	9-1/4	240	43-48	2-7/16	19
220A	12-1/2	8-3/4	19-1/4	280	100	1-5/8	22

COIL CASES
WELDED STEEL CASE DATA
AERIAL, UNDERGROUND AND BURIED

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
220B	16-1/2	8-3/4	19-1/4	300	150	1-29/32	22
220C	20-1/2	8-3/4	19-1/4	360	200	2-1/8	22
220D	28	8-3/4	19-1/4	450	300	2-17/32	22
220E	39	8-3/4	19-1/4	600	450	2-21/32	24
221A	22	9-1/2	12	290	50	1-5/32	22
221AG	22	9-1/2	12	260	50	1-5/32	22
222A	20	15	18-1/2	540	100	1-5/8	22
222AG	20	15	18-1/2	470	100	1-5/8	22
222B	24	15	18-1/2	650	150	1-29/32	22
222BG	24	15	18-1/2	590	150	1-29/32	22
222C	32	15	18-1/2	810	200	2-1/8	22
222CG	32	15	18-1/2	760	200	2-1/8	22
223A	28-1/2	15	25-1/2	1,040	300	2-17/32	22
223AG	28-1/2	15	25-1/2	950	300	2-17/32	22
225A	17-3/4	6-1/4	6-1/4	105	75-100	1-3/8	24
225B	25	6-1/4	6-1/4	110	152	1-29/32	22
225C	32-1/4	6-1/4	6-1/4	135	202	2-1/5	22
226A	26-1/4	8	8	160	303	2-17/32	22
226B	37-1/4	8	8	195	455	2-3/4	24
252A	30	16-1/4	21	350	6-7	2-3/32	19
252B	27-1/2	16-1/4	24-1/2	440	9-10	2-11/32	19
252C	28	16-1/4	14	180	2-4	2-1/8	19

3. WELDED STEEL BURIED CASE DATA

3.01 The following table lists the standard buried welded steel loading coil cases as well as the superseded types. The table gives the dimensions and weights of the cases and the diameter and gauge of the stubs. The asterisks (*) indicate the current standard cases.

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
258A	12-1/4	9-1/4	9-1/4	110	7-12	1-19/32	19
258B	16-3/8	9-1/4	9-1/4	125	13-18	1-3/4	19
258C	20-3/8	9-1/4	9-1/4	150	19-24	1-29/32	19
258D	24-1/4	9-1/4	9-1/4	180	25-30	2-3/32	19
258E	28-1/4	9-1/4	9-1/4	205	31-36	2-3/16	19
258F	32-1/4	9-1/4	9-1/4	230	37-42	2-9/32	19
258G	36-1/4	9-1/4	9-1/4	255	43-48	2-7/16	19
*259A	8-5/8	9-1/2	9-1/2	50	1-4	13/16	22
*259B	12-5/8	9-1/2	9-1/2	65	5-8	1	22
*260A	12-5/8	12-3/4	12-3/4	125	9-16	1-1/4	22
*260B	16-3/4	12-3/4	12-3/4	150	17-24	1-7/16	22
*260C	20-3/4	12-3/4	12-3/4	190	25-32	1-21/32	22
*260D	24-3/4	12-3/4	12-3/4	225	33-40	1-25/32	22
*260E	28-3/4	12-3/4	12-3/4	260	41-48	1-15/16	22
*261A	16	9-1/2	9-1/2	55	1-4	15/16	19
*261B	20	9-1/2	9-1/2	70	5-8	1-1/8	19
*262A	20-3/4	12-3/4	12-3/4	130	9-16	1-3/8	19
*262B	24-3/4	12-3/4	12-3/4	160	17-24	1-19/32	19
*262C	28-3/4	12-3/4	12-3/4	200	25-32	1-25/32	19

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
*262D	32-3/4	12-3/4	12-3/4	235	33-40	1-15/16	19
*262E	36-3/4	12-3/4	12-3/4	275	41-48	2-1/16	19
*274B	13-3/8	4-1/8 diam.		35	16-26	15/16	24
*274C	19-7/8	4-1/8 diam.		50	35-51	1-1/8	24
*278A	17-1/8	6-5/8	6-5/8	72	16-51	1-1/8	24
*278B	25-3/4	6-5/8	6-5/8	100	60-101	1-7/16	24
*280A	13	12-3/4	12-3/4	65	1	21/32	19
*280B	17-1/4	12-3/4	12-3/4	85	2	23/32	19
*280C	21-1/4	12-3/4	12-3/4	105	1	23/32	19
*280D	23-1/4	12-3/4	12-3/4	130	4	1-1/8	19
*280E	31-1/4	12-3/4	12-3/4	175	6	1-1/4	19
*280F	31-1/4	12-3/4	12-3/4	175	2	1-1/8	19
*280G	37-1/4	12-3/4	12-3/4	220	8	1-9/32	19
*280H	41-1/4	12-3/4	12-3/4	240	3	1-7/32	19
*280J	44	12-3/4	12-3/4	270	10	1-13/32	19
*281A	17	20-1/2	20-1/2	330	12	1-17/32	19
*281B	17	20-1/2	20-1/2	330	4	1-9/32	19
*281C	20-1/2	20-1/2	20-1/2	450	5	1-13/32	19
*281D	20-1/2	20-1/2	20-1/2	450	16	1-29/32	19
*281E	24	20-1/2	20-1/2	545	6	1-17/32	19
*281F	27-1/2	20-1/2	20-1/2	650	8	1-29/32	19
*285A	22	6-5/8	6-5/8	85	60-101	1-7/16	24

Code Designation	Approx. Height (Inches)	Approx. Thickness (Inches)	Approx. Width (Inches)	Approx. Weight (Pounds)	No. of Coils or Units	Stub Cable	
						Diam. (Inches)	Gauge
*285B	29-1/2	6-5/8	6-5/8	110	152	1-23/32	24
*286A	16-1/2	12-3/4	12-3/4	135	202	1-15/16	24
*286B	20	12-3/4	12-3/4	180	303	2-5/16	24
*287A	22-1/4	6-5/8	6-5/8	60	16-51	1-1/8	24
*287B	29-1/2	6-5/8	6-5/8	100	60-101	1-7/16	24
*288A	19-1/2	12-3/4	12-3/4	130	152	1-23/32	24
*288B	23-7/8	12-3/4	12-3/4	160	160-202	1-15/16	24
*288C	30-1/4	12-3/4	12-3/4	200	303	2-5/16	24
*289A	12	6 Diam.		27	2-4	15/16	19
*289B	17	6 Diam.		38	5 or 6	1-1/16	19
*289C	20-3/4	6 Diam.		53	7-10	1-5/32	19
*291A	17	6 Diam.		35	2-4	1-1/16	19
*291B	20-3/4	6 Diam.		45	5 or 6	1-3/16	19
*291C	26	6 Diam.		60	7-10	1-5/16	19
295B	13-3/8	4-1/8 Diam.		29	6-10	3/4	24
295C	17-7/8	4-1/8 Diam.		35	11-15	3/4	24
*550A	21	8-1/2	8-1/2	130	27-51	1-11/32	24
*550B	17	8-1/2	8-1/2	105	16-26	1-3/32	24
*550C	27-1/2	8-1/2	8-1/2	155	52-76	1-9/16	24
*551A	21-1/4	12-3/4	12-3/4	200	77-101	1-11/16	24
*551B	23-1/4	12-3/4	12-3/4	240	152	1-31/32	24
*551C	27-1/4	12-3/4	12-3/4	300	160-202	2-7/32	24

COIL CASES
WELDED STEEL CASE DATA
AERIAL, UNDERGROUND AND BURIED

659.010.3

Page 13
13 Pages