

POLE DOLLY

NOTES CONCERNING THIS ADDENDUM

This addendum has been reissued to include in these instructions the turntable pole dolly and the rigid top pole dolly now in use in this area.

The following should be marked "See Addendum" and be treated as indicated:

- Paragraph 1.03 - Added
- Paragraph 2.04 - Added
- Paragraph 3.02 - Supplemented
- Paragraph 3.03 - Supplemented
- Paragraph 3.06 - Added
- Paragraph 3.07 - Added
- Paragraph 3.08 - Added
- Paragraph 4.01 - Supplemented
- Paragraph 4.02 - Supplemented
- Paragraph 4.07 - Supplemented
- Paragraph 4.10 - Added

1. GENERAL

- 1.03 The instructions covering the operation of the pole dolly in this practice shall also be applied to the turntable and rigid top pole dollies now in general use in this area with the exceptions noted in this addendum.

Note: The turntable pole dolly is for use in confining locations, where the rigid top pole dolly cannot be used.

2. SAFETY PRECAUTIONS

- 2.04 Extreme care should be exercised when loading and unloading pole dollies from truck to avoid personal injury or damage to other equipment.

3. DESCRIPTION AND NAMES OF PARTS

- 3.02 When the pole dolly is not equipped with a chain tightening clamp, a chain hoist shall be employed to lash the pole to the dolly.
- 3.03 The handle bar shall not be used for pushing the loaded dolly on grades or over uneven ground. See Paragraph 4.07 of this addendum for the methods to be used under these conditions.
- 3.06 The turntable pole dolly is equipped with a turntable which will turn approximately 6-1/2 inches to either the left or right position.
- 3.07 The upper pin in the center leg of the turntable dolly is to keep the turntable in a rigid position.
- 3.08 The lower pin in the center leg of the turntable dolly is to allow the turntable to turn only approximately 6-1/2 inches to either the left or right position.

4. OPERATION

- 4.01 When loading a pole on the turntable dolly the top or stationary pin shall be in position at all times.
- 4.02 Everyone shall stand clear of pole dollies while a pole is being lowered into position. In particular no one shall hold the handle of the dolly during this operation.
- 4.07 When transporting poles on all types of pole dollies on grades or rough terrain, the movement and direction of the dolly shall be controlled from the end of the pole. Rope slings may be used to pull the load. This precaution shall be taken whenever there is a possibility of the dolly tipping.
- 4.10 When it is necessary to maneuver a loaded turntable dolly through a confining location the top pin in the center leg shall be removed to allow table to turn either to the left or right position.