

SEQUENCE CHART

SENDER SELECTION	TR KEY	OPERATED
*S-(SL)	*TR	(POS)
*SCI	*TR	(POS)
*ON1	*SC2	*ST (POS)
*SB-(SU)	*FO-F9	*ROI (POS)
*ON2		*R02 (POS)
*TC1		
*TC2		

HUNTING IDLE POSITION

*OA/OB	*FOO/FIO
*PB	*SR
*P	*STPB
*DT (IDLE POS)	
*SR	
*PF	
*PFI	*PD (POS)
*XC	*CI
	*LK LAMP FLASHING

BATTERY ON H LEAD

TO SHEET 2



NOTES:  
 1. AN OPERATED PB RELAY PREVENTS SENDER HUNTING BY OPENING THE H LEAD AND P RELAY PATH AS SHOWN ON SHEET 1.  
 2. REFER TO SC103-1 FOR SEQUENCE CHART.

- |   |              |         |
|---|--------------|---------|
| KEY SET TRANSFER                            | SD-55992-01, | ISS. 3  |
| POSITION BUSY AND NIGHT ALARM CKT.          | SD-21139-01, | ISS. 22 |
| CORD CKT.                                   | SD-64737-01, | ISS. 9  |
| GROUPING CKT.                               | SD-64740-01, | ISS. 10 |
| INCOMING TRUNK CKT.                         | SD-25875-01, | ISS. 2  |
| KEY AND LAMP CKT.                           | SD-56029-01, | ISS. 6  |
| OPERATOR'S TELEPHONE CKT. (TOLL)            | SD-55110-01, | ISS. 14 |
| POSITION CKT.                               | SD-55996-01, | ISS. 6  |
| *SENDER AND POSITION FINDER CKT.            | SD-25014-01, | ISS. 25 |
| TERMINATING SENDER LINK AND CONTROLLER CKT. | SD-25459-01, | ISS. 18 |





"B" SWITCHBOARD  
 COMBINED TOLL-DSA-DSB POSITION

ISSUE	1	DATE	9-16-50
-------	---	------	---------

ISSUE	1	NAME	
DATE	3-16-70		



'B' SWITCHBOARD COMBINED TOLL-DSA-DSB POSITION




"B" SWITCHBOARD  
COMBINED TOLL-DSA-DSB POSITION


4 SHEETS, SHEET 3 MP-11512

ISSUE 1	MARKED
DATE	5-16-50

### SENDER AND POSITION FINDER CIRCUIT



### NIGHT (CALL WAITING) ALARM



\*B\* SWITCHBOARD  
COMBINED TOLL-DSA-DSB POSITION