



Carrier VoIP

CS2000 Core Manager Performance Management

Document status: Standard
Document version: 08.02
Document date: 20 October 2006

Copyright © 2006, Nortel Networks
All Rights Reserved.

The information in this document is sourced in Canada, the United States of America, and the United Kingdom.

This is the Way, This is Nortel, Nortel, the Nortel logo, the globemark design, and the NORTEL NETWORKS corporate logo, are trademarks of Nortel Networks. All other trademarks are the property of their respective owners. All rights reserved.

Contents

Core and Billing Manager 850 Performance Management	5
Starting the OMUI	7
Adding a report element	9
Adding a data collection schedule	16
Adding a file rotation schedule	21
Adding a file transfer destination	27
Adding a file transfer schedule	32
Adding a report registration	38
Adding OM groups to a report element	42
Adding a register to an existing OM group in a report element	49
Deleting a data collection schedule	58
Deleting a file rotation schedule	61
Deleting a file transfer destination	64
Deleting a report element	67
Deleting a report registration	70
Deleting a register from an existing OM group in a report element	73
Deleting a file transfer schedule	81
Deleting OM groups from a report element	84
Listing data collection schedules	89
Listing file rotation schedules	93
Listing a file transfer destination	97
Listing a file transfer schedule	101
Listing report element information	104
Listing report registrations	109
Modifying a data collection schedule	113
Modifying a file rotation schedule	118
Modifying a file transfer destination	124
Modifying a file transfer schedule	130
Modifying OM groups in a report element	136
Setting the file retention period	139
Setting the report registration limit	142
Quitting the OMUI	145

4 Contents

Core Manager Performance Management

New in this release for Core Manager Performance Management in SN09U

The following sections detail what's new in the Core and Billing Manager 850 Performance Management document:

- ["Features"](#) (page 5)
- ["Other changes"](#) (page 6)

Features

The following feature-related changes have been made in the documentation:

- With the addition of new role groups, the CBM user group improvements feature allows you to perform CBM maintenance procedures without having to be the root user. The CBM user group improvements feature required changes to the procedures that require new authorization level and access:
 - addition of a statement in the prerequisites section indicating the authorization level required to complete the procedure
 - if non-restricted shell access is required to complete the procedure, addition of a statement in the prerequisites section indicating that non-restricted shell access is required
 - addition of a table in the prerequisites section listing procedures relating to authorization level and access
- The Passphrase Protected Keys for SSH feature required additions/changes to the following procedures:
 - ["Listing a file transfer destination"](#) (page 97), to show the Transfer Type in the example as Secure-Password, and Secure-Key
 - ["Adding a file transfer destination"](#) (page 27), to show the choice of either password-based authentication, or key-based authentication

- "Modifying a file transfer destination" (page 124), to show the choice of either password-based authentication, or key-based authentication

Other changes

There are no other changes for this release.

Performance management strategy

Performance Management strategy consists of collecting and reporting on operational measurements. The Operational Measurement Delivery (OMD) application is the primary core manager component that supports performance management.

The primary performance management utility is the OMD application. Operational measurement data is grouped into user-defined report elements, formatted into comma-separated value (CSV) format, and delivered to a customer operations support system (OSS).

Specific procedures for performance management through the OMD application are provided in this document.

Starting the OMUI

Purpose

Use the following procedure to start the Operational Measurements User Interface (OMUI).

Prerequisites

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Starting the OMUI

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|--|
| 1 | Log into the core manager. |
| 2 | Start the OMUI:
<code>omui</code>
The OM Delivery Main menu appears. |

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

3 You have completed this procedure.

—End—

Adding a report element

Purpose

Use this procedure to add a report element.

Prerequisites

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Adding a report element

To add a new report element, you must specify the information in the following table.

Component	Description
Report element name	User-defined name of the report element to be added (max. 20 alphanumeric, dash, and underscore characters)
OM group name	Name of a valid OM group to be added to the report element
Reporting interval	Interval between OM reports (either 5 minutes, or office transfer period)
Register	Name the registers of OM groups to be included in the report. For more information, refer to "Operational Measurements Delivery Overview" in the CBM Basics document.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Adding a report element

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Display the Report Element Main Menu:

1

Example response:

```
Report Element Main Menu

1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >
```

4 Add a new report element:

2

Example response:

```

Add Report Element
Type "EXIT" to return to previous menu
Report Element name >
    
```

5 Enter the report element name.

The name can be a maximum of 20 alphanumeric, dash, and underscore characters.

Example response:

```
Reporting Interval (1=FIVE, 2=TRANSFER) >
```

6 Determine the reporting interval.

If you want to set the reporting interval to	Do
five minutes	enter 1
the office transfer period	enter 2

Example response:

```
OM Group Name >
```

7

ATTENTION

If you do not know the name of the OM group, press the Enter key and type n at the system prompt. Identify the name of the OM group and repeat this procedure.

Enter the OM group name.

If the response is	Do
Register or All >	step 8
Non-subtraction register >	step 12

- 8 You set the reporting interval to the office transfer period.

If you	Do
want to add a register	step 9
want to add all registers	step 10
do not want to add a register	press the Enter key, and go to step 19

- 9 Enter the name of the register.

Example response:

Register or All >

If you	Do
want to add another register	repeat step 9
want to add all registers	step 10
do not want to add another registers	press the Enter key, and go to step 19

- 10 Add all the registers of the OM group:

all

Example response:

<n> registers have been added >

where

<n> is the number of registers in the OM group

- 11 Press the Enter key and go to step 19.

- 12 You set the reporting interval to five minutes.

If you	Do
want to add a non-subtraction register	step 13
do not want to add a non-subtraction register	step 14

- 13 Enter the name of the non-subtraction register.

Example response:

Non-subtraction register >

If you	Do
want to add another non-subtraction register	repeat step 13
do not want to add another non-subtraction register	step 14

- 14 Press the Enter key.

Example response:

Single subtraction register >

If you	Do
want to add a single subtraction register	step 15
do not want to add a single subtraction register	step 16

- 15 Enter the name of the single subtraction register.

Example response:

Single subtraction register >

If you	Do
want to add another single subtraction register	repeat step 15
do not want to add another single subtraction register	step 16

- 16 Press the Enter key.

Example response:

Double subtraction register (base) >

If you	Do
want to add the base of a double subtraction register	step 17
do not want to add the base of a double subtraction register	step 19

- 17 Type the name of the base register.

Example response:

Double subtraction register (ext) >

- 18 Enter the name of the extension (ext) register.

To use the double subtraction register, you must enter a base and extension register name. Each register must use different register names.

Example response:

Double subtraction register (base) >

If you	Do
want to add another double subtraction register	step 17
do not want to add another double subtraction register	step 19

19 Press the Enter key.

Example response:

Add OM group (Y/N) ?

If you	Do
want to add the OM group to this report element	enter y
do not want to add the OM group to this report element	enter n

20 Press the Enter key.

Example response:

OM group name>

If you	Do
want to add another OM group to this report element	step 7
do not want to add another OM group to this report element	step 21

21 Press the Enter key.

Example response:

Add report element (Y/N) ?

If you	Do
want to add the new report element	step 22
do not want to add the new report element	type n and go to step 23

22 Confirm that you have chosen to add the report element:

y

Example response:

```
Please wait...  
RE1: the request was successful  
Press Enter for Report Element Menu
```

- 23** Press the Enter key to return to the Report Element Menu.

Example response:

```
Report Element Main Menu  
  
1. List Report Elements  
2. Add Report Elements  
3. Delete Report Elements  
4. Modify Report Elements  
5. Help  
6. Return to Main Menu  
  
Select Option >
```

- 24** Return to the OM Delivery Main Menu:

6

- 25** You have completed this procedure.

—End—

Adding a data collection schedule

Purpose

Use this procedure to add a data collection schedule.

Procedure	Document
Logging in to the CS 2000 Core Manager	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611
Displaying information about a user or role group	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

The name of the data collection schedule can include up to 20 alphanumeric, dash, and underscore characters. The data can be collected daily, weekly, or monthly. You must also specify the start and stop times for the specified dates.

You cannot specify a start time of 2400. Valid entities for stop times include 0000 and 2400. The start time must always be less than the stop time unless the stop time is 0000.

When a data collection schedule is configured, the start time and stop times are used to determine the time period over which the OM report collections takes place. The collecting interval determines how often within the time period an OM report is collected.

For example, for a data collection schedule of 0400 to 0500 (4:00 am to 5:00 am), with a 5-minute collecting interval, the first OM report collection takes place at 0405. It contains OM data for the report period of 0400 to 0405. The last OM report collection takes place at 0500, and contains OM data for the report period of 0455 to 0500. This creates a true picture of all the OM data that is generated between 4:00 am and 5:00 am.

Refer to the table "Data collection schedules" (page 17) for information about variables you need to specify when you create a data collection schedule.

Data collection schedules

Repetition	Schedule information
Daily	Daily repetition includes the start and stop time of the day. The start and stop times need to be in the format of hhmm, where hh stands for the hour (from 00 to 24) and mm stands for the minute (00 or 30). Only a single time period can be specified within the schedule. Multiple times periods within the same day require defining multiple schedules.
Weekly	Days of the week are Sunday, Monday, Tuesday, Wednesday, Thursday, Friday, and Saturday. Start time and stop time must be in the hhmm format (see daily repetition). Multiple days of the week can be specified within the same schedule.
Monthly	Days of the month can be any days from the 1st to the 31st. Start time and stop time must be in the hhmm format (see daily repetition). Multiple days in the month can be specified within the schedule.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Adding a data collection schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- 1 Log into the core manager.
- 2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Access the Data Collection Schedule Menu:

2

Example response:

```
Data Collection Schedule

1. List Data Collection Schedule
2. Add Data Collection Schedule
3. Delete Data Collection Schedule
4. Modify Data Collection Schedule
5. Help
6. Return to Main Menu

Select Option >
```

4 Add a new data collection schedule:

2

Example response:

```
Add Data Collection Schedule

Type "EXIT" to return to previous menu

Data Collection Schedule name >
```

5 Enter the data collection schedule name (you can use up to 20 alphanumeric characters, dash, and underscore characters).

Example response:

Repetition (1 = DAILY, 2 = WEEKLY, 3 = MONTHLY) >

If you want to add a data collection schedule with a	Do
daily repetition rate (schedule collections once each day)	step 6
weekly repetition rate (schedule collection once each week)	step 8
monthly repetition rate (schedule collections on the same day each month)	step 11

- 6** Create a data collection schedule based on a daily interval. Set a daily repetition rate:

1

Example response:

Start time (HHMM) >

- 7** Go to step 13.

- 8** Create a data collection schedule based on a weekly interval. Set a weekly repetition rate:

2

Example response:

Day of Week (1 = Monday, 2 = Tuesday, ..., 7 = Sunday) >

- 9** Enter the number for the day of the week that you have chosen for data collection to take place.

Example response:

Start time (HHMM) >

- 10** Go to step 13.

- 11** Create a data collection schedule based on a monthly interval. Set a monthly repetition rate:

3

Example response:

Day of the Month (1-31) >

- 12** Enter the number for the day of the month to collect data.

To specify multiple days of the month to collect data, separate days with a comma.

Example response:

Start time (HHMM) >

- 13 Enter the time of day to start collecting data.

Example response:

```
Stop time (HHMM) >
```

- 14 Enter the time of day to stop collecting data.

Example response:

```
Add Data Collection Schedule (Y/N) ?
```

- 15 Confirm your choice to add the data collection schedule:

```
y
```

Example response:

```
Please wait...
dcsname: The request was successful.
Press Enter for Data Collection Schedule Menu.
```

- 16 Press the Enter key to return to the Data Collection Schedule Menu.

The OMUI displays the following screen:

```
                Data Collection Schedule

1. List Data Collection Schedule
2. Add Data Collection Schedule
3. Delete Data Collection Schedule
4. Modify Data Collection Schedule
5. Help
6. Return to Main Menu

Select Option >
```

- 17 Return to the OM Delivery Main Menu:

```
6
```

- 18 You have completed the procedure.

—End—

Adding a file rotation schedule

Purpose

Use this procedure to add a file rotation schedule.

Prerequisites

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Application

File rotation schedules are used by report registrations to specify when to rotate report files. File rotation involves closing an open report file and moving it to the /cbmdata/00/omdata/closedNotSent directory.

To create a new file rotation schedule, you must specify the name of the schedule and how often you want the system to rotate the files. The name of the file rotation schedule can include up to 20 alphanumeric, dash, and underscore characters. The files can be rotated daily, weekly, monthly, based on the number of reports accumulated in the open file, or based on the number of hours elapsed, as described in the table "[File rotation schedule variables](#)" (page 21).

File rotation schedule variables

Variable	Schedule information
Daily	Select the time of day to rotate the report file and input in the hhmm format, where hh stands for the hour (from 00 to 24) and mm stands for the minute (00 or 30). Only a single time can be specified within the schedule. Multiple rotations within the same day require you to define multiple rotation schedules.
Weekly	Select a day of the week to rotate report files. Select the time of day to rotate the report file (see Daily). Multiple rotation days within the same week require multiple rotation schedules.

Variable	Schedule information
Monthly	Select a day of the month to rotate report files from 1 to 31.
Reports	Select the number of reports to be collected before rotating the report file.
Hours	Select the number of hours to elapse before rotating the report file.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Adding a file rotation schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OMUI Main Menu

3 Access the File Rotation Schedule Menu:

3

Example response:

```

File Rotation Schedule Menu
1. List File Rotation Schedules
2. Add File Rotation Schedule
3. Delete File Rotation Schedule
4. Modify File Rotation Schedule
5. Help
6. Return to Main Menu

Select Option >

```

4 Add a new file rotation schedule:

2

Example response:

```

Add File Rotation Schedule
Type "EXIT" to return to previous menu
File Rotation Schedule name >

```

5 Enter the file rotation schedule name and press the Enter key (you can use up to 20 alphanumeric, dash, and underscore characters).

Response:

Repetition (1=DAILY, 2=WEEKLY, 3=MONTHLY, 4=REPORTS, 5=HOURS) >

If you want a	Do
daily file rotation	step 6
weekly file rotation	step 9
monthly file rotation	step 13
rotation based on number of reports	step 17
rotation based on elapsed hours between rotation	step 20

6 Configure a daily file rotation: select a daily repetition:

1

Example response:

Rotation time (HHMM) >

7 Enter the time of day to close and rotate the report file and press the Enter key.

Example response:

Add File Rotation Schedule (Y/N)?

- 8 Go to step 22.
- 9 Configure a weekly file rotation. Select a weekly repetition:
2
Example response:
Day of Week (1=Monday, 2=Tuesday, ..., 7=Sunday)
- 10 Enter the number for the day of the week that the report file is closed and rotated.
Example response:
Rotation time (HHMM) >
- 11 Enter the time of day to close and rotate the report file and press the Enter key.
Example response:
Add File Rotation Schedule (Y/N)?
- 12 Go to step 22.
- 13 Configure a monthly file rotation. Select a monthly repetition:
3
Example response:
Day of Month (1-28, 0 is the last day of month) >
- 14 Enter the number of day of the month to rotate the report file.
Example response:
Rotation time (HHMM) >
- 15 Enter the time of day to close and rotate the report file.
Example response:
Add File Rotation Schedule (Y/N)?
- 16 Go to step 22.
- 17



CAUTION

Possible loss of service and data

Selecting a large number of reports can exhaust available file system space, resulting in lost OM data and possible loss of service. If you collect a high volume of OM reports each day, it is recommended that you reduce your file retention period for closedSent files to one day.

Configure a file rotation schedule based on the number of reports collected. Select a repetition by reports:

4

Example response:

Number of Reports >

- 18** Enter the maximum number of reports to collect before file rotation initiates (from 1 to 4032).

Example response:

Add File Rotation Schedule (Y/N)?

- 19** Go to step [22](#).

- 20** Configure a file rotation schedule based on the hours elapsed between the time an open report file is open and closed. Select rotation by hours:

5

Example response:

Number of Hours >

- 21**



CAUTION

Possible loss of service and data

Selecting a large number of hours can exhaust available file system space, resulting in lost OM data and possible loss of service. It is recommended that you select a number of hours smaller than 25. As an alternative, use the daily file rotation if you wish to record data for more than 24 hours.

Enter the number of hours that must elapse before the open report file is closed and rotated (from 1 to 999).

Example response:

Rotate on the Hour (Y/N)?

Add File Rotation Schedule (Y/N)?

- 22** Confirm that you want to add the file rotation schedule:

y

Example response:

```
Please wait...
frsname: The request was successful.
Press Enter for File Rotation Schedule Menu.
```

- 23** Press the Enter key to return to the File Rotation Schedule Menu.

Example response:

```
File Rotation Schedule Menu
1. List File Rotation Schedules
2. Add File Rotation Schedule
3. Delete File Rotation Schedule
4. Modify File Rotation Schedule
5. Help
6. Return to Main Menu

Select Option >
```

- 24** Return to the OM Delivery Main Menu:

6

- 25** You have completed this procedure.

—End—

Adding a file transfer destination

Purpose

Use the following procedure to add a new file transfer destination.

Prerequisites

You must have the root user ID and password to log into the server.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

ATTENTION

Special instruction after the customer upgrades the SDM/CBM from a previous release to 23 release:

After an upgrade of SDM/CBM to release 23, once a new File Transfer Destination is added, the customer is not advised to fallback since the old password details (stored in PDM) are re-formatted and stored as a new file. In such scenario, if the customer falls back to a previous release, the old password details (stored in PDM) would not be available as the old data file would have been deleted, and hence the customer may have to reconfigure the File Transfer Destinations in order to get the OM files transferred to downstream.

ATTENTION

Special instruction after the customer upgrades the SDM/CBM from a previous release to MTX13 release:

After an upgrade of SDM/CBM to release MTX13, once a new File Transfer Destination is added, the customer is not advised to fallback since the old password details (stored in PDM) are re-formatted and stored as a new file. In such scenario, if the customer falls back to a previous release, the old password details (stored in PDM) would not be available as the old data file would have been deleted, and hence the customer may have to reconfigure the File Transfer Destinations in order to get the OM files transferred to downstream.

ATTENTION

Special instruction after the customer upgrades the SDM/CBM from a previous release to GSM19 release:

After an upgrade of SDM/CBM to release GSM19, once a new File Transfer Destination is added, the customer is not advised to fallback since the old password details (stored in PDM) are re-formatted and stored as a new file. In such scenario, if the customer falls back to a previous release, the old password details (stored in PDM) would not be available as the old data file would have been deleted, and hence the customer may have to reconfigure the File Transfer Destinations in order to get the OM files transferred to downstream.

Procedure

Adding a file transfer destination

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OMUI Main Menu

3 Access the File Transfer Destination Main Menu:

4

Example response:

```

                                File Transfer Destination

1. List File Transfer Destinations
2. Add File Transfer Destination
3. Delete File Transfer Destination
4. Modify File Transfer Destination
5. Help
6. Return to Main Menu

Select Option >

```

4 Add a file transfer destination:

2

Example response:

```

Add file Transfer Destination
Type EXIT to return to previous menu

File Transfer Destination name >

```

- 5 Enter the name of the file transfer destination.

This name is used by the file transfer schedule option of the OMUI. The name can be up to 20 alphanumeric characters long.

Example response:

```
Destination IP Address >
```

- 6 Enter the IP address for the file transfer destination (the IP address of the computer you want to send the files to).

Example response:

```
Type of file transfer: Standard/Secure >
```

- 7 Enter the type of file transfer that you require for this destination. Enter

- **standard** for un-encrypted file transfer using the standard FTP protocol, or
- **secure** for encrypted file transfer using the OpenSSH program, sftp

Example response:

```
Type of Authentication: Password/Key >
```

- 8 Enter the type of authentication you require for the file transfer. Enter

- **Password** for password-based authentication, or
- **Key** for key-based authentication

Example response:

```
Destination Port [xx] >
```

- 9 Enter the destination port number assigned for use with the IP address you entered in [step 6](#).

The default is 21 for Standard file transfer and 22 for Secure file transfer.

Example response:

```
Destination Login >
```

- 10** Type the destination login ID you use to log on to the file transfer destination system receiving the OM files.

Example response if password-based authentication was chosen in step 8 :

```
Destination Password >
```

Example response if key-based authentication was chosen in step 8 :

```
WARNING: File Transfer to this destination will fail if
OpenSSH is not installed. Please install OpenSSH if it
is not already installed.
```

```
Add file transfer destination (Y/N) ?
```

If you	Do
chose password-based authentication in step 8	step 11
chose key-based authentication in step 8	step 12

- 11** Enter the password for the login ID.

The password for the destination system is case-sensitive.

Example response:

```
Destination Password >
```

```
WARNING: File Transfer to this destination will fail if
OpenSSH is not installed. Please install OpenSSH if it
is not already installed.
```

```
Add file transfer destination (Y/N) ?
```

Confirm that you want to add the file transfer destination:

```
y
```

Example response if password-based authentication was chosen in step 8:

```
Please wait...
ftdname: The request was successful.
Press Enter for File Transfer Destination
Menu.
```

- 12** *Example response if key-based authentication was chosen in step 8 :*

```
Please wait....
```

```
The public key is stored at: /home/maint/.ssh:ftdname
_rsa.pub
```

```
Please append this public key to the user's
authorization file on the destination machine.
```

```
ftdname: the request was successful.
```

Press Enter for File Transfer Destination menu.

ATTENTION

Adding a file transfer destination with transfer type as secure and authentication as key-based will not prompt for password.

- 13** Press the Enter key to return to the File Transfer Destination Menu.

Example response:

```
File Transfer Destination Menu

1. List File Transfer Destination
2. Add File Transfer Destination
3. Delete File Transfer Destination
4. Modify File Transfer Destination
5. Help
6. Return to Main Menu

Select Option >
```

- 14** Return to the OM Delivery Main Menu:

6

- 15** You have completed this procedure.

—End—

Adding a file transfer schedule

Purpose

Use this procedure to create a new transfer schedule to automatically send closed OM files to a remote system. A single schedule can be set up to transfer OM files to as many as 16 destinations at once.

Prerequisites

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Adding a new file transfer schedule

To add a new file transfer schedule, you must specify the following information:

- **File transfer schedule name:**
the name of the file transfer schedule to be added (you can use up to 20 alphanumeric, dash, and underscore characters).
- **Repetition:**
the frequency you choose to set to transfer the OM file. The repetition can be daily, weekly, monthly, or after a scheduled OM file rotation is completed, as indicated by the following list:
 - **Rotate time:**
specifies the time of day to transfer the report files (in multiples of 30 minutes) when the repetition is daily.
 - **Day of week:**
specifies the day of the week to rotate files when the repetition is weekly.

- Day of month:
specifies the day of the month to rotate files when the repetition is monthly.
- After rotation:
specifies that the transfer takes place after file rotation.
- File transfer destination name: the name of the file transfer destination name.

A file transfer destination must already be defined (refer to procedure ["Adding a file transfer destination" \(page 27\)](#)).

- Destination directory path:
the destination directory path on the file transfer destination system.

Procedure

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Adding a file transfer schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OMUI Main Menu

3 Access the File Transfer Schedule Main Menu:.

5

Example response:

```

File Transfer Schedule Menu

1. List File Transfer Schedule
2. Add File Transfer Schedule
3. Delete File Transfer Schedule
4. Modify File Transfer Schedule
5. Help
6. Return to Main Menu

Select Option >
    
```

4 Add a file transfer schedule:

2

Example response:

```

Add File Transfer Schedule

Type "EXIT" to return to previous menu

File Transfer Schedule name >
    
```

5 Enter the name of the file transfer schedule.

The name can be up to 20 alphanumeric characters long.

Example response:

Repetition (1=DAILY, 2=WEEKLY, 3=MONTHLY, 4=AFTER ROTATE) >

If you want to transfer files	Do
daily	step 6
weekly	step 8
monthly	step 11
immediately after a file rotation	step 14

6 Configure a daily file transfer schedule. Select daily:

1

Example response:

Time of Day (HHMM) >

7 Go to step 16 to continue.

- 8 Configure a weekly file transfer schedule. Select weekly:
2
Example response
Day of Week (1=Monday, 2=Tuesday, ... 7=Sunday) >
- 9 Enter the number for the day of the week to rotate the OM file.
Example response:
Time of Day (HHMM) >
- 10 Go to step 16.
- 11 Configure a monthly file transfer schedule. Select monthly:
3
Example response:
Day of Month (1-28, 0 is the last day of month) >
- 12 Enter the number for the day of the month to rotate the OM file. For example, 1 is for the first day of the month and 2 is for the second day of the month.
Use 0 for the last day of the month.
Example response:
Time of Day (HHMM) >
- 13 Go to step 16.
- 14 Configure a file transfer schedule that transfers OM files immediately after the files are closed and rotated. Select AFTER ROTATE:
4
Example response:
File Transfer Destination name ("quit" to exit) >
- 15 Go to step 17 to continue.
- 16 Enter the time of day to transfer the file.
Example response:
File Transfer Destination name ("quit" to exit) >
- 17 Enter the name of the file transfer destination and press the Enter key.

ATTENTION

Ensure a file transfer destination was created, and use the same FTD name. Failure to do so prevents you from creating the file transfer schedule.

Example response:

```
Destination Dir >
```

- 18** Enter the path of the destination directory where the OM files are transferred.

You must enter the full path name of the destination directory. The format for the destination is often displayed as /<destdir>/<destsubdir>.

If you are uncertain as to the proper destination directory or path on a specific machine, contact your site system administrator for assistance.

Example response:

```
File Transfer Destination name ("quit" to exit) >
```

If you	Do
want to add other destinations to this transfer schedule	step 17
do not want to add other destinations to this transfer schedule	step 19

A single schedule can be set up to transfer OM files to as many as 16 destinations at once.

- 19** Complete the file transfer schedule:

```
quit
```

Example response:

```
Add File Transfer Schedule (Y/N) ?
```

- 20** Confirm that you want to add the file transfer schedule:

```
y
```

Example response:

```
Please wait...
ftsname: The request was successful.
Press Enter for File Transfer Schedule Menu.
```

- 21** Press Enter to return to the File Transfer Schedule Menu.

Example response:

File Transfer Schedule Menu

1. List File Transfer Schedule
2. Add File Transfer Schedule
3. Delete File Transfer Schedule
4. Modify File Transfer Schedule
5. Help
6. Return to Main Menu

Select Option >

22 Return to the OM Delivery Main Menu:

6

23 You have completed the procedure.

—End—

Adding a report registration

Purpose

Use this procedure to add a report registration.

Prerequisites

Procedure	Document
Logging in to the CS 2000 Core Manager	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611
Displaying information about a user or role group	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Adding a report registration

To add a report registration, you must specify the following information:

- report registration name:
the name of the report registration can include up to 20 alphanumeric, dash, and underscore characters.
- report element name:
the name of the report element that is linked to the report registration.
- data collection schedule name:
the name of the data collection schedule that is linked to the report registration.
- file rotation schedule name:

the name of the file rotation schedule that is linked to the report registration.

- file transfer schedule name:
the name of the file transfer schedule that is linked to the report registration (optional).

You must define the report element, data collection schedule, file rotation schedule, and file transfer schedule before you can link them to a report registration. The data collection schedule, file rotation schedule, and file transfer schedule become active immediately after you add (create) the report registration.

Procedure

Use the following procedure to add a report registration.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Adding a report registration

Step	Action
<i>At the workstation UNIX prompt or VT-100 terminal prompt:</i>	
1	Log into the core manager.
2	Start the OMUI: omui The OM Delivery Main menu appears.
<div style="border: 1px solid black; border-radius: 15px; padding: 10px; margin: 10px 0;"> <p style="text-align: center;">OM Delivery Main Menu</p> <ol style="list-style-type: none"> 1. Report Element 2. Data Collection Schedule 3. File Rotation Schedule 4. File Transfer Destination 5. File Transfer Schedule 6. Report Registration 7. Set File Retention Period 8. Set Report Registration Limit 9. Help 10. Quit <p>Select Option -></p> </div>	
<i>At the OM Delivery Main Menu</i>	

3 Access the Report Registration Menu:

6

Example response:

```
Report Registration
1. List Report Registration
2. Add Report Registration
3. Delete Report Registration
4. Help
5. Return to Main Menu

Select Option >
```

4 Add a report registration:

2

Example response:

```
Add Report Registration

Type "EXIT" to return to previous menu

Report Registration name >
```

5 Enter the name you have chosen to give the report registration (you can use up to 20 alphanumeric, dash, and underscore characters).

Example response:

Report element name >

6 Enter the report registration name.

Example response:

Data Collection Schedule name >

7 Enter the data collection schedule name.

Example response:

File Rotation Schedule name >

8 Enter the file rotation schedule name.

Example response:

File Transfer Schedule name >

9 Enter the file transfer schedule name.

Example response:

Add Report Registration (Y/N)?

10 Confirm that you want to add the report registration:

y

Example response:

```

Please wait....
RR1: the request was successful.
Press Enter for Report Registration Menu.
    
```

11 Press the Enter key.

Example response:

```

Report Registration
1. List Report Registration
2. Add Report Registration
3. Delete Report Registration
4. Help
5. Return to Main Menu

Select Option >
    
```

If you	Do
want to add another report registration	step 4
do not want to add another report registration	step 12

12 Return to the OM Delivery Main Menu:

5

13 You have completed the procedure.

—End—

Adding OM groups to a report element

Purpose

Use this procedure to add an OM group to an existing report element.

Prerequisites

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Adding OM groups

To add OM groups to an existing report element, you must specify the information in the following table.

Component	Description
Report element name	Name of the report element (maximum of 20 alphanumeric, dash, and underscore characters)
OM group name	Name of the OM group being added to the report element
Register	Name the registers of OM groups to be included in the report. For more information, refer to "Operational Measurements Delivery Overview" in the CBM Basics document.

Procedure

Use the following procedure to add an OM group to an existing report element.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Adding OM groups to a report element

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OM Delivery Main Menu

3 Display the Report Element Main Menu:

1

Example response:

```
Report Element Main Menu

1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >
```

4 Access the Modify Report Element Menu:

4

Example response:

```
Modify Report Element Menu

1. Add OM groups to a Report Element
2. Delete OM groups from a Report Element
3. Modify OM groups in a Report Element
4. Help
5. Return to Report Element Menu

Select Option >
```

5 Initiate the process of adding OM groups to an existing report element:

1

Example response:

```
Add OM Groups to a Report Element

Type "EXIT" to return to previous menu

Report Element name >
```

6 Enter the report element name.

Example response:

```
Selected OM Groups in the report element:

      OM group1      OM group2      OM group3
      OM group4      .....      .....
              :              :              :
              :              :              :
      .....      .....      OM groupn

OM group to add >
```

where

OM groups 1 to n is the OM groups that are datafilled in the report element

7 Enter the OM group name.

If the OMUI displays the message	Do
<i>Register or All ></i> the reporting interval for this OM group is set to TRANSFER	step 8
<i>Non-subtraction Register ></i> the reporting interval for this OM group is set to FIVE	step 11

8 Determine if a register is to be added.

If you	Do
want to add a register	step 9
want to add all registers	step 10
do not want to add a register	step 18

9 Enter the name of the register.

Example response:

Register or All >

If you	Do
want to add another register	repeat step 9
want to add all registers	step 10
do not want to add another register	step 18

10 Add each of the registers of the OM group.

a11

Example response:

<n> registers have been added >

where

<n> is the number of registers in the OM group

11 Press the Enter key.

Example response:

Non-subtraction register >

If you	Do
want to add a non-subtraction register	step 12
do not want to add a non-subtraction register	step 13

- 12** Enter the name of the register.

Example response:

Non-subtraction register >

If you	Do
want to add another non-subtraction register	repeat step 12
do not want to add another non-subtraction register	step 13

- 13** Press the Enter key.

Example response:

Single subtraction register >

If you	Do
want to add a single subtraction register	step 14
do not want to add a single subtraction register	step 15

- 14** Enter the name of the register.

Example response:

Single subtraction register >

If you	Do
want to add another single subtraction register	repeat step 14
do not want to add another single subtraction register	step 15

- 15** Press the Enter key.

Example response:

Double subtraction register (base) >

If you	Do
want to add the base of a double subtraction register	step 16
do not want to add the base of a double subtraction register	step 18

16 Type the name of the base register.

Example response:

Double subtraction register (ext) >

17 Enter the name of the extension (ext) register.

To use the double subtraction register, you must enter a base and extension register name. The register names must be unique.

Example response:

Double subtraction register (base) >

If you	Do
want to add another double subtraction register	step 16
do not want to add another double subtraction register	step 18

18 Press the Enter key.

Example response:

Add OM group (Y/N) ?

If you	Do
want to add the OM group	enter y
do not want to add the OM group	enter n

19 Press the Enter key.

Example response:

OM group to add >

If you	Do
want to add another OM group to the report element	repeat step 19
do not want to add another OM group to the report element	step 20

20 Press the Enter key.

Example response:

WARNING: If the report element is currently used by a report registration, the file will be closed and a new report file will be opened. Add OM groups (Y/N) ?

If you	Do
want to add these OM groups to the report element	step 21
do not want to add these OM groups to the report element	type n and go to step 22

21 Add the OM groups to this report element:

y

Example response:

```
Please wait. This may take a few minutes.
RE1: the request was successful.
Report Registrations affected by this modification: RR list
Press Enter for Modify Report Element Menu.
```

22 Press the Enter key to return to the Modify Report Element Menu.

Example response:

```

                Modify Report Element Menu

1. Add OM groups to a Report Element
2. Delete OM groups from a Report Element
3. Modify OM groups in a Report Element
4. Help
5. Exit to Report Element Menu

Select Option >
```

23 Return to the Report Element Menu:

5

24 Return to the OM Delivery Main Menu:

6

25 You have completed this procedure.

—End—

Adding a register to an existing OM group in a report element

Purpose

Use this procedure to add a register to an existing OM group in a report element.

Prerequisites

Logging on to the CS 2000 Core Manager

You must be a user authorized to perform performance-admin actions in order to perform this procedure.

For information on how to log in to the CS 2000 Core Manager as an authorized user or how to display other information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CS 2000 Core Manager	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611
Displaying information about a user or role group	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Adding a register

To add a register to an existing operational measurements (OM) group in a report element, you need the information in the following table.

Component	Description
Report element name	user-defined name of the report element of the OM groups being modified
OM group name	name of a valid OM group to be modified in the report element
Register	Name the registers of OM groups to be included in the report. For more information, refer to "Operational Measurements Delivery Overview" in the CBM Basics document.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Use the following procedure to add a register to an existing OM group in a report element.

Adding a register to an existing OM group in a report element

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|--|
| 1 | Log into the core manager. |
| 2 | Start the OMUI:

<code>omui</code>

The OM Delivery Main menu appears. |

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Display the Report Element Main Menu:

1

Example response:

```
Report Element Main Menu

1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >
```

4 Display the Modify Report Element Menu:

4

Example response:

```
Modify Report Element Menu

1. Add OM groups to a Report Element
2. Delete OM groups from a Report Element
3. Modify OM groups in a Report Element
4. Help
5. Exit to Report Element Menu

Select Option >
```

5 Display the Modify OM groups in a Report Element Menu:

3

Example response:

```

Modify OM Groups in a Report Element Menu
1. Add Register(s) to OM groups to a Report Element
2. Delete Register(s) from OM groups in a Report Element
3. Help
4. Return to Modify Report Element Menu
Select Option >
    
```

6 Begin the process of adding a register or registers to an existing OM group of a report element:

1

Example response:

```

Add Register(s) to OM groups in a Report Element
Type "EXIT" to return to previous menu
Report Element name >
    
```

7 Enter the report element name.

Example response:

```

Selected OM Groups in the report element:
      OM group1      OM group2      OM group3
      OM group4      .....      .....
              :              :              :
              :              :              :
      .....      .....      OM groupn
OM group to modify >
    
```

where

OM groups 1 to n is the OM groups that are datafilled in the report element

8 Enter the OM group name.

If the reporting interval for the OM group is set to	Do
TRANSFER	step 9
FIVE	step 12

The OMUI displays the following response:

Example response:

```

Selected Registers in the OM group:
      Register1      Register2      Register3
          :          .....
          :          .....
          :          .....
          :          .....      Registern
Register or All >
    
```

9 Enter the name of the register.

Example response:

Register or All >

If you	Do
want to add another register	repeat step 9
want to add <i>all</i> registers	step 10
do not want to add another register	step 19

10 Add each of the registers of the OM group:.

all

Example response:

<n> registers have been added >

where

<n> is the number of registers in the OM group

11 Go to step 19.

12 The OMUI displays the following response:

Example response:

```

Selected Registers in the OM group:

Non-subtraction Registers
  Register1   Register2   Register3
    :         :         :
    :         :         :
Single Subtraction Registers
  :         :         :
  :         :         :
Double Subtraction Registers
  :         :         :
  :         :         :
  :         :         :
Non-subtraction register >

```

where

Register1, Register2 ... are the registers that are datafilled for the OM group in the report element.

If you	Do
want to add a non-subtraction register	step 13
do not want to add a non-subtraction register	step 14

- 13** Enter the name of the register.

Example response:

```
Non-subtraction register >
```

If you	Do
want to add another non-subtraction register	repeat step 13
do not want to add another non-subtraction register	step 14

- 14** Press the Enter key.

Example response:

```
Single subtraction register >
```

If you	Do
want to add a single subtraction register	step 15
do not want to add a single subtraction register	step 16

- 15** Enter the name of the register.

Example response:

Single subtraction register >

If you	Do
want to add another single subtraction register	repeat step 15
do not want to add another single subtraction register	step 16

- 16 Press the Enter key.

Example response:

Double subtraction register (base) >

If you	Do
want to add the base of a double subtraction register	step 17
do not want to add the base of a double subtraction register	step 19

- 17 Type the name of the base register.

Example response:

Double subtraction register (ext) >

- 18 Type the name of the extension (ext) register.

To use the double subtraction register, you must enter a base and extension register name. Each register must have different register names.

Example response:

Double subtraction register (base) >

If you	Do
want to add another double subtraction register	step 17
do not want to add another double subtraction register	step 19

- 19 Press the Enter key.

Example response:

Modify OM group (Y/N)?

If you	Do
want to modify the OM group	enter y
do not want to modify the OM group	enter n

- 20 Press the Enter key.

Example response:

OM group to modify >

If you	Do
want to modify another OM group	return to step 8
do not want to modify another OM group of the report element	step 21

- 21** Press the Enter key.

Example response:

WARNING: If the report element is currently used by a report registration, the file will be closed and a new report file will be opened.
Add Registers to OM groups (Y/N)?

If you	Do
want to modify the OM groups to the report element	step 22
do not want to modify the OM groups to the report element	type n and go to step 23

- 22** Modify the OM groups to the report element:

y

Example response:

Please wait. This may take a few minutes.
RE1: the request was successful.
Report Registrations affected by this modification: RR list
Press Enter for Modify OM group in a Report Element menu.

- 23** Return to the Modify OM group in a Report Element Menu by pressing the Enter key.

Modify OM Group in a Report Element Menu

1. Add Register(s) to OM groups in a Report Element
2. Delete Register(s) from OM groups in a Report Element
3. Help
4. Return to Modify Report Element Menu

Select Option >

- 24 Return to the Modify Report Element Menu:
4
- 25 Return to the Report Element Menu:
5
- 26 Return to the OM Delivery Main Menu:
6
- 27 You have completed this procedure.

—End—

Deleting a data collection schedule

Purpose

Use this procedure to delete a data collection schedule.

Prerequisites

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Application

Removing report registration

Before deleting a data collection schedule, you must delete the report registration using the report registration menu.

Procedure

Use the following procedure to delete a data collection schedule.

Deleting a data collection schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|----------------------------|
| 1 | Log into the core manager. |
| 2 | Start the OMUI: |

```
omui
```

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu**3** Access the Data Collection Schedule Menu:

2

Example response:

```

Data Collection Schedule

1. List Data Collection Schedule
2. Add Data Collection Schedule
3. Delete Data Collection Schedule
4. Modify Data Collection Schedule
5. Help
6. Return to Main Menu

Select Option >

```

4**ATTENTION**

If you do not know the data collection schedule name (DCS name) to delete, use the "List Data Collection Schedule" option to review the list of the currently defined data collection schedules.

Delete a data collection schedule:

3

Example response:

```

Delete Data Collection Schedule
Data Collection Schedule Name >

```

5 Enter the name of the data collection schedule that you have chosen to delete.*Example response:*

Delete data collection schedule (Y/N) ?

6 Confirm that you want to delete the data collection schedule entry:

y

Example response:

```

Please wait...
dcsname: The request was successful.
Press Enter for Data Collection Schedule Menu.

```

7 Return to the OM Delivery Main Menu:

6

8 Press the Enter key to return to the Data Collection Schedule Menu.

Example response:

```
                Data Collection Schedule
1. List Data Collection Schedule
2. Add Data Collection Schedule
3. Delete Data Collection Schedule
4. Modify Data Collection Schedule
5. Help
6. Return to Main Menu

Select Option >
```

9 You have completed the procedure.

—End—

Deleting a file rotation schedule

Purpose

Use the following procedure to delete a file rotation schedule.

You can delete file rotation schedules as long as there are no report registrations using them. If a file rotation schedule is being used by a report registration, you must first delete the report registration, then you can delete the file rotation schedule. In addition, the file rotation schedule name is required to delete a file rotation schedule.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Deleting a file rotation schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|---|
| 1 | Log into the core manager. |
| 2 | Start the OMUI:

omui

The OM Delivery Main menu appears. |

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Access the File Rotation Schedule Menu:

3

Example response:

```
File Rotation Schedule Menu

1. List File Rotation Schedules
2. Add File Rotation Schedule
3. Delete File Rotation Schedule
4. Modify File Rotation Schedule
5. Help
6. Return to Main Menu

Select Option >
```

4

ATTENTION

If you do not know the file rotation schedule name (FRS name) you have chosen to delete, use the "List File Rotation Schedule" option to review the list of currently defined file rotation schedules.

Delete a file rotation schedule:

3

Example response:

```
Delete File Rotation Schedule

File Rotation Schedule name >
```

5 Enter the name of the file rotation schedule that you want to delete.

Example response:

Delete file rotation schedule (Y/N)?

- 6 Confirm that you want to delete the file rotation schedule entry:

y

Example response:

```
Please wait...
frsname: The request was successful.
Press Enter for File Rotation Schedule Menu.
```

- 7 Press Enter to return to the File Rotation Schedule Menu.

Example response:

```
Please wait...
frsname: The request was successful.
Press Enter for File Rotation Schedule Menu.
```

- 8 Return to the OM Delivery Main Menu:

6

- 9 You have completed the procedure.

—End—

Deleting a file transfer destination

Purpose

Use this procedure to remove a file transfer destination.

Prerequisites

Procedure	Document
Logging in to the CS 2000 Core Manager	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611
Displaying information about a user or role group	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Removing report registration

Before you can delete a file transfer destination, you must remove the report registration using the Report Registration Menu and the file transfer schedule.

Procedure

Use the following procedure to remove a file transfer destination.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Deleting a file transfer destination

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- 1 Log into the core manager.
- 2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OMUI Main Menu

- 3 Access the File Transfer Destination Main Menu:

4

Example response:

```
File Transfer Destination

1. List File Transfer Destinations
2. Add File Transfer Destination
3. Delete File Transfer Destination
4. Modify File Transfer Destination
5. Help
6. Return to Main Menu

Select Option >
```

- 4 Select Delete File Transfer Destination:

3

Example response:

```
File Transfer Destination Main Menu
File Transfer Destination name >
```

- 5 Enter the name of the file transfer destination you want to delete.

Example response:

```
Delete file transfer destination (Y/N) ?
```

- 6 Confirm that you want to delete the file transfer destination entry:

y

Example response:

```
Please wait...
ftdname: The request was successful.
Press Enter for File Transfer Destination
Menu.
```

- 7 Press the Enter key to return to the File Transfer Destination Menu.

Example response:

```
File Transfer Destination Menu

1. List File Transfer Destination
2. Add File Transfer Destination
3. Delete File Transfer Destination
4. Modify File Transfer Destination
5. Help
6. Return to Main Menu

Select Option >
```

- 8 Return to the OM Delivery Main Menu:

6

- 9 You have completed the procedure.

—End—

Deleting a report element

Purpose

Use this procedure to delete a report element.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

You can delete report elements as long as there are no report registrations using the report elements. If a report registration is using a report element, you must first delete the report registration, then you can delete the report element.

Procedure

Use the following procedure to delete a report element.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Deleting a report element

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|-----------------------------|
| 1 | Log into the core manager. |
| 2 | Start the OMUI:

omui |

The OM Delivery Main menu appears.

```
OM Delivery Main Menu
1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OMUI Main Menu

3 Display the Report Element Main Menu:

1

Example response:

```
Report Element Main Menu
1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >
```

4 Select Delete a Report Element:

3

Example response:

```
Delete Report Element
Report Element name >
```

5 Type the report element name and press the Enter key.

Example response:

Delete Report Element (Y?N) ?

6 Confirm that you want to delete the report element:

y

Example response:

```
Please wait...  
RE1: the request was successful.  
Press Enter for Report Element Menu
```

7 Press the Enter key.

Example response:

```
Report Element Main Menu  
1. List Report Elements  
2. Add Report Element  
3. Delete Report Element  
4. Modify Report Element  
5. Help  
6. Return to Main Menu  
  
Select Option >
```

8 Return to the OM Delivery Main Menu:

6

9 You have completed the procedure.

—End—

Deleting a report registration

Purpose

Use this procedure to delete a report registration.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

You can delete a report registration, which stops the process of collecting data and unties the report element, the data collection schedule, the file rotation schedule, and the file transfer schedule.

The components that form a report registration (report element, data collection schedule, file rotation schedule, and optional file transfer schedule) are not changed when a report registration is deleted.

If data collection is in progress when a report registration is deleted, data collection ceases and the report file is closed. The report file is not rotated unless the same rotation schedule is tied to another report registration.

Procedure

Use the following procedure to delete a report registration.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Deleting a report registration

Step	Action
------	--------

At the OMUI Main Menu

1 Access the File Report Registration Menu:

6

Example response:

```

Report Registration

1. List Report Registration
2. Add Report Registration
3. Delete Report Registration
4. Help
5. Return to Main Menu

Select Option >

```

2 Select Delete Report Registration:

3

Example response:

```

Delete Report Registration
Report Registration name >

```

3 Enter the report registration name you want to delete.

Example response

Delete Report Registration(Y/N) >

4 Confirm that you want to delete the report registration:

y

Example response:

```

Please wait....
RR1: the request was successful.
Press Enter for Report Registration Menu.

```

5 Press the Enter key.

Example response:

```
Report Registration
1. List Report Registration
2. Add Report Registration
3. Delete Report Registration
4. Help
5. Return to Main Menu

Select Option >
```

6 Return to the OM Delivery Main Menu:

5

7 You have completed the procedure.

—End—

Deleting a register from an existing OM group in a report element

Purpose

Use this procedure to delete a register from an existing OM group in a report element.

Prerequisites

To delete a register from an existing operational measurements (OM) group in a report element, you need the information in the following table.

Component	Description
Report element name	user-defined name of the report element of the OM groups being modified
OM group name	name of a valid OM group to be modified in the report element
Register	Name the registers of OM groups to be included in the report. For more information, refer to "Operational Measurements Delivery Overview" in the CBM Basics document.

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Procedure

Use the following procedure to delete a register from an existing OM group in a report element.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Deleting a register from an existing OM group in a report element

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Display the Report Element Main Menu:

1

Example response:

```
Report Element Main Menu

1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >
```

4 Display the Modify Report Element Menu:

4

Example response:

```
Modify Report Element Menu

1. Add OM groups to a Report Element
2. Delete OM groups from a Report Element
3. Modify OM groups in a Report Element
4. Help
5. Exit to Report Element Menu

Select Option >
```

5 Display the Modify OM groups in a Report Element Menu:

3

Example response:

```
Modify OM Groups in a Report Element Menu

1. Add Register(s) to OM groups to a Report Element
2. Delete Register(s) from OM groups in a Report Element
3. Help
4. Return to Modify Report Element Menu

Select Option >
```

6 Initiate the process of deleting registers from an existing OM group in a report element:

2

Example response:

```
Delete Register(s) from OM groups in a Report Element

Type EXIT to return to previous menu

Report Element name >
```

7 Enter the report element name.

Example response:

```

Selected OM Groups in the report element:

      OM group1      OM group2      OM group3
      OM group4      .....
      :              :
      :              :
      .....         .....         OM groupn

OM group to modify >

```

where

OM group1, OMgroup2 ... are the OM groups that already are datafilled in the report element

- 8 Enter the OM group name.

If the reporting interval for the OM group is set to	Do
TRANSFER	step 9
FIVE	step 10

- 9 The OMUI displays the following response:

Example response:

```

Selected Registers in the OM group:

      Register1      Register2      Register3
      :              .....
      :              .....
      :              .....         Registern

Register >

```

where

Register1, Register2 ... are the registers of the specified OM group that are datafilled

If you	Do
want to delete a register	step 10
do not want to delete a register	step 17

- 10 Enter the name of the register you want to delete.

Example response:

Register >

If you	Do
want to delete another register	repeat step 10
do not want to delete another register	step 17

The OMUI displays the following response:

```

Selected Registers in the OM group:

Non-subtraction Registers
      Register1      Register2      Register3
          :           .....
          :           .....

Single Subtraction Registers
          :           .....
          :           .....

Double Subtraction Registers
          :           .....
          :           .....
          :           .....
          :           .....
          :           Registern
    
```

where

Register1, Register2 ... are the registers that are datafilled for the OM group in the report element.

If the registers datafilled are	Do
non-subtraction	step 11
single subtraction	step 13
double subtraction	step 15

11 The OMUI displays the following response.

Example response:

Non-subtraction register>

If you	Do
want to delete a non-subtraction register	step 12
do not want to delete a non-subtraction register	step 13

12 Type the name of the register you want to delete and press the Enter key.

Example response:

Non-subtraction register >

If you	Do
want to delete another non-subtraction register	repeat step 12
do not want to delete another non-subtraction register	step 13

- 13 Press the Enter key.

Example response:

Single subtraction register >

If you	Do
want to delete a single subtraction register	step 14
do not want to delete a single subtraction register	step 15

- 14 Type the name of the register you want to delete.

Example response:

Single subtraction register >

If you	Do
want to delete another single subtraction register	repeat step 14
do not want to delete another single subtraction register	step 15

- 15 Press the Enter key.

Example response:

Double subtraction register (base) >

If you	Do
want to delete a double subtraction register	step 16
do not want to delete a double subtraction register	step 17

- 16 Type the name of the base register.

Example response:

Double subtraction register (base) >

If you	Do
want to delete another double subtraction register	repeat step 16
do not want to delete another double subtraction register	step 17

17 Press the Enter key.

Example response:

Modify OM group (Y/N)? >

If you	Do
want to modify the OM group	type y
do not want to modify the OM group	type n

18 Press the Enter key.

Example response:

OM group to modify >

If you	Do
want to modify another OM group of the report element	return to step 8
do not want to modify another OM group of the report element	step 19

19 Press the Enter key.

Example response:

WARNING: If the report element is currently used by a report registration, the file will be closed and a new report file will be opened.
Add Registers to OM groups (Y/N)?

If you	Do
want to modify the OM groups to the report element	step 20
do not want to modify the OM groups to the report element	step 21

20 Modify the OM groups to the report element:

y

Example response:

Please wait. This may take a few minutes.
RE1: the request was successful.
Report Registrations affected by this modification: RR list
Press Enter for Modify OM group in a Report Element menu.

- 21** Return to the Modify OM group in a Report Element menu by pressing the Enter key.

Example response:

```
Modify OM Group in a Report Element Menu

1. Add Register(s) to OM groups in a Report Element
2. Delete Register(s) from OM groups in a Report Element
3. Help
4. Return to Modify Report Element Menu

Select Option >
```

- 22** Return to the Modify Report Element Menu:

4

- 23** Return to the Report Element Menu:

5

- 24** Return to the OM Delivery Main Menu:

6

- 25** You have completed this procedure.

—End—

Deleting a file transfer schedule

Purpose

Use this procedure to delete a file transfer schedule.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

Removing report registration

Before deleting a file transfer schedule, you must delete the report registration using the report registration menu.

Procedure

Use the following procedure to delete a file transfer schedule.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Deleting a file transfer schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|-----------------------------|
| 1 | Log into the core manager. |
| 2 | Start the OMUI:

omui |

The OM Delivery Main menu appears.

```
OM Delivery Main Menu
1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OMUI Main Menu

3 Access the File Transfer Schedule Main Menu:

5

Example response:

```
File Transfer Schedule Menu
1. List File Transfer Schedule
2. Add File Transfer Schedule
3. Delete File Transfer Schedule
4. Modify File Transfer Schedule
5. Help
6. Return to Main Menu

Select Option >
```

4

ATTENTION

If you do not know the file transfer schedule name (FTS name) you have chosen to delete, use the "[Listing a file transfer schedule](#)" (page 101) procedure to review the list of currently defined file transfer schedules.

Select Delete File Transfer Schedule:

3

The OMUI responds with the following screen:

```
Delete File Transfer Schedule name >
```

- 5 Enter the name of the file transfer schedule you want to delete.

Example response:

```
Delete file transfer schedule (Y/N)?
```

- 6 Confirm that you want to delete the file transfer schedule entry:

y

Example response:

```
Please wait...
ftsname: The request was successful.
Press Enter for File Transfer Schedule Menu.
```

- 7 Press Enter to return to the File Transfer Schedule Menu.

Example response:

```
File Transfer Schedule Menu

1. List File Transfer Schedule
2. Add File Transfer Schedule
3. Delete File Transfer Schedule
4. Modify File Transfer Schedule
5. Help
6. Return to Main Menu

Select Option >
```

- 8 Return to the OM Delivery Main Menu:

6

- 9 You have completed the procedure.

—End—

Deleting OM groups from a report element

Purpose

Use this procedure to delete an OM group from a report element.

Prerequisites

To delete OM groups in a report element, you need the information in the following table.

Component	Description
Report element name	user-defined name of the report element from which the OM group is to be deleted
OM group name	name of a valid OM group or groups to be deleted from the report element

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Procedure

Use the following procedure to delete an OM group from a report element.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Deleting OM groups from a report element

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|----------------------------|
| 1 | Log into the core manager. |
| 2 | Start the OMUI: |

omui

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Display the Report Element Main Menu:

1

Example response:

```
Report Element Main Menu

1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >
```

4 Select the Modify Report Element Menu:

4

Example response:

```
Modify Report Element Menu

1. Add OM groups to a Report Element
2. Delete OM groups from a Report Element
3. Modify OM groups in a Report Element
4. Help
5. Exit to Report Element Menu

Select Option >
```

5 Select Delete OM groups from a Report Element:

2

Example response:

```

Delete OM Groups from a Report Element
Type "EXIT" to return to previous menu
Report Element name >
    
```

6

ATTENTION

If you do not know the name of the report element with the OM group to delete, enter **5** to return to the Report Element Main Menu. Select option **1** (List Report Elements) to locate the report element that you want to delete from the OM group.

Enter the name of the report element.

Example response:

```

Selected OM Groups in the report element:
      OM group1      OM group2      OM group3
      OM group4      .....      .....
      :              :              :
      :              :              :
      .....      .....      OM groupn

OM group to delete >
    
```

where

OM group1, OM group 2 ... are the OM groups that are datafilled in the report element

7 Enter the name of the OM group you want to delete.

Example response:

Delete OM group (Y/N) ?

If you	Do
want to delete an OM group from the report element	type y
do not want to delete an OM group from the report element	type n

8 Press the Enter key.

Example response:

OM group to delete >

If you	Do
want to delete another OM group from the report element	return to step 7
do not want to delete another OM group from the report element	step 9

9 Press the Enter key.

Example response:

Delete OM groups (Y/N) ?

If you	Do
want to delete the OM groups from the report element	step 10
do not want to delete the OM groups from the report element	type n and go to step 11

10 Delete the OM groups for this report element:

y

Example response:

```

Please wait....
RE1: the request was successful.
Report Registrations affected by this modification:
RR list
Press Enter for Modify Report Element
    
```

11 Press the Enter key to return to the Modify Report Element Menu.

```

                Modify Report Element Menu

1. Add OM groups to a Report Element
2. Delete OM groups from a Report Element
3. Modify OM groups in a Report Element
4. Help
5. Exit to Report Element Menu

Select Option >
    
```

12 Return to the Report Element Menu:

5

13 Return to the OM Delivery Main Menu:

6

14 You have completed this procedure.

—End—

Listing data collection schedules

Purpose

Use this procedure to list data collection schedule information.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

The list data collection schedule option displays the following information:

- the list of names of the data collection schedules that are currently configured
- the data collection schedule usage screen shows all the data collection schedule names and their corresponding report registrations

Procedure

Use the following procedure to a list data collection schedule.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

List data collection schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|----------------------------|
| 1 | Log into the core manager. |
|---|----------------------------|

2 Start the OMUI:

`omui`

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Access the Data Collection Schedule Menu:

`2`

Example response:

```
Data Collection Schedule

1. List Data Collection Schedule
2. Add Data Collection Schedule
3. Delete Data Collection Schedule
4. Modify Data Collection Schedule
5. Help
6. Return to Main Menu

Select Option >
```

4 Select List Data Collection Schedule:

`1`

Example response:

```

List of Data Collection Schedule

DCS name      Repetition      Schedule Information
dcs1          Daily           0:00-0:00
dcs2          Weekly          Tue. Fri. Sun. 13:00-19:00
dcs3          Monthly         1, 2, 5, 23, 31 10:00-17:00

1. List Data Collection Schedule Usage
2. Return to Data Collection Schedule Menu

Select Option >

```

If you	Do
want more details	step 5
do not want more details	step 7

5 List the data collection schedule:

1

```

Data Collection Schedule Usage

DCS Name      Report Registration Name
DCS1          RE1                RE2
DCS2          RE2                RE2
DCS3          RE3                RE4

Press Enter for List Data Collection Schedule Menu.

```

6 Press the Enter key to return to the List of Data Collection Schedules screen.

7 Return to the Data Collection Schedule Menu:

2

The OMUI displays the following screen:

```

                                Data Collection Schedule
1. List Data Collection Schedule
2. Add Data Collection Schedule
3. Delete Data Collection Schedule
4. Modify Data Collection Schedule
5. Help
6. Return to Main Menu

Select Option >
```

8 Return to the OM Delivery Main Menu:

6

9 You have completed the procedure.

—End—

Listing file rotation schedules

Purpose

Use this procedure to list file rotation schedule information.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

The list file rotation schedule option displays the following information:

- names of the file rotation schedules that are currently configured
- file rotation schedule usage screen that shows all of the file rotation schedule names and their corresponding report registrations

Procedure

Use the following procedure to list file rotation schedule information.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Listing file rotation schedules

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|----------------------------|
| 1 | Log into the core manager. |
| 2 | Start the OMUI: |

omui

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Access the File Rotation Schedule Menu:

3

Example response:

```
File Rotation Schedule Menu

1. List File Rotation Schedules
2. Add File Rotation Schedule
3. Delete File Rotation Schedule
4. Modify File Rotation Schedule
5. Help
6. Return to Main Menu

Select Option >
```

4 Select List File Rotation Schedules:

1

Example response:

```

List of File Rotation Schedule

FRS name      Repetition Schedule Information

FRS1         Daily      16:00
FRS2         Weekly     Fri. 12:00
FRS3         Monthly    End of the Month,0:00
FRS4         Reports    Every 20 reports
FRS5         Hours      Every 2 hours

1. List File Rotation Schedule Usage.
2. Return to File Rotation Schedule Menu.

Select Option >

```

If you	Do
want more details	step 5
do not want more details	step 7

5 Select List File Rotation Schedule Usage:

1

Example response:

```

File Rotation Schedule Usage

FRS Name      Report Registration Name

FRS1         RR1          RR2
             RR3          RR4

FRS5         RR5

Press Enter for List File Rotation Schedule Menu.

```

6 Press the Enter key to return to the List of File Rotation Schedules screen.

7 Return to the File Rotation Schedule Menu:

2

8 Return to the OM Delivery Main Menu:

6

9 You have completed the procedure.

—End—

Listing a file transfer destination

Purpose

Use this procedure to display information about file transfer destinations.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Use the following procedure to display information about any currently defined file transfer destinations.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Listing a file transfer destination

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|---|
| 1 | Log into the core manager. |
| 2 | Start the OMUI:
<code>omui</code>
<i>The OM Delivery Main menu appears.</i> |

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Access the File Transfer Destination Menu:

4

Example response:

```
File Transfer Destination

1. List File Transfer Destination
2. Add File Transfer Destination
3. Delete File Transfer Destination
4. Modify File Transfer Destination
5. Help
6. Return to Main Menu

Select Option >
```

4 Select List File Transfer Destination:

1

The following example shows two defined destinations, the first with secure file transfer password-based authentication, and the second with secure key-based authentication .

```

List of file Transfer Destinations
FTD name IP Address  Transfer Type Port Login name

```

1. List File Transfer Destination Usage.
2. Return to File Transfer Destination Menu.

Select Option >

If you	Do
want more details	step 5
do not want more details	step 7

5 Select List File Transfer Destination Usage:

1

Example response:

```

File Transfer Destination Usage
FTD name          Report Registration Name

FTD1              RR1
FTD2              RR2

Press Enter for List of File Transfer Destination
Menu.

```

6 Press the Enter key to return to the List of File Transfer Destination screen.

7 Return to the File Transfer Destination Menu:

2

Example response:

```

File Transfer Destination Menu

1. List File Transfer Destination
2. Add File Transfer Destination
3. Delete File Transfer Destination
4. Modify File Transfer Destination
5. Help
6. Return to Main Menu

Select Option >

```

- 8 Return to the OM Delivery Main Menu:
6
- 9 You have completed the procedure.

—End—

Listing a file transfer schedule

Purpose

Use the following procedure to display information about any currently defined file transfer schedules.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Use the following procedure to list a file transfer schedule.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Listing a file transfer schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|--|
| 1 | Log into the core manager. |
| 2 | Start the OMUI:

<code>omui</code>

The OM Delivery Main menu appears. |

```

OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OM Delivery Main Menu

3 Access the File Transfer Schedule Menu:

5

Example response:

```

File Transfer Schedule Menu

1. List File Transfer Schedule
2. Add File Transfer Schedule
3. Delete File Transfer Schedule
4. Modify File Transfer Schedule
5. Help
6. Return to Main Menu

Select Option >

```

4 Select List File Transfer Schedule:

1

The following example shows two defined schedules.

```

List of File Transfer Schedule

FTS name      Repetition      Schedule Information
FTS 1         Daily           1830
--> FTD name - FTD1
--> FTD Dir - /home/u1/ronaldp/dest1
--> FTD name - FTD2
--> FTD Dir - /home/u1/ronaldp/dest2

1. List File Transfer Schedule Usage.
2. Return to File Transfer Schedule Menu.

Select Option >

```

If the device has more than three file transfer schedules defined, use the scroll bar in your terminal window to review all of the schedules listed.

- 5 Review the details of a specific file transfer schedule:

1

Example response:

```
File Transfer Schedule Usage
FTS name      Report Registration Name
FTS1          RR1
Press Enter for List of File Transfer Schedule Menu
```

- 6 Press the Enter key to return to the List of File Transfer Schedule Menu.

- 7 Return to the File Transfer Schedule Menu:

2

Example response:

```
File Transfer Schedule Menu
1. List File Transfer Schedule
2. Add File Transfer Schedule
3. Delete File Transfer Schedule
4. Modify File Transfer Schedule
5. Help
6. Return to Main Menu
Select Option >
```

- 8 Return to the OM Delivery Main Menu:

6

- 9 You have completed the procedure.

—End—

Listing report element information

Purpose

Use this procedure to list report element names, and associated information.

Application

Use the list report element information option to display the names of report elements that are currently configured. For each report element, you can also display the following information:

- the reporting interval for a report element
- the names of report registrations using a report element
- the names of the OM groups in the report element
- the names and types of registers in each OM group in the report element

For more detailed information about OM report elements and their use within the OM Delivery application, refer to "Operational Measurements Delivery Overview" in the CBM Basics document.

Procedure	Document
Logging in to the CS 2000 Core Manager	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611
Displaying information about a user or role group	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Use the following procedure to list report element information.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Listing report element information

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OM Delivery Main Menu

3 Display the Report Element Main Menu:

```
1
```

Example response:

```

                                Report Element Main Menu

1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >

```

- 4 Display a list of currently defined report elements from the Report Element Main Menu:

1

Example response:

```

List of Report Elements

Report Element name

RE1
RE2
RE3
RE4
TRK1

Enter a report element name for more detail
or press ENTER for Report Element Menu >
    
```

If you	Do
want more details for a specific report element	step 5
do not want more details	step 8

- 5 Display detailed information for a specified report element by entering the report element name.

Example response:

```

Report Element Information

Report Element name > RE1

Reporting Interval:Interval

Used By Report Registration: RR1 TRK1

OM Groups: OMG1, OMG2, OMG3

Enter OM group name for more detail or press
Enter for List Report Elements Menu. >
    
```

If you	Do
want more details for a specific OM group	step 6
do not want more details	step 7

- 6 Display detailed information for a specified OM group by entering the name of the OM group.

Example response:

```

OM Groups information
OM group: OMG1

Non-subtraction Registers:
  NSR1
Single Subtraction Registers:
  SSR1
Double Subtraction Registers:
  DSR1base
  DSR1ext

Enter OM group name for more detail
or press Enter for Report Element Information >

```

If you	Do
want details about a different OM group	step 6
do not want more details: Return to the Report Element Information Menu by pressing the Enter key	step 7

- 7 Return to the List Report Elements Menu by pressing the Enter key.

If you	Do
want more details about a specific report element	step 5
do not want more details	step 8

- 8 Return to the Report Element Main Menu by pressing the Enter key.
The OMUI displays the following Screen:

```

Report Element Main Menu

1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >

```

- 9 Return to the OM Delivery Main Menu:
6
- 10 You have completed the procedure.

—End—

Listing report registrations

Purpose

Use this procedure to list report registrations, and to list detailed information for each report registration.

Application

The list report registrations option displays the following information:

- File retention period:
the number of days the report file is kept before being deleted.
- Report registration limit:
the maximum number of report registrations allowed in the system.
- Report registration:
a list of all report registrations which have been configured in the system.
- Report registration details:
the associated report element, data collection schedule, file transfer schedule, and file rotation schedule for the report registration.

Procedure	Document
Logging in to the CS 2000 Core Manager	<i>CS 2000 Core Manager Security and Administration, NN10170-611</i>
Displaying information about a user or role group	<i>CS 2000 Core Manager Security and Administration, NN10170-611</i>

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration, NN10358-611</i>
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration, NN10358-611</i>

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Use the following procedure to list report registrations that have been configured, and to list detailed information for each report registration.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Listing report registrations

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OM Delivery Main Menu

3 Access the Report Registration Menu:

```
6
```

The OMUI displays the following:

```

                                Report Registration

1. List Report Registration
2. Add Report Registration
3. Delete Report Registration
4. Help
5. Return to Main Menu

Select Option >

```

4 Display a list of current report registrations:

1

Example response:

```

List of Report Registration
File Retention Period: num
Report Registration Limit: num

Report Registration:

RR1
RR2
RR3

Enter a report registration name for more detail
or press Enter for Report Registration Menu. >
    
```

If you	Do
want more details for a specific report registration	step 5
do not want more details	step 7

5 Display detailed information for a specified report registration by entering the report registration name.

Example response:

```

Report Registration Information

Report Registration: RR1
Report Element: RE1
Data Collection Schedule: DCS1
File Rotation Schedule: FRS1
File Transfer Schedule: FTS1

Press Enter for List Report Registration Menu.
    
```

6 Return to the List Report Registration Menu by pressing the Enter key.

If you	Do
want more details about a specific report registration	step 5
do not want more details	step 7

7 Return to the Report Element Main Menu by pressing the Enter key.

Example response:

```
Report Registration
1. List Report Registration
2. Add Report Registration
3. Delete Report Registration
4. Help
5. Return to Main Menu

Select Option >
```

8 Return to the OM Delivery Main Menu:

5

9 You have completed the procedure.

—End—

Modifying a data collection schedule

Purpose

Use this procedure to modify a data collection schedule.

Application

Data collection schedules can be modified whether or not they are used by report registrations. If a data collection schedule is modified while being used by one or more report registrations, all OM report files for the registrations are closed and rotated. New report files are opened based on the newly modified data collection schedule.

Prerequisites

The following information is required to modify a data collection schedule:

- Data collection schedule name:
the name of data collection schedule to be modified.
- Repetition:
the schedule for the data collection is performed regularly. The repetition can be daily, weekly, or monthly.

You must also specify the start and stop times. You cannot specify a start time of 2400, but you can specify a stop time of 0000 or 2400. The start time must always be less than the stop time, unless the stop time is 0000.

Refer to "[Adding a data collection schedule](#)" (page 16) for information about data collection schedule variables and each data collection repetition type.

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN20000-320
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN20000-320

Procedure	Document
Logging in to the CS 2000 Core Manager	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611
Displaying information about a user or role group	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611

Procedure

Use the following procedure to modify a data collection schedule.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Modifying a data collection schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- | | |
|---|---|
| 1 | Log into the core manager. |
| 2 | Start the OMUI:

<pre>omui</pre> <p><i>The OM Delivery Main menu appears.</i></p> |

```

OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OM Delivery Main Menu

- 3 Access the Data Collection Schedule Menu:

2

Example response:

```

Data Collection Schedule

1. List Data Collection Schedule
2. Add Data Collection Schedule
3. Delete Data Collection Schedule
4. Modify Data Collection Schedule
5. Help
6. Return to Main Menu

Select Option >

```

- 4 Modify a data collection schedule:

4

Example response:

```

Modify Data Collection Schedule

Type "EXIT" to return to previous menu
Data Collection Schedule name >

```

If you do not know the data collection schedule name (DCS name) to delete, use the ["Listing data collection schedules"](#) (page 89) option to review the list of the currently defined data collection schedules.

- 5 Enter the name of the data collection schedule to modify.

Example response:

Repetition (1 = DAILY, 2 = WEEKLY, 3 = MONTHLY) >

If you want to change the data collection schedule to a	Do
daily repetition rate (schedule collections once each day)	step 6
weekly repetition rate (schedule collections once each week)	step 8
monthly repetition rate (schedule collections once each month)	step 11

6 Change a data collection schedule to a daily interval:

1

Example response:

Start time (HHMM) >

7 Go to step 13.

8 Change a data collection schedule to a weekly interval:

2

Example response:

Day of Week (1 = Monday, 2 = Tuesday, ..., 7 = Sunday) >

9 Enter the number for the day of the week that you want for data collection to take place.

To specify multiple days of the week to collect data, separate days with a comma. For example, to collect on Monday and Wednesday, enter 1,3.

Example response:

Start time (HHMM) >

10 Go to step 13.

11 Change a data collection schedule to a monthly interval:

3

Example response:

Day of Month (1-31) >

12 Enter the number for the day or days of the month to collect data.

To specify multiple days of the month to collect data, separate the days with a comma. For example, to collect on the third and 23rd, enter 3,23.

Example response:
Start time (HHMM) >

13 Enter the time of day to start collecting data:

Example response:
Stop time (HHMM) >

14 Enter the time of day to stop collecting data:

Example response:
Modify Data Collection Schedule (Y/N) ?

15 Confirm that you want to modify the data collection schedule:

y
Example response:
Please wait ...
dcsname: The request was successful
Press Enter for Data Collection Schedule Menu

16 Press the Enter key to return to the Data Collection Schedule Menu.

Example response:

```

                                Data Collection Schedule

    1. List Data Collection Schedule
    2. Add Data Collection Schedule
    3. Delete Data Collection Schedule
    4. Modify Data Collection Schedule
    5. Help
    6. Return to Main Menu

    Select Option >
    
```

17 Return to the OM Delivery Main Menu:

6

18 You have completed the procedure.

—End—

Modifying a file rotation schedule

Purpose

Use the following procedure to modify a file rotation schedule.

You can modify file rotation schedules whether or not they are used by report registrations. If you modify a file rotation schedule that is used by one or more report registrations, all report files for the report registrations using this schedule are closed and rotated. A new report file is opened for the same report registration with a modified file rotation schedule when a scheduled data collection period for that report registration begins.

Prerequisites

To modify a file rotation schedule you need the following information:

- File rotation schedule:
the name of the file rotation schedule to be deleted
- Repetition:
the schedule of a file rotation that is to be repeatedly performed. Refer to "[Adding a file rotation schedule](#)" (page 21) for more information.

Procedure	Document
Logging in to the CS 2000 Core Manager	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611
Displaying information about a user or role group	<i>CS 2000 Core Manager Security and Administration</i> , NN10170-611

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Procedure

Use the following procedure to modify a file rotation schedule.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Modifying a file rotation schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OM Delivery Main Menu

3 Access the File Rotation Schedule Menu:

```
3
```

Example response:

```

                                File Rotation Schedule

1. List File Rotation Schedules
2. Add File Rotation Schedule
3. Delete File Rotation Schedule
4. Modify File Rotation Schedule
5. Help
6. Return to Main Menu

Select Option >

```

4 Modify a file rotation schedule:

4

Example response:

```

Modify File Rotation Schedule
Type "EXIT" to return to previous menu
File Rotation Schedule name >
    
```

5 Enter the name of the file rotation schedule that you want to modify.

If you do not know the file rotation schedule name (FRS name) to modify, use the "List File Rotation Schedule" option to review the list of currently defined file rotation schedules.

Example response:

Repetition (1=DAILY,2=WEEKLY, 3=MONTHLY, 4=REPORTS, 5=HOURS

If you change a file rotation schedule to a	Do
daily repetition rate (schedule rotation once a day)	step 6
weekly repetition rate (schedule rotation once a week)	step 9
monthly repetition rate (schedule rotation on the same day each month)	step 13
schedule rotation based on the number of reports collected	step 17
a repetition based on hours (schedule rotation after a specified number of hours have elapsed)	step 19

6 Change the file rotation schedule to a daily interval:

1

Example response:

Rotation time (HHMM) >

7 Enter the time of day to close and rotate the report file.

Example response:

Modify File rotation schedule (Y/N)?

8 Go to step 22.

9 Change the file rotation schedule to a weekly interval.

2

Response

Day of Week (1=Monday,2=Tuesday, ..., 7=Sunday) >

10 Enter the number for the day of the week that the report file is closed and rotated.

Example response:

Rotation time (HHMM) >

11 Enter the time of day to close and rotate the report file.

Example response:

Modify File rotation schedule (Y/N)?

12 Go to step 22.

13 Change the file rotation schedule to a monthly interval

3

Example response:

Day of Month (1-28, 0 is the last day of month) >

14 Enter the number for the day of the month to rotate the file.

Example response:

Rotation time (HHMM) >

15 Enter the time of day to close and rotate the report file.

Example response:

Modify File rotation schedule (Y/N)?

16 Go to step 22.

17



CAUTION

Possible loss of service and data

Selecting a large number of reports can exhaust available file system space, resulting in lost OM data and possible loss of service. If you collect a high volume of OM reports each day, reduce your file retention period for closedSent files to one day.

Change the file rotation schedule to one based on the number of reports collected. Set the repetition to reports:

4

Example response:

Number of Reports >

- 18 Enter the maximum number of reports to collect before file rotation is initiated (from 1 to 4032).

Example response:

Modify File rotation schedule (Y/N)?

- 19 Go to step 22.

20



CAUTION

Possible loss of service and data

Selecting a large number of hours can exhaust available file system space, resulting in lost OM data and possible loss of service. Select a number of hours smaller than 25. As an alternative, use the daily file rotation if you wish to record data for more than 24 hours.

Change the file rotation schedule to one that schedules file rotation after a specified amount of time has elapsed. Set the repetition to hours:

5

Example response:

Number of hours

- 21 Enter the number of hours that must elapse before the open report file is closed and rotated (from 1 to 999).

Example response:

Rotate on the hour (Y/N)?

Modify File rotation schedule (Y/N)?

- 22 Confirm that you want to modify the file rotation schedule:

y

Example response:

Please wait...
frsname: The request was successful.
Press Enter for File Rotation Schedule Menu.

- 23 Press Enter to return to the File Rotation Schedule Menu.

The OMUI displays the following screen:

```
File Rotation Schedule

1. List File Rotation Schedules
2. Add File Rotation Schedule
3. Delete File Rotation Schedule
4. Modify File Rotation Schedule
5. Help
6. Return to Main Menu

Select Option >
```

24 Return to the OM Delivery Main Menu:

6

25 You have completed the procedure.

—End—

Modifying a file transfer destination

Purpose

Use this procedure to modify the information for a file transfer destination.

Prerequisites

You must have the root user ID and password to log into the server.

If you have chosen to change the name of the file transfer destination, use the "Modifying a file transfer destination" (page 124) procedure first to create a new file transfer destination using that destination name. Then, delete the old file transfer destination.

Application

You can modify the following file transfer destination information:

- the IP address of the destination system
- the FTP port address defined for the IP address on the destination system
- the remote login ID used to access the destination system
- the password for the remote login ID

ATTENTION

Special instruction after the customer upgrades the SDM/CBM from a previous release to 23 release:

After an upgrade of SDM/CBM to release 23, once a new File Transfer Destination is added, the customer is not advised to fallback since the old password details (stored in PDM) are re-formatted and stored as a new file. In such scenario, if the customer falls back to a previous release, the old password details (stored in PDM) would not be available as the old data file would have been deleted, and hence the customer may have to reconfigure the File Transfer Destinations in order to get the OM files transferred to downstream.

ATTENTION

Special instruction after the customer upgrades the SDM/CBM from a previous release to GSM19 release:

After an upgrade of SDM/CBM to release GSM19, once a new File Transfer Destination is added, the customer is not advised to fallback since the old password details (stored in PDM) are re-formatted and stored as a new file. In such scenario, if the customer falls back to a previous release, the old password details (stored in PDM) would not be available as the old data file would have been deleted, and hence the customer may have to reconfigure the File Transfer Destinations in order to get the OM files transferred to downstream.

ATTENTION**Special instruction after the customer upgrades the SDM/CBM from a previous release to MTX13 release:**

After an upgrade of SDM/CBM to release MTX13, once a new File Transfer Destination is added, the customer is not advised to fallback since the old password details (stored in PDM) are re-formatted and stored as a new file. In such scenario, if the customer falls back to a previous release, the old password details (stored in PDM) would not be available as the old data file would have been deleted, and hence the customer may have to reconfigure the File Transfer Destinations in order to get the OM files transferred to downstream.

Procedure

Use the following procedure to modify a file transfer destination.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Modifying a file transfer destination**Step Action*****At the workstation UNIX prompt or VT-100 terminal prompt:***

1 Log into the core manager.

2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OMUI Main Menu

3 Perform the procedure "[Listing a file transfer destination](#)" (page 97) to review and record information about the particular file transfer

destination you have chosen to modify. This allows the default values for that file transfer destination to be available.

4 Access the File Transfer Destination Main Menu:

4

Example response:

```

File Transfer Destination
1. List File Transfer Destinations
2. Add File Transfer Destination
3. Delete File Transfer Destination
4. Modify File Transfer Destination
5. Help
6. Return to Main Menu

Select Option >
    
```

5 Select Modify File Transfer Destination:

4

Example response:

```

Modify File Transfer Destination

Type "EXIT" to return to previous menu

File Transfer Destination name >
    
```

6 Enter the name of the file transfer destination you want to modify.

Example response:

Destination IP Address [xxx.xxx.xxx.xxx] >

If you	Do
want to change the IP address	step 7
do not want to change the IP address	press Enter to accept the default, and go to step 8

7 Enter the new IP address for the file transfer destination (the computer you have chosen to send the files to).

Example response:

Type of file transfer: Standard/Secure >

8 Enter the type of file transfer that you require for this destination.
Enter:

- **standard**

for un-encrypted file transfer using the standard FTP protocol.

- **secure**
for encrypted file transfer using the OpenSSH program, sftp.

Example response:

Type of Authentication: Password/Key >

9 Enter the type of authentication you require for the file transfer. Enter

- **Password** for password-based authentication, or
- **Key** for key-based authentication

Example response:

Destination Port [xx] >

If you	Do
want to change the destination port	step 10
do not want to change the destination port	press Enter to accept the default and go to step 11

10 Enter the new destination port number assigned for use with the IP address you entered in step 7.

Example response:

Destination Login:

If you	Do
want to change the destination login ID	step 11
do not want to change the destination login ID	press Enter to accept the default and go to step 12.

11 Enter the new destination login ID you use to log onto the file transfer destination system receiving the OM files.

Example response if password-based authentication was chosen in step 9:

Destination Password >

Example response if key-based authentication was chosen in step 9:

WARNING: File Transfer to this destination will fail if OpenSSH is not installed. Please install OpenSSH if it is not already installed.

Modify file transfer destination (Y/N) ?

If you	Do
chose password-based authentication in step 9, and want to change the destination password	step 12
chose password-based authentication in step 9, and do not want to change the destination password	press Enter to accept the default and go to step 13

ATTENTION

The following step is skipped for key-based authentication.

- 12** Enter the new password for the login ID.

Response

WARNING: File Transfer to this destination will fail if OpenSSH is not installed. Please install OpenSSH if it is not already installed.

Modify file transfer destination (Y/N) ?

- 13** Review the information you entered or changed.

If the information you changed for the file transfer destination is	Do
correct	continue with step 14
not correct	type n , press the Enter key, and return to step 3.

- 14** Confirm that you want to make the modifications to the file transfer destination entry:

y

Example response if password-based authentication was chosen in step 9:

```
Please wait...
ftdname: The request was successful.
Press Enter for File Transfer Destination
Menu.
```

Example response if key-based authentication was chosen in step 9:

Please wait....

The public key is stored at:
 /home/maint/.ssh:ftdname_rsa.pub
 Please append this public key to the user's
 authorization file on the destination machine.
 ftdname: the request was successful.
 Press Enter for File Transfer Destination menu.

- 15** Press the Enter key to return to the File Transfer Destination Menu.

Example response:

```

      File Transfer Destination
    1. List File Transfer Destination
    2. Add File Transfer Destination
    3. Delete File Transfer Destination
    4. Modify File Transfer Destination
    5. Help
    6. Return to Main Menu

  Select Option >
  
```

- 16** Return to the OM Delivery Main Menu:

6

- 17** You have completed the procedure.

—End—

Modifying a file transfer schedule

Purpose

Use this procedure to modify a file transfer schedule.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

You can modify the following file transfer schedule information:

- Repetition:
the schedule frequency you have chosen to transfer OM files to.
- File transfer destination system:
specifies the name of the file transfer destination system.
- Destination directory path:
specifies the destination directory path on the file transfer destination system.

Procedure

Use the following procedure to modify a file transfer schedule.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Modifying a file transfer schedule

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- 1 Log into the core manager.
- 2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OMUI Main Menu

- 3 Perform the procedure ["Listing a file transfer schedule"](#) (page 101) to:
 - list the contents of the file transfer schedule and
 - review and record information about the specific file transfer schedule you have chosen to modify

This allows the default values for that file transfer schedule to be available

- 4 Access the File Transfer Schedule Main Menu:.

5

Example response:

```

File Transfer Schedule Menu

1. List File Transfer Schedule
2. Add File Transfer Schedule
3. Delete File Transfer Schedule
4. Modify File Transfer Schedule
5. Help
6. Return to Main Menu

Select Option >

```

5 Select Modify File Transfer Schedule:

4

Example response:

```

Modify File Transfer Schedule

Type "EXIT" to return to previous menu

File Transfer Schedule name >

```

6 Enter the name of the file transfer schedule you want to modify.

If you do not know the name of the file transfer schedule (FTS) name you need to modify, use the ["Listing a file transfer schedule"](#) (page 101) procedure to review the list of currently defined file transfer schedules.

Example response:

```

Repetition (1=DAILY, 2=WEEKLY, 3=MONTHLY, 4=AFTER
ROTATE) >

```

If you want to change a file transfer schedule to	Do
transfer files immediately after file rotation	step 7
a monthly repetition rate (transfer files on the same day of each month)	step 9
a weekly repetition rate (transfer files on the same day each month)	step 12
a daily repetition rate (transfer files once a day)	step 15

7 Change a file transfer schedule to transfer OM files immediately after they are closed and rotated. Set the repetition to After Rotate

4

Example response:

```

File Transfer Destination name ("quit" to exit) >

```

- 8 Go to step 17.
- 9 Change a file transfer schedule to a monthly repetition rate:
3
Example response:
Day of Month (1-28, 0 is the last day of month) >
- 10 Enter the number for the day of the month to rotate the OM file.
For example, one is for the first day of the month and two is for the second day of the month.
Use 0 for the last day of the month.
Example response:
Time of Day (HHMM) >
- 11 Go to step 16.
- 12 Change a file transfer schedule to a weekly repetition rate. Set the repetition rate to weekly:
2
Example response:
Day of Week (1=Monday, 2=Tuesday, ... 7=Sunday) >
- 13 Enter the number for the day of the week to rotate the OM file.
Example response:
Time of Day (HHMM) >
- 14 Go to step 16.
- 15 Change a file transfer schedule to a daily repetition rate:
1
Example response:
Time of Day (HHMM) >
- 16 Enter the time of day to transfer the file.
Example response:
File Transfer Destination name ("quit" to exit) >
- 17 Enter the name of a file transfer destination.

ATTENTION

Ensure you have created a file transfer destination using the same FTD name you are using in this step. Failure to do so prevents you from creating the file transfer schedule.

Example response:

Destination Dir >

- 18** Enter the path of the destination directory where you want the OM files to be transferred to. The format for the destination is often displayed as /destdir/destsubdir.

If you are uncertain as to the correct destination directory or path on a specific machine, contact your site system administrator for assistance.

Example response:

File Transfer Destination name ("quit" to exit) >

- 19** A single file transfer schedule can be set up to transfer OM files to as many as 16 destinations at once.

If you	Do
want to add other machines to this daily transfer schedule	step 17
do not want to add other machines to this transfer schedule	step 20

- 20** Complete this file transfer schedule:

quit

Example response:

Modify file transfer destination (Y/N) ?

- 21** Confirm that you want to make the modifications to the file transfer schedule entry:

y

Example response:

```
Please wait...
ftsname: The request was successful.
Press Enter for File Transfer Schedule Menu.
```

- 22** Press Enter to return to the File Transfer Schedule Menu.

Example response:

File Transfer Schedule Menu

1. List File Transfer Schedule
2. Add File Transfer Schedule
3. Delete File Transfer Schedule
4. Modify File Transfer Schedule
5. Help
6. Return to Main Menu

Select Option >

23 Return to the OM Delivery Main Menu:

6

24 You have completed the procedure.

—End—

Modifying OM groups in a report element

Purpose

Use this procedure to modify OM groups in a report element.

Prerequisites

To modify operational measurements (OM) groups in a report element, you need the information in the following table.

Component	Description
Report element name	Name of the report element of the OM groups to be modified
OM group name	Name of an OM group to be modified in the report element
Register	Name the registers of OM groups to be included in the report.
	For more information, refer to "Operational Measurements Delivery Overview" in the CBM Basics document.

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Procedure

Use the following procedure to modify OM groups in a report element.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Modifying OM groups in a report element

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

omui

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OM Delivery Main Menu

3 Display the Report Element Main Menu:

1

Example response:

```

                                Report Element Main Menu

1. List Report Elements
2. Add Report Element
3. Delete Report Element
4. Modify Report Element
5. Help
6. Return to Main Menu

Select Option >

```

4 Use the Modify Report Element option:

4

Example response:

```
Modify Report Element Menu

1. Add OM groups to a Report Element
2. Delete OM groups from a Report Element
3. Modify OM groups in a Report Element
4. Help
5. Exit to Report Element Menu

Select Option >
```

5 Access the Modify OM Groups in a Report Element Menu:

3

Example response:

```
Modify OM Groups in a Report Element Menu

1. Add Register(s) to OM groups in a Report Element
2. Delete Register(s) from OM groups in a Report Element
3. Help
4. Return to Modify Report Element Menu

Select Option >
```

6 To add a register to an existing OM group in a report element, refer to procedure ["Adding a register to an existing OM group in a report element"](#) (page 49) . To delete a register from an existing OM group in a report element refer to procedure ["Deleting a register from an existing OM group in a report element"](#) (page 73).

7 You have completed this procedure.

—End—

Setting the file retention period

Purpose

Use the following procedure to set the file retention period.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

OM report files that have been sent to a downstream location are located in the /cbmdata/00/omdata/closedSent directory. They are deleted regularly at an interval based on the file retention period you defined in the OMUI. You can set the interval from 1 to 14 days.

When the OMD application is installed, the default interval is set to 7 days. Before you set the new interval, the OMUI displays the current report registration limit.

Procedure

Use the following procedure to set the file retention period.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Setting the file retention period

Step Action

At the workstation UNIX prompt or VT-100 terminal prompt:

1 Log into the core manager.

2 Start the OMUI:

`omui`

The OM Delivery Main menu appears.

```
OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->
```

At the OM Delivery Main Menu

3 Set the file retention period:

`7`

Example response:

```
Set File Retention Period

Current File Retention Period: 7. days
New File Retention Period (Max 14 days) >
```

4 Enter the number of days (from 1 to 14) you want to retain OM report files in the /cbmdata/00/omdata/closedSent directory.

This represents the number of days you want to store a closed OM report file after it has been copied to a downstream location.

Example response:

Are you sure (Y/N)?

5 Confirm that you want to change the file retention period:

`y`

Example response:

```
Please wait...
The file retention period was successfully
changed to 10.

Press Enter for Main Menu.
```

- 6 Press the Enter key to return to the OM Delivery Main Menu.
- 7 You have completed the procedure.

—End—

Setting the report registration limit

Purpose

Use this procedure to set the report registration limit.

Logging in to the CBM

All users are authorized to perform this procedure.

For information on how to log in to the CBM as an authorized user or how to display information about a user or role group, review the procedures in the following table.

Procedure	Document
Logging in to the CBM	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611
Displaying actions a role group is authorized to perform	<i>Core and Billing Manager 850 Security and Administration</i> , NN10358-611

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Application

The report registration limit is the maximum number of report registrations that you can set up on a single core manager. The maximum number of report registrations can be set between 1 and 32, with 32 being the default value. However, a large number of report registrations can affect the performance of the core manager.



CAUTION

Possible loss of service and data

Selecting a large number of reports can exhaust available file system space, resulting in lost OM data and possible loss of service. If you collect a high volume of OM reports each day, reduce the file retention period for closedSent files to one day.

Procedure

Use the following procedure to set the report registration limit.

Instructions for entering commands in the following procedure do not show the prompting symbol, such as #, >, or \$, displayed by the system through a GUI or on a command line.

Setting the report registration limit

Step	Action
------	--------

At the workstation UNIX prompt or VT-100 terminal prompt:

- 1 Log into the core manager.
- 2 Start the OMUI:

```
omui
```

The OM Delivery Main menu appears.

```

                                OM Delivery Main Menu

1. Report Element
2. Data Collection Schedule
3. File Rotation Schedule
4. File Transfer Destination
5. File Transfer Schedule
6. Report Registration
7. Set File Retention Period
8. Set Report Registration Limit
9. Help
10. Quit

Select Option ->

```

At the OM Delivery Main Menu

- 3 Set the report registration limit:

```
8
```

Example response:

```

Set Report Registration Limit
Current Report Registration Limit (Max 32 report
registrations: 32)

New Report Registration Limit >

```

- 4 Enter the maximum number of report registrations (from 1 to 32) that you have chosen to allow on this device.

Example response:

```
Are you sure (Y/N)?
```

- 5 Confirm that you want to change the maximum number of report registrations:

```
y
```

Example response:

```
Please wait...
The file report registration limit was successfully
changed to 20.

Press Enter for Main Menu.
```

- 6 Press the Enter key to return to the OM Delivery Main Menu.
- 7 You have completed the procedure.

—End—

Quitting the OMUI

Purpose

Use this procedure to exit the OMUI, and return to the root or maint user prompt.

Procedure

Quitting the OMUI

Step	Action
------	--------

At the UNIX workstation or VT-100 terminal:

1 Exit the OMUI:

> 10

Example response:

Are you sure [Y/N] ?

2 Confirm that you have chosen to quit the OMUI:

> y

The OMUI returns you to the root or maint user prompt.

3 You have completed the procedure.

—End—

Carrier VoIP

CS2000 Core Manager Performance Management

Copyright © 2006, Nortel Networks
All Rights Reserved.

Publication: NN10148-711
Document status: Standard
Document version: 08.02
Document date: 20 October 2006

To provide feedback or report a problem in this document , go to <http://www.nortel.com/documentfeedback>

The information in this document is sourced in Canada, the United States of America, and the United Kingdom.

The information contained herein is the property of Nortel Networks and is strictly confidential. Except as expressly authorized in writing by Nortel Networks, the holder shall keep all information contained herein confidential, shall disclose it only to its employees with a need to know, and shall protect it, in whole or in part, from disclosure and dissemination to third parties with the same degree of care it uses to protect its own confidential information, but with no less than reasonable care. Except as expressly authorized in writing by Nortel Networks, the holder is granted no rights to use the information contained herein.

This is the Way, This is Nortel, Nortel, the Nortel logo, the globemark design, and the NORTEL NETWORKS corporate logo, are trademarks of Nortel Networks. All other trademarks are the property of their respective owners. All rights reserved.

