



- NOTES:
1. DEAD DRESS THESE SPADE TIPPED LEADS PER A-85C071-39 AND STORE.
 2. LACE TOGETHER CONDUCTORS INDICATED FOR 7.00 INCHES WITH LACING TAPE, ITEM 77 OF P-82B100.
 3. WHEN A 617A KEY IS USED IN THE TELEPHONE SET, ATTACH THE SPADE-TIPPED CONDUCTOR OF THE KEY TO THE SG TERMINAL ON THE MOUNTING CORD TERMINAL STRIP. REMOVE THE SPADE-TIPPED STRAP FROM THE CG TERMINAL ON THE STRIP.
 4. ITEM NUMBERS REFERRED TO ARE SHOWN IN STOCK LIST OF P-82B100-499.

REDUCE TO 8 1/2 INCHES

P-25E052	
DATE	ISSUE
8-17-62	ISSUE-1
CHANGED: BL-W LEAD FROM THE SWITCH TO TERM. 4 OF THE TERM. BOARD WAS BR-Y; BL-R, 52 LEAD FROM TERM. 3 OF TERM. BOARD & TERM. 1 OF THE NETWORK WAS R-S, 62; BR-R, 53 LEAD FROM TERM. 3 OF TERM. BOARD & TERM. 2 OF THE NETWORK WAS S-R, 61; 15S AND OF LABEL WAS (1) BK-BL, 60 LEAD FROM TERM. 1 OF THE AMPLIFIER TO TERM. C OF THE NETWORK WAS O-Y, 62.	
12-12-62	
CHANGED: BK-S FROM T 2 OF JK B WAS CONN. TO T 2 OF AMP; Y-BL WAS CONN FROM T 3 OF AMP TO T F OF NET; W-BL WAS CONN TO T 4 OF AMP; BL-Y FROM T 7 OF JK B WAS CONN TO T 2 OF T 80; R-G FROM T 1 OF JK B WAS CONN TO T 1 OF AMP; BK-BL WAS CONN BETWEEN T 1 OF AMP & T C OF NET; Y-G FROM T 4 OF JK B WAS CONN TO T 2 OF AMP; S-BK FROM T 6 OF SW WAS CONN TO T 2 OF AMP; ISSUE OF CIRCUIT LABEL WAS 2	
ADDED: BL-G LEAD BETWEEN T 1 & T 7 OF JK B	
10-1-63	
CHANGED: AT NET UNDER S-R & S-BK LEADS WERE SHOWN SOLDERED; CIR. LABEL WAS ISS. 3	
10-3-63	
FOR CHARGES REFER TO DFTG CARD INDEX	
LABEL, WIRING & CIRCUIT	
SCALE 2/1	
WESTERN ELECTRIC CO. INC. ENGINEER OF MANUFACTURE	
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES. UNLIMITED DIMENSIONS OTHER THAN SIZE OF RAW MATERIAL SHALL BE HELD AS FOLLOWS WHEN EXPRESSED: TO 3 DECIMAL PLACES 2 AS ANGLE 2	
TO 3 DECIMAL PLACES 2 FOR GENERAL INFORMATION ON SYMBOLS AND NOTES REFER TO MANUFACTURING STANDARD 18.000, PART 2, SECTION 2.7.	
6S	P-25E052

PRINTED IN U.S.A.

PRINT BLACK