

American Telephone and Telegraph Company

BELL SYSTEM PRACTICES
Teletypewriter Stations

ADDENDUM P36.476
Issue C, 8-31-54
Long Lines Department
Dist. Class. 602.02AC

NO. 15 TELETYPEWRITER
TP 96892 MOTOR CONTROL PARTS
INSTALLATION AND MAINTENANCE

1. GENERAL

1.01 This addendum supplements Section P36.476 by furnishing additional information regarding (1) the treatment of the base power switch in 15-type teletypewriters with remote motor control and (2) to specify new wiring information for the remote motor control parts.

1.02 This issue supersedes Issue B. This addendum is reissued to omit Item 1.01 (3) and to change cross references.

1.05 Change Paragraph 1.05 to read: "When providing remote motor control on No. 15 teletypewriters whose base power switch is accessible through the cover, this power switch should be operative to permit turning power off when replacing ribbon or paper". Note Caution following Paragraph 1.05 of the section.

1.051 Add Paragraph 1.051: "When providing remote motor control on No. 15 teletypewriters whose base power switch is not accessible through the cover but where a power switch is accessible in the table (such as installations having 15J covers and 15J tables), the power switch in the teletypewriter shall be made inoperative in the closed position per appropriate M plans and the switch in the table shall be used to turn off the power when replacing ribbon or paper".

1.052 Add Paragraph 1.052: "In applying the TP 96892 motor control parts to Nos. 15 and 19 teletypewriters the parts shall be installed and adjusted in accordance with Section P36.476 but wired in accordance with Section P90.908 (with the exception noted in Paragraph 1.051 above) instead of using the wiring shown in Section P36.476. The information on fusing for 15C, 15D and 15J tables is contained in Section P90.958, and that for 19 type tables in Section P90.908. The information on fusing for 15P tables is covered temporarily in Section P30.921".