

BELL SYSTEM PRACTICES
Teletypewriter Stations

ADDENDUM P36.479
Issue 1, September, 1957
AT&TCo Standard

INSTALLATION OF TP96807 OR TP115889 SET OF PARTS TO PROVIDE SWITCHING CONTACTS WHICH CLOSE AND OPEN AN EXTERNAL CIRCUIT ON 15 TELETYPEWRITER

1. GENERAL

- 1.001 This addendum supplements Section P36.479, Issue 4.
- 1.002 This addendum is issued to include an additional keytop which is required for a keyboard machine.

2. LIST OF PARTS

The following change applies to Part 2 of the section:

(a) 2.07—revised

- 2.07 In addition to the TP96807 or TP115889 set of parts, the following parts are required for keyboard machines.
 - 1—(*) Keytop with (**) in upper case and (**) in lower case (This keytop is for use with contact-close operation.)
 - 1—(*) Keytop with (**) in upper case and (**) in lower case (This keytop is for use with contact-open operation.)

* Specify whether spring cushion, pneumatic, or celluloid.

** Specify character. This information may be obtained from the private-line service order.

ADDENDUM
P36.479

Page 1
1 Page

**INSTALLATION OF TP96807 OR
TP115889 SET OF PARTS TO PROVIDE
SWITCHING CONTACTS WHICH CLOSE
AND OPEN AN EXTERNAL CIRCUIT
ON 15 TELETYPEWRITER**